Overview Tasks Solutions

SOLUTIONS

Below, you can find solutions for each task. Remember, though, that you can follow your own strategy, which may be different from the one explained in the following lab.

Task 1: Create a MANs file of APTA.VMEM.

1. Open Redline and select **From a Saved Memory File** under **Analyze Data**.

2. Select the memory image **APTA.VMEM** and click **Open**.

3. Change **Memory Images** to **All Files (*)**.



4. Choose **apta.mem** and choose **Next**.
5. Click **Edit your script** select **Strings** for both **Process Listing** and **Drivers Enumeration** then choose **Ok**.
6. Change the **Name** to **APTA** and choose **Ok**.
7. If UAC is enabled, select **Yes**.

You should see Redline creating the analysis of the memory file, as shown below.

Task 2: Analyze the MANS file from task 1.

1. After analysis is complete, we can look at the processes by selecting **Processes** under **Analysis Data**.

As we can see nothing is redlined. Based on what we know about Windows processes we can attempt to see if anything is odd (wrong parent process, wrong path, etc.). To do this we can switch to **Hierarchical Processes** view.

1. Click on **Hierarchical Processes** view under **Analysis Data**.

Do we see anything out of the ordinary? If not then let's look at **Memory Sections** for signs of code injection.

1. Click on **Memory Sections** (submenu item under **Processes**) under **Analysis Data**.
2. Click on **Injected Memory Sections** under **Filters**.

We should see 24 items listed as injected with code and by glancing at the results it appears to be nearly every processes within the memory image.

We can look at **Strings** and/or **Ports** but instead we'll look at **Hooks** to see any indicators of some sort of rootkit.

1. Click on **Hooks** under **Analysis Data**.
2. Click on **SSDT Hooks** under **Filters**.
3. Click on **IDT Hooks** under **Filters**.
4. Click on **Untrusted Hooks** under **Filters**.

We didn't see anything under SSDT and IDT Hooks but we're seeing some entries under Untrusted Hooks. At this point, with the data gathered, we definitely know there was code injection in many processes. We can now take a closer look at things in VolatilityL

Task 3: Analyze APTA.VMEM within Volatility.

Copy paste the aptа.mem on desktop

We can see from the output that the profile is **Win2PSP0x86**.



If we compare Redline and Volatility we should see 1 process, cmd.exe (504), that we didn't see in Redline.

If we compare Redline and Volatility we should see another process, VMtp.exe (1044), that we didn't see in Redline.

This process looks like it's a child process to cmd.exe (504).

We can use the Volatility **PSTREE** plugin to get a hierarchical process.

From the output we can't see VMtp.exe (1044) which was spawned by cmd.exe (504) but we can see cmd.exe (504).

We can use **PSVIEW** to see if this process is showing indicators that it's a hidden process.

From the output we can't see this process 806 is made outbound connections on ports 1014 & 1016 to a IP on port 80. What is process 806? The answer is svchost.exe.

This process is one of the processes shown as injected. Let's us **MALFIND** to further examine.

Based on the output we can see 1 memory section containing an MZ header which is an indicator of code injection.

By the output from **PSVIEW** we see that VMtp.exe (1044) shows indicators of a hidden process, along with cmd.exe (504). Remember that we didn't see these 2 processes in Redline but does this mean that these 2 processes are malicious? Remember that Redline indicated many processes were injected except these 2 processes because they were not visible in Redline. Instead of VMtp.exe is trying to connect to any remote IP addresses by using **CONNSCAN** (Windows XP).

Based on the output we can see 1 memory section containing an MZ header which is an indicator of code injection.

Let's see if this process is hooking to any APIs with **APIHOOKS**.

From the output we see 2 APIs are hooked (**NtCreateThread** and **ZwCreateThread**). Unknown being shown as the **Hooking module** adds to conclusion suspicious activity.

Note: We have only focused on process 806 but you can see these techniques with nearly all of the processes as they're all injected. The malware you just examined was **Zeus**.

Task 4: Create a MANs file of APTA.VMEM.

Follow the same steps from Task 1 but you're performing the steps against **APTA.VMEM** and naming the analysis file as **APTA**.

1. Click on **Memory Sections** (submenu item under **Processes**) under **Analysis Data**.
2. Click on **Injected Memory Sections** under **Filters**.

We should see 1 item listed as injected with code and it has the same process as the previous memory image. Next we'll look at **Hooks** to see any indicators of some sort of rootkit.

1. Click on **Hooks** under **Analysis Data**.
2. Click on **SSDT Hooks** under **Filters**.
3. Click on **IDT Hooks** under **Filters**.
4. Click on **Untrusted Hooks** under **Filters**.

We didn't see anything under SSDT and IDT Hooks but we're seeing some entries under Untrusted Hooks. As before, we can now take a closer look at things in VolatilityL

Task 6: Analyze APT.VMEM within Volatility.

Since the goal is to look for a rootkit, we should only focus on the Volatility plugins for rootkit detection. Let's use **SSDT.**

From the output above we see some hooked functions pointing to the same driver, **i8042kbd.sys**. Alternatively the **THREADS** plugin could be used to obtain the same conclusion about the malicious driver.

Next, we can extract this malicious driver for further analysis. This process starts with using **MODULES**

We need to obtain the base address. The base address is **0xf7fd7000**. Now we can use **MODDUMP** to extract the driver from the memory image.

Let's look for this malicious driver in Redline and see if it would have been easy to identify.

1. Open Redline and load **APTA.MANS** file.
2. Click on **Driver Modules** under **Analysis Data**.
3. Click on the **Name** column to sort the column contents.

As we can see its not the only driver without a full path but it is the only driver that is named with a number value. Also you can see the Module Base address which was obtained in Volatility using **MODULES** and extracted using **MODDUMP**.

Note: The malware you just analyzed was **Black Energy**.

Conclusion

After this lab you will be able to Use Redline to find evidence of code injection and/or rootkits, Use Volatility to find evidence of code injection and/or rootkits, Use Volatility to find information that was not seen in Redline.