In-situ (LED Component) - WP1

Michael Mock * Ehab Qadah *

*Fraunhofer IAIS, Germany

Sunday 14th January, 2018



Outline

datAcron Architecture

Overview


Output Scheme

Deployment and Integration

Performance on YARN cluster

Conclusion


datAcron Architecture





In-situ (LED Component) ¹

Overview



In-situ LED

Functionalities

- ► Trajectory enrichment: computing trajectory statistics such as min/max/mean/var speed.
- Monitoring of AIS messages against areas information (detected areas)
- Derivation of low-level events for area entering and leaving



Real-time stream simulator

- ► Read raw AIS File to generate a reply stream
- ► Reconstruct the trajectories and use the actual time difference between the points to replay origin stream
- ► delayScale parameter to scale up/down the out stream rate



Output CSV scheme (29 fields)

timestamp,id,longitude,latitude,speed, heading,msgErrorFlag,turn,course,status, NumberOfPoints,AverageDiffTime,LastDiffTime, MinDiffTime,MaxDiffTime,MaxSpeed,MinSpeed, AverageSpeed,VarianceSpeed,MinLong, MaxLong,MinLat,MaxLat,MinTurn,MaxTurn, MinHeading,MaxHeading,isChangeInArea, detectedAreas

Deployment

► From deployment on a single VM machine


► To deployment on the YARN datAcron cluster (10 nodes X 8 cores)

In-situ deployment on datAcron YARN cluster

```
rocessingSlotsPerTaskManager:8
 Pull new code changes
git pull
nvn clean package
projectWorkDir=S(pwd
jarFile=Sifind $projectWorkDir/target/in-situ-processing*.jar
jobName:"in-situ-p:$parallelism-tm:$numberOfTaskManagers"
```

In-situ Performance

Throughput on datAcron YARN cluster



14/1/18

Conclusion

LED in-situ processing resources/CPU consumption and delay can be neglected

