

# Class 06: R Functions

Eli Haddad (A16308227)

## All about functions in R

Functions are the way we get stuff done in R. We call a function to read data, compute stuff, plot stuff, etc. etc.

R makes writing functions accessible but we should always start by trying to get a working snippet of code first before we write our function.

## Today's lab

We will grade a whole class of student assignments

Input vectors of students to start with

```
student1 <- c(100, 100, 100, 100, 100, 100, 100, 90)
student2 <- c(100, NA, 90, 90, 90, 90, 97, 80)
student3 <- c(90, NA, NA, NA, NA, NA, NA, NA)
```

If we want the average we can use the `mean()` function:

```
mean(student1)
```

```
[1] 98.75
```

Let's be nice instructors and drop the lowest score so the answer here should be 100.

I can use the `min()` function to find the lowest value

```
min(student1)
```

```
[1] 90
```

If found the `which.min()` function that may be useful here. How does it work? Let's just try it:

```
student1
```

```
[1] 100 100 100 100 100 100 100 90
```

```
which.min(student1)
```

```
[1] 8
```

I can use this minus syntax trick to get everything but the element with the min value.

```
student1[-which.min(student1)]
```

```
[1] 100 100 100 100 100 100 100
```

I have my first working snippet of code!

```
mean(student1[-which.min(student1)])
```

```
[1] 100
```

Let's test on the other students

```
student2
```

```
[1] 100 NA 90 90 90 90 97 80
```

```
mean(student2[-which.min(student2)])
```

```
[1] NA
```

Where is the problem? -oh it is the `mean()` with NA input returns NA by default, but I can change this...

```
mean(student2, na.rm=TRUE)
```

```
[1] 91
```

```
mean(student3, na.rm=TRUE)
```

```
[1] 90
```

No bueno. We need to fix this!

I want to stop working with `student1`, `student2` etc. and typing it out every time so let's instead work with an input called `x`

```
x <- student2  
x
```

```
[1] 100 NA 90 90 90 90 97 80
```

We want to overwrite the NA values with zero - if you miss a homework you score zero on this homework.

Google and Claude told me about the `is.na()` function. Let's see how it works.

```
x
```

```
[1] 100 NA 90 90 90 90 97 80
```

```
is.na(x)
```

```
[1] FALSE TRUE FALSE FALSE FALSE FALSE FALSE
```

```
x[is.na(x)] <- 0  
x
```

```
[1] 100 0 90 90 90 90 97 80
```

This is my working snippet of code that solve the problem for all my example student inputs!

```
x<-student3
# Mask NA values to zero

x[is.na(x)] <- 0

# Drop lowest score and get the mean

mean(x[-which.min(x)])
```

```
[1] 12.85714
```

Q1. Write a function `grade()` to determine an overall grade from a vector of student homework assignment scores dropping the lowest single score. If a student misses a homework (i.e. has an NA value) this can be used as a score to be potentially dropped. Your final function should be adequately explained with code comments and be able to work on an example class gradebook such as this one in CSV format: “<https://tinyurl.com/gradeinput>” [3pts]

```
grade <- function(x) {
  # Mask NA values to zero
  x[is.na(x)] <- 0
  # Drop lowest score and get the mean
  mean(x[-which.min(x)])
}
```

Use this function:

```
grade(student1)
```

```
[1] 100
```

```
grade(student2)
```

```
[1] 91
```

```
grade(student3)
```

```
[1] 12.85714
```

We need to read the gradebook

```
gradebook <- read.csv("https://tinyurl.com/gradeinput", row.names=1)
```

I can use the `apply()` function if I figure out how to use it!

```
ans <- apply(gradebook, MARGIN = 1, FUN = grade)
ans
```

student-1	student-2	student-3	student-4	student-5	student-6	student-7
91.75	82.50	84.25	84.25	88.25	89.00	94.00
student-8	student-9	student-10	student-11	student-12	student-13	student-14
93.75	87.75	79.00	86.00	91.75	92.25	87.75
student-15	student-16	student-17	student-18	student-19	student-20	
78.75	89.50	88.00	94.50	82.75	82.75	

Q2. Using your `grade()` function and the supplied gradebook, Who is the top scoring student overall in the gradebook? [3pts]

```
which.max(ans)
```

```
student-18
18
```

Q3. From your analysis of the gradebook, which homework was toughest on students (i.e. obtained the lowest scores overall)? [2pts]

We could calculate the `mean()` score for each homework.

```
mask <- gradebook
mask[is.na(mask)] <- 0
hw.ave <- apply(mask, 2, mean)
hw.ave
```

hw1	hw2	hw3	hw4	hw5
89.00	72.80	80.80	85.15	79.25

```
which.min(hw.ave)
```

```
hw2
2
```

We could take the sum

```
apply(gradebook, 2, sum, na.rm=T)
```

```
hw1 hw2 hw3 hw4 hw5
1780 1456 1616 1703 1585
```

Q4. Optional Extension: From your analysis of the gradebook, which homework was most predictive of overall score (i.e. highest correlation with average grade score)? [1pt]

```
hw.cor <- apply(mask, 2, cor, y=ans)
hw.cor
```

```
hw1 hw2 hw3 hw4 hw5
0.4250204 0.1767780 0.3042561 0.3810884 0.6325982
```

```
which.max(hw.cor)
```

```
hw5
5
```