

Class 10 Structural Bioinformatics

Eli Haddad A16308227

1) Introduction to the RCSB Protein Data Bank (PDB)

First let's see what is in the PDB database - the main repository of protein structures.

Downloaded composition stats from: <https://www.rcsb.org/stats/summary>

For context: Release 2023_24 of 13-Sep-2023 of UniProtKB/TrEMBL contains 251600,768 sequence entries. The PDB only contains 183,201

```
stats <- read.csv("Data Export Summary.csv", row.names = 1)
stats
```

	X.ray	EM	NMR	Multiple.methods	Neutron	Other
Protein (only)	158,844	11,759	12,296	197	73	32
Protein/Oligosaccharide	9,260	2,054	34	8	1	0
Protein/NA	8,307	3,667	284	7	0	0
Nucleic acid (only)	2,730	113	1,467	13	3	1
Other	164	9	32	0	0	0
Oligosaccharide (only)	11	0	6	1	0	4
Total						
Protein (only)	183,201					
Protein/Oligosaccharide	11,357					
Protein/NA	12,265					
Nucleic acid (only)	4,327					
Other	205					
Oligosaccharide (only)	22					

There is a problem there due to the commas in the numbers. This causes R to treat them as characters.

```
x <- stats$X.ray
x
```

```
[1] "158,844" "9,260" "8,307" "2,730" "164" "11"
```

```
as.numeric(gsub(",", "", x))
```

```
[1] 158844 9260 8307 2730 164 11
```

```
rm.comma <- function(x) {
  as.numeric(gsub(",", "", x))
}
```

```
rm.comma(stats$EM)
```

```
[1] 11759 2054 3667 113 9 0
```

I can use `apply()` to fix the whole table...

```
pdbstats <- apply(stats, 2, rm.comma)
rownames(pdbstats) <- rownames(stats)
head(pdbstats)
```

	X.ray	EM	NMR	Multiple.methods	Neutron	Other
Protein (only)	158844	11759	12296	197	73	32
Protein/Oligosaccharide	9260	2054	34	8	1	0
Protein/NA	8307	3667	284	7	0	0
Nucleic acid (only)	2730	113	1467	13	3	1
Other	164	9	32	0	0	0
Oligosaccharide (only)	11	0	6	1	0	4
Total						
Protein (only)	183201					
Protein/Oligosaccharide	11357					
Protein/NA	12265					
Nucleic acid (only)	4327					
Other	205					
Oligosaccharide (only)	22					

Q1: What percentage of structures in the PDB are solved by X-Ray and Electron Microscopy.

```
totals <- apply(pdbstats, 2, sum)
round(totals / totals["Total"] * 100, 2)
```

X.ray	EM	NMR	Multiple.methods
84.83	8.33	6.68	0.11
Neutron	Other	Total	
0.04	0.02	100.00	

Q2: What proportion of structures in the PDB are protein?

```
round(pdbstats[, "Total"] / sum(pdbstats[, "Total"]) * 100, 2)
```

Protein (only)	Protein/Oligosaccharide	Protein/NA
86.67	5.37	5.80
Nucleic acid (only)	Other	Oligosaccharide (only)
2.05	0.10	0.01

Q3: Type HIV in the PDB website search box on the home page and determine how many HIV-1 protease structures are in the current PDB?

SKIPPED for time!!

Protein structures in PDB as a function of UniProt sequences.

```
round((pdbstats[1, "Total"] / 251600768) * 100, 2)
```

[1] 0.07

Q4: Water molecules normally have 3 atoms. Why do we see just one atom per water molecule in this structure?


The resolution (2 Angstroms) is not small enough in order to capture the small size of the hydrogen atoms. That is why hydrogen is not seen anywhere in these structures. You need 1 Angstrom or better to see these smaller atoms.

Q5: There is a critical “conserved” water molecule in the binding site. Can you identify this water molecule? What residue number does this water molecule have

This water molecule is called HOH 308. It is important for making direct interactions with the ligand and with the protein.

Q6: Generate and save a figure clearly showing the two distinct chains of HIV-protease along with the ligand. You might also consider showing the catalytic residues ASP 25 in each chain and the critical water (we recommend “Ball & Stick” for these side-chains). Add this figure to your Quarto document.

Here is a lovely figure of HIV-Pr with the catalytic ASP residues, the MK1 compound and the all important water 308



The bio3d package for structural bioinformatics

```
library(bio3d)

pdb <- read.pdb("1hsg")
```

Note: Accessing on-line PDB file

```
pdb
```

Call: read.pdb(file = "1hsg")

```
Total Models#: 1
Total Atoms#: 1686, XYZs#: 5058 Chains#: 2 (values: A B)

Protein Atoms#: 1514 (residues/Calpha atoms#: 198)
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)

Non-protein/nucleic Atoms#: 172 (residues: 128)
Non-protein/nucleic resid values: [ HOH (127), MK1 (1) ]
```

Protein sequence:

```
PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYD
QILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFPQITLWQRPLVTIKIGGQLKE
ALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYDQILIEICGHKAIGTVLVGPTP
VNIIGRNLLTQIGCTLNF
```

```
+ attr: atom, xyz, seqres, helix, sheet,
      calpha, remark, call
```

```
head(pdb$atom)
```

	type	eleno	elety	alt	resid	chain	resno	insert	x	y	z	o	b
1	ATOM	1	N	<NA>	PRO	A	1	<NA>	29.361	39.686	5.862	1	38.10
2	ATOM	2	CA	<NA>	PRO	A	1	<NA>	30.307	38.663	5.319	1	40.62
3	ATOM	3	C	<NA>	PRO	A	1	<NA>	29.760	38.071	4.022	1	42.64
4	ATOM	4	O	<NA>	PRO	A	1	<NA>	28.600	38.302	3.676	1	43.40

```

5 ATOM      5      CB <NA>  PRO      A      1      <NA> 30.508 37.541 6.342 1 37.87
6 ATOM      6      CG <NA>  PRO      A      1      <NA> 29.296 37.591 7.162 1 38.40
  segid elesy charge
1  <NA>      N  <NA>
2  <NA>      C  <NA>
3  <NA>      C  <NA>
4  <NA>      O  <NA>
5  <NA>      C  <NA>
6  <NA>      C  <NA>

```

Predicting functional motions of a single structure

Let's finish today with a bioinformatics calculation to predict the functional motions of a PDB structure.

```
adk <- read.pdb("6s36")
```

Note: Accessing on-line PDB file


PDB has ALT records, taking A only, rm.alt=TRUE

```
m <- nma(adk)
```

Building Hessian... Done in 0.013 seconds.

Diagonalizing Hessian... Done in 0.275 seconds.

```
plot(m)
```



```
mktrj(m, file="adk_m7.pdb")
```

4. Comparative structure analysis of Adenylate Kinase

We need some packages for today's class. These include `bio3d` and `msa`

The `msa` package is from BioConductor. These packages focus on genomics type work and are managed by the `BiocManager` package.

Install `install.packages("BiocManager")` and then `BiocManager::install("msa")` all entered in the R "brain" console.

```
library(bio3d)

aa <- get.seq("lake_A")
```

Warning in `get.seq("lake_A")`: Removing existing file: `seqs.fasta`

Fetching... Please wait. Done.

aa

```

      1      .      .      .      .      .      .      60
pdb|1AKE|A  MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMLRAAVKSGSELGKQAKDIMDAGKLV
      1      .      .      .      .      .      .      60

      61      .      .      .      .      .      .      120
pdb|1AKE|A  DELVIALVKERIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFDVPDELIVDRI
      61      .      .      .      .      .      .      120

      121      .      .      .      .      .      .      180
pdb|1AKE|A  VGRRVHAPSGRVYHV KFNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQM TAPLIG
      121      .      .      .      .      .      .      180

      181      .      .      .      214
pdb|1AKE|A  YYSKEAEAGNTKYAKVDG TKPVAEVRADLEKILG
      181      .      .      .      214
```

Call:

```
read.fasta(file = outfile)
```

Class:

```
fasta
```

Alignment dimensions:

```
1 sequence rows; 214 position columns (214 non-gap, 0 gap)
```

```
+ attr: id, ali, call
```

Now I can search for the PDB database for related sequences:

```
#b <- blast.pdb(aa)
```

```
#hits <- plot(b)
```

```
#attributes(b)
```

```
#head(b)
```

These are the related structures in the PDB database that we found via a BLAST search...


```
hits <- NULL
hits$ pdb.id <- c('1AKE_A', '6S36_A', '6RZE_A', '3HPR_A', '1E4V_A', '5EJE_A', '1E4Y_A', '3X2S_A', '1E4V_A')
```

Q10. Which of the packages above is found only on BioConductor and not CRAN?

The `msa` package is found only in BioConductor and not CRAN.

Q11. Which of the above packages is not found on BioConductor or CRAN?:

The `Grantlab/bio3d-view` is installed using devtools, so this is not found on BioConductor or CRAN.

Q12. True or False? Functions from the devtools package can be used to install packages from GitHub and BitBucket?

True

Q13. How many amino acids are in this sequence, i.e. how long is this sequence?

There are 214 amino acids in this sequence.

Side-note: Lets annotate these structures (in other words find out what they are, what species they are from, stuff about the experiment they were solve in etc.)

For this we can use the `pdb.annotate()`

```
anno <- pdb.annotate(hits$ pdb.id)
```

```
#attributes(anno)
head(anno)
```

	structureId	chainId	macromoleculeType	chainLength	experimentalTechnique
1AKE_A	1AKE	A	Protein	214	X-ray
6S36_A	6S36	A	Protein	214	X-ray
6RZE_A	6RZE	A	Protein	214	X-ray
3HPR_A	3HPR	A	Protein	214	X-ray
1E4V_A	1E4V	A	Protein	214	X-ray
5EJE_A	5EJE	A	Protein	214	X-ray
	resolution	scopDomain	pfam		
1AKE_A	2.00	Adenylate kinase	Adenylate kinase, active site lid (ADK_lid)		
6S36_A	1.60	<NA>	Adenylate kinase, active site lid (ADK_lid)		
6RZE_A	1.69	<NA>	Adenylate kinase, active site lid (ADK_lid)		
3HPR_A	2.00	<NA>	Adenylate kinase, active site lid (ADK_lid)		
1E4V_A	1.85	Adenylate kinase	Adenylate kinase, active site lid (ADK_lid)		

```

5EJE_A      1.90      <NA> Adenylate kinase, active site lid (ADK_lid)
               ligandId                               ligandName
1AKE_A      AP5      BIS(ADENOSINE)-5'-PENTAPHOSPHATE
6S36_A CL (3),NA,MG (2) CHLORIDE ION (3),SODIUM ION,MAGNESIUM ION (2)
6RZE_A      NA (3),CL (2) SODIUM ION (3),CHLORIDE ION (2)
3HPR_A      AP5      BIS(ADENOSINE)-5'-PENTAPHOSPHATE
1E4V_A      AP5      BIS(ADENOSINE)-5'-PENTAPHOSPHATE
5EJE_A      AP5,CO BIS(ADENOSINE)-5'-PENTAPHOSPHATE,COBALT (II) ION
               source
1AKE_A      Escherichia coli
6S36_A      Escherichia coli
6RZE_A      Escherichia coli
3HPR_A      Escherichia coli K-12
1E4V_A      Escherichia coli
5EJE_A      Escherichia coli 0139:H28 str. E24377A

```

```

1AKE_A STRUCTURE OF THE COMPLEX BETWEEN ADENYLATE KINASE FROM ESCHERICHIA COLI AND THE INHIBIT
6S36_A
6RZE_A
3HPR_A
1E4V_A
5EJE_A

```

```

               citation rObserved  rFree
1AKE_A      Muller, C.W., et al. J Mol Biol (1992)    0.1960    NA
6S36_A      Rogne, P., et al. Biochemistry (2019)    0.1632  0.2356
6RZE_A      Rogne, P., et al. Biochemistry (2019)    0.1865  0.2350
3HPR_A      Schrank, T.P., et al. Proc Natl Acad Sci U S A (2009)  0.2100  0.2432
1E4V_A      Muller, C.W., et al. Proteins (1993)    0.1960    NA
5EJE_A      Kovermann, M., et al. Proc Natl Acad Sci U S A (2017)  0.1889  0.2358
               rWork spaceGroup
1AKE_A 0.1960 P 21 2 21
6S36_A 0.1594 C 1 2 1
6RZE_A 0.1819 C 1 2 1
3HPR_A 0.2062 P 21 21 2
1E4V_A 0.1960 P 21 2 21
5EJE_A 0.1863 P 21 2 21

```

Now we can download all these structures for further analysis with the `get.pdb()` function.

```

# Download related PDB files
files <- get.pdb(hits$ pdb.id, path="pdbs", split=TRUE, gzip=TRUE)

```

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1AKE.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6S36.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6RZE.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3HPR.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4V.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/5EJE.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4Y.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3X2S.pdb.gz exists. Skipping download


Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAP.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAM.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4K46.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3GMT.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4PZL.pdb.gz exists. Skipping download



Now we have all these related structures we can Align and Superpose

```
# Align related PDBs
pddb <- pddbalign(files, fit = TRUE, exefile="msa")
```

Reading PDB files:

```
pddb/split_chain/1AKE_A.pdb
pddb/split_chain/6S36_A.pdb
pddb/split_chain/6RZE_A.pdb
pddb/split_chain/3HPR_A.pdb
pddb/split_chain/1E4V_A.pdb
pddb/split_chain/5EJE_A.pdb
```

```

pdbs/split_chain/1E4Y_A.pdb
pdbs/split_chain/3X2S_A.pdb
pdbs/split_chain/6HAP_A.pdb
pdbs/split_chain/6HAM_A.pdb
pdbs/split_chain/4K46_A.pdb
pdbs/split_chain/3GMT_A.pdb
pdbs/split_chain/4PZL_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
.... PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
...

```

Extracting sequences

```

pdb/seq: 1   name: pdbs/split_chain/1AKE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 2   name: pdbs/split_chain/6S36_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 3   name: pdbs/split_chain/6RZE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 4   name: pdbs/split_chain/3HPR_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 5   name: pdbs/split_chain/1E4V_A.pdb
pdb/seq: 6   name: pdbs/split_chain/5EJE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 7   name: pdbs/split_chain/1E4Y_A.pdb
pdb/seq: 8   name: pdbs/split_chain/3X2S_A.pdb
pdb/seq: 9   name: pdbs/split_chain/6HAP_A.pdb
pdb/seq: 10  name: pdbs/split_chain/6HAM_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 11  name: pdbs/split_chain/4K46_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 12  name: pdbs/split_chain/3GMT_A.pdb
pdb/seq: 13  name: pdbs/split_chain/4PZL_A.pdb

```

pdbs

[Truncated_Name:10] 6HAM_A.pdb	RICQEDSRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD
[Truncated_Name:11] 4K46_A.pdb	RIAQDDCAKGFLLDGFPR TIPQADGLKEVGVVVDYVIEFD
[Truncated_Name:12] 3GMT_A.pdb	RLKEADCANGYLFDFGPR TIPQADAMKEAGVAIDYVLEID
[Truncated_Name:13] 4PZL_A.pdb	RISKNDCCNNGFLLDGVPR TIPQAQELDKLGVNIDYIVEVD
	*^ * ^* ** ***** ^ ^* ^** ^* *
	81 . . . 120
	121 . . . 160
[Truncated_Name:1] 1AKE_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG
[Truncated_Name:2] 6S36_A.pdb	VPDELIVDKIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG
[Truncated_Name:3] 6RZE_A.pdb	VPDELIVDAIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG
[Truncated_Name:4] 3HPR_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDGTG
[Truncated_Name:5] 1E4V_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG
[Truncated_Name:6] 5EJE_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG
[Truncated_Name:7] 1E4Y_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG
[Truncated_Name:8] 3X2S_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG
[Truncated_Name:9] 6HAP_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG
[Truncated_Name:10] 6HAM_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV KFNPPKVEGKDDVTG
[Truncated_Name:11] 4K46_A.pdb	VADSVIVERMAGRRAHLASGR TYHNVPKVEGKDDVTG
[Truncated_Name:12] 3GMT_A.pdb	VPFSEIIERMSGRRTHPASGR TYHV KFNPPKVEGKDDVTG
[Truncated_Name:13] 4PZL_A.pdb	VADNLLIERITGRRIH PASGR TYHTKFNPPKVADKDDVTG
	* ^^^ ^ *** * *** * ^***** *** **
	121 . . . 160
	161 . . . 200
[Truncated_Name:1] 1AKE_A.pdb	EELTTRKDDQEETVRKRLVEYHQMTAP LIGYYSKEAEAGN
[Truncated_Name:2] 6S36_A.pdb	EELTTRKDDQEETVRKRLVEYHQMTAP LIGYYSKEAEAGN
[Truncated_Name:3] 6RZE_A.pdb	EELTTRKDDQEETVRKRLVEYHQMTAP LIGYYSKEAEAGN
[Truncated_Name:4] 3HPR_A.pdb	EELTTRKDDQEETVRKRLVEYHQMTAP LIGYYSKEAEAGN
[Truncated_Name:5] 1E4V_A.pdb	EELTTRKDDQEETVRKRLVEYHQMTAP LIGYYSKEAEAGN
[Truncated_Name:6] 5EJE_A.pdb	EELTTRKDDQEECVRKRLVEYHQMTAP LIGYYSKEAEAGN
[Truncated_Name:7] 1E4Y_A.pdb	EELTTRKDDQEETVRKRLVEYHQMTAP LIGYYSKEAEAGN
[Truncated_Name:8] 3X2S_A.pdb	EELTTRKDDQEETVRKRLCEYHQMTAP LIGYYSKEAEAGN
[Truncated_Name:9] 6HAP_A.pdb	EELTTRKDDQEETVRKRLVEYHQMTAP LIGYYSKEAEAGN
[Truncated_Name:10] 6HAM_A.pdb	EELTTRKDDQEETVRKRLVEYHQMTAP LIGYYSKEAEAGN
[Truncated_Name:11] 4K46_A.pdb	EDLVIREDDKEETVLARLG VYHNQTAP LIAYYGKEAEAGN
[Truncated_Name:12] 3GMT_A.pdb	EPLVQRDDDKKEETVKKRLDV YE AQT KPLITYYGDWARRGA
[Truncated_Name:13] 4PZL_A.pdb	EPLITRTDDNEDTVKQRLSVYHAQTAK LIDFYRNFSSNT
	* * * * * ^* * * * * ^*
	161 . . . 200
	201 . . . 227
[Truncated_Name:1] 1AKE_A.pdb	T--KYAKVDGTPVAEVRADLEKILG-

```

[Truncated_Name:2]6S36_A.pdb      T--KYAKVDGTPVAEVRADLEKILG-
[Truncated_Name:3]6RZE_A.pdb      T--KYAKVDGTPVAEVRADLEKILG-
[Truncated_Name:4]3HPR_A.pdb      T--KYAKVDGTPVAEVRADLEKILG-
[Truncated_Name:5]1E4V_A.pdb      T--KYAKVDGTPVAEVRADLEKILG-
[Truncated_Name:6]5EJE_A.pdb      T--KYAKVDGTPVAEVRADLEKILG-
[Truncated_Name:7]1E4Y_A.pdb      T--KYAKVDGTPVAEVRADLEKILG-
[Truncated_Name:8]3X2S_A.pdb      T--KYAKVDGTPVAEVRADLEKILG-
[Truncated_Name:9]6HAP_A.pdb      T--KYAKVDGTPVCEVRADLEKILG-
[Truncated_Name:10]6HAM_A.pdb     T--KYAKVDGTPVCEVRADLEKILG-
[Truncated_Name:11]4K46_A.pdb     T--QYLKFDGTKAVAEVSAELEKALA-
[Truncated_Name:12]3GMT_A.pdb     E-----NGLKAPA-----YRKISG-
[Truncated_Name:13]4PZL_A.pdb     KIPKYIKINGDQAVEKVSQDIFDQLNK
                                     *
                                201      .      .      227

```

Call:

```
pdbaln(files = files, fit = TRUE, exefile = "msa")
```

Class:

```
pdbs, fasta
```

Alignment dimensions:

```
13 sequence rows; 227 position columns (204 non-gap, 23 gap)
```


```
+ attr: xyz, resno, b, chain, id, ali, resid, sse, call
```

Principal Component Analysis

```


# Perform PCA
pc.xray <- pca(pdbs)
plot(pc.xray)


```

```
pc1 <- mktrj(pc.xray, pc=1, file="pc_1.pdb")
```

Monomer





Dimer

8. Custom analysis of resulting models

```
results_dir <- "hivpr_dimer_23119"  
pdb_files <- list.files(path=results_dir,  
                        pattern="*.pdb",  
                        full.names = TRUE)
```

pdb_files

```
[1] "hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_001_alphafold2_multimer_v3_model_1_s  
[2] "hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_002_alphafold2_multimer_v3_model_5_s  
[3] "hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_003_alphafold2_multimer_v3_model_4_s  
[4] "hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_004_alphafold2_multimer_v3_model_2_s  
[5] "hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_005_alphafold2_multimer_v3_model_3_s
```

```
library(bio3d)
```

```
pdb<- pdbaln(pdb_files, fit=TRUE, exefile="msa")
```

Reading PDB files:

```
hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_001_alphafold2_multimer_v3_model_1_seed_0
hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_002_alphafold2_multimer_v3_model_5_seed_0
hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_003_alphafold2_multimer_v3_model_4_seed_0
hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_004_alphafold2_multimer_v3_model_2_seed_0
hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_005_alphafold2_multimer_v3_model_3_seed_0
.....
```

Extracting sequences

```
pdb/seq: 1 name: hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_001_alphafold2_multimer_v3_model_1_seed_0
pdb/seq: 2 name: hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_002_alphafold2_multimer_v3_model_5_seed_0
pdb/seq: 3 name: hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_003_alphafold2_multimer_v3_model_4_seed_0
pdb/seq: 4 name: hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_004_alphafold2_multimer_v3_model_2_seed_0
pdb/seq: 5 name: hivpr_dimer_23119/hivpr_dimer_23119_unrelaxed_rank_005_alphafold2_multimer_v3_model_3_seed_0
```

```
pdb<-
```

```
1 . . . 50
[Truncated_Name:1]hivpr_dime PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGI
[Truncated_Name:2]hivpr_dime PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGI
[Truncated_Name:3]hivpr_dime PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGI
[Truncated_Name:4]hivpr_dime PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGI
[Truncated_Name:5]hivpr_dime PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGI
*****
1 . . . 50

51 . . . 100
[Truncated_Name:1]hivpr_dime GGFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFP
[Truncated_Name:2]hivpr_dime GGFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFP
[Truncated_Name:3]hivpr_dime GGFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFP
[Truncated_Name:4]hivpr_dime GGFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFP
[Truncated_Name:5]hivpr_dime GGFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFP
*****
51 . . . 100
```

```

101 . . . . 150
[Truncated_Name:1]hivpr_dime QITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGIG
[Truncated_Name:2]hivpr_dime QITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGIG
[Truncated_Name:3]hivpr_dime QITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGIG
[Truncated_Name:4]hivpr_dime QITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGIG
[Truncated_Name:5]hivpr_dime QITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWPKPMIGGIG
*****
101 . . . . 150

151 . . . . 198
[Truncated_Name:1]hivpr_dime GFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNF
[Truncated_Name:2]hivpr_dime GFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNF
[Truncated_Name:3]hivpr_dime GFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNF
[Truncated_Name:4]hivpr_dime GFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNF
[Truncated_Name:5]hivpr_dime GFIKVRQYDQILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNF
*****
151 . . . . 198

```

Call:

```
pdbaln(files = pdb_files, fit = TRUE, exefile = "msa")
```

Class:

```
pdbs, fasta
```

Alignment dimensions:

```
5 sequence rows; 198 position columns (198 non-gap, 0 gap)
```

```
+ attr: xyz, resno, b, chain, id, ali, resid, sse, call
```

```
rd <- rmsd(pdbbs)
```


Warning in rmsd(pdbbs): No indices provided, using the 198 non NA positions

```
range(rd)
```

```
[1] 0.000 20.431
```

```
library(pheatmap)
```

```
colnames(rd) <- paste0("m",1:5)
rownames(rd) <- paste0("m",1:5)
pheatmap(rd)
```




```
pdb <- read.pdb("1hsg")
```

Note: Accessing on-line PDB file

Warning in get.pdb(file, path = tempdir(), verbose = FALSE):
/var/folders/97/bkcl6mms5d74hwhqjg57_51m0000gn/T//Rtmpvao892/1hsg.pdb exists.
Skipping download

```
plotb3(pdb$b, typ="l", lwd=2, sse=pdb)
points(pdb$b[2,], typ="l", col="red")
points(pdb$b[3,], typ="l", col="blue")
points(pdb$b[4,], typ="l", col="darkgreen")
points(pdb$b[5,], typ="l", col="orange")
abline(v=100, col="gray")
```



```
core <- core.find(pdb)
```

```
core size 197 of 198 vol = 6154.839
core size 196 of 198 vol = 5399.676
core size 195 of 198 vol = 5074.795
core size 194 of 198 vol = 4802.518
core size 193 of 198 vol = 4520.256
core size 192 of 198 vol = 4305.362
core size 191 of 198 vol = 4089.792
core size 190 of 198 vol = 3886.145
core size 189 of 198 vol = 3758.321
core size 188 of 198 vol = 3620.18
core size 187 of 198 vol = 3496.698
core size 186 of 198 vol = 3389.985
core size 185 of 198 vol = 3320.114
core size 184 of 198 vol = 3258.683
core size 183 of 198 vol = 3208.591
core size 182 of 198 vol = 3156.736
core size 181 of 198 vol = 3141.668
core size 180 of 198 vol = 3136.574
core size 179 of 198 vol = 3155.52
core size 178 of 198 vol = 3185.362
```

core size 177 of 198	vol = 3204.487
core size 176 of 198	vol = 3211.978
core size 175 of 198	vol = 3234.993
core size 174 of 198	vol = 3244.062
core size 173 of 198	vol = 3237.845
core size 172 of 198	vol = 3218.77
core size 171 of 198	vol = 3180.743
core size 170 of 198	vol = 3130.369
core size 169 of 198	vol = 3067.881
core size 168 of 198	vol = 2989.546
core size 167 of 198	vol = 2928.272
core size 166 of 198	vol = 2851.193
core size 165 of 198	vol = 2780.877
core size 164 of 198	vol = 2708.433
core size 163 of 198	vol = 2636.516
core size 162 of 198	vol = 2563.25
core size 161 of 198	vol = 2478.024
core size 160 of 198	vol = 2404.793
core size 159 of 198	vol = 2330.997
core size 158 of 198	vol = 2250.477
core size 157 of 198	vol = 2159.432
core size 156 of 198	vol = 2070.759
core size 155 of 198	vol = 1983.579
core size 154 of 198	vol = 1917.913
core size 153 of 198	vol = 1842.556
core size 152 of 198	vol = 1775.398
core size 151 of 198	vol = 1695.133
core size 150 of 198	vol = 1632.173
core size 149 of 198	vol = 1570.391
core size 148 of 198	vol = 1497.238
core size 147 of 198	vol = 1434.802
core size 146 of 198	vol = 1367.706
core size 145 of 198	vol = 1302.596
core size 144 of 198	vol = 1251.985
core size 143 of 198	vol = 1207.976
core size 142 of 198	vol = 1167.112
core size 141 of 198	vol = 1118.27
core size 140 of 198	vol = 1081.664
core size 139 of 198	vol = 1029.75
core size 138 of 198	vol = 981.766
core size 137 of 198	vol = 944.446
core size 136 of 198	vol = 899.224
core size 135 of 198	vol = 859.402

core size 134 of 198 vol = 814.694
core size 133 of 198 vol = 771.862
core size 132 of 198 vol = 733.807
core size 131 of 198 vol = 702.053
core size 130 of 198 vol = 658.757
core size 129 of 198 vol = 622.574
core size 128 of 198 vol = 578.29
core size 127 of 198 vol = 543.07
core size 126 of 198 vol = 510.934
core size 125 of 198 vol = 481.595
core size 124 of 198 vol = 464.672
core size 123 of 198 vol = 451.721
core size 122 of 198 vol = 430.417
core size 121 of 198 vol = 409.141
core size 120 of 198 vol = 378.942
core size 119 of 198 vol = 348.325
core size 118 of 198 vol = 324.738
core size 117 of 198 vol = 312.394
core size 116 of 198 vol = 300.89
core size 115 of 198 vol = 279.976
core size 114 of 198 vol = 263.434
core size 113 of 198 vol = 250.263
core size 112 of 198 vol = 229.592
core size 111 of 198 vol = 209.929
core size 110 of 198 vol = 196.379
core size 109 of 198 vol = 180.628
core size 108 of 198 vol = 167.088
core size 107 of 198 vol = 155.875
core size 106 of 198 vol = 142.595
core size 105 of 198 vol = 128.924
core size 104 of 198 vol = 114.054
core size 103 of 198 vol = 100.936
core size 102 of 198 vol = 90.431
core size 101 of 198 vol = 81.972
core size 100 of 198 vol = 74.017
core size 99 of 198 vol = 66.855
core size 98 of 198 vol = 59.525
core size 97 of 198 vol = 52.263
core size 96 of 198 vol = 43.699
core size 95 of 198 vol = 35.813
core size 94 of 198 vol = 28.888
core size 93 of 198 vol = 20.692
core size 92 of 198 vol = 14.975

```

core size 91 of 198  vol = 9.146
core size 90 of 198  vol = 5.232
core size 89 of 198  vol = 3.53
core size 88 of 198  vol = 2.657
core size 87 of 198  vol = 1.998
core size 86 of 198  vol = 1.333
core size 85 of 198  vol = 1.141
core size 84 of 198  vol = 1.012
core size 83 of 198  vol = 0.891
core size 82 of 198  vol = 0.749
core size 81 of 198  vol = 0.618
core size 80 of 198  vol = 0.538
core size 79 of 198  vol = 0.479
FINISHED: Min vol ( 0.5 ) reached

```

```
core.inds <- print(core, vol=0.5)
```


```

# 80 positions (cumulative volume <= 0.5 Angstrom^3)
  start end length
1    10  25     16
2    27  48     22
3    53  94     42

```

```
xyz <- pdbfit(pdb, core.inds, outpath="corefit_structures")
```


Core superposed structure



```
rd <- rmsd(xyz)
```


Warning in rmsd(xyz): No indices provided, using the 198 non NA positions

```
colnames(rd) <- paste0("m",1:5)  
rownames(rd) <- paste0("m",1:5)  
pheatmap(rd)
```



```
rf <- rmsf(xyz)

plotb3(rf, sse=pdb)
abline(v=100, col="gray", ylab="RMSF")
```



Predicted Alignment Error for domains

```
library(jsonlite)

pae_files <- list.files(path=results_dir,
                        pattern=".*model.*\\.json",
                        full.names = TRUE)
```

1st and 5th files for example

```
pae1 <- read_json(pae_files[1],simplifyVector = TRUE)
pae5 <- read_json(pae_files[5],simplifyVector = TRUE)

attributes(pae1)
```

```
$names
[1] "plddt"  "max_pae" "pae"     "ptm"     "iptm"
```

```
# Per-residue pLDDT scores
# same as B-factor of PDB..
```


```
head(pae1$plddt)
```

```
[1] 92.50 96.56 96.94 96.62 97.69 96.00
```


```
pae1$max_pae
```

```
[1] 15.54688
```

```
plot.dmat(pae1$pae,  
          xlab="Residue Position (i)",  
          ylab="Residue Position (j)")
```




```
plot.dmat(pae5$pae,  
          xlab="Residue Position (i)",  
          ylab="Residue Position (j)",  
          grid.col = "black",  
          zlim=c(0,30))
```



Model 1 plot with the same Z-range

```
plot.dmat(pae1$pae,
          xlab="Residue Position (i)",
          ylab="Residue Position (j)",
          grid.col = "black",
          zlim=c(0,30))
```



Residue conservation from alignment file

```
aln_file <- list.files(path=results_dir,
                       pattern=".a3m$",
                       full.names = TRUE)
aln_file
```

```
[1] "hivpr_dimer_23119/hivpr_dimer_23119.a3m"
```

```
aln <- read.fasta(aln_file[1], to.upper = TRUE)
```

```
[1] " ** Duplicated sequence id's: 101 **"
```

```
[2] " ** Duplicated sequence id's: 101 **"
```


Amount of sequences in this alignment

```
dim(aln$ali)
```

```
[1] 5378 132
```


Score of residue conservation

```
sim <- conserv(aln)
plotb3(sim[1:99], sse=trim.pdb(pdb, chain="A"))
```



Conserved Active Site residue D25, T26, G27, A28

```
con <- consensus(aln, cutoff = 0.9)
con$seq
```

```
[1] "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-"
[19] "-" "-" "-" "-" "-" "-" "D" "T" "G" "A" "-" "-" "-" "-" "-" "-" "-"
[37] "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-"
[55] "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-"
[73] "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-"
[91] "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-"
[109] "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-" "-"
[127] "-" "-" "-" "-" "-" "-"
```

Mapping the conservation score to the Occupancy column of a PDB file

```
m1.pdb <- read.pdb(pdb_files[1])  
occ <- vec2resno(c(sim[1:99], sim[1:99]), m1.pdb$atom$resno)  
write.pdb(m1.pdb, o=occ, file="m1_conserv.pdb")
```

