
# 11: Managing Multiple Nodes



This section's goal is to have you bootstrap another node, this time a web server, and add it to the proxy members.

# Slide 2

# **Objectives**



After completing this module, you should be able to

- > Bootstrap, update the run\_list, and run chef-client on a node
- > Append values to an attribute within a recipe
- Version a cookbook and upload it to the Chef Server


©2015 Chef Software Inc.

11-2



In this module you will learn how to bootstrap, update the run list, and run chef-client on a node. You will also learn how to update a default attribute within a recipe, version and upload a cookbook.

# Slide 3




After completing this module, you will have configured three nodes:

Node 1: A web server

Node 2: The proxy server

Node 3: Another web server


# Slide 4



Now its time to create a third node. The third node will be the second web server node.


We will provide you with a new node for the following exercise.

#### Slide 5



Bootstrap the new node and name it node3.

# Slide 6



Verify that you bootstrapped the node.

# Slide 7

```
Lab: Set the Run List


$ knife node run_list add node3 "recipe[apache]"

node3:
    run_list: recipe[apache]

©2015 Chel Software Inc.
```


Set the run list for this node by running the apache cookbook's default recipe.

#### Slide 8



Apply that run list by logging into that node and running sudo chef-client or remotely administer the node with the 'knife ssh' command as shown here.

# Slide 9




Verify that the node serves up the default html page that contains the node's internal IP address and hostname.

# Slide 10



Now that you have the third node. It is time to add that node to the member's list for the proxy server.

# Slide 11



If you use 'knife node show' to display the 'cloud' attribute for node3, you will see the local, private, and public connection information.

Capture and write down the public hostname and the public ipv4 address of node3. You will need this in the recipe you are going to write.

#### Slide 12

Add the second web server (node3) to the Proxy server's members list. You may need to run 'knife node show node3 -a cloud' to get the hostname and ipaddress values.

# Slide 13

```
Lab: Update the Version

-/chef-repo/cookbooks/myhaproxy/metadata.rb

name 'myhaproxy'
maintainer 'The Authors'
maintainer_email 'you@example.com'
license 'all_rights'
description 'Installs/Configures myhaproxy'
long_description 'Installs/Configures myhaproxy'
version '0.2.0'

depends 'haproxy', '~> 1.6.6'
```


Update the version number in myhaproxy cookbook's metadata.

# Slide 14



Change into the 'myhaproxy' cookbook directory and then run 'berks install' to install any dependencies for the 'myhaproxy' cookbook.

# Slide 15



Run 'berks upload' to upload the myhaproxy cookbook to Chef Server.

#### Slide 16

```
Lab: Converge the Cookbook
       knife ssh "*:*" -x USERNAME -P PWD "sudo chef-client"
    ec2-54-210-192-12.compute-1.amazonaws.com Starting Chef Client, version 12.3.0
    ec2-54-175-46-24.compute-1.amazonaws.com Starting Chef Client, version 12.3.0
    ec2-54-210-86-164.compute-1.amazonaws.com Starting Chef Client, version 12.3.0
    ec2-54-210-192-12.compute-1.amazonaws.com resolving cookbooks for run list:
    ec2-54-175-46-24.compute-1.amazonaws.com resolving cookbooks for run list:
    ["apache"]
    ec2-54-175-46-24.compute-1.amazonaws.com Synchronizing Cookbooks:
    ec2-54-175-46-24.compute-1.amazonaws.com - apache
    ec2-54-175-46-24.compute-1.amazonaws.com Compiling Cookbooks...
    ec2-54-210-192-12.compute-1.amazonaws.com Synchronizing Cookbooks:
    ec2-54-175-46-24.compute-1.amazonaws.com Converging 3 resources
    ec2-54-175-46-24.compute-1.amazonaws.com Recipe: apache::server
    ec2-54-210-192-12.compute-1.amazonaws.com - build-essential
©2015 Chef Software Inc.
                                        11-16
```

Converge the cookbook by logging into that node and running 'sudo chef-client' or remotely administer the node with the 'knife ssh' command as shown here.

Within the output you should see the haproxy configuration file will update with a new entry that contains the information of the second member (node3).

#### Slide 17




Point a web browser to the URL of your Proxy server and then click Refresh a few times. You should see each of your web server's HTML page as the Proxy server switches between each web server.

This is not a very scientific way of seeing that the proxy server is balancing requests between these two web nodes.

# Slide 18



# Slide 19



Answer these questions.

With your answers, turn to another person and alternate asking each other asking these questions and sharing your answers.

# Slide 20



# Slide 21

