MCCOO2759

Device Information

Product Name: HP Color LaserJet MFP E57540
Nickname: HP Color LaserJet MFP E57540
Model Number: 3GY25A
DC Controller Version: 4.138
Product Serial Number: MXBCP150BJ
Formatter Number: 2A708BZ
CPB: 3.096
SCB: xxxxFA1744BR 1.0
Firmware Bundle Version: 5.1
Firmware Revision: 2501124_004337
Firmware Datecode: 20201209
HP FutureSmart Level: HP FutureSmart 5
NFC revision: Not Installed
Service ID: 31043
Document Feeder Kit Interval: 75000
Pages Since Last Doc Feeder Maintenance: 12
PS Wait Time-out: 300 seconds
Engine Cycles*: 52
Color Engine Cycles*: 23
Supply Protection: Off
Cartridge Policy: Off
Cartridge Index: NHCC MDGM
*Not weighted for billing

Installed Personalities and Options

PCL: 20010402
PCLXL: 20010402
POSTSCRIPT: 20010402
PDF: 20130901
AirPrint: 2040201
PWGRASTER: 2040201
TIFF: 20150522
Internal Disk: Hard Disk: Enabled
   Serial Number: 90FRTQ4TT
   Model: TOSHIBA MQ01ABU050W
   Capacity: 476940 MB
   Hard Disk Encryption Status: Encrypted
Internal Fax: Ver11.4A
Embedded Jetdirect Page: 10.95.0.194
LDAP Gateway: 0.0.0.0
Digital Send Advanced
Custom Print Quality Solutions: Not Installed

HP Web Services

HP Web Services: Disabled
ePrint: Disabled

Color Density

	C	M	Y	K
Highlights	0	0	0	0
Midtones	0	0	0	0
Shadows	0	0	0	0

Customized Color Themes

Color Theme	Date Modified	Description

Calibration Information

Last CPR (Engine Cycles): 0
Last CPR: 2/13/2021 12:04:12 AM
Last DMax/DHalf (Engine Cycles): 0
Last DMax/DHalf: 2/13/2021 12:04:12 AM

Memory

Total RAM: 1792 MB

Event Log

Number of Entries in Use: 2
Three Most Recent Entries:

Number	Cycles	Event
2	0	10.99.40
1	3	10.23.59

Security

Hard Disk Encryption Status:
   Internal Disk: Encrypted
Job Data Encryption Status: Encrypted
Job Data Persistence: Persistent (not volatile)
File Erase Mode: Non-Secure Fast Erase (No
overwrite)
Control Panel Password: Disabled
Support Key: UMKH-DE19-W4FH
Host USB plug and play: Enabled
Device USB: Disabled
HP SureStart: Present
Whitelisting: Present

Paper Trays and Options

Default Paper Size: Letter (8.5x11)
Tray 1 Size: Any Size
Tray 1 Type: Any Type
Tray 2 Size: Letter (8.5x11)
Tray 2 Type: Plain
Duplex Unit
Standard bin: 250 Sheets

--------- General Information ----------
Status: I/O Card Ready

Model Number: J8032E
Hardware Address: 3024A9C5B886
Firmware Version: JSI25010008
LAA: 3024A9C5B886
Port Config: 100TX FULL
Auto Negotiation: On
Manufacturing ID: 6047604700****-W
Date Manufactured: 11/2020

Google Cloud Print: Not Registered
GCP Name:
HP Color LaserJet MFP E57540 [C5B886]

---------- Security Settings -----------
802.1X: Not Specified
IPsec: Disabled
Secure Web: HTTPS Required
Cert Expires: 2026-02-12 00:02 UTC
SNMP Versions: 1;2
SNMP Set Cmty Name: Not Specified
SNMP Get Cmty Name:Not Specified/Default
Access List: Not Specified
Admin Password: Not Specified
Announcement Agent: Failed
FIPS: Disabled
DNS Protected Mode: No

---------- Network Statistics ----------
Total Packets Received: 1024
Unicast Packets Received: 0
Bad Packets Received: 30
Total Packets Transmitted: 36
Framing Errors Received: 0
Unsendable Packets: 0
Transmit Collisions: 0
Transmit Late Collisions: 0
Last Wake:
000000A000000000000000000000000000
00000000000000000000000000000000000
00000000000000000000000000000000002

----------------- TCP/IP -----------------
IPv4:   Enabled
IPv6:   Enabled
Host Name: NPIC5B886
IPv4 Domain Name: Not Specified
IPv6 Domain Name: Not Specified
Primary DNS Server: Not Specified
Secondary DNS Server: Not Specified
DNS(IPv6):
Not Specified
Not Specified
WINS Server: Not Specified
TCP Idle Timeout: 270 sec

----------------- IPv4 -----------------
Status: Initializing
  BOOTP/DHCP IN PROGRESS

IP Address: 0.0.0.0
Subnet Mask: 0.0.0.0
Default Gateway: 0.0.0.0
Config By: Not Configured
BOOTP/DHCP Server: 0.0.0.0
TFTP Server: 0.0.0.0
Bonjour Service Name:
HP Color LaserJet MFP E57540 [C5B886]

----------------- IPv6 -----------------
Status: Ready

Link-Local:
fe80::3224:a9ff:fec5:b886
Stateless:
Not Configured

DHCPv6:
Not Configured
Manual:
Not Configured

Hardware Information

Product: LSI CFAX34 Ver11.4A (May 9 2017) +V34Fax+Class 2.0 ECM+Sphone
Modem Firmware Version: Ver11.4A
Modem Status: Operational/Enabled

Fax Information

Fax Job Count: 3

Fax Setup Settings

Country/Region: United States
Current Date: Feb 16, 2021
Current Time: 12:16 AM
Phone Number: 02
Company Name: 01
Fax Archive: Disabled
Fax Forwarding: Disabled
Fax Forwarding Method: Internal Modem
Forward Fax Number:
Fax Dial Volume: Soft
Ringer Volume: Soft
Error Correction: Enabled
JBIG Compression: Disabled
Ring Interval: 600
Ring Frequency: 68
Fax Number Confirmation: Disabled
Fax V.34: Enabled

Fax Send Settings

Fax Send: Enabled
Default Resolution: Standard (100 x 200dpi)
Fax Header: Prepend
Dialing Mode: Tone
Redial on Error: 2
Redial on Busy: 3
Redial on No Answer: Never
Redial Interval: 5
Detect Dial Tone: Disabled
Fax Send Speed: Medium (v.17 - 14.4k)
Dialing Prefix: Off
PC Fax Send: Enabled
Billing Code: Off
Billing Code Digits: 1

Fax Receive Settings

Fax Receive: Enabled
Fax Receive Speed: Medium (v.17 - 14.4k)
Rings to Answer: 1
Stamp Received Faxes: Off
Fit to Page: Enabled
Paper Selection: PrinterSelect
Output Bin: Output Bin 1, 250 Sheets, Standard bin
Fax Printing Schedule: Always print faxes
Sides: Simplex
Pages flip up: Unchecked

Fax Report Setting

Sent Fax Report: Never automatically generate
Received Fax Report: Never automatically generate
Fax T.30 Tracer Report: Never automatically print

Thumbnail on Report: Off
Thumbnail on Report: Off