$\mu' = -\frac{2}{3}\mu + \kappa$

§B.1 NEWTON'S LAW OF VISCOSITY

$$[\tau = +\mu(\nabla v + (\nabla v)^\dagger) + (\tfrac{2}{3}\mu + \kappa)(\nabla \cdot v)\delta]$$

Cartesian coordinates (x, y, z):

$$\tau_{xx} = +\mu\left[2\frac{\partial v_x}{\partial x}\right] + (\tfrac{2}{3}\mu + \kappa)(\nabla \cdot \mathbf{v})$$

$$\tau_{yy} = +\mu\left[2\frac{\partial v_y}{\partial y}\right] + (\tfrac{2}{3}\mu + \kappa)(\nabla \cdot \mathbf{v})$$

$$\tau_{zz} = +\mu\left[2\frac{\partial v_z}{\partial z}\right] + (\tfrac{2}{3}\mu + \kappa)(\nabla \cdot \mathbf{v})$$

$$\tau_{xy} = \tau_{yx} = +\mu\left[\frac{\partial v_y}{\partial x} + \frac{\partial v_x}{\partial y}\right]$$

$$\tau_{yz} = \tau_{zy} = +\mu\left[\frac{\partial v_z}{\partial y} + \frac{\partial v_y}{\partial z}\right]$$

$$\tau_{zx} = \tau_{xz} = +\mu\left[\frac{\partial v_x}{\partial z} + \frac{\partial v_z}{\partial x}\right]$$

$$(\nabla \cdot \mathbf{v}) = \frac{\partial v_x}{\partial x} + \frac{\partial v_y}{\partial y} + \frac{\partial v_z}{\partial z}$$

Cylindrical coordinates (r, θ, z):

$$\tau_{rr} = +\mu\left[2\frac{\partial v_r}{\partial r}\right] + (\tfrac{2}{3}\mu + \kappa)(\nabla \cdot \mathbf{v})$$

$$\tau_{\theta\theta} = +\mu\left[2\left(\frac{1}{r}\frac{\partial v_\theta}{\partial \theta} + \frac{v_r}{r}\right)\right] + (\tfrac{2}{3}\mu + \kappa)(\nabla \cdot \mathbf{v})$$

$$\tau_{zz} = +\mu\left[2\frac{\partial v_z}{\partial z}\right] + (\tfrac{2}{3}\mu + \kappa)(\nabla \cdot \mathbf{v})$$

$$\tau_{r\theta} = \tau_{\theta r} = +\mu\left[r\frac{\partial}{\partial r}\left(\frac{v_\theta}{r}\right) + \frac{1}{r}\frac{\partial v_r}{\partial \theta}\right]$$

$$\tau_{\theta z} = \tau_{z\theta} = +\mu\left[\frac{1}{r}\frac{\partial v_z}{\partial \theta} + \frac{\partial v_\theta}{\partial z}\right]$$

$$\tau_{zr} = \tau_{rz} = +\mu\left[\frac{\partial v_r}{\partial z} + \frac{\partial v_z}{\partial r}\right]$$

$$(\nabla \cdot \mathbf{v}) = \frac{1}{r}\frac{\partial}{\partial r}(rv_r) + \frac{1}{r}\frac{\partial v_\theta}{\partial \theta} + \frac{\partial v_z}{\partial z}$$

Spherical coordinates (r, θ, ϕ):

$$\tau_{rr} = +\mu\left[2\frac{\partial v_r}{\partial r}\right] + (\tfrac{2}{3}\mu + \kappa)(\nabla \cdot \mathbf{v})$$

$$\tau_{\theta\theta} = +\mu\left[2\left(\frac{1}{r}\frac{\partial v_\theta}{\partial \theta} + \frac{v_r}{r}\right)\right] + (\tfrac{2}{3}\mu + \kappa)(\nabla \cdot \mathbf{v})$$

$$\tau_{\phi\phi} = +\mu\left[2\left(\frac{1}{r \sin \theta}\frac{\partial v_\phi}{\partial \phi} + \frac{v_r + v_\theta \cot \theta}{r}\right)\right] + (\tfrac{2}{3}\mu + \kappa)(\nabla \cdot \mathbf{v})$$

$$\tau_{r\theta} = \tau_{\theta r} = +\mu\left[r\frac{\partial}{\partial r}\left(\frac{v_\theta}{r}\right) + \frac{1}{r}\frac{\partial v_r}{\partial \theta}\right]$$

$$\tau_{\theta\phi} = \tau_{\phi\theta} = +\mu\left[\frac{\sin \theta}{r}\frac{\partial}{\partial \theta}\left(\frac{v_\phi}{\sin \theta}\right) + \frac{1}{r \sin \theta}\frac{\partial v_\theta}{\partial \phi}\right]$$

$$\tau_{\phi r} = \tau_{r\phi} = +\mu\left[\frac{1}{r \sin \theta}\frac{\partial v_r}{\partial \phi} + r\frac{\partial}{\partial r}\left(\frac{v_\phi}{r}\right)\right]$$

$$(\nabla \cdot \mathbf{v}) = \frac{1}{r^2}\frac{\partial}{\partial r}(r^2 v_r) + \frac{1}{r \sin \theta}\frac{\partial}{\partial \theta}(v_\theta \sin \theta) + \frac{1}{r \sin \theta}\frac{\partial v_\phi}{\partial \phi}$$

---

[a] When the fluid is assumed to have constant density, the term containing $(\nabla \cdot \mathbf{v})$ may be omitted. For monatomic gases at low density, the dilatational viscosity κ is zero.

§B.5 THE EQUATION OF MOTION IN TERMS OF τ

$$[\rho D\mathbf{v}/Dt = -\nabla p + [\nabla \cdot \boldsymbol{\tau}] + \rho \mathbf{g}]$$

Cartesian coordinates (x, y, z):[a]

$$\rho\left(\frac{\partial v_x}{\partial t} + v_x \frac{\partial v_x}{\partial x} + v_y \frac{\partial v_x}{\partial y} + v_z \frac{\partial v_x}{\partial z}\right) = -\frac{\partial p}{\partial x} + \left[\frac{\partial}{\partial x}\tau_{xx} + \frac{\partial}{\partial y}\tau_{yx} + \frac{\partial}{\partial z}\tau_{zx}\right] + \rho g_x \quad \text{(B.5-1)}$$

$$\rho\left(\frac{\partial v_y}{\partial t} + v_x \frac{\partial v_y}{\partial x} + v_y \frac{\partial v_y}{\partial y} + v_z \frac{\partial v_y}{\partial z}\right) = -\frac{\partial p}{\partial y} + \left[\frac{\partial}{\partial x}\tau_{xy} + \frac{\partial}{\partial y}\tau_{yy} + \frac{\partial}{\partial z}\tau_{zy}\right] + \rho g_y \quad \text{(B.5-2)}$$

$$\rho\left(\frac{\partial v_z}{\partial t} + v_x \frac{\partial v_z}{\partial x} + v_y \frac{\partial v_z}{\partial y} + v_z \frac{\partial v_z}{\partial z}\right) = -\frac{\partial p}{\partial z} + \left[\frac{\partial}{\partial x}\tau_{xz} + \frac{\partial}{\partial y}\tau_{yz} + \frac{\partial}{\partial z}\tau_{zz}\right] + \rho g_z \quad \text{(B.5-3)}$$

[a] These equations have been written without making the assumption that τ is symmetric. This means, for example, that when the usual assumption is made that the stress tensor is symmetric, τ_{xy} and τ_{yx} may be interchanged.

Cylindrical coordinates (r, θ, z):[b]

$$\rho\left(\frac{\partial v_r}{\partial t} + v_r \frac{\partial v_r}{\partial r} + \frac{v_\theta}{r}\frac{\partial v_r}{\partial \theta} + v_z \frac{\partial v_r}{\partial z} - \frac{v_\theta^2}{r}\right) = -\frac{\partial p}{\partial r} + \left[\frac{1}{r}\frac{\partial}{\partial r}(r\tau_{rr}) + \frac{1}{r}\frac{\partial}{\partial \theta}\tau_{\theta r} + \frac{\partial}{\partial z}\tau_{zr} - \frac{\tau_{\theta\theta}}{r}\right] + \rho g_r \quad \text{(B.5-4)}$$

$$\rho\left(\frac{\partial v_\theta}{\partial t} + v_r \frac{\partial v_\theta}{\partial r} + \frac{v_\theta}{r}\frac{\partial v_\theta}{\partial \theta} + v_z \frac{\partial v_\theta}{\partial z} + \frac{v_r v_\theta}{r}\right) = -\frac{1}{r}\frac{\partial p}{\partial \theta} + \left[\frac{1}{r^2}\frac{\partial}{\partial r}(r^2\tau_{r\theta}) + \frac{1}{r}\frac{\partial}{\partial \theta}\tau_{\theta\theta} + \frac{\partial}{\partial z}\tau_{z\theta} + \frac{\tau_{\theta r} - \tau_{r\theta}}{r}\right] + \rho g_\theta \quad \text{(B.5-5)}$$

$$\rho\left(\frac{\partial v_z}{\partial t} + v_r \frac{\partial v_z}{\partial r} + \frac{v_\theta}{r}\frac{\partial v_z}{\partial \theta} + v_z \frac{\partial v_z}{\partial z}\right) = -\frac{\partial p}{\partial z} + \left[\frac{1}{r}\frac{\partial}{\partial r}(r\tau_{rz}) + \frac{1}{r}\frac{\partial}{\partial \theta}\tau_{\theta z} + \frac{\partial}{\partial z}\tau_{zz}\right] + \rho g_z \quad \text{(B.5-6)}$$

[b] These equations have been written without making the assumption that τ is symmetric. This means, for example, that when the usual assumption is made that the stress tensor is symmetric, $\tau_{r\theta} - \tau_{\theta r} = 0$.

Spherical coordinates (r, θ, ϕ):[c]

$$\rho\left(\frac{\partial v_r}{\partial t} + v_r \frac{\partial v_r}{\partial r} + \frac{v_\theta}{r}\frac{\partial v_r}{\partial \theta} + \frac{v_\phi}{r\sin\theta}\frac{\partial v_r}{\partial \phi} - \frac{v_\theta^2 + v_\phi^2}{r}\right) = -\frac{\partial p}{\partial r}$$

$$+ \left[\frac{1}{r^2}\frac{\partial}{\partial r}(r^2\tau_{rr}) + \frac{1}{r\sin\theta}\frac{\partial}{\partial \theta}(\tau_{\theta r}\sin\theta) + \frac{1}{r\sin\theta}\frac{\partial}{\partial \phi}\tau_{\phi r} - \frac{\tau_{\theta\theta} + \tau_{\phi\phi}}{r}\right] + \rho g_r \quad \text{(B.5-7)}$$

$$\rho\left(\frac{\partial v_\theta}{\partial t} + v_r \frac{\partial v_\theta}{\partial r} + \frac{v_\theta}{r}\frac{\partial v_\theta}{\partial \theta} + \frac{v_\phi}{r\sin\theta}\frac{\partial v_\theta}{\partial \phi} + \frac{v_r v_\theta - v_\phi^2 \cot\theta}{r}\right) = -\frac{1}{r}\frac{\partial p}{\partial \theta}$$

$$+ \left[\frac{1}{r^3}\frac{\partial}{\partial r}(r^3\tau_{r\theta}) + \frac{1}{r\sin\theta}\frac{\partial}{\partial \theta}(\tau_{\theta\theta}\sin\theta) + \frac{1}{r\sin\theta}\frac{\partial}{\partial \phi}\tau_{\phi\theta} + \frac{(\tau_{\theta r} - \tau_{r\theta}) - \tau_{\phi\phi}\cot\theta}{r}\right] + \rho g_\theta \quad \text{(B.5-8)}$$

$$\rho\left(\frac{\partial v_\phi}{\partial t} + v_r \frac{\partial v_\phi}{\partial r} + \frac{v_\theta}{r}\frac{\partial v_\phi}{\partial \theta} + \frac{v_\phi}{r\sin\theta}\frac{\partial v_\phi}{\partial \phi} + \frac{v_\phi v_r + v_\theta v_\phi \cot\theta}{r}\right) = -\frac{1}{r\sin\theta}\frac{\partial p}{\partial \phi}$$

$$+ \left[\frac{1}{r^3}\frac{\partial}{\partial r}(r^3\tau_{r\phi}) + \frac{1}{r\sin\theta}\frac{\partial}{\partial \theta}(\tau_{\theta\phi}\sin\theta) + \frac{1}{r\sin\theta}\frac{\partial}{\partial \phi}\tau_{\phi\phi} + \frac{(\tau_{\phi r} - \tau_{r\phi}) + \tau_{\phi\theta}\cot\theta}{r}\right] + \rho g_\phi \quad \text{(B.5-9)}$$

[c] These equations have been written without making the assumption that τ is symmetric. This means, for example, that when the usual assumption is made that the stress tensor is symmetric, $\tau_{r\theta} - \tau_{\theta r} = 0$.