



Project: Donate Blood Save Life

Course Code: CSE435

Section: 02

Submitted To:

Dr. Shamim H Ripon

Professor

Department of Computer Science & Engineering

Submitted by:

Name:

ID:

Ehsanul Haque

2018-1-68-079

Istiak Ahmed

2016-3-60-042


Md.Tauhidul islam Bhuiyan

2016-2-60-036

Introduction:

Donor seeker is an online platform for all kind of people who need emergency blood. This is not like traditional blood banks, it is a place of regular blood donor. The blood seeker will be able to search blood donor by his/her(blood seeker) location, the blood seeker will be able to search by two available options such as he/she can post to forum by his/her certain location, donor will get notification according to certain location. Another option is blood seeker will see the list of all donors by blood groups and locations, blood seeker will be able to call or notify one by one from the list of donors...

Sequence Diagram(1) for Admin to Database :



Promela Code(1) :

```
mtype {MSG, ACK};  
chan toAdmin = [1] of {mtype, bit};  
chan toDatabase = [1] of {mtype, bit};  
  
proctype Admin(chan in, out)  
{  
    bit sendbit, rcvbit;  
    do  
        :: out ! MSG, sendbit ->  
            in ? ACK, rcvbit;  
            if  
                :: rcvbit == sendbit ->  
                    sendbit = 1-sendbit;  
                :: else  
                    fi  
            od  
    }  
  
proctype Database(chan in, out)  
{  
    bit rcvbit;  
    do  
        :: in ? MSG(rcvbit) ->  
            out ! ACK(rcvbit);
```


```


    od
}


init
{
    run Admin(toAdmin, toDatabase);
    run Database(toDatabase, toAdmin);
}

```


Automata View :









Simulation :





Sequence Diagram(2) for Donor sign up:



Promela Code(2)

```
mtype {MSG, ACK};  
chan toDonor = [1] of {mtype, bit};  
chan toController = [1] of {mtype, bit};  
  
proctype Donor(chan in, out)  
{  
    bit sendbit, rcvbit;  
    do  
        :: out ! MSG, sendbit ->
```

```

        in ? ACK, recvbit;
    if
        :: recvbit == sendbit ->
            sendbit = 1-sendbit;
        :: else
    fi
od
}

```

```

proctype Controller(chan in, out)
{
    bit recvbit;
    do
        :: in ? MSG(recvbit) ->
            out ! ACK(recvbit);
    od
}


```


```


init
{
    run Donor(toDonor, toController);
    run Controller(toController, toDonor);
}

```

Automata View :







Simulation:

