

Greetings agent

```
# You may need to add your working directory to the Python path. To do so,
uncomment the following lines of code
# import sys
# sys.path.append("/Path/to/directory/agentic-framework") # Replace with
your directory path
```

```
import logging
```

```
from baf.core.agent import Agent
from baf.core.session import Session
from baf.exceptions.logger import logger
```

```
# Configure the logging module (optional)
logger.setLevel(logging.INFO)
```

```
# Create the agent
agent = Agent('greetings_agent') # set persist_sessions=True to enable
session persistence across restarts
# Load agent properties stored in a dedicated file
agent.load_properties('config.yaml')
# Define the platform your agent will use
# set authenticate_users=True to enable user authentication and previous
history loading in the UI
websocket_platform = agent.use_websocket_platform(use_ui=True)
```

```
# STATES
```

```
initial_state = agent.new_state('initial_state', initial=True)
hello_state = agent.new_state('hello_state')
good_state = agent.new_state('good_state')
bad_state = agent.new_state('bad_state')
```

```
# INTENTS
```

```
hello_intent = agent.new_intent('hello_intent', [
    'hello',
    'hi',
])
```

```
good_intent = agent.new_intent('good_intent', [
    'good',
    'fine',
])
```

```
bad_intent = agent.new_intent('bad_intent', [
```

```
        'bad',  
        'awful',  
    1)
```

```
# STATES BODIES' DEFINITION + TRANSITIONS
```

```
initial_state.when_intent_matched(hello_intent).go_to(hello_state)
```

```
def hello_body(session: Session):  
    session.reply('Hi! How are you?')
```

```
hello_state.set_body(hello_body)  
hello_state.when_intent_matched(good_intent).go_to(good_state)  
hello_state.when_intent_matched(bad_intent).go_to(bad_state)
```

```
def good_body(session: Session):  
    session.reply('I am glad to hear that!')
```

```
good_state.set_body(good_body)  
good_state.go_to(initial_state)
```

```
def bad_body(session: Session):  
    session.reply('I am sorry to hear that...')
```

```
bad_state.set_body(bad_body)  
bad_state.go_to(initial_state)
```

```
# RUN APPLICATION
```

```
if __name__ == '__main__':
```

```
    agent.run()
```