

```

Telegram agent
# You may need to add your working directory to the Python path. To do so,
uncomment the following lines of code
# import sys
# sys.path.append("/Path/to/directory/agent-framework") # Replace with
your directory path

import logging

from telegram import Update
from telegram.ext import CommandHandler, ContextTypes

from baf.core.agent import Agent
from baf.core.session import Session
from baf.exceptions.logger import logger

# Configure the logging module (optional)
logger.setLevel(logging.INFO)

agent = Agent('telegram_agent')
# Load agent properties stored in a dedicated file
agent.load_properties('config.yaml')
# Define the platform your agent will use
telegram_platform = agent.use_telegram_platform()

# Adding a custom handler for the Telegram Application: command /help
async def help(update: Update, context: ContextTypes.DEFAULT_TYPE):
    session = agent.get_or_create_session(str(update.effective_chat.id),
telegram_platform)
    session.reply('I am an agent, tell me something!')
help_handler = CommandHandler('help', help)
telegram_platform.add_handler(help_handler)

# STATES

s0 = agent.new_state('s0', initial=True)
hello_state = agent.new_state('hello_state')
bye_state = agent.new_state('bye_state')
howareyou_state = agent.new_state('howareyou_state')

# INTENTS

hello_intent = agent.new_intent('hello_intent', [
    'hello',
    'hi'
])

bye_intent = agent.new_intent('bye_intent', [
    'bye',
    'goodbye',
    'see you'
])

```

```

    ])

    howareyou_intent = agent.new_intent('howareyou_intent', [
        'how are you?',
        'how r u',
    ])

    # GLOBAL VARIABLES

    count_hello = 0
    count_bye = 0

    # STATES BODIES' DEFINITION + TRANSITIONS

    def global_fallback_body(session: Session):
        telegram_platform.reply(session, 'Greetings from global fallback')

    # Assigned to all agent states (overriding all currently assigned fallback
    bodies).
    agent.set_global_fallback_body(global_fallback_body)

    def s0_body(session: Session):
        telegram_platform.reply(session, 'Waiting...')

    s0.set_body(s0_body)
    s0.when_intent_matched(hello_intent).go_to(hello_state)
    s0.when_intent_matched(howareyou_intent).go_to(howareyou_state)

    def hello_body(session: Session):
        global count_hello
        count_hello = count_hello + 1
        telegram_platform.reply(session, f'You said hello {count_hello} times')

    # Custom fallback for hello_state
    def hello_fallback_body(session: Session):
        telegram_platform.reply(session, 'Greetings from hello fallback')

    hello_state.set_body(hello_body)
    hello_state.set_fallback_body(hello_fallback_body)
    hello_state.when_intent_matched(bye_intent).go_to(bye_state)

    def bye_body(session: Session):
        global count_bye
        count_bye = count_bye + 1
        telegram_platform.reply(session, f'You said bye {count_bye} times')

```

```
bye_state.set_body(bye_body)
bye_state.go_to(s0)
```

```
def howareyou_body(session: Session):
    telegram_platform.reply(session, f'I am fine, thanks!')
```

```
howareyou_state.set_body(howareyou_body)
howareyou_state.go_to(s0)
```

```
# RUN APPLICATION
```

```
if __name__ == '__main__':
    agent.run()
```