

Weather agent

You may need to add your working directory to the Python path. To do so, uncomment the following lines of code

```
# import sys
```

```
# sys.path.append("/Path/to/directory/agent-framework") # Replace with your directory path
```

```
import logging
```

```
import random
```

```
from baf.core.agent import Agent
```

```
from baf.core.session import Session
```

```
from baf.exceptions.logger import logger
```

```
from baf.nlp.intent_classifier.intent_classifier_prediction import  
IntentClassifierPrediction
```

```
# Configure the logging module (optional)
```

```
logger.setLevel(logging.INFO)
```

```
agent = Agent('weather_agent')
```

```
# Load agent properties stored in a dedicated file
```

```
agent.load_properties('config.yaml')
```

```
# Define the platform your agent will use
```

```
websocket_platform = agent.use_websocket_platform(use_ui=True)
```

```
# STATES
```

```
s0 = agent.new_state('s0', initial=True)
```

```
weather_state = agent.new_state('weather_state')
```

```
# ENTITIES
```

```
city_entity = agent.new_entity('city_entity', entries={  
    'Barcelona': ['BCN', 'barna'],  
    'Madrid': [],  
    'Luxembourg': ['LUX']  
})
```

```
# INTENTS
```

```
weather_intent = agent.new_intent('weather_intent', [  
    'what is the weather in CITY?',  
    'what is the weather like in CITY?',  
    'weather in CITY',  
])
```

```
weather_intent.parameter('city1', 'CITY', city_entity)
```

```
# STATES BODIES' DEFINITION + TRANSITIONS
```

```
def s0_body(session: Session):  
    session.reply(  
        "Welcome! 🖐️\n"  
        "I can tell you the weather in a city.\n"  
        "Just type something like:\n"  
        "- 'What is the weather in Barcelona?'\n"  
    )
```

```
s0.set_body(s0_body)  
s0.when_intent_matched(weather_intent).go_to(weather_state)
```

```
def weather_body(session: Session):  
    predicted_intent: IntentClassifierPrediction =  
session.event.predicted_intent  
    city = predicted_intent.get_parameter('city1')  
    temperature = round(random.uniform(0, 30), 2)  
    if city.value is None:  
        session.reply("Sorry, I didn't get the city")  
    else:  
        session.reply(f"The weather in {city.value} is {temperature}°C")  
        if temperature < 15:  
            session.reply('🥶')  
        else:  
            session.reply('🥵')
```

```
weather_state.set_body(weather_body)  
weather_state.go_to(s0)
```

```
# RUN APPLICATION
```

```
if __name__ == '__main__':
```

```
    agent.run()
```