

Every pre-registered bar, and how it went

21 bars committed under four freeze tags before any encoder scored any pair. Source: results/verification/bar_ledger.json

E1-H1	approval $\geq 90\%$ at ≥ 0.80	FAIL	89.3 / 89.7 on two configs
E1-H2	AUROC band + matched certification	QUALIFIED	range clause passed; certification clause failed → stratified-only fallback
E1-H3	modal + quantity are top classes	FAIL	0/9 under both partitions
E1-H4	fitted repairs drop ≥ 0.10 on bis	FAIL	improved instead — became the sign-flip law
E1-H5	granularity decay ≥ 0.10	FAIL	drop 0.019 (floor effect)
E2-H1	$\alpha \in [0.8, 1.2]$ mean-pooled	UNRESOLVED	7/10 spline-only; membership pending
E2-H2a	AUROC < 0.60 by L=512	QUALIFIED	pass excluding 7 vacuous configs
E2-H2b	< 0.65 by L=1024, caliper	QUALIFIED	pass excluding vacuous
E2-H2c	production ≤ 0.55 at every bin	PASS	max CI-lower 0.528
E2-H3a	position effect ≥ 0.05	FAIL	0/10; deltas $-0.014 \dots +0.015$
E2-H4	miss rates at shipped thresholds	QUALIFIED	pass excluding non-evaluable (MiniLM)
E2-H5	$ r < 0.10$ by L=512	PASS	
E2-H6	transfer inside fitted bands	FAIL	69/101 evaluable cells
E3-HE3-1	caliper collapses elicited separability	FAIL	0/9 → minimal-pairhood criterion
E3-HE3-2	every config ≥ 0.80 naive on QQP	PASS	9/9
E3-HE3-3	all nine in $[0.50, 0.75]$ on PAWS	FAIL	production 0.679 highest of nine
E3-HE3-4	no shipped-threshold cell > 0.70 BA	FAIL	28 cells
E3-HE3-5	AUROC ranks by coupling magnitude	FAIL	1/9
E4-B1	practical floor > 0.40 for $\geq 7/9$	FAIL	1/9 (gte only)
E4-B2	practical floor > 0.60 for $\geq 5/9$	FAIL	0/9
E4-B3	observed min $\geq$ hard floor, 100% of cells	FAIL	6 cells breach the scope condition; investigated per prereg §3

fail · 13 qualified · 4 pass · 3 unresolved · 1

Of 21 pre-registered bars, 13 failed outright, one failed at its certification clause, one is unresolved, and three passed only for the configurations able to evaluate them.