N-Channel 60-V (D-S) MOSFET

PRODUCT SUMMARY				
Part Number	**$V_{(BR)DSS}$ Min (V)**	**$r_{DS(on)}$ Max (Ω)**	**$V_{GS(th)}$ (V)**	**I_D (A)**
2N7000	60	5 @ V_{GS} = 10 V	0.8 to 3	0.2
2N7002		7.5 @ V_{GS} = 10 V	1 to 2.5	0.115
VQ1000J		5.5 @ V_{GS} = 10 V	0.8 to 2.5	0.225
VQ1000P		5.5 @ V_{GS} = 10 V	0.8 to 2.5	0.225
BS170		5 @ V_{GS} = 10 V	0.8 to 3	0.5

FEATURES

- Low On-Resistance: 2.5 Ω
- Low Threshold: 2.1 V
- Low Input Capacitance: 22 pF
- Fast Switching Speed: 7 ns
- Low Input and Output Leakage

BENEFITS

- Low Offset Voltage
- Low-Voltage Operation
- Easily Driven Without Buffer
- High-Speed Circuits
- Low Error Voltage

APPLICATIONS

- Direct Logic-Level Interface: TTL/CMOS
- Drivers: Relays, Solenoids, Lamps, Hammers, Displays, Memories, Transistors, etc.
- Battery Operated Systems
- Solid-State Relays

TO-226AA
(TO-92)



Top View

2N7000

TO-236
(SOT-23)



Top View

Marking Code: 72*wll*

72 = Part Number Code for 2N7002
w = Week Code
ll = Lot Traceability

Dual-In-Line



Top View

Plastic: VQ1000J
Sidebraze: VQ1000P

TO-92-18RM
(TO-18 Lead Form)



Top View

BS170

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C UNLESS OTHERWISE NOTED)

Parameter		Symbol	2N7000	2N7002	Single VQ1000J	Single VQ1000P	Total Quad VQ1000J/P	BS170	Unit
Drain-Source Voltage		V_{DS}	60	60	60	60		60	V
Gate-Source Voltage—Non-Repetitive		V_{GSM}	±40	±40	±30			±25	V
Gate-Source Voltage—Continuous		V_{GS}	±20	±20	±20	±20		±20	V
Continuous Drain Current (T_J = 150°C)	T_A= 25°C	I_D	0.2	0.115	0.225	0.225		0.5	A
	T_A= 100°C		0.13	0.073	0.14	0.14		0.175	A
Pulsed Drain Current[a]		I_{DM}	0.5	0.8	1	1			A
Power Dissipation	T_A= 25°C	P_D	0.4	0.2	1.3	1.3	2	0.83	W
	T_A= 100°C		0.16	0.08	0.52	0.52	0.8		W
Thermal Resistance, Junction-to-Ambient		R_{thJA}	312.5	625	96	96	62.5	156	°C/W
Operating Junction and Storage Temperature Range		T_J, T_{stg}	–55 to 150						°C

Notes
a. Pulse width limited by maximum junction temperature.
b. $t_p \leq 50$ μs.

SPECIFICATIONS—2N7000 AND 2N7002 (T_A = 25°C UNLESS OTHERWISE NOTED)

Parameter	Symbol	Test Conditions	Typ[a]	Limits 2N7000 Min	Limits 2N7000 Max	Limits 2N7002 Min	Limits 2N7002 Max	Unit
Static								
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 10 μA	70	60		60		V
Gate-Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 1 mA	2.1	0.8	3			V
		V_{DS} = V_{GS}, I_D = 0.25 mA	2.0			1	2.5	V
Gate-Body Leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ±15 V			±10			nA
		V_{DS} = 0 V, V_{GS} = ±20 V					±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 48 V, V_{GS} = 0 V			1			μA
		T_C = 125°C			1000			μA
		V_{DS} = 60 V, V_{GS} = 0 V					1	μA
		T_C = 125°C					500	μA
On-State Drain Current[b]	$I_{D(on)}$	V_{DS} = 10 V, V_{GS} = 4.5 V	0.35	0.075				A
		V_{DS} = 7.5 V, V_{GS} = 10 V	1			0.5		A
Drain-Source On-Resistance[b]	$r_{DS(on)}$	V_{GS} = 4.5 V, I_D = 0.075 A	4.5		5.3			Ω
		V_{GS} = 5 V, I_D = 0.05 A	3.2				7.5	Ω
		T_C = 125°C	5.8				13.5	Ω
		V_{GS} = 10 V, I_D = 0.5 A	2.4		5		7.5	Ω
		T_J = 125°C	4.4		9		13.5	Ω
Forward Transconductance[b]	g_{fs}	V_{DS} = 10 V, I_D = 0.2 A		100		80		mS
Common Source Output Conductance[b]	g_{os}	V_{DS} = 5 V, I_D = 0.05 A	0.5					mS
Dynamic								
Input Capacitance	C_{iss}	V_{DS} = 25 V, V_{GS} = 0 V f = 1 MHz	22		60		50	pF
Output Capacitance	C_{oss}		11		25		25	pF
Reverse Transfer Capacitance	C_{rss}		2		5		5	pF

SPECIFICATIONS—2N7000 AND 2N7002 (T_A = 25°C UNLESS OTHERWISE NOTED)

Parameter	Symbol	Test Conditions	Typ[a]	Limits 2N7000 Min	Limits 2N7000 Max	Limits 2N7002 Min	Limits 2N7002 Max	Unit
Switching[d]								
Turn-On Time	t_{ON}	V_{DD} = 15 V, R_L = 25 Ω I_D ≅ 0.5 A, V_{GEN} = 10 V, R_G = 25 Ω	7		10			ns
Turn-Off Time	t_{OFF}		7		10			
Turn-On Time	t_{ON}	V_{DD} = 30 V, R_L = 150 Ω I_D ≅ 0.2 A, V_{GEN} = 10 V, R_G = 25 Ω	7				20	
Turn-Off Time	t_{OFF}		11				20	

SPECIFICATIONS—VQ1000J/P AND BS170 (T_A = 25°C UNLESS OTHERWISE NOTED)

Parameter	Symbol	Test Conditions	Typ[a]	Limits VQ1000J/P Min	Limits VQ1000J/P Max	Limits BS170 Min	Limits BS170 Max	Unit
Static								
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 100 μA	70	60		60		V
Gate-Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 1 mA	2.1	0.8	2.5	0.8	3	
Gate-Body Leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ±10 V			±100			nA
		T_J = 125°C			±500			
		V_{DS} = 0 V, V_{GS} = ±15 V					±10	
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 25 V, V_{GS} = 0 V					0.5	μA
		V_{DS} = 48 V, V_{GS} = 0 V, T_J = 125°C			500			
		V_{DS} = 60 V, V_{GS} = 0 V			10			
On-State Drain Current[b]	$I_{D(on)}$	V_{DS} = 10 V, V_{GS} = 10 V	1	0.5				A
Drain-Source On-Resistance[b]	$r_{DS(on)}$	V_{GS} = 5 V, I_D = 0.2 A	4		7.5			Ω
		V_{GS} = 10 V, I_D = 0.2 A	2.3				5	
		V_{GS} = 10 V, I_D = 0.3 A	2.3		5.5			
		T_J = 125°C	4.2		7.6			
Forward Transconductance[b]	g_{fs}	V_{DS} = 10 V, I_D = 0.2 A				100		mS
		V_{DS} = 10 V, I_D = 0.5 A		100				
Common Source Output Conductance[b]	g_{os}	V_{DS} =5 V, I_D = 0.05 A	0.5					
Dynamic								
Input Capacitance	C_{iss}	V_{DS} =25 V, V_{GS} = 0 V f = 1 MHz	22		60		60	pF
Output Capacitance	C_{oss}		11		25			
Reverse Transfer Capacitance	C_{rss}		2		5			
Switching[d]								
Turn-On Time	t_{ON}	V_{DD} = 15 V, R_L = 23 Ω I_D ≅ 0.6 A, V_{GEN} = 10 V, R_G = 25 Ω	7		10			ns
Turn-Off Time	t_{OFF}		7		10			
Turn-On Time	t_{ON}	V_{DD} = 25 V, R_L = 125 Ω I_D ≅ 0.2 A, V_{GEN} = 10 V, R_G = 25 Ω	7				10	
Turn-Off Time	t_{OFF}		7				10	

Notes
a. For DESIGN AID ONLY, not subject to production testing.
b. Pulse test: PW ≤ 80 μs duty cycle ≤ 1%.
c. This parameter not registered with JEDEC.
d. Switching time is essentially independent of operating temperature.

VNBF06

TYPICAL CHARACTERISTICS (T_A = 25°C UNLESS OTHERWISE NOTED)

Output Characteristics



Transfer Characteristics



On-Resistance vs. Drain Current



Capacitance



Gate Charge



On-Resistance vs. Junction Temperature



TYPICAL CHARACTERISTICS (T_A = 25°C UNLESS OTHERWISE NOTED)

Source-Drain Diode Forward Voltage



On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage



Normalized Effective Transient Thermal Impedance, Junction-to-Ambient (TO-226AA, BS170 Only)



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay:
VQ1000P VQ1000J 2N7002K-T1 2N7002\E9 2N7002 2N7000 BS170 BS250 VQ1000P-E3 2N7002-T1 2N7002-E3 2N7002E-T1-E3 BS107 BSS92 2N7002E 2N7000KL-TR1-E3 2N7002K-T1-E3 2N7002-T1-E3 2N7000KL-TR1