

Congratulations

y training tasks

You have completed a Codility training test.

Sign up for our newsletter!

Like us on Facebook!

Training ticket

Session

ID: trainingK7TQQC-RFK
Time limit: 120 min.

Status: closed

Created on: 2016-06-04 19:53 UTC Started on: 2016-06-04 19:53 UTC Finished on: 2016-06-04 19:55 UTC

Tasks in test

1 | **TapeEquilibrium**Submitted in: Java

Correctness

100%

Performance

Task score

100% 100 out of 100 points

1. TapeEquilibrium

Minimize the value |(A[0] + ... + A[P-1]) - (A[P] + ... + A[N-1])|.

score: 100 of 100



Task description

A non-empty zero-indexed array A consisting of N integers is given. Array A represents numbers on a tape.

Any integer P, such that 0 < P < N, splits this tape into two non-empty parts: A[0], A[1], ..., A[P - 1] and A[P], A[P + 1], ..., A[N - 1].

The difference between the two parts is the value of: |(A[0] + A[1] + ... + A[P-1]) - (A[P] + A[P+1] + ... + A[N-1])|

In other words, it is the absolute difference between the sum of the first part and the sum of the second part.

For example, consider array A such that:

A[0] = 3

A[1] = 1

A[2] = 2

A[3] = 4

A[4] = 3

We can split this tape in four places:

- P = 1, difference = |3 10| = 7
- P = 2, difference = |4 9| = 5
- P = 3, difference = |6 7| = 1
- P = 4, difference = |10 3| = 7

Write a function:

```
class Solution { public int solution(int[] A); }
```

that, given a non-empty zero-indexed array A of N integers, returns the minimal difference that can be achieved.

For example, given:

A[0] = 3

Solution

Programming language used: Java

Total time used: 2 minutes

Effective time used: 2 minutes

Notes: not defined yet

 $\overline{}$

Task timeline





19:55:07

Code: 19:55:07 UTC, java, final,

show code in pop-up

score: 100

19:53:46

```
// you can also use imports, for example:
     // import java.util.*;
3
4
     // you can write to stdout for debugging purposes, e.g.
5
     // System.out.println("this is a debug message");
6
     import java.util.Arrays;
8
9
     class Solution {
10
11
           public int solution(int[] A) {
12
             int diff = Integer.MAX_VALUE;
13
             int nsu = 0;
             int summ = Arrays.stream(A).sum();
             int tmp = 0;
```

```
A[1] = 1
A[2] = 2
A[3] = 4
A[4] = 3
```

the function should return 1, as explained above.

Assume that:

- N is an integer within the range [2..100,000];
- each element of array A is an integer within the range [-1,000..1,000].

Complexity:

- expected worst-case time complexity is O(N);
- expected worst-case space complexity is O(N), beyond input storage (not counting the storage required for input arguments).

Elements of input arrays can be modified.

Copyright 2009–2016 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

```
16
               for (int i = 1; i<A.length; i++) {</pre>
17
                 nsu += A[i-1];
18
                 summ -= A[i-1];
                 tmp = Math.abs(summ - nsu);
20
                 if (tmp < diff) {
  diff = tmp;</pre>
21
22
23
24
25
               return diff;
26
27
28
     }
```

Analysis summary

The solution obtained perfect score.

Analysis

Detected time complexity: O(N)

O(N)			
expand	all Example tests		
	example xample test	•	OK
expand	all Correctness tes	ts	
	louble wo elements	•	OK
	simple_positive imple test with positive numbers, length = 5	•	OK
	simple_negative imple test with negative numbers, length = 5	•	OK
	small_random andom small, length = 100	•	OK
	small_range ange sequence, length = ~1,000	•	OK
,	small mall elements	•	OK
expand all Performance tests			
r	nedium_random1 andom medium, numbers from 0 to 100, ength = \sim 10,000	•	ок
r	nedium_random2 andom medium, numbers from -1,000 to 50, ength = ~10,000	~	OK
la	arge_ones arge sequence, numbers from -1 to 1, length ~100,000	~	OK
	arge_random andom large, length = ~100,000	•	OK
	arge_sequence arge sequence, length = ~100,000	•	ОК
la	arge_extreme arge test with maximal and minimal values, ength = ~100,000	•	OK

Training center