

Congratulations

You have completed a Codility training test.

[Sign up for our newsletter!](#)
[Like us on Facebook!](#)

Training ticket

Session

ID: trainingEF45YZ-JFM
Time limit: 120 min.

Status: closed

Created on: 2016-06-09 13:41 UTC
Started on: 2016-06-09 13:41 UTC
Finished on: 2016-06-09 13:42 UTC

Tasks in test

1 | **PassingCars**
Submitted in: Java

Correctness

100%

Performance

100%

Task score

100%

Test score

100%

100 out of 100 points

EASY

1. PassingCars

Count the number of passing cars on the road.

score: 100 of 100



Task description

A non-empty zero-indexed array A consisting of N integers is given. The consecutive elements of array A represent consecutive cars on a road.

Array A contains only 0s and/or 1s:

- 0 represents a car traveling east,
- 1 represents a car traveling west.

The goal is to count passing cars. We say that a pair of cars (P, Q), where $0 \leq P < Q < N$, is passing when P is traveling to the east and Q is traveling to the west.

For example, consider array A such that:

```
A[0] = 0
A[1] = 1
A[2] = 0
A[3] = 1
A[4] = 1
```

We have five pairs of passing cars: (0, 1), (0, 3), (0, 4), (2, 3), (2, 4).

Write a function:

```
class Solution { public int solution(int[] A); }
```

that, given a non-empty zero-indexed array A of N integers, returns the number of pairs of passing cars.

The function should return -1 if the number of pairs of passing cars exceeds 1,000,000,000.

For example, given:

```
A[0] = 0
A[1] = 1
A[2] = 0
```

Solution


Programming language used: Java

Total time used: 1 minutes

Effective time used: 1 minutes

Notes: *not defined yet*

Task timeline



Code: 13:42:44 UTC, java, final,
score: 100

[show code in pop-up](#)

```
1 // you can also use imports, for example:
2 // import java.util.*;
3
4 // you can write to stdout for debugging purposes, e.g.
5 // System.out.println("this is a debug message");
6
7 class Solution {
8     public int solution(int[] a) {
9         int counter = 0;
10        int zeros = 0;
11        for (int i = 0; i < a.length; i++) {
12            if (a[i] == 0) {
13                zeros++;
14            } else if (a[i] == 1) {
15                counter += zeros;
```

A[3] = 1
A[4] = 1
the function should return 5, as explained above.

Assume that:

- N is an integer within the range [1..100,000];
- each element of array A is an integer that can have one of the following values: 0, 1.

Complexity:

- expected worst-case time complexity is O(N);
- expected worst-case space complexity is O(1), beyond input storage (not counting the storage required for input arguments).

Elements of input arrays can be modified.

Copyright 2009–2016 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

```
16     }
17     if (counter > 1_000_000_000) {
18         return -1;
19     }
20 }
21 return counter;
22 }
23 }
```

Analysis summary

The solution obtained perfect score.

Analysis



Detected time complexity:
O(N)

Example tests	
▶ example example test	✓ OK
Correctness tests	
▶ single single element	✓ OK
▶ double two elements	✓ OK
▶ simple simple test	✓ OK
▶ small_random random, length = 100	✓ OK
▶ small_random2 random, length = 1000	✓ OK
Performance tests	
▶ medium_random random, length = ~10,000	✓ OK
▶ large_random random, length = ~100,000	✓ OK
▶ large_big_answer 0..01..1, length = ~100,000	✓ OK
▶ large_alternate 0101..01, length = ~100,000	✓ OK
▶ large_extreme large test with all 1s/0s, length = ~100,000	✓ OK