Intel[®] oneAPI VTune[™] Profiler 2021.1.1 Gold

Recommendations:

Increase execution time:

Application execution time is too short. Metrics data may be unreliable. Consider reducing the sampling interval or increasing your application execution time.

Elapsed Time: 0.053s

Application execution time is too short. Metrics data may be unreliable. Consider reducing the sampling interval or increasing your application execution time.

CPU Time: 0.039s

Memory Bound:3.8% of Pipeline SlotsL1 Bound:0.0% of ClockticksL2 Bound:5.5% of ClockticksL3 Bound:5.5% of ClockticksDRAM Bound:0.0% of Clockticks

DRAM Bandwidth Bound: 0.0% of Elapsed Time

Store Bound: 0.0% of Clockticks

Loads: 15,000,000 **Stores:** 9,000,000

LLC Miss Count: 0
Average Latency (cycles): 8
Total Thread Count: 1
Paused Time: 0s

Bandwidth Utilization:

Bandwidth Domain	Platform Maximum	Observed Maximum	Average	% of Elapsed Time with High BW Utilization(%)
DRAM, GB/ sec	10	1.400	0.936	0.0%

Collection and Platform Info:

Application Command Line: ./codecs/HM/decoder/TAppDecoderStatic "-b" "./bin/HM/encoder_randomaccess_main.cfg/CLASS_C/ RaceHorses 416x240 30 OP 37 HM.bin"

User Name: root

Operating System: 5.4.0-72-generic DISTRIB_ID=Ubuntu

DISTRIB RELEASE=18.04 DISTRIB CODENAME=bionic

DISTRIB DESCRIPTION="Ubuntu 18.04.5 LTS"

Computer Name: eimon

Result Size: 13.1 MB

Collection start time: 22:27:46 18/04/2021 UTC

Collection stop time: 22:27:46 18/04/2021 UTC

Collector Type: Event-based sampling driver

CPU:

Name: Intel(R) Processor code named Kabylake

ULX

Frequency: 1.992 GHz

Logical CPU Count: 8

Max DRAM Single-Package Bandwidth: 10.000 GB/s

Cache Allocation Technology:

Level 2 capability: not detected

Level 3 capability: not detected

Intel[®] oneAPI VTune[™] Profiler 2021.1.1 Gold

Recommendations:

Increase execution time:

Application execution time is too short. Metrics data may be unreliable. Consider reducing the sampling interval or increasing your application execution time.

Elapsed Time: 0.037s

Application execution time is too short. Metrics data may be unreliable. Consider reducing the sampling interval or increasing your application execution time.

CPU Time: 0.024s

Memory Bound:9.6% of Pipeline SlotsL1 Bound:5.6% of ClockticksL2 Bound:5.6% of ClockticksL3 Bound:0.0% of ClockticksDRAM Bound:5.6% of Clockticks

DRAM Bandwidth Bound: 0.0% of Elapsed Time

Store Bound: 0.0% of Clockticks

Loads: 20,640,000 **Stores:** 7,320,000

LLC Miss Count: 0
Average Latency (cycles): 7
Total Thread Count: 1
Paused Time: 0s

Bandwidth Utilization:

Bandwidth Domain	Platform Maximum	Observed Maximum	Average	% of Elapsed Time with High BW Utilization(%)
DRAM, GB/ sec	10	0.900	0.815	0.0%

Collection and Platform Info:

Application Command Line: ./codecs/HM/decoder/TAppDecoderStatic "-b" "./bin/HM/encoder_randomaccess_main.cfg/CLASS_C/ RaceHorses_416x240_30_QP_37_HM.bin"

User Name: root

Operating System: 5.4.0-72-generic DISTRIB_ID=Ubuntu DISTRIB RELEASE=18.04 DISTRIB CODENAME=bionic

DISTRIB DESCRIPTION="Ubuntu 18.04.5 LTS"

Computer Name: eimon

Result Size: 12.4 MB

Collection start time: 07:46:57 19/04/2021 UTC

Collection stop time: 07:46:57 19/04/2021 UTC

Collector Type: Event-based sampling driver

CPU:

Name: Intel(R) Processor code named Kabylake

ULX

Frequency: 1.992 GHz

Logical CPU Count: 8

Max DRAM Single-Package Bandwidth: 10.000 GB/s

Cache Allocation Technology:

Level 2 capability: not detected

Level 3 capability: not detected