Intel® oneAPI VTune™ Profiler 2021.1.1 Gold

Elapsed Time: 0.040s

> Application execution time is too short. Metrics data may be unreliable. Consider reducing the sampling interval or increasing your application execution time.

Clockticks:	33,300,000
Instructions Retired:	49,860,000
CPI Rate:	0.668
MUX Reliability:	0.881
Retiring:	40.5% of Pipeline Slots
Light Operations:	37.4% of Pipeline Slots
FP Arithmetic:	0.0% of uOps
FP x87:	0.0% of uOps
FP Scalar:	0.0% of uOps
FP Vector:	0.0% of uOps
Other:	100.0% of uOps
Heavy Operations:	3.1% of Pipeline Slots
Microcode Sequencer:	10.1% of Pipeline Slots
Assists:	0.0% of Pipeline Slots
Front-End Bound:	24.3% of Pipeline Slots

> Issue: A significant portion of Pipeline Slots is remaining empty due to issues in the Front-End.
>
> Tips: Make sure the code working size is not too large, the code layout does not require too many memory accesses per cycle to get enough instructions for filling four pipeline slots, or check for microcode assists.

Front-End Latency: 16.2% of Pipeline Slots

> This metric represents a fraction of slots during which CPU was stalled due to front-end latency issues, such as instruction-cache misses, ITLB misses or fetch stalls after a branch misprediction. In such cases, the front-end delivers no uOps.

ICache Misses: 0.0% of Clockticks
ITLB Overhead: 1.6% of Clockticks
Branch Resteers: 0.0% of Clockticks
Mispredicts Resteers: 0.0% of Clockticks
Clears Resteers: 0.0% of Clockticks
Unknown Branches: 0.0% of Clockticks
DSB Switches: 0.0% of Clockticks
Length Changing Prefixes: 0.0% of Clockticks
MS Switches: 0.0% of Clockticks

> Issue: A significant fraction of cycles was stalled due to switches of uOp delivery to the Microcode Sequencer (MS). Commonly used instructions are optimized for delivery by the DSB or MITE pipelines. Certain operations cannot be handled natively by the execution pipeline, and must be performed by microcode (small programs injected into the execution stream). Switching to the MS too often can negatively impact performance. The MS is designated to deliver long uOp flows required by CISC instructions like CPUID, or uncommon conditions like Floating Point Assists when dealing with Denormals. Note that this metric value may be highlighted due to Microcode Sequencer issue.

Front-End Bandwidth: 8.1% of Pipeline Slots
Front-End Bandwidth MITE: 32.4% of Clockticks
Front-End Bandwidth DSB: 0.0% of Clockticks
(Info) DSB Coverage: 18.2%
Bad Speculation: 8.1% of Pipeline Slots
Branch Mispredict: 0.0% of Pipeline Slots
Machine Clears: 8.1% of Pipeline Slots
Back-End Bound: 27.0% of Pipeline Slots

> A significant portion of pipeline slots are remaining empty. When operations take too long in the back-end, they introduce bubbles in the pipeline that ultimately cause fewer pipeline slots containing useful work to be retired per cycle than the machine is capable to support. This opportunity cost results in slower execution. Long-latency operations like divides and memory operations can cause this, as can too many operations being directed to a single execution port (for example, more multiply operations arriving in the back-end per cycle than the execution unit can support).

Memory Bound: 19.2% of Pipeline Slots
- **L1 Bound:** 16.2% of Clockticks
  - **DTLB Overhead:** 1.6% of Clockticks
    - **Load STLB Hit:** 0.0% of Clockticks
    - **Load STLB Miss:** 1.6% of Clockticks
  - **Loads Blocked by Store Forwarding:** 0.0% of Clockticks
  - **Lock Latency:** 0.0% of Clockticks
  - **Split Loads:** 0.0% of Clockticks
  - **4K Aliasing:** 0.8% of Clockticks
  - **FB Full:** 0.0% of Clockticks
- **L2 Bound:**
- **L3 Bound:** 0.0% of Clockticks
  - **Contested Accesses:**
  - **Data Sharing:**
  - **L3 Latency:**
  - **SQ Full:** 0.0% of Clockticks
- **DRAM Bound:**
  - **Memory Bandwidth:** 0.0% of Clockticks
  - **Memory Latency:** 16.2% of Clockticks

Store Bound: 0.0% of Clockticks
Store Latency: 0.0% of Clockticks
False Sharing: 0.0% of Clockticks
Split Stores: 0.0% of Clockticks
DTLB Store Overhead: 2.4% of Clockticks
Store STLB Hit: 0.0% of Clockticks
Store STLB Hit: 2.4% of Clockticks
Core Bound: 7.8% of Pipeline Slots
Divider: 0.0% of Clockticks
Port Utilization: 6.6% of Clockticks
Cycles of 0 Ports Utilized: 16.2% of Clockticks
Serializing Operations: 0.0% of Clockticks
Mixing Vectors: 0.0% of uOps
Cycles of 1 Port Utilized: 8.1% of Clockticks
Cycles of 2 Ports Utilized: 8.1% of Clockticks
Cycles of 3+ Ports Utilized: 16.2% of Clockticks
ALU Operation Utilization: 20.3% of Clockticks
Port 0: 16.2% of Clockticks
Port 1: 16.2% of Clockticks
Port 5: 16.2% of Clockticks
Port 6: 32.4% of Clockticks
Load Operation Utilization: 8.1% of Clockticks
Port 2: 16.2% of Clockticks
Port 3: 16.2% of Clockticks
Store Operation Utilization: 16.2% of Clockticks
Port 4: 16.2% of Clockticks
Port 7: 0.0% of Clockticks
Vector Capacity Usage (FPU): 0.0%
Average CPU Frequency: 930.606 MHz
Total Thread Count: 1
Paused Time: 0s

Effective Physical Core Utilization: 22.3% (0.891 out of 4)

```
The metric value is low, which may signal a poor physical
CPU cores utilization caused by:
    - load imbalance
    - threading runtime overhead
    - contended synchronization
    - thread/process underutilization
    - incorrect affinity that utilizes logical cores instead
of physical cores
Explore sub-metrics to estimate the efficiency of MPI and
OpenMP parallelism or run the Locks and Waits analysis to
identify parallel bottlenecks for other parallel runtimes.
```

Effective Logical Core Utilization: 11.1% (0.891 out of 8)

```
The metric value is low, which may signal a poor logical
CPU cores utilization. Consider improving physical core
```

> utilization as the first step and then look at opportunities to utilize logical cores, which in some cases can improve processor throughput and overall performance of multi-threaded applications.

Collection and Platform Info:

Application Command Line: ./codecs/hm/decoder/TAppDecoderStatic "-b" "./bin/hm/encoder_lowdelay_main.cfg/CLASS_B/BasketballPass_416x240_50_QP_37_hm.bin"

User Name: root

Operating System: 5.4.0-65-generic DISTRIB_ID=Ubuntu DISTRIB_RELEASE=18.04 DISTRIB_CODENAME=bionic DISTRIB_DESCRIPTION="Ubuntu 18.04.5 LTS"

Computer Name: eimon

Result Size: 9.3 MB

Collection start time: 09:51:12 10/02/2021 UTC

Collection stop time: 09:51:12 10/02/2021 UTC

Collector Type: Event-based sampling driver

CPU:

Name: Intel(R) Processor code named Kabylake ULX

Frequency: 1.992 GHz

Logical CPU Count: 8

Cache Allocation Technology:

Level 2 capability: not detected

Level 3 capability: not detected