

Recommendations:**Increase execution time:**

Application execution time is too short. Metrics data may be unreliable. Consider reducing the sampling interval or increasing your application execution time.

Elapsed Time: 0.068s

Application execution time is too short. Metrics data may be unreliable. Consider reducing the sampling interval or increasing your application execution time.

CPU Time: 0.053s
Memory Bound: 7.1% of Pipeline Slots
L1 Bound: 10.0% of Clockticks
L2 Bound: 0.0% of Clockticks
L3 Bound: 3.3% of Clockticks
DRAM Bound: 3.3% of Clockticks
DRAM Bandwidth Bound: 0.0% of Elapsed Time
Store Bound: 0.0% of Clockticks
Loads: 27,480,000
Stores: 12,240,000
LLC Miss Count: 0
Average Latency (cycles): 8
Total Thread Count: 1
Paused Time: 0s

Bandwidth Utilization:

Bandwidth Domain	Platform Maximum	Observed Maximum	Average	% of Elapsed Time with High BW Utilization(%)
DRAM, GB/sec	11	1.300	0.876	0.0%

Collection and Platform Info:

Application Command Line: ./codecs/HM/decoder/TAppDecoderStatic
 "-b" ".bin/HM/encoder_randomaccess_main.cfg/CLASS_C/
 RaceHorses_416x240_30_QP_22_HM.bin"

User Name: root

Operating System: 5.4.0-72-generic DISTRIB_ID=Ubuntu
DISTRIB_RELEASE=18.04 DISTRIB_CODENAME=bionic
DISTRIB_DESCRIPTION="Ubuntu 18.04.5 LTS"

Computer Name: eimon

Result Size: 13.2 MB

Collection start time: 22:24:36 18/04/2021 UTC

Collection stop time: 22:24:36 18/04/2021 UTC

Collector Type: Event-based sampling driver

CPU:

Name: Intel(R) Processor code named Kabylake
ULX

Frequency: 1.992 GHz

Logical CPU Count: 8

Max DRAM Single-Package Bandwidth: 11.000 GB/s

Cache Allocation Technology:

Level 2 capability: not detected

Level 3 capability: not detected

Intel® oneAPI VTune™ Profiler 2021.1.1 Gold

Recommendations:

Increase execution time:

Application execution time is too short. Metrics data may be unreliable. Consider reducing the sampling interval or increasing your application execution time.

Elapsed Time: 0.066s

Application execution time is too short. Metrics data may be unreliable. Consider reducing the sampling interval or increasing your application execution time.

CPU Time: 0.050s
Memory Bound: 8.9% of Pipeline Slots
L1 Bound: 13.2% of Clockticks
L2 Bound: 0.0% of Clockticks
L3 Bound: 3.3% of Clockticks
DRAM Bound: 6.6% of Clockticks
DRAM Bandwidth Bound: 0.0% of Elapsed Time
Store Bound: 0.0% of Clockticks
Loads: 23,640,000
Stores: 13,920,000
LLC Miss Count: 0
Average Latency (cycles): 10
Total Thread Count: 1
Paused Time: 0s

Bandwidth Utilization:

Bandwidth Domain	Platform Maximum	Observed Maximum	Average	% of Elapsed Time with High BW Utilization(%)
DRAM, GB/sec	10	1.000	0.455	0.0%

Collection and Platform Info:

Application Command Line: ./codecs/HM/decoder/TAppDecoderStatic "-b" ".bin/HM/encoder_randomaccess_main.cfg/CLASS_C/RaceHorses_416x240_30_QP_22_HM.bin"

User Name: root

Operating System: 5.4.0-72-generic DISTRIB_ID=Ubuntu
 DISTRIB_RELEASE=18.04 DISTRIB_CODENAME=bionic
 DISTRIB_DESCRIPTION="Ubuntu 18.04.5 LTS"

Computer Name: eimon

Result Size: 13.2 MB

Collection start time: 07:43:58 19/04/2021 UTC

Collection stop time: 07:43:58 19/04/2021 UTC

Collector Type: Event-based sampling driver

CPU:

Name: Intel(R) Processor code named Kabylake
 ULX

Frequency: 1.992 GHz

Logical CPU Count: 8

Max DRAM Single-Package Bandwidth: 10.000 GB/s

Cache Allocation Technology:

Level 2 capability: not detected

Level 3 capability: not detected