

Knowledge Representation and Reasoning

Computational Argumentation

Jean-Guy Mailly

M1 Computer Science

Outline

- 1 General Introduction to Argumentation
- 2 Abstract Argumentation Framework
 - Basics of Abstract Argumentation
 - Acceptability Semantics
 - Computational Approaches for Reasoning with Dung's AFs
 - Other Semantics
- 3 Other Frameworks

Where to eat?

Arguments are used in everyday life to defend or explain a point of view

Where to eat?

Arguments are used in everyday life to defend or explain a point of view

- **John:** "I'm hungry, let's go to this restaurant."

Where to eat?

Arguments are used in everyday life to defend or explain a point of view

- **John:** "I'm hungry, let's go to this restaurant."
- **Yoko:** "I've seen on Tripadvisor that the food is bad, let's go somewhere else."

Where to eat?

Arguments are used in everyday life to defend or explain a point of view

- **John:** "I'm hungry, let's go to this restaurant."
- **Yoko:** "I've seen on Tripadvisor that the food is bad, let's go somewhere else."
- **John:** "The Tripadvisor grades are old and there is a new chef, so it should be better now."

Where to eat?

Arguments are used in everyday life to defend or explain a point of view

- **John:** "I'm hungry, let's go to this restaurant."
- **Yoko:** "I've seen on Tripadvisor that the food is bad, let's go somewhere else."
- **John:** "The Tripadvisor grades are old and there is a new chef, so it should be better now."
- **John:** "Moreover, the other restaurants in the streets are closed."

Formalizing Arguments

Formally, an argument is made of a support which allows to deduce a given claim

Formalizing Arguments

Formally, an argument is made of a **support** which allows to deduce a given **claim**

I'm hungry, **let's go to this restaurant.**

Conflicts between Arguments

The support (or the claim) of an argument can be incompatible with the support (or the claim) of another argument: **attack**

Conflicts between Arguments

The support (or the claim) of an argument can be incompatible with the support (or the claim) of another argument: **attack**

- **claim** vs **claim** (rebuttal): "I'm hungry, **let's go to this restaurant.**" vs "Its grades on Tripadvisor are bad, **let's go somewhere else.**"

Conflicts between Arguments

The support (or the claim) of an argument can be incompatible with the support (or the claim) of another argument: **attack**

- **claim** vs **claim** (rebuttal): "I'm hungry, **let's go to this restaurant.**" vs "Its grades on Tripadvisor are bad, **let's go somewhere else.**"
- **claim** vs **support** (undercut): "The Tripadvisor grades are old and there is a new chef, **so it should be better now.**" vs "I've seen on Tripadvisor that **the food is bad**, let's go somewhere else."


Different argumentation formalisms

Several **formalisms** capture the nature of **arguments** and **attacks**

- Deductive argumentation [Besnard and Hunter 2008]
- Rule-based argumentation
[Kakas and Moraitis 2003, Toni 2014, Modgil and Prakken 2014]

Support and claims are represented as logical formulas or rules, then arguments and attacks are built

Argument mining



[Lippi and Torroni 2016]

References



P. Besnard and A. Hunter, *Elements of Argumentation* . MIT Press, 2008.



F. Toni, *A tutorial on assumption-based argumentation*. *Argument & Computation* 5(1), pp 89-117, 2014.



A. Kakas, P. Moraitis, *Argumentation based decision making for autonomous agents*. *AAMAS'03*, pp 883-890, 2013.



S. Modgil, H. Prakken, *The ASPIC+ framework for structured argumentation: a tutorial*. *Argument & Computation* 5(1), pp 31-62, 2014.



M. Lippi and P. Torroni, *Argumentation mining: State of the art and emerging trends*. *ACM Transactions on Internet Technology (TOIT)*, 2016.

Outline

1 General Introduction to Argumentation

2 Abstract Argumentation Framework

- Basics of Abstract Argumentation
- Acceptability Semantics
- Computational Approaches for Reasoning with Dung's AFs
- Other Semantics

3 Other Frameworks

Dung's Argumentation Framework [Dung 1995]

Argumentation Framework (AF for short): $F = \langle A, R \rangle$ where

- A is a set of arguments
- $R \subseteq A \times A$ represents attacks between arguments

Dung's Argumentation Framework [Dung 1995]

Argumentation Framework (AF for short): $F = \langle A, R \rangle$ where

- A is a set of arguments
- $R \subseteq A \times A$ represents attacks between arguments


- Example:

- a_1 : (John) "I'm hungry, let's go to this restaurant."
- a_2 : (Yoko) "I've seen on Tripadvisor that the food is bad, let's go somewhere else."
- a_3 : (John) "The Tripadvisor grades are old and there is a new chef, so it should be better now."
- a_4 : (John) "Moreover, the other restaurants in the streets are closed."

$F = \langle A, R \rangle$ with

$A = \{a_1, a_2, a_3, a_4\},$

$R = \{(a_2, a_1), (a_3, a_2), (a_4, a_2)\}$



Acceptability


Given an argumentation framework $F = (A, R)$:

- What is **acceptable**?

Acceptability

Given an argumentation framework $F = (A, R)$:


- What is **acceptable**?
- Intuitively:



Acceptability

Given an argumentation framework $F = (A, R)$:


- What is **acceptable**?
- Intuitively:



Acceptability

Given an argumentation framework $F = (A, R)$:


- What is **acceptable**?
- Intuitively:



Acceptability

Given an argumentation framework $F = (A, R)$:


- What is **acceptable**?
- Intuitively:



Acceptability

Given an argumentation framework $F = (A, R)$:

- What is **acceptable**?
- Intuitively:



- We say that a_1 is defended by a_3 and a_4 against a_2

Cycles: Dilemmas

- a_1 : "I like this restaurant, let's eat here." (John)
- a_2 : "I don't like this restaurant, let's go somewhere else." (Yoko)



Cycles: Dilemmas


- a_1 : "I like this restaurant, let's eat here." (John)
- a_2 : "I don't like this restaurant, let's go somewhere else." (Yoko)



What can we accept?


Cycles: Paradoxes

- a_1 : "John says that Paul is a liar."
- a_2 : "Paul says that George is a liar."
- a_3 : "George says that John is a liar."



Cycles: Paradoxes

- a_1 : "John says that Paul is a liar."
- a_2 : "Paul says that George is a liar."
- a_3 : "George says that John is a liar."



What can we accept?

Extension-based Semantics [Dung 1995]

- **Extension:** set of jointly acceptable arguments
 - "solution" of the debate
 - "point of view" about the situation
- A set of arguments has to satisfy some properties to be an extension: *e.g.* we don't accept arguments a_1 and a_2 together if there is an attack between them
- **Semantics:** Function σ which maps an AF $F = \langle A, R \rangle$ to a set of extensions $\sigma(F) \subseteq 2^A$

Dung's Semantics

Basic principles

A set $S \subseteq A$ is

- conflict-free (**cf**) w.r.t. F if $\nexists a_i, a_j \in S$ s.t. $(a_i, a_j) \in R$
- admissible (**ad**) w.r.t. F if S is cf and S defends each $a_i \in S$ (i.e. $\forall a_i \in S, \forall a_j$ s.t. $(a_j, a_i) \in R, \exists a_k \in S$ s.t. $(a_k, a_j) \in R$)

Classical semantics

A set $S \subseteq A$ is

- complete (**co**) w.r.t. F if S is ad and S contains all the arguments that it defends
- preferred (**pr**) w.r.t. F if S is a maximal co extension (w.r.t. \subseteq)
- stable (**st**) w.r.t. F if S is cf and S attacks every $a_j \in A \setminus S$
- grounded (**gr**) w.r.t. F if S is a minimal co extension (w.r.t. \subseteq)

Arguments' Acceptance

Skeptical Acceptance


Given $F = \langle A, R \rangle$ and σ , $a \in A$ is skeptically accepted by F w.r.t. σ iff $\forall S \in \sigma(F)$,
 $a \in S$
 $skep_\sigma(F)$ is the set of skeptically accepted arguments

Credulous Acceptance

Given $F = \langle A, R \rangle$ and σ , $a \in A$ is credulously accepted by F w.r.t. σ iff $\exists S \in \sigma(F)$,
s.t. $a \in S$
 $cred_\sigma(F)$ is the set of credulously accepted arguments

Dung's Semantics

Example:



- $\{a_1, a_3, a_4\}$ is the unique complete (resp. preferred, stable, grounded) **extension**.
- This set is then also the set of **skeptically** and of **credulously** accepted arguments under these semantics.

How Semantics Deal with Dilemmas



How Semantics Deal with Dilemmas



Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\emptyset\}$	\emptyset	\emptyset

How Semantics Deal with Dilemmas



Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\emptyset\}$	\emptyset	\emptyset
stable	$\{\{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset

How Semantics Deal with Dilemmas



Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\emptyset\}$	\emptyset	\emptyset
stable	$\{\{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset

How Semantics Deal with Dilemmas



Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\emptyset\}$	\emptyset	\emptyset
stable	$\{\{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset
preferred	$\{\{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset

How Semantics Deal with Dilemmas



Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\emptyset\}$	\emptyset	\emptyset
stable	$\{\{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset
preferred	$\{\{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset

How Semantics Deal with Dilemmas



Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\emptyset\}$	\emptyset	\emptyset
stable	$\{\{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset
preferred	$\{\{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset
complete	$\{\emptyset, \{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset

How Semantics Deal with Dilemmas




Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\emptyset\}$	\emptyset	\emptyset
stable	$\{\{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset
preferred	$\{\{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset
complete	$\{\emptyset, \{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset

How Semantics Deal with Dilemmas




Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\emptyset\}$	\emptyset	\emptyset
stable	$\{\{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset
preferred	$\{\{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset
complete	$\{\emptyset, \{a_1\}, \{a_2\}\}$	$\{a_1, a_2\}$	\emptyset

How Semantics Deal with Paradoxes




How Semantics Deal with Paradoxes




Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\emptyset\}$	\emptyset	\emptyset
stable	\emptyset	\emptyset	$\{a_1, a_2, a_3\}$
preferred	$\{\emptyset\}$	\emptyset	\emptyset
complete	$\{\emptyset\}$	\emptyset	\emptyset

Exercise




Exercise




Questions:

- What are the **extensions** under the various semantics (grounded, stable, preferred, complete)?
- Under each semantics, which arguments are **credulously** accepted? Which ones are **skeptically** accepted?

Example: Semantics Comparison




Example: Semantics Comparison




Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\{a_1\}\}$	$\{a_1\}$	$\{a_1\}$
stable	$\{\{a_1, a_4, a_6\}\}$	$\{a_1, a_4, a_6\}$	$\{a_1, a_4, a_6\}$
preferred	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$
complete	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}, \{a_1\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$

Example: Semantics Comparison




Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\{a_1\}\}$	$\{a_1\}$	$\{a_1\}$
stable	$\{\{a_1, a_4, a_6\}\}$	$\{a_1, a_4, a_6\}$	$\{a_1, a_4, a_6\}$
preferred	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$
complete	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}, \{a_1\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$

Example: Semantics Comparison




Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\{a_1\}\}$	$\{a_1\}$	$\{a_1\}$
stable	$\{\{a_1, a_4, a_6\}\}$	$\{a_1, a_4, a_6\}$	$\{a_1, a_4, a_6\}$
preferred	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$
complete	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}, \{a_1\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$

Example: Semantics Comparison




Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\{a_1\}\}$	$\{a_1\}$	$\{a_1\}$
stable	$\{\{a_1, a_4, a_6\}\}$	$\{a_1, a_4, a_6\}$	$\{a_1, a_4, a_6\}$
preferred	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$
complete	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}, \{a_1\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$

Example: Semantics Comparison




Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\{a_1\}\}$	$\{a_1\}$	$\{a_1\}$
stable	$\{\{a_1, a_4, a_6\}\}$	$\{a_1, a_4, a_6\}$	$\{a_1, a_4, a_6\}$
preferred	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$
complete	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}, \{a_1\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$

Example: Semantics Comparison



Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\{a_1\}\}$	$\{a_1\}$	$\{a_1\}$
stable	$\{\{a_1, a_4, a_6\}\}$	$\{a_1, a_4, a_6\}$	$\{a_1, a_4, a_6\}$
preferred	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$
complete	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}, \{a_1\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$

Example: Semantics Comparison



Semantics σ	σ -extensions	$cred_{\sigma}$	$skep_{\sigma}$
grounded	$\{\{a_1\}\}$	$\{a_1\}$	$\{a_1\}$
stable	$\{\{a_1, a_4, a_6\}\}$	$\{a_1, a_4, a_6\}$	$\{a_1, a_4, a_6\}$
preferred	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$
complete	$\{\{a_1, a_4, a_6\}, \{a_1, a_3\}, \{a_1\}\}$	$\{a_1, a_3, a_4, a_6\}$	$\{a_1\}$

Computational Complexity

- Reasoning with AFs is generally hard [Dvorak and Dunne 2018]

Problem	Grounded	Stable	Preferred	Complete
Exist	Trivial	NP-c	Trivial	Trivial
Exist ^{NT}	L	NP-c	NP-c	NP-c
Verif	P-c	L	coNP-c	L
Cred	P-c	NP-c	NP-c	NP-c
Skep	P-c	coNP-c	Π_2^P -c	P-c

- Exist: For F and σ , is $\sigma(F) \neq \emptyset$?
- Exist^{NT}: For F and σ , is $\sigma(F) \neq \emptyset$ s.t. F has at least one non-empty extension?
- Verif: For F , S and σ , is $S \in \sigma(F)$?
- Cred: For F , a and σ , is there some $S \in \sigma(F)$ s.t. $a \in S$?
- Skep: For F , a and σ , is $a \in S$ for each $S \in \sigma(F)$?

A (very) naive approach

- Apply the definitions: compute all the **cf** sets, and then choose among them
 - Choose the ones that attack everything else: **st**
 - Choose the ones that defend themselves: **ad**
 - Choose the ones that contain everything they defend: **co**
 - Choose the \subseteq -maximal **ad** sets: **pr**
 - Choose the \subseteq -minimal **co** extension: **gr**

A (very) naive approach

- Apply the definitions: compute all the **cf** sets, and then choose among them
 - Choose the ones that attack everything else: **st**
 - Choose the ones that defend themselves: **ad**
 - Choose the ones that contain everything they defend: **co**
 - Choose the \subseteq -maximal **ad** sets: **pr**
 - Choose the \subseteq -minimal **co** extension: **gr**
- **Not efficient at all!**
 - The number of conflict-free sets can be exponential

Dung's Characteristic Function

Definition

The characteristic function of an AF $\langle A, R \rangle$ is $\mathcal{F} : 2^A \rightarrow 2^A$ defined, for $S \subseteq A$, by

$$\mathcal{F}(S) = \{a \in A \mid S \text{ defends } a\}$$

Dung's Characteristic Function

Definition

The characteristic function of an AF $\langle A, R \rangle$ is $\mathcal{F} : 2^A \rightarrow 2^A$ defined, for $S \subseteq A$, by

$$\mathcal{F}(S) = \{a \in A \mid S \text{ defends } a\}$$

Proposition

Let S be a conflict-free set. $S \in \text{ad}(F)$ iff $S \subseteq \mathcal{F}(S)$

Dung's Characteristic Function

Definition

The characteristic function of an AF $\langle A, R \rangle$ is $\mathcal{F} : 2^A \rightarrow 2^A$ defined, for $S \subseteq A$, by

$$\mathcal{F}(S) = \{a \in A \mid S \text{ defends } a\}$$

Proposition

Let S be a conflict-free set. $S \in \text{ad}(F)$ iff $S \subseteq \mathcal{F}(S)$

We can use the characteristic function to determine the extensions for all the semantics based on admissibility

co-Extensions and Characteristic Function

Proposition

Let S be a conflict-free set. $S \in \text{co}(F)$ iff $S = \mathcal{F}(S)$


co-Extensions and Characteristic Function

Proposition

Let S be a conflict-free set. $S \in \text{co}(F)$ iff $S = \mathcal{F}(S)$

- To compute a complete extension, consider a conflict-free set S , and apply iteratively the characteristic function until a fixed point is reached

Example



- $S = \{a_1, a_4\}$


co-Extensions and Characteristic Function

Proposition

Let S be a conflict-free set. $S \in \text{co}(F)$ iff $S = \mathcal{F}(S)$

- To compute a complete extension, consider a conflict-free set S , and apply iteratively the characteristic function until a fixed point is reached

Example



- $S = \{a_1, a_4\}$
- $S^2 = \mathcal{F}(S) = \{a_1, a_4, a_6\}$


co-Extensions and Characteristic Function

Proposition

Let S be a conflict-free set. $S \in \text{co}(F)$ iff $S = \mathcal{F}(S)$

- To compute a complete extension, consider a conflict-free set S , and apply iteratively the characteristic function until a fixed point is reached

Example




- $S = \{a_1, a_4\}$
- $S^2 = \mathcal{F}(S) = \{a_1, a_4, a_6\}$
- $S^3 = \mathcal{F}(S^2) = \{a_1, a_4, a_6\}$

pr-Extensions and Characteristic Function

- To compute a preferred extension with the characteristic function, first compute a complete extension S
- Then, define $A^S = \{a \in A \setminus S \mid S \cup \{a\} \in \mathbf{cf}(F)\}$
- If $A^S = \emptyset$, then S is a preferred extension of F
- Otherwise, choose some $a \in A^S$, and apply iteratively \mathcal{F} from $S \cup \{a\}$ until a new complete extension S^2 is obtained
- Repeat the process: if $A^{S^2} = \emptyset$, then S^2 is a preferred extension, otherwise choose some $a \in A^{S^2}$, etc.

Computing **pr**-Extensions


Example



- $S = \{a_1\}$ is a **co**-extension
- $A^S = \{a_3, a_4, a_5, a_6, a_7\}$

Computing **pr**-Extensions


Example



- $S = \{a_1\}$ is a **co**-extension
- $A^S = \{a_3, a_4, a_5, a_6, a_7\}$
- Pick $a_4 \in A^S$

Computing **pr**-Extensions


Example



- $S = \{a_1\}$ is a **co**-extension
- $A^S = \{a_3, a_4, a_5, a_6, a_7\}$
- Pick $a_4 \in A^S$
- $S^2 = \mathcal{F}(S \cup \{a_4\}) = \{a_1, a_4, a_6\}$

Computing **pr**-Extensions

Example



- $S = \{a_1\}$ is a **co**-extension
- $A^S = \{a_3, a_4, a_5, a_6, a_7\}$
- Pick $a_4 \in A^S$
- $S^2 = \mathcal{F}(S \cup \{a_4\}) = \{a_1, a_4, a_6\}$
- $A^{S^2} = \emptyset : S^2 \in \text{pr}(F)$

gr-Semantics and Characteristic Function

Proposition

The grounded extension of F is the fixed-point obtained when \mathcal{F} is applied iteratively from \emptyset

In short: take the unattacked arguments, and then propagate


gr-Semantics and Characteristic Function

Proposition

The grounded extension of F is the fixed-point obtained when \mathcal{F} is applied iteratively from \emptyset

In short: take the unattacked arguments, and then propagate

Example




gr-Semantics and Characteristic Function

Proposition

The grounded extension of F is the fixed-point obtained when \mathcal{F} is applied iteratively from \emptyset

In short: take the unattacked arguments, and then propagate

Example




gr-Semantics and Characteristic Function

Proposition

The grounded extension of F is the fixed-point obtained when \mathcal{F} is applied iteratively from \emptyset

In short: take the unattacked arguments, and then propagate

Example




gr-Semantics and Characteristic Function

Proposition

The grounded extension of F is the fixed-point obtained when \mathcal{F} is applied iteratively from \emptyset

In short: take the unattacked arguments, and then propagate

Example




gr-Semantics and Characteristic Function

Proposition

The grounded extension of F is the fixed-point obtained when \mathcal{F} is applied iteratively from \emptyset

In short: take the unattacked arguments, and then propagate

Example




gr-Semantics and Characteristic Function

Proposition

The grounded extension of F is the fixed-point obtained when \mathcal{F} is applied iteratively from \emptyset

In short: take the unattacked arguments, and then propagate

Example



Well-founded AFs

Definition [Dung 1995]

An AF $F = \langle A, R \rangle$ is well-founded iff $\nexists a_0, a_1, \dots$ an infinite sequence of arguments s.t. $\forall i \in \mathbb{N}^+, (a_{i+1}, a_i) \in R$

Well-founded AFs

Definition [Dung 1995]

An AF $F = \langle A, R \rangle$ is well-founded iff $\nexists a_0, a_1, \dots$ an infinite sequence of arguments s.t. $\forall i \in \mathbb{N}^+, (a_{i+1}, a_i) \in R$

- If A is finite, then well-founded is equivalent to acyclic

Well-founded AFs

Definition [Dung 1995]

An AF $F = \langle A, R \rangle$ is well-founded iff $\nexists a_0, a_1, \dots$ an infinite sequence of arguments s.t. $\forall i \in \mathbb{N}^+, (a_{i+1}, a_i) \in R$

- If A is finite, then well-founded is equivalent to acyclic

Theorem [Dung 1995]

For every well-founded AF F , $\text{gr}(F) = \text{st}(F) = \text{pr}(F) = \text{co}(F)$

- So it might be useful to check whether the graph is acyclic before computing extensions

Stable Semantics and SAT

Intuition:

- Encoding arguments' acceptance in Boolean variables
- Define a formula such that each model corresponds to an extension

Logical Encoding of Stable Semantics [Besnard and Doutre 2004]

For $F = \langle A, R \rangle$, $S \subseteq A$ is a stable extension of F iff S is a model of

$$\phi_{st}(F) = \bigwedge_{a \in A} (a \leftrightarrow \bigwedge_{(b,a) \in R} \neg b)$$

Stable Semantics and SAT

Intuition:

- Encoding arguments' acceptance in Boolean variables
- Define a formula such that each model corresponds to an extension

Logical Encoding of Stable Semantics [Besnard and Doutre 2004]

For $F = \langle A, R \rangle$, $S \subseteq A$ is a stable extension of F iff S is a model of

$$\phi_{st}(F) = \bigwedge_{a \in A} (a \leftrightarrow \bigwedge_{(b,a) \in R} \neg b)$$

- Stable extensions corresponds to kernels of the graph (see the Algorithmic Complexity lessons)

Admissible Sets and SAT

Logical Encoding of Conflict-freeness [Besnard and Doutre 2004]

For $F = \langle A, R \rangle$, $S \subseteq A$ is conflict-free in F iff S is a model of

$$\phi_{cf}(F) = \bigwedge_{(a,b) \in R} (\neg a \vee \neg b)$$

Logical Encoding of Defense [Besnard and Doutre 2004]

For $F = \langle A, R \rangle$, $S \subseteq A$ defends itself in F iff S is a model of

$$\phi_{def}(F) = \bigwedge_{a \in A} (a \rightarrow \bigwedge_{(b,a) \in R} (\bigvee_{(c,b) \in R} c))$$

Logical Encoding of Admissibility [Besnard and Doutre 2004]

For $F = \langle A, R \rangle$, $S \subseteq A$ is admissible in F iff S is a model of

$$\phi_{ad}(F) = \phi_{cf}(F) \wedge \phi_{def}(F)$$

Complete Extensions and SAT

- Complete extensions contain everything that they defend
- Modify $\phi_{def}(F)$:

$$\phi'_{def}(F) = \bigwedge_{a \in A} (a \leftrightarrow \bigwedge_{(b,a) \in R} (\bigvee_{(c,b) \in R} c))$$

Logical Encoding of Complete Semantics [Besnard and Doutre 2004]

For $F = \langle A, R \rangle$, $S \subseteq A$ is a complete extension of F iff S is a model of

$$\phi_{co}(F) = \phi_{cf}(F) \wedge \phi'_{def}(F)$$

- For grounded semantics, just apply unit propagation to $\phi_{co}(F)$

Preferred Extensions and SAT

- Preferred extensions cannot be directly encoded to SAT, since skeptical acceptance is Π_2^P -complete (except if the polynomial hierarchy collapses)
- An algorithm for using SAT at the second level of polynomial hierarchy: CEGAR [Dvorak *et al* 2012]
- Counter Example Guided Abstraction Refinement
- Principle of the algorithm:
 - Find an abstraction of the solution (e.g. a complete extension S instead of a preferred extension)
 - If S is preferred, then it's ok
 - Otherwise, modify the logical encoding to forbid S , and try again

A Competition of Solvers

- Since 2015, ICCMA (International Competition of Computational Models of Argumentation) evaluates the best algorithms for reasoning with AFs
- The best solvers are usually based on SAT
 - CoQuiAAS [Lagniez *et al* 2015]
 - ArgSemSAT [Cerruti *et al* 2014]
 - Cegartix [Dvorak *et al* 2012]
 - μ -Toksia (<https://www.cs.helsinki.fi/u/andreasn/>)
- Next competition: in 2023
 - <http://argumentationcompetition.org>

More Semantics

Other **extension-based** semantics:

- naive
- ideal
- stage
- semi-stable
- eager
- ...

See [Baroni *et al* 2018]

Other types of semantics:

- **Labelling-based** semantics

- Every argument is assigned a label: **in**, **out** or **undec**.
- a is labelled **in** iff $\forall b$ s.t. $(b, a) \in R$, b is labelled out
- a is labelled **out** iff $\exists b$ s.t. $(b, a) \in R$ and b is labelled in
- a is labelled **undec** iff a is neither labelled in nor out
- Several possible labellings can result.
- Correspondence shown between labellings and extensions

⇒ [Caminada 2006]

More Semantics

Other types of semantics:

- **Ranking-based** semantics

- A **pre-order** on arguments is defined, instead of sets of collectively acceptable arguments.
- The pre-order compares the acceptability of arguments.
- The comparison may be based on the number of attacking and defending arguments, for example.

⇒ See [Bonzon, Delobelle, Konieczny, Maudet 2016] for a comparative study of ranking-based semantics

References



P. M. Dung, *On the Acceptability of Arguments and its Fundamental Role in Nonmonotonic Reasoning, Logic Programming and n-Person Games*. Artificial Intelligence, 1995.



W. Dvorák and P.E. Dunne, *Computational Problems in Formal Argumentation and their Complexity*. Handbook of Formal Argumentation (1), pp. 631–688, 2018.



P. Besnard and S. Doutre, *Checking the acceptability of a set of arguments*. NMR 2004: 59-64;



W. Dvorák, M. Jarvisalo, J. P. Wallner and S. Woltran, *Complexity-Sensitive Decision Procedures for Abstract Argumentation*. KR 2012

References



J.-M. Lagniez, E. Lonca and J.-G. Mailly, *CoQuiAAS: A Constraint-Based Quick Abstract Argumentation Solver*. ICTAI 2015: 928-935



F. Cerutti, M. Giacomin and M. Vallati, *ArgSemSAT: Solving Argumentation Problems Using SAT*. COMMA 2014: 455-456



P. Baroni, M. Caminada and M. Giacomin, *Abstract Argumentation Frameworks and Their Semantics*. Handbook of Formal Argumentation (1), pp. 159–236, 2018



M. Caminada, *On the Issue of Reinstatement in Argumentation*. JELIA 2006: 111-123



E. Bonzon, J. Delobelle, S. Konieczny and N. Maudet, *A Comparative Study of Ranking-Based Semantics for Abstract Argumentation*. AAAI, 2016.

Outline

- 1 General Introduction to Argumentation
- 2 Abstract Argumentation Framework
 - Basics of Abstract Argumentation
 - Acceptability Semantics
 - Computational Approaches for Reasoning with Dung's AFs
 - Other Semantics
- 3 Other Frameworks

Generalization of Dung's Framework

There are many ways to **extend** the expressiveness of abstract argumentation, e.g.:

- Preferences
- Uncertainty in the graph
- Support relation
- Abstract dialectical frameworks

Preference-based Argumentation

- besides conflicts between arguments, the agent has some **preferences** between arguments [Amgoud and Cayrol 2002]
- if a_1 is preferred to a_2 , then no attack from a_2 to a_1 can succeed

Preference-based Argumentation

- besides conflicts between arguments, the agent has some **preferences** between arguments [Amgoud and Cayrol 2002]
- if a_1 is preferred to a_2 , then no attack from a_2 to a_1 can succeed



$PrF = \langle A, R, \leq \rangle$ with

- $A = \{a_1, a_2\}$
- $R = \{(a_1, a_2), (a_2, a_1)\}$
- $a_2 \leq a_1$ (i.e. a_1 is "better than" a_2)


Preference-based Argumentation

- besides conflicts between arguments, the agent has some **preferences** between arguments [Amgoud and Cayrol 2002]
- if a_1 is preferred to a_2 , then no attack from a_2 to a_1 can succeed



$PrF = \langle A, R, \leq \rangle$ with

- $A = \{a_1, a_2\}$
- $R = \{(a_1, a_2), (a_2, a_1)\}$
- $a_2 \leq a_1$ (i.e. a_1 is "better than" a_2)



\simeq

$F = \langle A, R \rangle$ with

- $A = \{a_1, a_2\}$
- $R = \{(a_1, a_2)\}$

Preference-based Argumentation


- besides conflicts between arguments, the agent has some **preferences** between arguments [Amgoud and Cayrol 2002]
- if a_1 is preferred to a_2 , then no attack from a_2 to a_1 can succeed



$PrF = \langle A, R, \leq \rangle$ with

- $A = \{a_1, a_2\}$
- $R = \{(a_1, a_2), (a_2, a_1)\}$
- $a_2 \leq a_1$ (i.e. a_1 is "better than" a_2)
 - Other definitions exist for the defeat relation [Amgoud and Vesic 2014, Kaci et al 2018]

\simeq



$F = \langle A, R \rangle$ with

- $A = \{a_1, a_2\}$
- $R = \{(a_1, a_2)\}$


Uncertainty in Abstract Argumentation

- Uncertainty is omnipresent in real world, and should be taken into account in AI
- Two possibilities:
 - Qualitative uncertainty: "I'm not sure whether this is true or false"
 - Quantitative uncertainty: "I believe that this is true at some degree"
→ probabilities, possibilities, . . .


Uncertainty in Abstract Argumentation

- Uncertainty is omnipresent in real world, and should be taken into account in AI
- Two possibilities:
 - Qualitative uncertainty: "I'm not sure whether this is true or false"
 - Quantitative uncertainty: "I believe that this is true at some degree"
→ probabilities, possibilities, . . .
- Both qualitative and quantitative approaches are considered in argumentation:
 - Probabilistic argumentation
[Li *et al* 2011, Thimm 2012, Hunter 2014, Gaignier *et al* 2021]
 - Partial/Incomplete argumentation frameworks
[Coste-Marquis *et al* 2007, Baumeister *et al* 2018, Dimopoulos *et al* 2018]

Incomplete AFs [Baumeister *et al* 2018]



Incomplete AFs [Baumeister *et al* 2018]




Bipolar Argumentation

- besides conflicts between arguments, there are **supports** between arguments
- pure support graphs also exist (e.g. recommendation letter, job application, ...)

Bipolar Argumentation

- besides conflicts between arguments, there are **supports** between arguments
- pure support graphs also exist (e.g. recommendation letter, job application, ...)





- Concepts like conflict-freeness and admissibility are generalized for this setting, then semantics can also be defined (see [Amgoud *et al* 2008] for technical details)

Abstract Dialectical Frameworks

- Proposed by [Brewka *et al* 2013]
- Abstract entities are called **statements**
- Statements can be linked together
- Each statement s_i is associated with a propositional formula built on other statements s_j s.t. there is a **link** from s_j to s_i
- s_i is accepted if its formula is true
- acceptance formulas can express (collective) attacks, (collective) supports or any complex relation



Abstract Dialectical Frameworks

- Proposed by [Brewka *et al* 2013]
- Abstract entities are called **statements**
- Statements can be linked together
- Each statement s_i is associated with a propositional formula built on other statements s_j s.t. there is a **link** from s_j to s_i
- s_i is accepted if its formula is true
- acceptance formulas can express (collective) attacks, (collective) supports or any complex relation





Abstract Dialectical Frameworks

- Proposed by [Brewka *et al* 2013]
- Abstract entities are called **statements**
- Statements can be linked together
- Each statement s_i is associated with a propositional formula built on other statements s_j s.t. there is a **link** from s_j to s_i
- s_i is accepted if its formula is true
- acceptance formulas can express (collective) **attacks**, (collective) supports or any complex relation





Abstract Dialectical Frameworks

- Proposed by [Brewka *et al* 2013]
- Abstract entities are called **statements**
- Statements can be linked together
- Each statement s_i is associated with a propositional formula built on other statements s_j s.t. there is a **link** from s_j to s_i
- s_i is accepted if its formula is true
- acceptance formulas can express (collective) attacks, (collective) **supports** or any complex relation










Abstract Dialectical Frameworks

- Proposed by [Brewka *et al* 2013]
- Abstract entities are called **statements**
- Statements can be linked together
- Each statement s_i is associated with a propositional formula built on other statements s_j s.t. there is a **link** from s_j to s_i
- s_i is accepted if its formula is true
- acceptance formulas can express (collective) attacks, (collective) supports or any complex relation



References

-  L. Amgoud and C. Cayrol, *Inferring from Inconsistency in Preference-Based Argumentation Frameworks*. J. Autom. Reasoning 29(2), pp 125-169, 2002.
-  L. Amgoud and S. Vesic, *Rich preference-based argumentation frameworks*. Int. J. Approx. Reason. 55(2): 585-606, 2014
-  S. Kaci, L. van der Torre and S. Villata, *Preference in Abstract Argumentation*. COMMA 2018: 405-412, 2018
-  H. Li, N. Oren and T. J. Norman, *Probabilistic argumentation frameworks*. TAFA'11, 1–16, 2011
-  A. Hunter, *Probabilistic qualification of attack in abstract argumentation*. Int. J. Approx. Reasoning 55(2):607–638, 2014
-  M. Thimm, *A probabilistic semantics for abstract argumentation*. ECAI'12, 750–755, 2012
-  F. Gaignier, Y. Dimopoulos, J.-G. Mailly, P. Moraitis, *Probabilistic Control Argumentation Frameworks*. AAMAS'21.

References



S. Coste-Marquis, C. Devred, S. Konieczny, M.-C. Lagasquie-Schiex and P. Marquis, *On the merging of Dung's argumentation systems*. Artif. Intell. 171(10-15): 730-753, 2007



D. Baumeister, D. Neugebauer, J. Rothe and H. Schadrack, *Verification in incomplete argumentation frameworks*. Artif. Intell. 264: 1-26, 2018



Y. Dimopoulos, J.-G. Mailly and P. Moraitis, *Control Argumentation Frameworks*. AAIL'18: 4678-4685, 2018



L. Amgoud, C. Cayrol, M.-C. Lagasquie-Schiex and P. Livet, *On bipolarity in argumentation frameworks*. Int. J. Intell. Syst. 23(10), 1062-1093, 2008.



G. Brewka, H. Strass, S. Ellmauthaler, J. . Wallner, S. Woltran, *Abstract Dialectical Frameworks Revisited*. IJCAI'13, 2013.