

IDENTIFICATION - ANALOG CARD

How to identification Analog Card in system health (software) is good or not?

1 Identification Analog Card on DCS Display



LED GREEN ON = Good Integrity
LED RED ON = BAD Integrity
LED PURPLE ON = No Card

Possibility :
IO Channel is Bad Integrity

IO Card Status
Information card status already
commisioned

2 Identification Analog Card using Diagnostic



Click this Symbol to open diagnostic page

Process	Channel	Unit	Current Integrity	Status	Alarm Name
Process 1	Channel 1	Unit 1	0.0000	Good	Unit 1
Process 2	Channel 2	Unit 2	0.0000	Good	Unit 2
Process 3	Channel 3	Unit 3	0.0000	Good	Unit 3
Process 4	Channel 4	Unit 4	0.0000	Good	Unit 4
Process 5	Channel 5	Unit 5	0.0000	Good	Unit 5
Process 6	Channel 6	Unit 6	0.0000	Good	Unit 6
Process 7	Channel 7	Unit 7	0.0000	Good	Unit 7
Process 8	Channel 8	Unit 8	0.0000	Good	Unit 8
Process 9	Channel 9	Unit 9	0.0000	Good	Unit 9
Process 10	Channel 10	Unit 10	0.0000	Good	Unit 10
Process 11	Channel 11	Unit 11	0.0000	Good	Unit 11
Process 12	Channel 12	Unit 12	0.0000	Good	Unit 12
Process 13	Channel 13	Unit 13	0.0000	Good	Unit 13
Process 14	Channel 14	Unit 14	0.0000	Good	Unit 14
Process 15	Channel 15	Unit 15	0.0000	Good	Unit 15
Process 16	Channel 16	Unit 16	0.0000	Good	Unit 16
Process 17	Channel 17	Unit 17	0.0000	Good	Unit 17
Process 18	Channel 18	Unit 18	0.0000	Good	Unit 18
Process 19	Channel 19	Unit 19	0.0000	Good	Unit 19
Process 20	Channel 20	Unit 20	0.0000	Good	Unit 20

Check IO channel which one is problem or disconnected

How to identification Analog Card in system health (hardware) is good or not?



LED correct operating condition	Fault indication	Probable cause and corrective action
Power-On (green)	Off	System power is not supplied to unit due to a possible input power problem. Check the power supply connections and the bulk power supply connections.
	Internal fault	Contact technical support.
Error-Off (red)	On (continuous)	Unit failed a self-test. Contact technical support.
	On (flashing)	The CPU is not scanning the card. Check the CPU's operation.
	Hardware error	Replace the card with a good card of the same type and contact technical support.

IDENTIFICATION - DISCRETE CARD

How to identification Discrete Card in system health (software) is good or not?


1 Identification Discrete Card on DCS Display



LED GREEN ON = Good Integrity
LED RED ON = BAD Integrity

Possibility :
IO Card is failure

2 Identification Discrete Card using Diagnostic



Click this Symbol to open diagnostic page

Process	Channel	Unit	Current Integrity	Status	Alarm Name
Process 1	Channel 1	Unit 1	0.0000	Good	Unit 1
Process 2	Channel 2	Unit 2	0.0000	Good	Unit 2
Process 3	Channel 3	Unit 3	0.0000	Good	Unit 3
Process 4	Channel 4	Unit 4	0.0000	Good	Unit 4
Process 5	Channel 5	Unit 5	0.0000	Good	Unit 5
Process 6	Channel 6	Unit 6	0.0000	Good	Unit 6
Process 7	Channel 7	Unit 7	0.0000	Good	Unit 7
Process 8	Channel 8	Unit 8	0.0000	Good	Unit 8
Process 9	Channel 9	Unit 9	0.0000	Good	Unit 9
Process 10	Channel 10	Unit 10	0.0000	Good	Unit 10
Process 11	Channel 11	Unit 11	0.0000	Good	Unit 11
Process 12	Channel 12	Unit 12	0.0000	Good	Unit 12
Process 13	Channel 13	Unit 13	0.0000	Good	Unit 13
Process 14	Channel 14	Unit 14	0.0000	Good	Unit 14
Process 15	Channel 15	Unit 15	0.0000	Good	Unit 15
Process 16	Channel 16	Unit 16	0.0000	Good	Unit 16
Process 17	Channel 17	Unit 17	0.0000	Good	Unit 17
Process 18	Channel 18	Unit 18	0.0000	Good	Unit 18
Process 19	Channel 19	Unit 19	0.0000	Good	Unit 19
Process 20	Channel 20	Unit 20	0.0000	Good	Unit 20

Check IO channel which one is problem or disconnected

How to identification Discrete Card in system health (hardware) is good or not?



LED correct operating condition	Fault indication	Possible cause and corrective action
Power-On (green)	Off	System power is not supplied to the unit. Check the power supply connections and bulk power supply connections.
	Internal fault	Contact technical support.
Error-Off (red)	On (continuous)	Unit failed a self-test. Contact technical support.
	On (flashing)	The CPU is not scanning the card. Check the CPU operation.
	Hardware error	Replace with a good card of the same type and contact technical support.