

REFINERY PLANT IV 56										Page : 2 of 3		E&I PROJECT										
Project Code :										Date :		30/10/2018										
Document Name :										ELECTRICAL LOAD LIST												
Document No :										BED-DOC-REF2-EI-01												
MVA Sizing										REV 0												
Electromotor Data										Cable Connection				Panel								
No.	Original Tag	Winar Tag	Designation	continuous availability	Starting	Rated Power (KW)	Nom. Current (A)	PF	Poles/Rated Speed rpm	Rated Voltage (V)	Motor Brand	Motor Type/Model	EEX Prod. Req.	Index Protection	Type	Size (sqmm)	Pulling Quantity / (Set)	Length / Pulling (m)	Total Length(m)	Gland Size (mm)	Connecting	Remarks
ISBL																						
2	PT506	PU2006	Vacuum Dryer Oil Pump	1	DOL	18.5	37.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x16mm	1	80	80	M32		
3	PT534CA	PU2034CA	Clinic Acid Dosing Pump	1	VFD	0.75	2.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-26B1	PTC
4	PT534PA	PU2034PA	Phosphoric Acid Dosing Pump	1	VFD	0.55	1.6			380 V 50 Hz 3Ph			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-26B1	PTC
5	MT503A	AG2003A	Aldex Mixer	1	DOL	37	72.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x35mm	1	80	80	M32	MCC-26B1	As Per PSA Result
6	MT503-A	AG2003A	Anilator for TS03	1	DOL	7.5	15.5			380 V 50 Hz 3Ph			N/A		YYY-FR	4x6mm	1	80	80	M25	MCC-26B1	
7	MT534CA	AG234CA	Anilator for TS34CA	1	DOL	0.75	2.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-26B1	
8	MS64C	AG264C	Anilator for 604C	1	DOL	22	44.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x16mm	1	80	80	M32	MCC-26B1	
9	P604C	PU2604C	Filter Aid Pump	1	DOL	15	30.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x10mm	1	80	80	M25	MCC-26B1	
10	P622-1	PU2622-1	Filter Feed Pump	1	DOL	15	30.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x10mm	1	80	80	M25	MCC-26B1	
11	P622-2	PU2622-2	Filter Feed Pump	1	DOL	15	30.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x10mm	1	80	80	M25	MCC-26B1	
12	P622-3	PU2622-3	Filter Feed Pump	1	DOL	15	30.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x10mm	1	80	80	M25	MCC-26B1	
13	P622-4	PU2622-4	Filter Feed Pump	1	DOL	15	30.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x10mm	1	80	80	M25	MCC-26B1	
14	P622-5	PU2622-5	Filter Feed Pump	1	DOL	15	30.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x10mm	1	80	80	M25	MCC-26B1	
15	P680A	PU080A	Recovered Oil Pump	1	DOL	4	8.5			380 V 50 Hz 3Ph			N/A		YYY-FR	4x2.5mm	1	80	80	M20	MCC-26B1	
16	P682B	PU2682B	Filtered Oil Pump	1	DOL	22	44.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x16mm	1	80	80	M32	MCC-26B1	
17	P641X	PU2641X	Vacuum Pump	1	DOL	37	72.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x35mm	1	80	80	M32	MCC-26B1	As Per PSA Result
18	P641X-CP	PU041X-CP	Circulation pump for P641X	1	DOL	1.5	3.5			380 V 50 Hz 3Ph			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-26B1	Hardwire interlock with P641X motor starter circuit
19	P802	PU2702	Desalter Transfer Pump	1	DOL	37	72.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x35mm	1	80	80	M32	MCC-26B1	As Per PSA Result
20	P614AG	PU2714AG	Fatty Acids Circulation Pump	1	DOL	45	95.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x35mm	1	80	80	M32	MCC-26B1	As Per PSA Result
21	P650B-1AG	PU2720	Fatty Acids Tempered Water Pump	1	DOL	7.5	15.5			380 V 50 Hz 3Ph			N/A		YYY-FR	4x6mm	1	80	80	M25	MCC-26B1	
22	P822C1	PU2722C1	Deodorizer Oil Transfer Pump	1	DOL	15	34.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x10mm	1	80	80	M25	MCC-26B1	c/w Dry Run Protection Relay (Supply by Desmet)
23	P822C2	PU2722C2	Deodorizer Oil Transfer Pump	1	DOL	15	34.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x10mm	1	80	80	M25	MCC-26B1	c/w Dry Run Protection Relay (Supply by Desmet)
24	P822	PU2722	Deodorizer Oil Pump	1	DOL	30	66.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x25mm	1	80	80	M32	MCC-26B1	c/w Dry Run Protection Relay (Supply by Desmet) As Per PSA Result
25	P822-2	PU2722-2	Deodorizer Oil Pump	1	DOL	30	66.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x25mm	1	80	80	M32	MCC-26B1	c/w Dry Run Protection Relay (Supply by Desmet) As Per PSA Result
26	MB34C-A	AG2734C-A	Anilator for TR34C-A	1	DOL	0.75	2.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-26B1	
27	P534CA	BU2734CA	Clink Acid Dosing Pump	1	VFD	0.75	1.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-26B1	
28	P641X	PU2741X	Vacuum Pump	1	DOL	5.5	11.5			380 V 50 Hz 3Ph			N/A		YYY-FR	4x4mm	1	80	80	M20	MCC-26B1	
29	850HP	PU2950HP	Boiler	1	OIG	43	75.0			380 V 50 Hz 3Ph			N/A		YYY-FR	4x35mm	1	80	80	M32	MCC-26B1	
30			Sightglass Lighting		OIG	0.25				24 V AC			N/A		YYY-FR						MCC-26B1	5 nos Sightglass lighting 50W 24VAC,Need Transformer 220VAC // 24 AC
31			Sightglass Lighting		OIG	0.80				24 V AC			N/A		YYY-FR						MCC-26B1	16 nos Sightglass lighting 100W 24VAC,Need Transformer 220VAC // 24 AC
Total Connected Load				B+C	A	471.6	944.1	KW	A													
Max Load				B	A	425.60	844.10															
Stand by Load				C	A	45.00	100.00			633.1												