

		Continues Refinery (QCD) Plant										Page : 2 of 4		E&I PROJECT									
		Project Code :		ELECTRICAL LOAD LIST								Date : 01/08/2018											
MNA Serang		Document No :		BED-DCC-CRF-EI-01										REV.0									
Electromotor Data															Cable Connection					Panel	Remarks		
No.	Original Tag	Wilmar Tag	Designation	Requirement continuous standby	Starting	Rated Power (KW)	Nom. Current (A)	PF	Poles/Rated Speed rpm	Rated Voltage (V)	Motor Brand	Motor Type/Model	EEX Proof Req	Index Protection	Type	Size (sqmm)	Pulling Quantity (Set)	Length / Pulling (m)	Total Length(m)	Gland Size (mm)		Connecting	
RSBL																							
1	2PU321	PU1021	Phosphoric Acid Pump	1	1	VFD	0.25	0.5		380 V 50 Hz 3PH			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-29B3		
2	2PU322	PU1022	Citric Acid Pump	1		DOL	0.25	0.5		380 V 50 Hz 3PH			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-29B3		
3	2MX311	MX1011	Acid Mixer	1		DOL	4	7.5		380 V 50 Hz 3PH			N/A		YYY-FR	4x2.5mm	1	80	80	M20	MCC-29B3		
4	2MX312	MX1012	Decarboxium Reactor	1		DOL	0.75	1.4		380 V 50 Hz 3PH			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-29B3		
5	2MX322	MX1022	Mixer for Citric Acid Tank	1		DOL	0.38	0.7		380 V 50 Hz 3PH			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-29B3		
6	EP631	PU1631	Fan Blower for Converter System	1		DOL	18.5	34.5		380 V 50 Hz 3PH			N/A		YYY-FR	4x16mm	1	80	80	M32	MCC-29B3		
7	2PU621	PU1621	Filter Feed Pump 1	1		DOL	18.5	34.5		380 V 50 Hz 3PH			N/A		YYY-FR	4x16mm	1	80	80	M32	MCC-29B3		
8	2PU622	PU1622	Filter Feed Pump 2	1		DOL	18.5	34.5		380 V 50 Hz 3PH			N/A		YYY-FR	4x16mm	1	80	80	M32	MCC-29B3		
9	2PU641	PU1641	Slop Oil Pump	1		DOL	7.5	14.0		380 V 50 Hz 3PH			N/A		YYY-FR	4x6mm	1	80	80	M25	MCC-29B3		
10	2PU661	PU1661	Filtrate Transfer Pump	1		DOL	7.5	14.0		380 V 50 Hz 3PH			N/A		YYY-FR	4x6mm	1	80	80	M25	MCC-29B3		
11	2VB632A	PU1632A	Electric Vibrator for TK632A	1		DOL	0.18	0.3		380 V 50 Hz 3PH			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-29B3		
12	2VB632B	PU1632B	Electric Vibrator for TK632B	1		DOL	0.18	0.3		380 V 50 Hz 3PH			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-29B3		
13	2PU701	PU1701	Deodorizer Feed Pump	1		VFD	18.5	34.5		380 V 50 Hz 3PH			N/A		YYY-FR	4x16mm	1	80	80	M32	MCC-29B3		
14	2PU721A	PU1721A	Hot Oil Discharge Pump	1		VFD	18	33.6		380 V 50 Hz 3PH			N/A		YYY-FR	4x16mm	1	80	80	M32	MCC-29B3		
15	2PU721B	PU1721B	Hot Oil Discharge Pump	1		VFD	18	33.6		380 V 50 Hz 3PH			N/A		YYY-FR	4x16mm	1	80	80	M32	MCC-29B3		
16	2PU751	PU1751	Fatty Acid Distillate Pump	1		VFD	15	28.0		380 V 50 Hz 3PH			N/A		YYY-FR	4x10mm	1	80	80	M25	MCC-29B3		
17	2PU752	PU1752	Tempered Water Circulation Pump	1		DOL	7.5	14.0		380 V 50 Hz 3PH			N/A		YYY-FR	4x6mm	1	80	80	M25	MCC-29B3		
18	2PU761	PU1761	Citric Acid / Anti-Oxidant Pump	1		DOL	0.25	0.5		380 V 50 Hz 3PH			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-29B3		
19	MX761	MX1761	Mixer for Anti-Oxidant Day Tank	1		DOL	0.38	0.7		380 V 50 Hz 3PH			N/A		YYY-FR	4x1.5mm	1	80	80	M20	MCC-29B3		
20	2HB721	HP51721	High Pressure Steam Boiler	1		OG	30	55.9		380 V 50 Hz 3PH			N/A		YYY-FR	4x25mm	1	80	80	M52	MCC-29B3		
21	2VPS61	PU1651	Vacuum Pump (Bleaching Section)	1		DOL	15	28.0		380 V 50 Hz 3PH			N/A		YYY-FR	4x10mm	1	80	80	M25	MCC-29B3		
				20	1	75 % Max Load																	
Total Connected Load				B+C	A	199.12	371.19	KW	A														
Max Load				B	A	188.87	370.72	149.21	278.0														
Stand by Load				C		0.25	0.47																