

Backend Incoming Changes — Mobile Team Sync

PIF Directors Gathering · backend pull `cd2410b..6704047` on branch `testing`

Generated: 2026-05-17 · 181 files · +16,743 / -34 lines · 39 new migrations · 30 new controllers · 21 new models

Purpose. Surface every backend change in this pull that affects the Flutter mobile client — new endpoints, auth flow, real-time channels, push notifications, white-label config, and required infra. Use this as the agenda for the upcoming mobile-team sync. All mobile routes live under `/api/mobile/*` and (except identity bootstrap) require a Sanctum token via `Authorization: Bearer <token>`.

Table of contents

1. Summary of features shipped	12. Sponsors (F5b)
2. Identity & OTP login (F1)	13. Publications (F13)
3. Device token registration (FCM/APNs/HMS)	14. Media Center (F12)
4. Account deletion (Apple Review)	15. QR scanner (F14)
5. App Review demo account bypass	16. Meeting-room booking (F9)
6. App config & white-label theme (F5)	17. In-app notifications (F6)
7. Event days / programs (F2)	18. 1-on-1 Chat — REST + FCM + Reverb (F7/F8)
8. Speakers (F3)	19. Required environment variables
9. Sessions + favorites + feedback (F4)	20. Composer / infrastructure dependencies
10. Workshops + registration + feedback (F18)	21. Cross-cutting conventions
11. Attendee directory (F10)	22. Open items to discuss

1. Summary of features shipped

#	Feature	Mobile prefix	Auth	Real-time?	Push?
F1	Identity / OTP login + token expiry	<code>/api/mobile/identity</code>	throttled public + sanctum	—	—
F2	Event Days (programs)	<code>/api/mobile/event-days</code>	sanctum + guest	—	—
F3	Speakers	<code>/api/mobile/speakers</code>	sanctum + guest	—	—
F4	Sessions + favorites + feedback	<code>/api/mobile/sessions</code>	sanctum + guest	—	—
F5	App config / white-label theme	<code>/api/app-config</code> + <code>.../version</code>	public	—	—
F5b	Sponsors (decoupled from Conference)	<code>/api/mobile/sponsors</code>	sanctum + guest	—	—
F6	In-app notifications	<code>/api/mobile/notifications</code>	sanctum + guest	—	FCM

#	Feature	Mobile prefix	Auth	Real-time?	Push?
F7/F8	1-on-1 chat (REST + FCM + Reverb)	/api/mobile/chat	sanctum + guest	Reverb WSS	FCM
F9	Meeting-room booking	/api/mobile/rooms	sanctum + guest	—	FCM
F10	Attendee directory	/api/mobile/attendees	sanctum + guest	—	—
F12	Media Center (docs / videos / images)	/api/mobile/media-center	sanctum + guest	—	—
F13	Publications	/api/mobile/publications	sanctum + guest	—	—
F14	QR scanner → guest resolve	/api/mobile/qr	sanctum + guest	—	—
F18	Workshops (capacity-aware) + feedback	/api/mobile/workshops	sanctum + guest	—	—
F21	Account-deletion (Apple Review)	/api/mobile/identity/delete-account	sanctum + guest	—	—

All sanctum-guarded mobile routes also pass through `auth.guest` (rejects admin tokens) and `localization` middleware (`Accept-Language` = `en|ar`, falls back to `en`).

2. Identity & OTP login (F1)

Endpoints NEW

Method	Path	Auth	Notes
POST	/api/mobile/identity/check-email	PUBLIC	throttled <code>sensitive-api</code> ; sends OTP if guest is <code>Accepted</code> / <code>Invited</code>
POST	/api/mobile/identity/verify-otp	PUBLIC	returns <code>{ user, token }</code>
GET	/api/mobile/identity/register	PUBLIC	302 redirect to <code>MOBILE_REGISTER_URL</code>
GET	/api/mobile/identity/register-with-code	PUBLIC	302 redirect to <code>MOBILE_REGISTER_WITH_CODE_URL</code>
GET	/api/mobile/identity/logout	SANCTUM	revokes current access token

OTP rules BEHAVIOUR

- 6-digit numeric, sent via `GuestOtpMailable` (email channel).
- Expiry: `MOBILE_OTP_EXPIRY_MINUTES` (default `5`).
- Max attempts: `MOBILE_OTP_MAX_ATTEMPTS` (default `5`) — exceeding returns `429`.
- Wrong OTP increments `attempts` column on `email_verifications` ; correct OTP deletes the row.
- Sanctum token TTL: `MOBILE_TOKEN_EXPIRY_DAYS` (default `30`) — per-token expiry, not session-level.

Sample `user` payload (`GuestMobileResource`)

```
{
  "id": "uuid",
  "name": "Jane Doe",
  "first_name": "Jane",
  "last_name": "Doe",
  "email": "jane@example.com",
  "phone": "+9665...",
  "avatar": "https://.../personal_image/xxx.jpg" | null,
  "role": "speaker" | "attendee",
  "category": "speakers" | "directors" | ...,
  "status": "accepted" | "invited",
  "company": "Acme",
  "job_title": "Director",
  "isSpeaker": true,
  "interests": [],           // session UUIDs once favorites are loaded
  "createdAt": "...",
  "updatedAt": "..."
}
```

Heads-up. If a guest has filed an account-deletion request, `check-email` intentionally returns the same "not registered" response as if the email never existed. Treat it as a normal 400 — don't branch on a special message.

3. Device token registration (FCM / APNs / HMS) NEW

Method	Path	Body	Notes
POST	/api/mobile/identity/device-tokens	<pre>{ token: string, platform?: "fcm" "apns" "hms" }</pre>	idempotent on <code>(guest_id, token)</code> ; defaults <code>platform="fcm"</code>

- Mobile **must** call this after login and on every token refresh, otherwise the guest receives no FCM pushes (chat, room booking, notifications module).
- Returns the refreshed `user` payload — UI can rely on it for an instant profile rehydrate.

4. Account deletion (Apple Review) NEW

Method	Path	Effect
GET	/api/mobile/identity/delete-account	Inserts <code>account_deletion_requests</code> row, revokes every Sanctum token for the guest (all devices logged out), and invalidates any pending OTP. Subsequent logins return the "not registered" response until an admin processes the request.

Mobile UX requirement: a deletion CTA must be reachable from the Settings screen and gated behind `features.delete_account` in app-config (see §6 — there's a new `feature_delete_account` flag on `conferences`).

5. App Review demo account bypass NEW

Two new env vars allow a hard-coded credential pair for App Review without actually issuing OTPs (the reviewer's email won't be in our DB). When both are set, `check-email` returns success without sending email, and `verify-otp` accepts the literal `MOBILE_DEMO_OTP` .

```
MOBILE_DEMO_EMAIL=demo@reviewer.example
MOBILE_DEMO_OTP=246810
```

- The matching guest **must exist** in DB with status Accepted/Invited.
- Leave both blank to disable in prod once the review passes.
- Mobile doesn't need to change anything — the bypass is server-side only.

6. App config & white-label theme (F5) NEW PUBLIC

Method	Path	Purpose
GET	/api/app-config/version	cheap poll → <code>{ version: "abc123..." }</code>
GET	/api/app-config	full themed payload (both EN+AR)

Payload shape

```
{
  "version": "16-char-random",
  "theme": {
    "surfaces": { page_background, surface_color, card_secondary, surface_light, navigation_bar,
input_background },
    "brand": { accent_color, highlight_color, active_color, gradient_start, gradient_end,
timer_background, timer_border_start, timer_border_end, timer_label_color },
    "buttons": { button_background, button_border },
    "text": { text_primary, text_secondary, icon_color },
    "borders": { card_border, input_border },
    "status": { error_color, warning_color, pending_color },
    "fonts": { primary },
    "logo": { url }
  },
  "conference": { name_en, name_ar, start_date, end_date, location_en, location_ar,
location_url, hashtag, video_url, sessions_video_url },
  "content": { app_name_en, app_name_ar, welcome_message_en, welcome_message_ar,
about_en, about_ar, terms_url, privacy_url, registration_url },
  "features": { speakers, programs, my_agenda, attendees, chat, room_booking,
media_center, publications, partners, venue, notifications,
survey, qr_scanner, delete_account },
  "feature_labels": { ... } // ALWAYS a JSON object – never an array
  "feature_icons": { ... } // URLs already resolved
  "navigation": { ... } // ALWAYS a JSON object
  "links": { twitter, instagram, linkedin, youtube, facebook, tiktok, website,
support_email, support_phone },
  "defaults": { avatar_url, placeholder_image_url, splash_background_url,
home_banner_url, speaker_pattern_url }
}
```

Contract note. `feature_labels`, `feature_icons` and `navigation` are **always JSON objects** (`{}` when empty), never arrays. Flutter must deserialize them as `Map`. Backend validation already blocks indexed arrays from reaching this endpoint.

Recommended client flow

1. On app start (and periodically / on resume) call `/app-config/version`.
2. If `version` differs from cached one, fetch `/app-config` and store both.
3. All theme colors arrive as **hex strings** (e.g. `#1E3A8A`). Treat `null` as "use built-in fallback".
4. Drive feature toggles (chat, room_booking, media_center, delete_account, ...) off `features.*`.

7. Event days / programs (F2) NEW

Method	Path	Notes
<code>GET</code>	<code>/api/mobile/event-days/fetch</code>	response wrapper key is <code>"programs"</code> for Flutter contract compatibility

8. Speakers (F3) NEW

Method	Path	Notes
GET	/api/mobile/speakers	list
GET	/api/mobile/speakers/{id}	detail wrapped in <code>{ "speaker": { ... } }</code>

Backend speaker schema gained `bio`, `country`, and `company` columns — these show up in `SpeakerResource` and are now exposed in detail.

9. Sessions + favorites + feedback (F4) NEW

Method	Path	Notes
GET	/api/mobile/sessions	filters: <code>?date=YYYY-MM-DD</code> , <code>?speakerId=</code> , <code>?programId=</code> ; default <code>limit=100</code>
GET	/api/mobile/sessions/search	<code>?keyword=</code> matches <code>name_en/ar + description_en/ar</code>
GET	/api/mobile/sessions/favorite	current guest's favorites
POST	/api/mobile/sessions/favorite	<code>{ sessionId: uuid, action: "add" \ "remove" }</code>
GET	/api/mobile/sessions/{id}	flat JSON (no wrapper)
GET	/api/mobile/sessions/{id}/feedback	existing feedback for this guest (or empty)
POST	/api/mobile/sessions/{id}/feedback	submit

Detail shape (`SessionDetailResource`)

```
{
  "id", "name", "date", "duration", "address", "type", "description",
  "program": { id, name, icon } | null,
  "speakers": [ { id, name, subtitle, avatar } ],
  "isFavorite": bool,
  "hasSubmittedFeedback": bool,
  "interestedUsers": { avatars: [up to 5 URLs], total: int },
  "media": [ { name, type, url } ]
}
```

10. Workshops (capacity-aware) + feedback (F18) NEW

Method	Path	Notes
GET	/api/mobile/workshops	filters identical to sessions (<code>date/speakerId/programId</code>)
GET	/api/mobile/workshops/search	<code>?keyword=</code>
GET	/api/mobile/workshops/registered	workshops the current guest is registered for
POST	/api/mobile/workshops/{id}/register	capacity-aware, transactional — 409 with <code>error: "workshop_full"</code> when full; idempotent re-register returns 200 "Already registered"

Method	Path	Notes
DELETE	/api/mobile/workshops/{id}/register	idempotent — 204 whether registered or not
GET	/api/mobile/workshops/{id}	flat JSON
GET	/api/mobile/workshops/{id}/feedback	existing feedback
POST	/api/mobile/workshops/{id}/feedback	submit

Detail shape (`WorkshopDetailResource`)

```
{
  "id", "name", "date", "duration", "address", "type", "description",
  "capacity", "registeredCount", "seatsRemaining", "isFull",
  "isRegistered", "hasSubmittedFeedback",
  "floorMapUrl": string | null,
  "program": { id, name, icon } | null,
  "speakers": [ { id, name, subtitle, avatar } ],
  "registeredGuests": { avatars: [up to 5 URLs], total: int }
}
```

Capacity check is wrapped in `DB::transaction` with a row-level `lockForUpdate` on the workshop. The mobile UI does not need a client-side guard — just handle the `409` response.

11. Attendee directory (F10) NEW

Method	Path	Notes
GET	/api/mobile/attendees	default <code>per_page=1000</code> — Flutter loads all attendees at once and filters client-side

12. Sponsors (F5b) NEW

Method	Path	Notes
GET	/api/mobile/sponsors	active sponsors ordered by <code>label.order, sponsor.order, created_at</code> ; localized via <code>Accept-Language</code> or <code>?lang=</code>

Decoupled from `Conference` — sponsors are no longer embedded in app-config; the mobile client must call this endpoint separately.

13. Publications (F13) NEW

Method	Path	Notes
GET	/api/mobile/publications	flat array; <code>MediaResponse</code> model is shared with F12

Item shape (`PublicationResource`)

```
{
  "id", "title", "description",
  "fileUrl": "https://.../publications/xxx.pdf",
  "fileType": "pdf" | "docx" | ...,
  "order": int,
  "uploadedBy": { id, name, email } | null,
  "createdAt", "updatedAt"
}
```

14. Media Center (F12) NEW

Method	Path	Notes
<code>GET</code>	<code>/api/mobile/media-center</code>	grouped response: <code>{ videos, documents, images }</code> — not a flat array

Image uploads on the admin side dropped the dimension restriction in a follow-up commit — any image (jpg/png/webp) goes through.

15. QR scanner (F14) NEW

Method	Path	Notes
<code>POST</code>	<code>/api/mobile/qr</code>	Resolves a scanned code to a guest profile. Lookup priority: badge registration_number first, then Sanctum personal-access-token. Returns <code>QrGuestResource</code> .

16. Meeting-room booking (F9) NEW

Slot bookings are **race-safe**: an atomic UPDATE flips `is_booked false→true` in a single statement; the second concurrent request matches 0 rows and gets a 400. **Past slots are rejected** across book / edit / cancel.

Method	Path	Notes
<code>GET</code>	<code>/api/mobile/rooms</code>	variants: no params (flat with all slots) · <code>?date=YYYY-MM-DD</code> · <code>?grouped=true</code> (rooms grouped by date)
<code>GET</code>	<code>/api/mobile/rooms/bookings</code>	slots where current guest is host OR in invited <code>guests</code> pivot
<code>GET</code>	<code>/api/mobile/rooms/users</code>	<code>?name=&page=&limit=</code> search guests for invitation (Accepted/Invited only, excludes self)
<code>POST</code>	<code>/api/mobile/rooms/book</code>	<code>{ roomId, slotId, guests?: uuid[] }</code> → 201 <code>MobileSlotResource</code>
<code>DELETE</code>	<code>/api/mobile/rooms/bookings/{slotId}</code>	host OR invited guest can cancel; past blocked
<code>PATCH</code>	<code>/api/mobile/rooms/bookings/{slotId}</code>	host-only , swap to a new slot in the same room + same date

Push notifications fired by this module FCM

- **Book:** host gets "You have successfully booked ..."; invited guests get "{host} has booked ... and added you as a guest."
- **Cancel:** all participants get "{actor} has cancelled the booking for {room} on {date} at {time}".
- **Edit:** host + invited guests get the new time.

All FCM sends are wrapped in `try/catch` + logged — a Firebase outage never blocks the booking write.

17. In-app notifications (F6) NEW

Method	Path	Notes
GET	/api/mobile/notifications	Custom wrapper (NOT Laravel paginator): <code>{ notifications, totalNotifications, totalPages, currentPage }</code> . Query params: <code>pageNumber</code> (or <code>page</code>) and <code>pageSize</code> .
GET	/api/mobile/notifications/mark-read	side-effecting GET (matches Flutter <code>GetRequestStrategy</code>); body is the literal string <code>"OK"</code>
GET	/api/mobile/notifications/unread-count	body is a plain integer
GET	/api/mobile/notifications/clear	deletes this guest's <code>notification_recipients</code> rows (shared <code>app_notifications</code> stay intact)

All 4 endpoints are **GET**. Do not change the verb to PATCH/DELETE — Flutter's `GetRequestStrategy` wraps these calls and parses `"OK"` / integer responses literally.

18. 1-on-1 Chat — REST + FCM + Reverb (F7/F8) NEW REAL-TIME

REST

Method	Path	Notes
GET	/api/mobile/chat/rooms	rooms current guest participates in, ordered by last activity; default <code>limit=1000</code>
GET	/api/mobile/chat/rooms/{roomId}/messages	side-effect: marks unread messages received in this room as read
POST	/api/mobile/chat/messages	<code>{ participant_id: uuid, content: string≤5000 }</code> ; 201 if room auto-created, 200 if reused
GET	/api/mobile/chat/unread-count	total unread across all rooms

Real-time broadcast (Reverb)

- Channel: `private-chat.{room_id}` — uses Pusher protocol (Reverb is wire-compatible).
- Event name: `message.sent` (note the dot — set via `broadcastAs()`).

- Payload:

```
{
  "roomId": "room-uuid",
  "message": {
    "id": "msg-uuid",
    "content": "...",
    "sender": { id, name, avatar, role },
    "timestamp": "2026-05-17T11:22:33+00:00",
    "read": false
  }
}
```

- Authorization endpoint is the default Laravel one — Flutter Pusher client should POST to `/broadcasting/auth` with the bearer token. Channel guard checks the guest is a participant of the room.
- Server suppresses echo to the sender (`->toOthers()`) — the sender already has the message from the HTTP response.

FCM push on send

After persisting the message, the controller fans the message body out to every `DeviceToken` belonging to the recipient. FCM failure is non-blocking — Firebase down $\neq$ message lost.

Mobile Flutter connect snippet (illustrative)

```
final pusher = PusherClient(
  reverbAppKey, // REVERB_APP_KEY
  PusherOptions(
    host: 'pif-mobile-api.registration-panel.com',
    wsPort: 443, wssPort: 443,
    encrypted: true,
    auth: PusherAuth(
      'https://pif-mobile-api.registration-panel.com/broadcasting/auth',
      headers: { 'Authorization': 'Bearer $sanctumToken' },
    ),
  ),
);
pusher.subscribe('private-chat.$roomId')
  .bind('message.sent', (e) => addMessage(jsonDecode(e.data)));
```

19. Required environment variables CONFIG

Variable	Default / example	Purpose
<code>BROADCAST_DRIVER</code>	<code>reverb</code>	was <code>log</code> — must be <code>reverb</code> for chat broadcasts
<code>FIREBASE_CREDENTIALS</code>	absolute path to service-account JSON	kreait/firebase auto-discovery key
<code>REVERB_APP_ID</code>	<code>dg-2026</code>	app id (server-side)
<code>REVERB_APP_KEY</code>	<code>dg-2026-key</code>	public — shipped to Flutter

Variable	Default / example	Purpose
REVERB_APP_SECRET	(generate per env)	server-only
REVERB_HOST	pif-mobile-api.registration-panel.com	client-facing host (Nginx-terminated TLS)
REVERB_PORT	443	client-facing port
REVERB_SCHEME	https	https → useTLS=true
REVERB_SERVER_HOST	127.0.0.1	daemon binds to loopback only
REVERB_SERVER_PORT	8080	Nginx proxies in
MOBILE_DEMO_EMAIL	(blank in prod)	Apple Review bypass — guest must exist
MOBILE_DEMO_OTP	(blank in prod)	Apple Review bypass
MOBILE_REGISTER_URL	landing URL	target for identity/register 302
MOBILE_REGISTER_WITH_CODE_URL	landing URL	target for identity/register-with-code 302
MOBILE_OTP_EXPIRY_MINUTES	5	OTP TTL
MOBILE_OTP_MAX_ATTEMPTS	5	429 after threshold
MOBILE_TOKEN_EXPIRY_DAYS	30	per-token Sanctum expiry

20. Composer / infrastructure dependencies INFRA

Package	Why
kreait/laravel-firebase: ^6.2	FCM multicast for chat & room-booking notifications
laravel/verrb: ^1.10	WSS server for private chat channel
intervention/image: ^3.0	image processing / thumbnails (media center, conference assets)

Deployment needs (server team, not mobile): `composer install`, `php artisan migrate`, `php artisan storage:link`, `php artisan config:clear`, the Reverb daemon (`php artisan reverb:start`) under supervisor/systemd, and an Nginx `location /app/<REVERB_APP_KEY>` proxy block to `127.0.0.1:8080` with WS upgrade headers.

21. Cross-cutting conventions CONTRACT

- **Auth header:** `Authorization: Bearer <sanctum-token>` on every `/api/mobile/*` route except identity bootstrap.
- **Localization:** `Accept-Language: en|ar` or `?lang=en|ar`; default `en`. Resources fall back from `*_ar` to `*_en` when AR is blank.
- **IDs:** all primary keys are **UUID strings**.

- **Storage URLs:** resources return absolute URLs assembled from `PUBLIC_STORAGE_URL` / `PUBLIC_STORAGE_URL2` . Mobile should treat them as opaque — never reconstruct.
- **Pagination contracts vary by feature:**
 - Sessions/workshops: `{ items, pagination: { total, page, limit, totalPages } }`
 - Chat rooms/messages: `{ success, data: { items, pagination: { currentPage, totalPages, total*, hasMore } } }`
 - Notifications: `{ notifications, totalNotifications, totalPages, currentPage }`
 - Rooms list (no `?date`): bare array
- **Side-effecting GETs** are intentional in F6 (mark-read, clear). Do not refactor.
- **Empty maps** in app-config are encoded as `{}` not `[]` .
- **Localization fix:** `Localization` middleware was updated this pull — verify no regressions in AR rendering for sessions/workshops/sponsors.

22. Open items to discuss with mobile team

1. **Reverb client choice** — pinning a Flutter Pusher-compatible package (e.g. `pusher_channels_flutter`) and a single connection lifecycle (connect after login, disconnect on logout / background timeout).
2. **FCM channel id** on Android is `high_importance_channel` (set in `FirebaseNotificationService`). Mobile must create that channel on app start, or notifications won't be visible on Android 8+.
3. **Device-token lifecycle** — confirm we call `POST /identity/device-tokens` on: login success, FCM token refresh, OS permission grant. Stale tokens are auto-pruned server-side when FCM returns `UNREGISTERED` .
4. **Account-deletion UX** — confirm gating on `features.delete_account` and the confirmation copy (Apple requires "permanent and irreversible" wording).
5. **App-config cache busting** — agree on polling interval for `/app-config/version` (proposal: on app start + on resume + every 30 min while foreground).
6. **Workshop full → 409** — confirm UX path (toast vs modal) and copy in EN/AR for `error: "workshop_full"` .
7. **Chat message ceiling** — backend enforces `content ≤ 5000 chars` . Confirm client enforces the same and shows a counter.
8. **Past-slot guard** — surface "past slot" 400 errors with a specific copy, not a generic toast (room booking).
9. **Sponsors decoupling** — mobile needs to drop any sponsors block previously read from app-config and switch to `/mobile/sponsors` .
10. **Demo account for App Review** — agree on the credential pair we'll seed, and confirm the matching guest row exists in the prod DB with the right status.
11. **Migration window** — 39 new migrations; agree on whether mobile QA can hit testing right after deploy or needs a staging snapshot.

Source diff: `git log cd2410b..6704047` on `pif-directors-gathering-backend` · 181 files · +16,743 / -34 lines · see also `app/Http/Controllers/Mobile*` , `app/Http/Resources/Mobile/*` , and `routes/api.php` lines 937-1114.