



# Interface Design Description (IDD) for DataManager over REST

## **Abstract**

This document describes for the Interface Design Description (IDD) of the Arrowhead DataManager service's interfaces.

An Interface Design Description provides a detailed description of how the service is implemented/realized by using the Communication Profile and the chosen technologies.

This document outlines interfaces, message formats, metadata, and other important information to be able to use the DataManager system's interfaces.

1. Interface Design Description Overview	5
2. Services	5
2.1. Service 1: <b>Echo</b>	5
2.1.1. Echo: Information Model	5
1.1.1. Echo: Parameters	6
1.1.2. Echo: Response codes	6
1.1.3. Error handling	6
1.1.4. Interaction with consumers	6
2.2. Service 2: <b>Historian</b>	6
2.2.1. ListSystems: Information Model	7
1.1.5. ListSystems: Parameters	7
1.1.6. ListSystems: Response codes	7
1.1.7. ListSystems: Error handling	7
1.1.8. ListSystems: Interaction with consumers	8
2.2.2. ListServices: Information Model	8
1.1.9. ListServices: Parameters	8
1.1.10. ListServices: Response codes	8
1.1.11. ListServices: Error handling	8
1.1.12. ListServices: Interaction with consumers	9
2.2.3. GetData: Information Model	9
1.1.13. GetData: Parameters	9
1.1.14. GetData: Response codes	10
1.1.15. GetData: Error handling	10
1.1.16. GetData: Interaction with consumers	10
2.2.4. PutData: Information Model	10
1.1.17. PutData: Parameters	11
1.1.18. PutData: Response codes	11
1.1.19. PutData: Error handling	11
1.1.20. PutData: Interaction with consumers	11

2.3. Service 3: <b>Proxy</b>	12
2.3.1. ListSystems: Information Model	12
1.1.21. ListSystems: Parameters	12
1.1.22. ListSystems: Response codes	12
1.1.23. ListSystems: Error handling	13
1.1.24. ListSystems: Interaction with consumers	13
2.3.2. ListServices: Information Model	13
1.1.25. ListServices: Parameters	13
1.1.26. ListServices: Response codes	14
1.1.27. ListServices: Error handling	14
1.1.28. ListServices: Interaction with consumers	14
2.3.3. GetData: Information Model	14
1.1.29. GetData: Parameters	15
1.1.30. GetData: Response codes	15
1.1.31. GetData: Error handling	15
1.1.32. GetData: Interaction with consumers	15
2.3.4. PutData: Information Model	15
1.1.33. PutData: Parameters	16
1.1.34. PutData: Response codes	16
1.1.35. PutData: Error handling	16
1.1.36. PutData: Interaction with consumers	16
3. Security	17
3.1. Certificates	17
3.2. Payload protection	17
4. References	17
5. Revision history	17
5.1. Amendments	17
5.2. Quality Assurance	18
6. Appendixes	18



# 1. Interface Design Description Overview

This document describes how to utilize the DataManager system's Echo, Historian and Proxy services. Generic settings, unless otherwise noted per service, are;

- Protocol: HTTP(S)
- Encoding: JSON
- Compression: none
- Security: Optionally using TLS and X.509 certificates (server and client)
- Base path: The path /datamanager must be prepended before the individual service's own paths. For example, the Echo service is accessed at http(s)://<IP>:<PORT>/datamanager/echo

## 2. Services

The DataManager, being a part of the Arrowhead Framework [1], provides three services; **Echo**, **Historian**, and **Proxy**. The Echo service is used to check the availability of the DataManager system. The Historian service provides methods for storage and retrieval of SenML encoded sensor data for a database. The Proxy service provides a mail box like feature for sleepy devices to store one message per endpoint so that consumers can access the data even if the sleepy device is offline.

### 2.1. Service 1: Echo

Below are the specifics of this interface:

- The data model is plain text.
- No ontologies are in use.
- No schemas are currently defined.
- No payload encryption is used.

Table 1 Function description

Function	Service	Method	Input	Output
Echo	Echo	GET	-	String

#### 2.1.1. Echo: Information Model

The information for Echo is very basic. There is no input, and only plain text output, the string "Got it".

## 1.1.1. Echo: Parameters

This interface does not take any query path parameters.

## 1.1.2. Echo: Response codes

Code	Meaning	Comment
200	Successful request	Success
401	Unauthorized	Access denied

## 1.1.3. Error handling

There is no error handling for the Echo service, except the different response codes.

## 1.1.4. Interaction with consumers

Echo only supports read operations, where the response is always a string *"Got it"*. This can be used to test if the DataManager system is actually running. No authorization is needed.




FIGURE 1: ECHO INTERFACE

## 2.2. Service 2: Historian

Below are the specifics of this interface:

- The data model is JSON.
- No ontologies are in use.
- No schemas are currently defined.
- No payload encryption is used.

Table 2 Function description

Function	Service	Method	Input	Output
----------	---------	--------	-------	--------

ListSystems	Historian	GET	-	DataManager Systems
ListServices	Historian	GET	systemName	DataManager Services
GetData	Historian	GET	systemName, serviceName	Sensor data
PutData	Historian	PUT	systemName, serviceName, plus Sensor data	Result code

## 2.2.1. ListSystems: Information Model

In order to get a list of endpoints, a GET request must be sent to the /historian endpoint. The response upon success is a list of systems using the Historian service.

Output: Example DataManagerSystems response

```
{
  "systems": ["temperatureSys1", "humiditySys2", "humiditySys3"]
}
```

## 1.1.5. ListSystems: Parameters

This interface does not take any query path parameters.

## 1.1.6. ListSystems: Response codes

Code	Meaning	Comment
200	Successful request	Success
401	Unauthorized	Access denied
500	Internal server error	In case of database errors etc.

## 1.1.7. ListSystems: Error handling

All errors are handled using HTTP response codes, see above. An error message is also added in the response payload.

## 1.1.8. ListSystems: Interaction with consumers

Figure 2 shows how a client can perform a ListSystems operation.




FIGURE 2: HISTORIAN LISTSYSTEMS OPERATION

## 2.2.2. ListServices: Information Model

In order to get a list of service endpoints, a GET request must be sent to the corresponding URI. to the /historian/<systemName> endpoint. The response upon success is an list of all service endpoints.

Output: Example DataManagerServices response

```
{
  "services": ["temperature", "humidity"]
}
```

## 1.1.9. ListServices: Parameters

This interface does not take any query path parameters.

## 1.1.10. ListServices: Response codes

Code	Meaning	Comment
200	Successful request	Success
400	Bad request	If an incorrect parameter is used
401	Unauthorized	Access denied
500	Internal server error	In case of database errors etc.

## 1.1.11. ListServices: Error handling

All errors are handled using HTTP response codes, see above. An error message is also added in the response payload.



## 1.1.12. ListServices: Interaction with consumers

Figure 2 shows how a client must perform a ListServices operation.




FIGURE 4: HISTORIAN LISTSERVICES OPERATION

## 2.2.3. GetData: Information Model

In order to get data from an endpoint, a GET request must be sent to the corresponding URI. to the /historian/<systemName>/<serviceName> endpoint. The response upon success is a SenML formatted Response.

Output: Example SenML response

```
[
  {"bn": "temperature", "bt": 1593759331, "bu": "Cel"},
  {"n": "bearingTempInner", "v": 42.1},
  {"n": "bearingTempOuter", "v": 34.5}
]
```

## 1.1.13. GetData: Parameters

This interface takes the following query path parameters:

Parameter	Usage	Example
count	To limit the number of returned values	count=10 will return the 10 newest values.
sigX	Is used to select only certain signals. First signal is indicated with sig0, the second with sig1, etc.	sig0=temperature&sig1=humidty will only return two signals named humidity and humidity.
sigXcount	Is used to limit the number of returned values per signal.	sig0=temperature&sig0count=10 will return the 10 latest values for the signal temperature.

## 1.1.14. GetData: Response codes


Code	Meaning	Comment
200	Successful request	Success
400	Bad request	If the request contains incorrect parameters
401	Unauthorized	Access denied
404	Not found	If the requested system and service combination does not exist
500	Internal server error	If a database error occurs

## 1.1.15. GetData: Error handling

If the request was successful, a SenML message is returned with a response code of 200. If an error occurs, for example due to an incorrectly formatted request, an error message is returned with the reason.

## 1.1.16. GetData: Interaction with consumers

Figure 2 shows how a client must perform a GetData operation.



## 2.2.4. PutData: Information Model

In order to store data at an endpoint, a PUT request must be sent to the corresponding URI, to the /historian/<systemName>/<serviceName> endpoint. If the SenML encoded payload is OK, a 200 status code is returned. If the SenML message contains errors, an error is returned. For Example: to store two ball bearing temperatures (outer and inner) to the temperature service of the system *ballBearingSensor-342*, perform a PUT to *https://10.0.0.46:8461/datamanager/historian/ballBearingSensor-342/temperature* with the payload below. Content-type must be set to "application/json".

#### Input: Example PutData SenML request

```
[
  {"bn": "temperature", "bt": 1593759331, "bu": "Cel"},
  {"n": "bearingTempInner", "v": 42.1},
  {"n": "bearingTempOuter", "v": 34.5}
]
```

## 1.1.17. PutData: Parameters

This interface does not take any query path parameters.

## 1.1.18. PutData: Response codes

Code	Meaning	Comment
200	Successful request	Success
400	Bad request	Illegal or incorrect payload
401	Unauthorized	Access denied
500	Internal server error	If a database error occurs

## 1.1.19. PutData: Error handling

If the request was successful, a response code of 200. If an error occurs, for example due to an incorrectly formatted request, an error message is returned with the reason.

## 1.1.20. PutData: Interaction with consumers

Figure 2 shows how a client can store data at a service endpoint.




FIGURE 4: HISTORIAN PUTDATA OPERATION

## 2.3. Service 3: Proxy

Below are the specifics of this interface:

- The data model is JSON.
- No ontologies are in use.
- No schemas are currently defined.
- No payload encryption is used.

**Table 3 Function description**

Function	Service	Method	Input	Output
ListSystems	Proxy	POST	-	DataManagerSystems
ListServices	Proxy	GET	systemName	DataManagerServices
GetData	Proxy	GET	systemName, serviceName	Sensor data
PutData	Proxy	PUT	systemName, serviceName, plus Sensor data	Result code

### 2.3.1. ListSystems: Information Model

In order to get a list of endpoints, a GET request must be sent to the corresponding URI. to the /proxy endpoint. The response upon success is a DataManagerSystems list.

Output: Example DataManagerSystems response

```
{
  "systems": ["temperatureSys1", "humiditySys2"]
}
```

### 1.1.21. ListSystems: Parameters

This interface does not take any query path parameters.

### 1.1.22. ListSystems: Response codes

Code	Meaning	Comment
------	---------	---------


200	Successful request	Success
401	Unauthorized	Access denied
500	Internal server error	In case of errors etc.

## 1.1.23. ListSystems: Error handling

All errors are handled using HTTP response codes, see above. An error message is also added in the response payload.

## 1.1.24. ListSystems: Interaction with consumers

Figure 2 shows how a client can perform a ListSystems operation.



**FIGURE 3: PROXY LISTSYSTEMS OPERATION**

## 2.3.2. ListServices: Information Model

In order to get a list of service endpoints, a GET request must be sent to the corresponding URI. to the /proxy/<systemName> endpoint. The response upon success is a list of all service endpoints.

Output: Example DataManagerServices response

```

{
  "services": ["temperature", "humidity"]
}
  
```

## 1.1.25. ListServices: Parameters

This interface does not take any query path parameters.

## 1.1.26. ListServices: Response codes

Code	Meaning	Comment
200	Successful request	Success
400	Bad request	If an incorrect parameter is used
401	Unauthorized	Access denied
500	Internal server error	In case of errors etc.

## 1.1.27. ListServices: Error handling

All errors are handled using HTTP response codes, see above. An error message is also added in the response payload.

## 1.1.28. ListServices: Interaction with consumers

Figure 2 shows how a client must perform a ListServices operation.




FIGURE 4: PROXY LISTSERVICES OPERATION

## 2.3.3. GetData: Information Model

In order to get data from an endpoint, a GET request must be sent to the corresponding URI. to the /proxy/<systemName>/<serviceName> endpoint. The response upon success is a SenML formatted Response.

Output: Example SenML response

```
[{"bn": "temperature", "bt": 1593759331, "bu": "Cel"}, {"n": "bearingTempInner", "v": 42.1}, {"n": "bearingTempOuter", "v": 34.5}]
```

## 1.1.29. GetData: Parameters

Unlike the more advanced Historian service, the Proxy service does not take any query path parameters.

## 1.1.30. GetData: Response codes

Code	Meaning	Comment
200	Successful request	Success
400	Bad request	If the request contains incorrect parameters
401	Unauthorized	Access denied
404	Not found	If the requested system and service combination does not exist
500	Internal server error	If an error occurs

## 1.1.31. GetData: Error handling

If the request was successful, a SenML message is returned with a response code of 200. If an error occurs, for example due to an incorrectly formatted request, an error message is returned with the reason.

## 1.1.32. GetData: Interaction with consumers

Figure 2 shows how a client must perform a GetData operation.




FIGURE 4: PROXY GETDATA OPERATION

## 2.3.4. PutData: Information Model

In order to store data at an endpoint, a PUT request must be sent to the corresponding URI, to the /proxy/<systemName>/<serviceName> endpoint. If the SenML encoded payload is OK, a

200 status code is returned. If the SenML message contains errors, an error is returned. For Example: to store two ball bearing temperatures (outer and inner) to the temperature service of the system ballBearingMonitor - 342, perform a PUT to `https://10.0.0.46:8461/datamanager/proxy/ballBearingMonitor-342/temperature` with the payload below. Content-type must be set to "application/json".

#### Input: Example PutData request

```
[
  {"bn": "temperature", "bt": 1593759331, "bu": "Cel"},
  {"n": "bearingTempInner", "v": 42.1},
  {"n": "bearingTempOuter", "v": 34.5}
]
```

## 1.1.33. PutData: Parameters

This interface does not take any query path parameters.

## 1.1.34. PutData: Response codes

Code	Meaning	Comment
200	Successful request	Success
400	Bad request	If the request contains incorrect parameters
401	Unauthorized	Access denied
500	Internal server error	If an error occurs

## 1.1.35. PutData: Error handling

If the request was successful, a response code of 200. If an error occurs, for example due to an incorrectly formatted request, an error message is returned with the reason.

## 1.1.36. PutData: Interaction with consumers

Figure 2 shows how a client can store data at a service endpoint.






FIGURE 4: PROXY PUTDATA OPERATION

## 3. Security

This system can either run unencrypted over HTTP, or using TLS plus server and client side X.509 certificates.

### 3.1. Certificates

This IDD is using the same certificates as other core systems in the Java Spring versions.

### 3.2. Payload protection

Currently, no separate payload protection is supported.

## 4. References

[1] Arrowhead Framework repository: <https://github.com/arrowhead-f/core-java-spring>

[2]

## 5. Revision history

### 5.1. Amendments

No.	Date	Version	Subject of Amendments	Author
1	2015-02-15	1.0	Revision of text	Michele Albano / Luis Ferreira
2	2015-09-30	1.1	Refinement of the structure	Michele Albano / Luis Ferreira
3	2020-06-07	2.0	Major update	Jerker Delsing

4	2020-06-29	2.1	Added DataManager text	Jens Eliasson
5	2020-07-01	2.2	Added text, errors etc.	Jens Eliasson
6	2020-07-03	2.3	Finalized text and figures	Jens Eliasson
7				

## 5.2. Quality Assurance

No.	Date	Version	Approved by
1			
2			

## 6. Appendixes

Appendix A: REST Communication profile (CP)