

Rendering Ocean Water

John Isidoro
ATI Research

Alex Vlachos
ATI Research

Chris Brennan
ATI Research

In computer graphics, simulating water has always been a topic of much research. In particular, ocean water is particularly difficult due to the shape and combination of multiple waves, in addition to the reflection of the clouds, and the sun in the sky.

The shader in this article is meant to simulate the appearance of ocean water using vertex and pixel shaders. The interesting part of this shader is that it runs completely in hardware in a single pass on recent graphics cards (Radeon 8500). This has the advantage of leaving the CPU free for other calculations, as well as allowing for a courser tessellation of the input geometry that can be tessellated using N-Patches or other higher order surface schemes. The input geometry is a grid of quads with 1 set of texture coordinates and tangent space, though in theory only a position is actually needed if assumptions are made about the orientation of the up vector, and the scale of the ocean waves in the shader.

Sinusoidal Perturbation in a Vertex Shader

The vertex shader is responsible for generating the combination of sine waves that perturb the position, and cosine waves that perturb the tangent space vectors for the vertex. A Taylor series approximation is used to generate sine and cosine functions within the shader. Due to the SIMD nature of vertex shaders, 4 sine and cosine waves are calculated in parallel, and the results are weighted and combined using a single dp4. Each sine wave has fully adjustable direction, frequency, speed, and offset, that is configured in the constant store.

The first step is to compute each wave's starting phase into the sine or cosine function. The texture coordinates are multiplied by the direction and frequency of the four waves in parallel. c14 and c15 are the frequencies of the wave relative to S and T respectively.

```
mul r0, c14, v7.x      // use tex coords as inputs to sinusoidal warp
mad r0, c15, v7.y, r0  // use tex coords as inputs to sinusoidal warp
```

Next, the time, which is stored in c16.x, is multiplied by the speed of the waves (c and added in.

```
mov r1, c16.x          //time...
mad r0, r1, c13, r0    // add scaled time to move bumps according to frequency
add r0, r0, c12        // starting time offset
```

Rendering Ocean Water

This computes the input to the cosine function. A Taylor approximation, however, is only accurate for the range it is created for, and more terms are needed the larger that range is. So for a repeating function like a cosine wave, the fractional portion of the wave phase can be extracted and then expanded to the $-\pi$ to π range before calculating the Taylor series expansion.

```
frc r0.xy, r0          // take frac of all 4 components
frc r1.xy, r0.zwzw     //
mov r0.zw, r1.xyxy     //
mul r0, r0, c10.x       // multiply by fixup factor (due to inaccuracy)
sub r0, r0, c0.y        // subtract .5
mul r0, r0, c1.w        // mult tex coords by 2pi  coords range from(-pi to pi)
```

Calculate the Taylor series expansion of sine (*r4*) and cosine (*r5*):

```
mul r5, r0, r0          // (wave vec)^2
mul r1, r5, r0          // (wave vec)^3
mul r6, r1, r0          // (wave vec)^4
mul r2, r6, r0          // (wave vec)^5
mul r7, r2, r0          // (wave vec)^6
mul r3, r7, r0          // (wave vec)^7
mul r8, r3, r0          // (wave vec)^8

mad r4, r1, c2.y, r0     // (wave vec) - ((wave vec)^3)/3!
mad r4, r2, c2.z, r4     // + ((wave vec)^5)/5!
mad r4, r3, c2.w, r4     // - ((wave vec)^7)/7!

mov r0, c0.z            //1
mad r5, r5, c3.x, r0     //- (wave vec)^2/2!
mad r5, r6, c3.y, r5     //+ (wave vec)^4/4!
mad r5, r7, c3.z, r5     //- (wave vec)^6/6!
mad r5, r8, c3.w, r5     //+ (wave vec)^8/8!
```

The results are modulated by relative heights of each of the waves and the scaled sine wave is used to perturb the position along the normal. The new object space position is then transformed to compute the final position. The vertex input, *v5.x*, is used to allow artist control of how high the waves are in different parts of the ocean. This can be useful for shorelines where the ocean waves will be smaller than those further out to sea:

```
sub r0, c0.z, v5.x       //... 1-wave scale
mul r4, r4, r0           // scale sin
mul r5, r5, r0           // scale cos

dp4 r0, r4, c11          //multiply wave heights by waves

mul r0.xyz, v3, r0       //multiply wave magnitude at this vertex by normal
add r0.xyz, r0, v0       //add to position
mov r0.w, c0.z           //homogenous component

m4x4    oPos, r0, c4     // OutPos = ObjSpacePos * World-View-Proj Matrix
```

The tangent and normal vectors are perturbed in a similar manner using the cosine wave instead of the sine wave. This is done because the cosine is the first derivative of the sine, and therefore perturbs the tangent and normal vectors by the slope of the wave. The following code makes the assumption that the source art is a plane along the Z axis. Its worth mentioning that this vertex perturbation technique can be extended to sinusoidally warp almost any any geometry.

Rendering Ocean Water

```

mul    r1, r5, c11           //cos* waveheight
dp4    r9.x, -r1, c14         //normal x offset
dp4    r9.yzw, -r1, c15       //normal y offset and tangent offset
mov    r5, v3                //starting normal
mad    r5.xy, r9, c10.y, r5   //warped normal move nx, ny according to
                                //cos*wavedir*waveheight
mov    r4, v8                //tangent
mad    r4.z, -r9.x, c10.y, r4.z //warped tangent vector

dp3    r10.x, r5, r5
rsq    r10.y, r10.x
mul    r5, r5, r10.y         //normalize normal

dp3    r10.x, r4, r4
rsq    r10.y, r10.x
mul    r4, r4, r10.y         //normalize tangent

```

The binormal is then calculated using a cross product of the warped normal and the warped tangent vector to create a tangent space basis matrix. This matrix will be used later to transform the bump map's tangent space normal into world space for **cube mapped environment mapped bump mapping (CMEMBM)**.

```

mul    r3, r4.yzxw, r5.zxyw
mad    r3, r4.zxyw, -r5.yzxw, r3 //xprod to find binormal

```

CMEMBM needs the view vector to perform the reflection operation:

```

sub    r2, c8, r0           //view vector
dp3    r10.x, r2, r2
rsq    r10.y, r10.x
mul    r2, r2, r10.y        //normalized view vector

```

The height map shown in Figure 1 is used to create a normal map. The incoming texture coordinates are used as a starting point for to create two sets of coordinates that are rotated and scroll across each other based on time. These coordinates are used to scroll two bump maps past each other to produce the smaller ripples in the ocean. One interesting trick used in this shader is to swap the u and v coordinates for the second texture before compositing them. This eliminates the visual artifacts that occur when the scrolling textures align with each other exactly, and the ripples appear to stop for a moment. Swapping the texture coordinates ensure the maps never align with each other, (unless they are radially symmetric).




Figure 1: Height map used to create the normal map for the ocean shader

```

mov    r0, c16.x
mul    r0, r0, c17.xyxy
frc    r0.xy, r0             //frc of incoming time
add    r0, v7, r0           //add time to tex coords
mov    oT0, r0              //distorted tex coord 0

```

Excerpted from *ShaderX: Vertex and Pixel Shader Tips and Tricks*

Rendering Ocean Water

```
mov    r0, c16.x
mul    r0, r0, c17.zwzw
frc    r0.xy, r0          //frc of incoming time
add    r0, v7, r0         //add time to tex coords
mov    oT1, r0.yxzw       //distorted tex coord 1
```

The vertex shader is completed by the output of the remaining vectors used by the pixel shader. The pixel and vertex shader for the ocean water effect can be found in its entirety at the end of this section.

```
mov    oT2, r2            //pass in view vector (worldspace)
mov    oT3, r3            //tangent
mov    oT4, r4            //binormal
mov    oT5, r5            //normal
```

CMEMBM Pixel Shader with Fresnel Term

Once the vertex shader has completed, the pixel shader is responsible for producing the bump-mapped reflective ocean surface.

First, the pixel shader averages the two scrolling RGB normal bump maps to generate a composite normal. In this particular case, the bumps are softened further by dividing the x and y components in half. Next, it transforms the tangent space composite normal into world space and calculates a per-pixel reflection vector. The reflection vector is used to sample a skybox cubic environment map. (Figure 2) The shader also calculates $2 \cdot \mathbf{N} \cdot \mathbf{V}$, and uses it to sample a **Fresnel** 1-D texture (Figure 3). This Fresnel map gives the water a more greenish appearance when looking straight down into it, and a more bluish appearance when looking edge on. The scale by 2 is used to expand the range of the Fresnel map.

```
texld r0, t0              //bump map 0
texld r1, t1              //sample bump map 1
texcrd r2.rgb, t2         //View vector
texcrd r3.rgb, t3         //Tangent
texcrd r4.rgb, t4         //Binormal
texcrd r5.rgb, t5         //Normal

add_d4 r0.xy, r0_bx2, r1_bx2 //Scaled Average of 2 bumpmaps' xy offsets

mul r1.rgb, r0.x, r3
mad r1.rgb, r0.y, r4, r1
mad r1.rgb, r0.z, r5, r1    //Transform bumpmap normal into world space

dp3 r0.rgb, r1, r2          //V.N
mad r2.rgb, r1, r0_x2, -r2  //R = 2N(V.N)-V

mov_sat r1, r0_x2          //2 * V.N (sample over range of 1d map!)
```




Figure 2: Cubic Environment Map used for ocean water reflections.



Figure 3: 1-D texture used for the water color addressed by $1-N \cdot V$.

The second phase composites the water color, from the Fresnel map, the environment map, and other specular highlights extracted from the environment map. One trick we use is to square the environment map color values to make the colors brighter, and to enhance the contrast for compositing. The advantage to doing this in the pixel shader instead of as a preprocessing step is so the same skybox environment map can be used for other objects in the scene. To get the specular light sparkles in the water, a specular component is derived from the green channel of the environment map. For this example, the choice is based on the environment map artwork. The desired effect is to have the highlights in the water correspond to bright spots in the sky, and in this case, the green channel seemed to work best. To make sure the specular peaks were only generated from the brightest areas of the environment map, the specular value extracted from the green channel was raised to the eighth power. This has the effect of darkening all but the brightest areas of the image.

Another approach for encoding specular highlights in an environment map is to have the artists specify a glow map as an alpha channel of the environment map.

```
texcrd r0.rgb, r0
texld r2, r2           //cubic env map
texld r3, r1           //Index fresnel map using 2*V.N

mul r2.rgb, r2, r2     //Square the environment map
+mul r2.a, r2.g, r2.g   //use green channel of env map as specular
mul r2.rgb, r2, 1-r0.r  //Fresnel Term
+mul r2.a, r2.a, r2.a   //Specular highlight ^4
add_d4_sat r2.rgb, r2, r3_x2 //+= Water color
+mul r2.a, r2.a, r2.a   //Specular highlight ^8
mad_sat r0, r2.a, c1, r2 //+= Specular highlight * highlight color
```

Excerpted from *ShaderX: Vertex and Pixel Shader Tips and Tricks*

Ocean Water Shader Source Code

```

DefineParam texture rgbNormalBumpMap NULL
SetParamEnum rgbNormalBumpMap EP_TEX0

DefineParam texture waterGradientMap NULL
SetParamEnum waterGradientMap EP_TEX1

DefineParam texture cubeEnvMap NULL
SetParamEnum cubeEnvMap EP_TEX2

//Constant store
DefineParam vector4 commonConst (0.0, 0.5, 1.0, 2.0)

DefineParam vector4 appConst (0.0, 0.0, 0.0, 0.0) //Time, 1.0/lightFalloffDist
SetParamEnum appConst EP_VECTOR3

DefineParam vector4 worldSpaceCamPos (0, 0, 0, 0)
BindParamToState worldSpaceCamPos STATE_VECTOR_CAMERA_POSITION 0 WORLD_SPACE

DefineParam vector4 worldSpaceLightPos (-10000, -25000, 2000, 1)
SetParamEnum worldSpaceLightPos EP_VECTOR0

DefineParam matrix4x4 wvp [(1,0,0,0) (0,1,0,0) (0,0,1,0) (0,0,0,1)]
BindParamToState wvp STATE_MATRIX_PVW

//=====
//commonly used constants
//heights for waves 4 different fronts
DefineParam vector4 waveHeights (80.0, 100.0, 5.0, 5.0)

//offset in sine wave.. (ranges 0 to 1)
DefineParam vector4 waveOffset (0.0, 0.2, 0.0, 0.0)

//frequency of the waves (e.g. waves per unit time..)
DefineParam vector4 waveSpeed (0.2, 0.15, 0.4, 0.4)

//direction of waves in tangent space (also controls frequency in space)
DefineParam vector4 waveDirx (0.25, 0.0, -0.7, -0.8)
DefineParam vector4 waveDiry (0.0, 0.15, -0.7, 0.1)

//scale factor for distortion of base map coords

//bump map scroll speed
DefineParam vector4 bumpSpeed (0.031, 0.04, -0.03, 0.02)

DefineParam vector4 piVector (4.0, 1.57079632, 3.14159265, 6.28318530)

//Vectors for taylor's series expansion of sin and cos
DefineParam vector4 sin7 (1, -0.16161616, 0.0083333, -0.00019841)
DefineParam vector4 cos8 (-0.5, 0.041666666, -0.0013888889, 0.000024801587)

//frcFixup.x is a fixup to make the edges of the clamped sin wave match up again due to
// numerical inaccuracy
//frcFixup.y should be equal to the average of du/dx and dv/dy for the base texture
// coords.. this scales the warping of the normal

DefineParam vector4 frcFixup (1.02, 0.003, 0, 0)

DefineParam vector4 psCommonConst (0, 0.5, 1, 0.25)
DefineParam vector4 highlightColor (0.8, 0.76, 0.62, 1)

DefineParam vector4 waterColor (0.50, 0.6, 0.7, 1)

//=====
// 1 Pass
//=====

```

Excerpted from *ShaderX: Vertex and Pixel Shader Tips and Tricks*

Rendering Ocean Water

```
StartShader
Requirement VERTEXSHADERVERSION 1.1
Requirement PIXELSHADERVERSION 1.4
StartPass
    SetTexture 0 rgbNormalBumpMap
    SetTextureFilter 0 BILINEAR
    SetTextureStageState 0 MIPMAPLODBIAS -1.0

    SetTexture 1 rgbNormalBumpMap
    SetTextureFilter 1 BILINEAR
    SetTextureStageState 1 MIPMAPLODBIAS -1.0

    SetTexture 2 cubeEnvMap
    SetTextureWrap 2 CLAMP CLAMP CLAMP
    SetTextureFilter 2 BILINEAR
    SetTextureStageState 2 MIPMAPLODBIAS 0.0

    SetTexture 3 waterGradientMap
    SetTextureWrap 3 CLAMP CLAMP CLAMP
    SetTextureFilter 3 LINEAR

    SetVertexShaderConstant 0 commonConst
    SetVertexShaderConstant 1 piVector
    SetVertexShaderConstant 2 sin7
    SetVertexShaderConstant 3 cos8

    SetVertexShaderConstant 4 wvp
    SetVertexShaderConstant 8 worldSpaceCamPos
    SetVertexShaderConstant 9 worldSpaceLightPos

    SetVertexShaderConstant 10 frcFixup
    SetVertexShaderConstant 11 waveHeights
    SetVertexShaderConstant 12 waveOffset
    SetVertexShaderConstant 13 waveSpeed
    SetVertexShaderConstant 14 waveDirx
    SetVertexShaderConstant 15 waveDiry
    SetVertexShaderConstant 16 appConst
    SetVertexShaderConstant 17 bumpSpeed

StartVertexShader
    // v0 - Vertex Position
    // v3 - Vertex Normal
    // v7 - Vertex Texture Data u,v
    // v8 - Vertex Tangent (v direction)
    //
    // c0 - { 0.0, 0.5, 1.0, 2.0}
    // c1 - { 4.0, .5pi, pi, 2pi}
    // c2 - {1, -1/3!, 1/5!, -1/7! } //for sin
    // c3 - {1/2!, -1/4!, 1/6!, -1/8! } //for cos
    // c4-7 - Composite World-View-Projection Matrix
    // c8 - ModelSpace Camera Position
    // c9 - ModelSpace Light Position
    // c10 - {fixup factor for taylor series imprecision, }
    // c11 - {waveHeight0, waveHeight1, waveHeight2, waveHeight3}
    // c12 - {waveOffset0, waveOffset1, waveOffset2, waveOffset3}
    // c13 - {waveSpeed0, waveSpeed1, waveSpeed2, waveSpeed3}
    // c14 - {waveDirX0, waveDirX1, waveDirX2, waveDirX3}
    // c15 - {waveDirY0, waveDirY1, waveDirY2, waveDirY3}
    // c16 - { time, sin(time)}
    // c17 - {basetexcoord distortion x0, y0, x1, y1}

    vs.1.1

    mul r0, c14, v7.x // use tex coords as inputs to sinusoidal warp
    mad r0, c15, v7.y, r0 // use tex coords as inputs to sinusoidal warp

    mov r1, c16.x //time...
    mad r0, r1, c13, r0 // add scaled time to move bumps according to frequency
    add r0, r0, c12 // starting time offset
    frc r0.xy, r0 // take frac of all 4 components
```

Excerpted from *ShaderX: Vertex and Pixel Shader Tips and Tricks*

Rendering Ocean Water

```

frc r1.xy, r0.zwzw    //
mov r0.zw, r1.xyxy    //

mul r0, r0, c10.x      // multiply by fixup factor (due to inaccuracy)
sub r0, r0, c0.y        // subtract .5
mul r0, r0, c1.w        // mult tex coords by 2pi  coords range from(-pi to pi)

mul r5, r0, r0          // (wave vec)^2
mul r1, r5, r0          // (wave vec)^3
mul r6, r1, r0          // (wave vec)^4
mul r2, r6, r0          // (wave vec)^5
mul r7, r2, r0          // (wave vec)^6
mul r3, r7, r0          // (wave vec)^7
mul r8, r3, r0          // (wave vec)^8

mad r4, r1, c2.y, r0    //(wave vec) - ((wave vec)^3)/3!
mad r4, r2, c2.z, r4    // + ((wave vec)^5)/5!
mad r4, r3, c2.w, r4    // - ((wave vec)^7)/7!

mov r0, c0.z            //1
mad r5, r5, c3.x, r0    //-(wave vec)^2/2!
mad r5, r6, c3.y, r5    //+(wave vec)^4/4!
mad r5, r7, c3.z, r5    //-(wave vec)^6/6!
mad r5, r8, c3.w, r5    //+(wave vec)^8/8!

sub r0, c0.z, v5.x      //... 1-wave scale
mul r4, r4, r0          // scale sin
mul r5, r5, r0          // scale cos

dp4 r0, r4, c11         //multiply wave heights by waves

mul r0.xyz, v3, r0      //multiply wave magnitude at this vertex by normal
add r0.xyz, r0, v0      //add to position
mov r0.w, c0.z          //homogenous component

m4x4    oPos, r0, c4    // OutPos = ObjSpacePos * World-View-Projection Matrix

mul      r1, r5, c11          //cos* waveheight
dp4      r9.x, -r1, c14       //normal x offset
dp4      r9.yzw, -r1, c15     //normal y offset and tangent offset
mov      r5, v3              //starting normal
mad      r5.xy, r9, c10.y, r5 //warped normal move nx, ny according to
                                //cos*wavedir*waveheight
mov      r4, v8              //tangent
mad      r4.z, -r9.x, c10.y, r4.z //warped tangent vector

dp3      r10.x, r5, r5
rsq      r10.y, r10.x
mul      r5, r5, r10.y        //normalize normal

dp3      r10.x, r4, r4
rsq      r10.y, r10.x
mul      r4, r4, r10.y        //normalize tangent

mul      r3, r4.yzxw, r5.zxyw
mad      r3, r4.zxyw, -r5.yzxw, r3 //xprod to find binormal

sub      r2, c8, r0          //view vector
dp3      r10.x, r2, r2
rsq      r10.y, r10.x
mul      r2, r2, r10.y        //normalized view vector

mov      r0, c16.x
mul      r0, r0, c17.xyxy
frc      r0.xy, r0            //frc of incoming time
add      r0, v7, r0          //add time to tex coords
mov      oT0, r0             //distorted tex coord 0

mov      r0, c16.x
mul      r0, r0, c17.zwzw

```

Excerpted from *ShaderX: Vertex and Pixel Shader Tips and Tricks*

Rendering Ocean Water

```
frc      r0.xy, r0          //frc of incoming time
add      r0, v7, r0         //add time to tex coords
mov      oT1, r0.yxzw       //distorted tex coord 1

mov      oT2, r2            //pass in view vector (worldspace)
mov      oT3, r3            //tangent
mov      oT4, r4            //binormal
mov      oT5, r5            //normal
EndVertexShader

SetPixelShaderConstant 0 psCommonConst
SetPixelShaderConstant 1 highlightColor

StartPixelShader
    ps.1.4

    texld r0, t0             //bump map 0
    texld r1, t1             //sample bump map 1
    texcrd r2.rgb, t2        //View vector
    texcrd r3.rgb, t3        //Tangent
    texcrd r4.rgb, t4        //Binormal
    texcrd r5.rgb, t5        //Normal

    add_d4 r0.xy, r0_bx2, r1_bx2 //Scaled Average of 2 bumpmaps xy offsets

    mul r1.rgb, r0.x, r3
    mad r1.rgb, r0.y, r4, r1
    mad r1.rgb, r0.z, r5, r1    //Put bumpmap normal into world space

    dp3 r0.rgb, r1, r2         //V.N
    mad r2.rgb, r1, r0_x2, -r2 //R = 2N(V.N)-V

    mov_sat r1, r0_x2         //2 * V.N (sample over range of 1d map!)

    phase
    texcrd r0.rgb, r0
    texld r2, r2              //cubic env map
    texld r3, r1              //Index fresnel map using 2*V.N

    mul r2.rgb, r2, r2         //Square the environment map
    +mul r2.a, r2.g, r2.g      //use green channel of env map as specular
    mul r2.rgb, r2, 1-r0.r     //Fresnel Term
    +mul r2.a, r2.a, r2.a      //Specular highlight ^4

    add_d4_sat r2.rgb, r2, r3_x2 //+= Water color
    +mul r2.a, r2.a, r2.a      //Specular highlight ^8

    mad_sat r0, r2.a, c1, r2    //+= Specular highlight * highlight color



EndPixelShader

EndPass
EndShader
```

Applications

This shader can be seen in the [ATI Island Demos](#), while source code is also available in the [Ocean Water sample](#).

Rendering Ocean Water



Excerpted from *ShaderX: Vertex and Pixel Shader Tips and Tricks*