



UNIVERSIDAD NACIONAL DE COLOMBIA
SEDE BOGOTÁ

FACULTAD DE INGENIERÍA
Vicedecanatura Académica
POSGRADOS

PROPOSAL SUBMISSION

DOCTORAL THESIS: ☒ MASTER THESIS: ☐
MASTER FINAL WORK: ☐ SPECIALIZATION FINAL WORK: ☐

1. **BIDDER:** Robinson Andrés Jaque Pirabán **ID:** 80190790
2. **PROGRAM:** Philosophy Doctoral in Computer Science and Systems Engineering
3. **ADVISOR:** Fabio Augusto González Osorio
DEPARTMENT: Computer Science and Industrial Engineering
4. **TITLE:** Kernel Tensor Factorization
5. **AREA:** Computer Science
6. **LINE OF RESEARCH:** Machine Learning
7. COMMENTARY WITH ADVISOR APROVAL

8. BIDDER SIGNATURE

9. SIGNATURE OF ADVISOR

Contents

1	Basics of tensors	3
1.1	Unfolding and Folding Tensors	4
2	Tensor Decomposition	4
2.1	Canonica Polyadic Decomposition / PARAFAC	6
2.2	Other methods	7
2.3	Tensor completion	7
2.4	Kernel methods	8
3	Problem Statement	9

1 Basics of tensors

Tensors are multidimensional arrays. i.e. An N -way or N -order tensor is an element of tensor product of N vector spaces, each of which has its own coordinate system. A first order tensor is a vector, a second order tensor is a matrix, tensors of higher order are called high-order tensors. The order (ways or modes) of a tensor is the number of dimensions. Figure 1 represents a 3-order tensor $\mathcal{X} \in \mathbb{R}^{I \times J \times K}$.




Figure 1: Third-order tensor

Fibers are defined by fixing every index by one. In a third-order tensor a column is a mode-1 fiber, denoted by $x_{:jk}$; a row is a mode-2 fiber, denoted by $x_{i:k}$; while a tube is a mode-3 fiber, denoted by $x_{i:k}$. 2 shows a fibers representation in 3rd-order tensor.




Figure 2: 3rd-order tensor fibers

Slices are two-dimensional sections of a tensor defined by fixing two indexes. For instance, slices of 3rd-order tensor \mathcal{X} are denoted by $X_{i::}$ (horizontal), $X_{:j:}$ (lateral) and $X_{::k}$ (frontal).

The *norm* of a tensor $\mathcal{X} \in \mathbb{R}^{I_1 \times I_2 \times \dots \times I_N}$ is analogous to the matrix Frobenius norm, i.e.

$$\|\mathcal{X}\| = \sqrt{\sum_{i_1=1}^{I_1} \sum_{i_2=1}^{I_2} \dots \sum_{i_N=1}^{I_N} x_{i_1 i_2 \dots i_N}^2} \quad (1)$$

1.1 Unfolding and Folding Tensors

Unfolding is the process of *matricization* of a tensor. In other words, elements of a tensors are sorted to assemble a matrix. The mode- k unfolding of a tensor $\mathcal{X} \in \mathbb{R}^{I_1 \times I_2 \times \dots \times I_N}$ is denoted by $X_{(k)} \in \mathbb{R}^{I_k \times \prod_{k' \neq k} I_{k'}}$ and arranges the mode- k tensor fibers as columns of resulting matrix. In addition, Kolda [35] presents a more general procedures of unfolding

Ding and Wei [24] present a fast algorithm for Hankel tensor-vector products.

[28] A method of fast linear transform algorithm synthesis for an arbitrary tensor

2 Tensor Decomposition

Tensor decomposition originated with Hitchcock in 1927 [34], and the the multi-way model is attributed to Cattell in 1944 [17].

Tensor works had attention in 60s with Tucker ([38], [39], [37]) and Carroll and Chang [16] and Harshman in 1970 [33] with applications in psychometrics. In 1981 Appellof and Davidson [9] used tensor decomposition in chemometrics which have been an popular field of application of tensor decomposition since then.

In last twenty years tensor decomposition applications have expanded to many fields such as signal processing, numerical linear algebra, computer vision, numerical analysis, neuroscience, data mining, graph analysis. Figure 3 attempt to summarize application fields of tensor decomposition.

Fanaee and Gama [30] introduce an interdisciplinary survey about tensor-based anomaly detection.

We suggest to readers to refer to Kolda [35], Acar [1] and [22] for an exhaustive a detailed review of fundamental decomposition methods and applications. Furthermore, [23] presents tensor properties as extension of estructural properties of matrices.

Chemometrics [18] A computationally efficient technique for the solution of multi-dimensional PBMs of granulation via tensor decomposition

Bioinformatics In [2] and [4] a multimodal problem is addressed, the authors formulate data fusion as a coupled matrix and tensor factorization problem and discuss its extension to a structure-revealing data fusion model in metabolomics.

Image processing [5] NNTF for facial expression recognition

Machine Learning [6] Tensor decompositions for learning latent variable models

Text mining [7] This paper describes a method for automatic detection of semantic relations between concept nodes of a networked ontological knowledge base by analyzing matrices of semantic-syntactic valences of words. These matrices are obtained by means of nonnegative factorization of tensors of syntactic compatibility of words.




Figure 3: Application fields of tensor decomposition

Numerical analysis [8] use of the sum-factorization for the calculation of the integrals arising in Galerkin isogeometric analysis. While introducing very little change in an isogeometric code based on element-by-element quadrature and assembling, the sum-factorization approach, taking advantage of the tensor-product structure of splines or NURBS shape functions, significantly reduces the quadrature computational cost.

[12] Fast iterative solution of the Bethe-Salpeter eigenvalue problem using low-rank and QTT tensor approximation.

[20] Blind identification of a second order Volterra-Hammerstein series using cumulant cubic tensor analysis.

Neuroscience [10] Decomposition of brain diffusion imaging data uncovers latent schizophrenias with distinct patterns of white matter anisotropy, using NNTF to clustering.

Signal processing Cichocki et.al. [21] sum up tensor decomposition approaches for signal processing problems.

Barker and Virtanen [11] deal with monaural sound source separation problem using NNTF of modulation spectrograms.

[14] Necessity to manually assign the NTF components to audio sources in order to be able to enforce prior information on the sources during the estimation process,

Automatic Allocation of NTF Components for User-Guided Audio Source Separation

[32] propose a shifted 2D non-negative tensor factorisation algorithm which extends non-negative matrix factor 2D deconvolution to the multi-channel case. The use of this algorithm for multi-channel sound source separation of pitched instruments is demonstrated.

Other applications [29] Discovering and Characterizing Mobility Patterns in Urban Spaces: A Study of Manhattan Taxi Data. by using non-negative tensor factorization (NTF), we are able to cluster human behavior based on spatio-temporal dimensions. Second, for understanding these clusters, we propose to use HypTrails, a Bayesian approach for expressing and comparing hypotheses about human trails.

[31] NNTF factorization for household electrical seasonal consumption disaggregation




Figure 4: Tensor decomposition methods

2.1 Canonica Polyadic Decomposition / PARAFAC

Canonica Polyadic (CP) decomposition or PARAFAC decompose a tensor as a finite sum of rank-one tensors.

Domanov [25] shows relaxed uniqueness conditions and algebraic algorithm for Canonical polyadic decomposition, as well as a reduction to generalized eigenvalue decomposition [26] and uniqueness properties [27] of third-order tensors.

2.2 Other methods

[13] The tensor decomposition addressed in this paper may be seen as a generalization of Singular Value Decomposition of matrices. We consider general multilinear and multihomogeneous tensors. We show how to reduce the problem to a truncated moment matrix problem and give a new criterion for flat extension of Quasi-Hankel matrices. We connect this criterion to the commutation characterization of border bases.

2.3 Tensor completion

Acar et.al [3] presents a scalable tensor factorization method to deal with completion problem using PARAFAC method.

[15] The existing studies involving matrix or tensor completion problems are commonly under the nuclear norm penalization framework due to the computational efficiency of the resulting convex optimization problem. Folded-concave penalization methods have demonstrated surprising developments in sparse learning problems due to their nice practical and theoretical properties. To share the same light of folded-concave penalization methods, we propose a new tensor completion model via folded-concave penalty for estimating missing values in tensor data. Two typical folded-concave penalties, the minmax concave plus (MCP) penalty and the smoothly clipped absolute deviation (SCAD) penalty, are employed in the new model. To solve the resulting nonconvex optimization problem, we develop a local linear approximation augmented Lagrange multiplier (LLA-ALM) algorithm which combines a two-step LLA strategy to search a local optimum of the proposed model efficiently. Finally, we provide numerical experiments with phase transitions, synthetic data sets, real image and video data sets to exhibit the superiority of the proposed model over the nuclear norm penalization method in terms of the accuracy and robustness.

[19] The success of research on matrix completion is evident in a variety of real-world applications. Tensor completion, which is a high-order extension of matrix completion, has also generated a great deal of research interest in recent years. Given a tensor with incomplete entries, existing methods use either factorization or completion schemes to recover the missing parts. However, as the number of missing entries increases, factorization schemes may overfit the model because of incorrectly predefined ranks, while completion schemes may fail to interpret the model factors. In this paper, we introduce a novel concept: complete the missing entries and simultaneously capture the underlying model structure. To this end, we propose a method called simultaneous tensor decomposition and completion (STDC) that combines a rank minimization technique with Tucker model decomposition. Moreover, as the model structure is implicitly included in the Tucker model, we use factor priors, which are usually known a priori in real-world tensor objects, to characterize the underlying joint-manifold drawn from the model factors. By exploiting this auxiliary information, our method leverages two classic schemes and accurately estimates the model factors and missing entries. We conducted experiments to empirically verify the convergence of our algorithm on synthetic data and evaluate its effectiveness on various kinds of

real-world data. The results demonstrate the efficacy of the proposed method and its potential usage in tensor-based applications. It also outperforms state-of-the-art methods on multilinear model analysis and visual data completion tasks.

Following Ji Lu et.al [36] notation
low rank matrix completion

$$\begin{aligned} \min_X \text{rank}(X) \\ \text{s.t. } X_\Omega = M_\Omega \end{aligned} \quad (2)$$

where Ω is an index set, then X_Ω is coping entries of X in the indexes Ω and missed entries $\hat{\Omega}$ would be 0

The missing entries in X are determined in order to minimize the matrix X rank. i.e. a non convex optimization problem since rank is nonconvex.

Frequently, trace norm (or nuclear norm) $\|\cdot\|_*$ is used to approximate the rank of matrices. Trace norm is the tightest convex envelop for the matrices rank.

$$\begin{aligned} \min_X \|X\|_* \\ \text{s.t. } X_\Omega = M_\Omega \end{aligned} \quad (3)$$

Since tensor is a generalization of the matrix concept, we generalize the optimization problem as

$$\begin{aligned} \min_{\mathcal{X}} \|\mathcal{X}\|_* \\ \text{s.t. } \mathcal{X}_\Omega = \mathcal{T}_\Omega \end{aligned} \quad (4)$$

Where \mathcal{X} and \mathcal{T} are n -order tensors with identical size.

2.4 Kernel methods

In contrast with traditional learning techniques, kernel methods do not need a vectorial representation of data. Instead, they use a kernel function. Therefore, kernel methods are naturally applied to unstructured, or complex structured, data such as texts, strings, trees and images [?].

Informally, a kernel function measures the similarity of two objects. Formally, a kernel function, $k : X \times X \rightarrow \mathbb{R}$, maps pairs (x, y) of objects in a set X , the problem space, to the reals. A kernel function implicitly generates a map, $\Phi : X \rightarrow F$, where F corresponds to a Hilbert space called the feature space. The dot product in F is calculated by k , specifically $k(x, y) = \langle \Phi(x), \Phi(y) \rangle_F$. Given an appropriate kernel function, complex patterns in the problem space may correspond to simpler patterns in the feature space. For instance, non-linear patterns in the problem space may correspond to linear patterns in the feature space.

Both k -means and SNMF have kernelized versions, which receive as input a kernel matrix instead of a set of sample represented by feature vectors. The kernel version

of k -means is called, unsurprisingly, kernel k -means (KKM). In the case of SNMF, the kernelized version works as follows.

SNMF starts with an initial estimation of the matrix factor H and iteratively update it using the updating equation:

$$H_{i,k} = H_{i,k}(1 - \beta + \beta \frac{((X^T X)H)_{i,k}}{(HH^T H)_{i,k}})$$

The kernel version of the algorithm is obtained by using a kernel matrix K instead of the expression $(X^T X)$, where K is an $l \times l$ matrix with $K_{i,j} = k(x_i, x_j)$. There are different types of kernels some of them general and some of them specifically defined for different types of data. The most popular general kernels are the linear kernel

$$k(x, y) = \langle x, y \rangle, \quad (5)$$

the polynomial kernel

$$k(x, y) = p(\langle x, y \rangle),$$

where $p(\cdot)$ is a polynomial with positive coefficients, and the Gaussian (or RBF) kernel

$$k(x, y) = e^{-\frac{\|x-y\|^2}{2\sigma^2}}. \quad (6)$$

The cluster centroids estimated by the kernel versions of both algorithms are in the feature space and correspond to the points $C_j = \frac{1}{n} \sum_{x_i \in C_j} \Phi(x_i)$. However, we are interested on the pre-image in the original space of this centroids, i.e., points \hat{C}_j such that $\Phi(\hat{C}_j) = C_j$. However, it is possible that a exact pre-image may not even exist, so we look for the \hat{C}_j that minimizes the following objective function: $\min_{\hat{C}_j} \|\hat{C}_j - C_j\|^2$. According to Kwok et al. [?], the optimum C_j can be found by iterating the following fixed-point formula:

$$\hat{C}_j^{t+1} = \frac{\sum_{i=1}^N \exp(\frac{-\|\hat{C}_j^t - x_i\|}{s}) x_i}{\sum_{i=1}^N \exp(\frac{-\|\hat{C}_j^t - x_i\|}{s})} \quad (7)$$

3 Problem Statement

The general problem addressed by this research proposal is the design of non-supervised learning algorithms, in particular tensor factorization algorithms, applied in the space induced by a kernel function. Matrix and analogous tensor factorization is central to different important tasks in machine learning and information retrieval such as: clustering, latent topic analysis, recommendation, among others. Another important focus of this research is to study robustness from a kernel method perspective.

Kernel methods are ubiquitous in machine learning and there are some connections between some types of kernels (Gaussian kernels) and robustness that has not been

fully explored yet. The general research question to be addressed by this research is whether the use of some types of kernels may bring robustness to particular clustering and factorization methods. A satisfactory solution of this general challenge requires to answer some particular **research questions**:

- How to decompose tensors in an space induced by a kernel function?

An answer to the question derivate in a method which factorize a given tensor in the feature space induced by a Kernel function. Naturally, to inquire about the effects of decompose tensors in an space induced by a kernel function open space to evaluate the proposal method performance as well as its capabilities dealing with multimodal data, scalability and robustness to noise and outliers.

References

References

- [1] E. Acar and B. Yener. Unsupervised Multiway Data Analysis: A Literature Survey. *IEEE Transactions on Knowledge and Data Engineering*, 21(1):6–20, jan 2009.
- [2] Evrim Acar, Rasmus Bro, and Age K. Smilde. Data Fusion in Metabolomics Using Coupled Matrix and Tensor Factorizations. *Proceedings of the IEEE*, 103(9):1602–1620, sep 2015.
- [3] Evrim Acar, Daniel M. Dunlavy, Tamara G. Kolda, and Morten Mørup. Scalable tensor factorizations for incomplete data. *Chemo-metrics and Intelligent Laboratory Systems*, 106(1):41–56, mar 2011.
- [4] Evrim Acar, Evangelos E Papalexakis, Gözde Gürdeniz, Morten A Rasmussen, Anders J Lawaetz, Mathias Nilsson, and Rasmus Bro. Structure-revealing data fusion. *BMC bioinformatics*, 15(1):239, jan 2014.
- [5] Gaoyun An, Shuai Liu, and Qiuqi Ruan. A sparse neighborhood preserving non-negative tensor factorization algorithm for facial expression recognition. *Pattern Analysis and Applications*, aug 2015.
- [6] Anima Anandkumar, Rong Ge, Daniel Hsu, Sham M. Kakade, and Matus Telgarsky. Tensor decompositions for learning latent variable models. pages 2773–2832, oct 2012.
- [7] A. V. Anisimov, O. O. Marchenko, and T. G. Vozniuk. Determining Semantic Valences of Ontology Concepts by Means of Nonnegative Factorization of Tensors of Large Text Corpora. *Cybernetics and Systems Analysis*, 50(3):327–337, jun 2014.

- [8] P. Antolin, A. Buffa, F. Calabrò, M. Martinelli, and G. Sangalli. Efficient matrix computation for tensor-product isogeometric analysis: The use of sum factorization. *Computer Methods in Applied Mechanics and Engineering*, 285:817–828, mar 2015.
- [9] C. J. Appellof and E. R. Davidson. Strategies for analyzing data from video fluorometric monitoring of liquid chromatographic effluents. *Analytical Chemistry*, 53(13):2053–2056, nov 1981.
- [10] Javier Arnedo, Daniel Mamah, David A Baranger, Michael P Harms, Deanna M Barch, Dragan M Svrakic, Gabriel A de Erausquin, C Robert Cloninger, and Igor Zwir. Decomposition of brain diffusion imaging data uncovers latent schizophrenias with distinct patterns of white matter anisotropy. *NeuroImage*, 120:43–54, oct 2015.
- [11] Tom Barker and Tuomas Virtanen. Semi-supervised non-negative tensor factorisation of modulation spectrograms for monaural speech separation. In *2014 International Joint Conference on Neural Networks (IJCNN)*, pages 3556–3561. IEEE, jul 2014.
- [12] Peter Benner, Venera Khoromskaia, and Boris N. Khoromskij. A reduced basis approach for calculation of the Bethe–Salpeter excitation energies by using low-rank tensor factorisations. *Molecular Physics*, pages 1–14, feb 2016.
- [13] A. Bernardi, J. Brachet, P. Comon, and B. Mourrain. General tensor decomposition, moment matrices and applications. *Journal of Symbolic Computation*, 52:51–71, may 2013.
- [14] Cagdas Bilen, Alexey Ozerov, and Patrick Pérez. Automatic Allocation of NTF Components for User-Guided Audio Source Separation, mar 2016.
- [15] Wenfei Cao, Yao Wang, Can Yang, Xiangyu Chang, Zhi Han, and Zongben Xu. Folded-concave penalization approaches to tensor completion. *Neurocomputing*, 152:261–273, mar 2015.
- [16] J. Douglas Carroll and Jih-Jie Chang. Analysis of individual differences in multidimensional scaling via an n-way generalization of “Eckart-Young” decomposition. *Psychometrika*, 35(3):283–319, sep 1970.
- [17] Raymond B. Cattell. “Parallel proportional profiles” and other principles for determining the choice of factors by rotation. *Psychometrika*, 9(4):267–283, dec 1944.
- [18] Anwesha Chaudhury, Ivan Oseledets, and Rohit Ramachandran. A computationally efficient technique for the solution of multidimensional PBMs of granulation via tensor decomposition. *Computers & Chemical Engineering*, 61:234–244, feb 2014.

- [19] Yi-Lei Chen, Chiou-Ting Hsu, and Hong-Yuan Mark Liao. Simultaneous tensor decomposition and completion using factor priors. *IEEE transactions on pattern analysis and machine intelligence*, 36(3):577–91, mar 2014.
- [20] I. Cherif and F. Fnaiech. Blind identification of a second order Volterra-Hammerstein series using cumulant cubic tensor analysis. In *2008 34th Annual Conference of IEEE Industrial Electronics*, pages 1851–1856. IEEE, nov 2008.
- [21] Andrzej Cichocki, Danilo Mandic, Lieven De Lathauwer, Guoxu Zhou, Qibin Zhao, Cesar Caiafa, and HUY ANH PHAN. Tensor Decompositions for Signal Processing Applications: From two-way to multiway component analysis. *IEEE Signal Processing Magazine*, 32(2):145–163, mar 2015.
- [22] Pierre Comon. Tensors : A brief introduction. *IEEE Signal Processing Magazine*, 31(3):44–53, may 2014.
- [23] Stephane Dartois. Tensor Models: extending the matrix models structures and methods. page 13, mar 2016.
- [24] Weiyang Ding, Liqun Qi, and Yimin Wei. Fast Hankel tensor-vector product and its application to exponential data fitting. *Numerical Linear Algebra with Applications*, 22(5):814–832, oct 2015.
- [25] I Domanov and L De Lathauwer. Canonical polyadic decomposition of third-order tensors: relaxed uniqueness conditions and algebraic algorithm. *arXiv preprint arXiv:1501.07251*, 2015.
- [26] I Domanov and LD Lathauwer. Canonical polyadic decomposition of third-order tensors: reduction to generalized eigenvalue decomposition. *SIAM Journal on Matrix Analysis and Applications*, 2014.
- [27] Ignat Domanov and Lieven De Lathauwer. On the Uniqueness of the Canonical Polyadic Decomposition of Third-Order Tensors—Part II: Uniqueness of the Overall Decomposition. *SIAM Journal on Matrix Analysis and Applications*, 34(3):876–903, jul 2013.
- [28] Pavel Dourbal. Synthesis of fast multiplication algorithms for arbitrary tensors. page 79, feb 2016.
- [29] Lisette Espín-Noboa, Florian Lemmerich, Philipp Singer, and Markus Strohmaier. Discovering and Characterizing Mobility Patterns in Urban Spaces: A Study of Manhattan Taxi Data. jan 2016.
- [30] Hadi Fanaee-T and Joao Gama. Tensor-based anomaly detection: An interdisciplinary survey. *Knowledge-Based Systems*, feb 2016.
- [31] M Figueiredo. Exploring the performance of non-negative multi-way factorization for household electrical seasonal consumption disaggregation. *Neural Networks (IJCNN) ...*, 2014.

- [32] D. Fitzgerald, M. Cranitch, and E. Coyle. Shifted 2D Non-negative Tensor Factorisation, 2006.
- [33] RA Harshman. Foundations of the PARAFAC procedure: Models and conditions for an " explanatory" multi-modal factor analysis. *UCLA Working Papers in Phonetics*, 1970.
- [34] Frank L. Hitchcock. The Expression of a Tensor or a Polyadic as a Sum of Products. *Journal of Mathematics and Physics*, 6(1-4):164–189, apr 1927.
- [35] Tamara G. Kolda and Brett W. Bader. Tensor Decompositions and Applications. *SIAM Review*, 51(3):455–500, aug 2009.
- [36] Ji Liu, Przemyslaw Musialski, Peter Wonka, and Jieping Ye. Tensor completion for estimating missing values in visual data. *IEEE transactions on pattern analysis and machine intelligence*, 35(1):208–20, jan 2013.
- [37] Ledyard R Tucker. Some mathematical notes on three-mode factor analysis. *Psychometrika*, 31(3):279–311, sep 1966.
- [38] LR Tucker. Implications of factor analysis of three-way matrices for measurement of change. *Problems in measuring change*, 1963.
- [39] LR Tucker. The extension of factor analysis to three-dimensional matrices. *Contributions to mathematical psychology*, 1964.