


Data Structures

Trees


Traversal Orders

- Imagine having a string shrink-wrapped around the tree.
- If we start at the root node and follow the string around the tree, we are **traversing** the tree.
- In what follows, we will always go around the tree counterclockwise.



Traversal Orders

- When we traverse the tree, each node is visited three times: on the left, underneath, and on the right.
 - To picture this for nodes with one or no children, just attach imaginary children.




3

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Traversal Orders

- The order of the nodes as they are passed **on the left** is called **preorder**.
- The order of the nodes as they are passed **underneath** is called **inorder**.
- The order of the nodes as they are passed **on the right** is called **postorder**.




4

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Traversal Orders: Example



- Preorder: a b d e c f
- Inorder: d b e a f c
- Postorder: d e b f c a

5

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Binary Search Tree

- Trees are generally used in index structures.
- To use them for this purpose, data should be placed in the tree in a certain order.
- The simplest ordering is the binary search tree.

Rule:


- A root node
 - values in the **left subtree** should be **smaller** than the value in the root
 - values in the **right subtree** should be **larger** than the value in the root.
- The right and left subtrees of a root node have the **search tree property**.

6

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Example



Note!

In the binary search tree, each data is located in only 1 node.

7

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012


Trees

```
isBST(node *ptr){
    node *t;
    if(nptr==null) return true;
    if(isBST(nptr->left)){ t=nptr->left;
        if(t!=null) {
            while(t->right) t=t->right;
            if(t->data>=nptr->data) return false;
        }
    }
    else return false;
    if(isBST(nptr->right)){t=nptr->right;
        if(t!=null) {
            while(t->left) t=t->left;
            if(t->data>=nptr->data) return false;
        }
    }
    else return false;
    return true;
}
```

8

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Phone Book



9

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Node Structure

```
// node.h
#define NAME_LENGTH 30
#define PHONENUM_LENGTH 15

struct Phone_node{
    char name[NAME_LENGTH];
    char phonenum[PHONENUM_LENGTH];
    Phone_node *left;
    Phone_node *right;
};
```

10

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Node Structure

```
// tree.h
struct Tree {
    Phone_node *root;
    int nodecount;
    char *filename;
    FILE *phonebook;
    void create();
    void close();
    void emptytree(Phone_node *);
    void add(Phone_node *);
    void remove(char *);
    void remove(Phone_node **);
    void traverse_inorder(Phone_node *);
    int search(char *);
    //void update(int recordnum);
    void read_fromfile();
    void write_inorder(Phone_node *);
    void write_tofile();
};
```

11

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Main Program

- Global definition (in phoneprog.cpp):
typedef Tree Datastructure;
- main(), print_menu(), and perform_operation() functions do not need to change.

12

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Constructing the Tree

```
// tree.cpp
```

```
void Tree::create() {
    root = NULL; // create empty tree
    nodecount = 0; // initialize nodecount to 0
    read_fromfile();
}
```

- We must make some changes to the function that reads the data from the file.
 - Every record read must be added to the tree in order.

13

ITÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Reading from File and Placing into Tree

```
// tree.cpp
```

```
void Tree::read_fromfile() {
    struct File_Record {
        char name[NAME_LENGTH];
        char phonenum[PHONENUM_LENGTH];
    };
    File_Record record;
    Phone_node *newnode;
    filename = "phonebook.txt";
    if (!(phonebook =
        fopen( filename, "r+" )))
        if (!(phonebook =
            fopen( filename, "w+" ))) {
            cerr << "Could not open file."
                << endl;
            cerr << "will work in"
                << " memory only."
                << endl;
            return;
        }
    fseek(phonebook, 0, SEEK_SET);
    while (!feof(phonebook)) {
        newnode = new Phone_node;
        fread(&record,
            sizeof (File_Record),
            1, phonebook);
        if ( feof(phonebook) )
            break;
        strcpy(newnode->name, record.name);
        strcpy(newnode->phonenum,
            record.phonenum);
        newnode->left = newnode->right = NULL;
        add(newnode);
        delete newnode;
    }
    fclose(phonebook);
}
```

14

ITÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Closing the Program

```
// tree.cpp
void Tree::close() {
    write_to_file();
    emptytree(root);
}

void Tree::write_to_file() {
    if ( !( phonebook = fopen( filename, "w+" ) ) ) {
        cerr << "Could not open file" << endl;
        return;
    }
    write_inorder(root);
    fclose(phonebook);
}
```

15

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Write In Order

```
// tree.cpp
void Tree::write_inorder(Phone_node *p) {
    struct File_Record {
        char name[NAME_LENGTH];
        char phonenum[PHONENUM_LENGTH];
    };
    File_Record record;
    if (p) {
        write_inorder(p->left);
        strcpy(record.name, p->name);
        strcpy(record.phonenum, p->phonenum);
        fwrite(&record, sizeof(File_Record), 1, phonebook);
        write_inorder(p->right);
    }
}
```

16

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Question

- If we write the tree to the file in order, what kind of problem would arise?
- **Answer:**
 - The data in the tree will be written to the file in alphabetical order.
 - When reading from the file and recreating the tree, the tree will be unbalanced.
 - The performance of the search operation in an unbalanced tree in the worst case may become the same as that in a linked list.
 - That is why implementing a "write_preorder" function instead of a "write_inorder" function will be more meaningful.

17

ITÜ, BLG 221E Data Structures, G. Eryigit, S. Kabadayı © 2012

Trees

write_preorder

```
// tree.cpp
void Tree::write_preorder(Phone_node *p) {
    struct File_Record {
        char name[NAME_LENGTH];
        char phonenum[PHONENUM_LENGTH];
    };
    File_Record record;
    if (p) {
        strcpy(record.name, p->name);
        strcpy(record.phonenum, p->phonenum);
        fwrite(&record, sizeof(File_Record), 1, phonebook);
        write_preorder(p->left);
        write_preorder(p->right);
    }
}
```

18

ITÜ, BLG 221E Data Structures, G. Eryigit, S. Kabadayı © 2012

Trees

To Delete the Tree from Memory (Postorder Logic)

```
// tree.cpp
void Tree::emptytree(Phone_node *p) {
    if (p) {
        if (p->left != NULL) {
            emptytree(p->left);
            p->left = NULL;
        }
        if (p->right != NULL) {
            emptytree(p->right);
            p->right = NULL;
        }
        delete p;
    }
}
```

19

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Searching for a Record

```
// phoneprog.cpp
void search_record() {
    char name[NAME_LENGTH];
    cout << "Please enter the name"
        << " of person you want to search for"
        << "(Press '*' for complete list):"
        << endl;
    cin.ignore(1000, '\n');
    cin.getline(name, NAME_LENGTH);
    if ( book.search(name) == 0 ) {
        cout << "Could not find record"
            << " matching search criteria" << endl;
    }
    getchar();
}
```

20

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Searching for a Record

// tree.cpp

```
int Tree::search(char *search_name) {
    Phone_node *traverse;
    traverse = root;
    int countfound = 0;
    bool all = false;
    if (search_name[0] == '*')
        all = true;
    if (all) {
        traverse_inorder(root);
        countfound++;
    }
    else { // single record search
        while (traverse && !countfound) {
            int comparison =
                strcmp(search_name, traverse->name);
            if (comparison < 0)
                traverse = traverse->left;
            else if (comparison > 0)
                traverse = traverse->right;
            else { // if names are equal, record found
                cout << traverse->name << " "
                    << traverse->phonenum << endl;
                countfound++;
            }
        }
    }
    return countfound;
}
```

21

ITÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Traversing the Whole Tree

// tree.cpp

- For a printout of all data:

```
void Tree::traverse_inorder(Phone_node *p) {
    if (p){
        traverse_inorder(p->left);
        cout << p->name << " " << p->phonenum << endl;
        traverse_inorder(p->right);
    }
}
```

- At the end of this traversal, the names in the tree will be listed in alphabetical order.
- If we perform inorder traversal in the binary search tree, the data will be ordered from the smallest to the largest.

22

ITÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Adding a Record

```
// phoneprog.cpp
void add_record(){
    Phone_Record newrecord;
    cout << "Please enter the information for the"
        << "person you want to record" << endl;
    cout << "Name : " ;
    cin.ignore(1000, '\n');
    cin.getline(newrecord.name, NAME_LENGTH);
    cout << "Phone number :";
    cin >> setw(PHONENUM_LENGTH)
        >>newrecord.phonenum;
    book.add(&newrecord);
    cout << "Record added" << endl;
    getchar();
}
```

23

ITÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Adding a Record: Adding a Node to the Tree

```
// tree.cpp
void Tree::add(Phone_node *toadd) {
    Phone_node *traverse, *newnode;
    traverse = root;
    int comparison;
    bool added = false;
    newnode = new Phone_node;
    strcpy(newnode->name, toadd->name);
    strcpy(newnode->phonenum,
        toadd->phonenum);
    newnode->left = NULL;
    newnode->right = NULL;
    if (root == NULL){
        //first node being added
        root = newnode;
        nodecount++;
        return;
    }
    while ((traverse != NULL) && (!added)){
        comparison = strcmp(newnode->name,
            traverse->name);
        if (comparison < 0) {
            if (traverse->left != NULL)
                traverse = traverse->left;
            else {
                traverse->left = newnode;
                added = true;
            }
        }
        else if (comparison > 0) {
            if (traverse->right != NULL)
                traverse = traverse->right;
            else {
                traverse->right = newnode;
                added = true;
            }
        }
        else
            cout << "Data cannot repeat.\n";
    }
    if (added) nodecount++;
}
```

24


ITÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Updating a Record

// phoneprog.cpp

```
void update_record() {
    char name[NAME_LENGTH];
    char choice;
    cout << "Please enter the name"
          << " of the person you want"
          << " to update:" << endl;
    cin.ignore(1000, '\n');
    cin.getline(name, NAME_LENGTH);

    int personcount = book.search(name);
    if (personcount == 0) {
        cout << "Could not find"
              << " record matching"
              << " criteria" << endl;
    }
    else {
        ... 
    }
    getchar();
}

cout << "Record found." << endl;
cout << "Do you want to update?"
      << " (y/n) ";
do {
    cin >> choice;
} while (choice != 'y' && choice != 'n');
if (choice == 'n') return;
Phone_Record newrecord;
cout << "Please enter current info"
      << endl;
cout << "Name : " ;
cin.ignore(1000, '\n');
cin.getline(newrecord.name, NAME_LENGTH);
cout << "Phone number :";
cin >> setw(PHONENUM_LENGTH)
    >> newrecord.phonenum;
book.remove(name);
book.add(&newrecord);
cout << "Record successfully updated"
      << endl;
```

25

ITÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Record


- The operation of removing from a binary search tree consists of two stages.
 - Searching for the element to be removed
 - Performing the remove operation
- Only the desired element should be removed from the tree without breaking the structure of the search tree.
- There are four cases to consider:
 - Removing a leaf
 - Removing a node that has only a left child
 - Removing a node that has only a right child
 - Removing a node that has both children

26

ITÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Leaf




27

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Node that Has a Single Child

- If the node has a single child, **the link between the parent and the node to be removed is** established between the parent and subtree of the node to be removed.



28

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Node That Has Both Children


- We move the right subtree to where the removed node used to be, and
- We try to link the left subtree to an appropriate node in the right subtree.
 - We must link the left subtree to the left of the leftmost child of the right subtree.

29

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Node That Has Both Children: Example



30

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Record

// [phoneprog.cpp](#)

```
void remove_record() {
    char name[NAME_LENGTH];
    char choice;
    cout << "Please enter name of person you want to delete:" << endl;
    cin.ignore(1000, '\n');
    cin.getline(name, NAME_LENGTH);
    int personcount = book.search\(name\);
    if (personcount == 0) {
        cout << "Could not find record matching search criteria" << endl;
    }
    else {
        cout << "Is this the record you want to delete?(y/n)";
        do {
            cin >> choice;
        } while (choice != 'y' && choice != 'n');
        if (choice == 'n') return;
        book.remove\(name\);
        cout << "Record removed" << endl;
    }
}
```

31


İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Record

// [tree.cpp](#)

```
void Tree::remove(char *remove_name){
    Phone_node *traverse, *parent;
    traverse = root;
    bool found = false;
    char direction = 'k';
    while (traverse && !found) {
        int comparison = strcmp(remove_name, traverse->name);
        if (comparison < 0) {
            parent = traverse;
            direction = 'l';
            traverse = traverse->left;
        }
        else if (comparison > 0) {
            parent = traverse;
            direction = 'r';
            traverse = traverse->right;
        }
        else // found record to remove
            found = true;
    }

    if (found) {
        
    }
    else
        cout << "Could not find"
            << " record to remove.\n";
}
```

32

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Node

- There are four possible cases:
 - Removing a leaf
 - Removing a node that has only a left child
 - Removing a node that has only a right child
 - Removing a node that has both children

33

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Leaf

```
// tree.cpp
if (traverse->left == NULL && traverse->right == NULL) {

    switch (direction) {
        case 'l':
            parent->left = NULL;
            break;
        case 'r':
            parent->right = NULL;
            break;
        default:
            root = NULL;
            break;
    }

    delete traverse;
}
```

34

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Node That Has Only Left Child

```
// tree.cpp
else if (traverse->right == NULL) {
    switch (direction) {
        case 'l':
            parent->left = traverse->left;
            break;
        case 'r':
            parent->right = traverse->left;
            break;
        default:
            root = traverse->left;
            break;
    }
}
delete traverse;
```

35

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Node That Has Only Right Child

```
// tree.cpp
else if (traverse->left == NULL) {
    switch (direction) {
        case 'l':
            parent->left = traverse->right;
            break;
        case 'r':
            parent->right = traverse->right;
            break;
        default:
            root = traverse->right;
            break;
    }
}
delete traverse;
```

36

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Node That Has Both Children


```
// tree.cpp
else {
    Phone_node *q = traverse->right;
    while ( q->left )
        q = q->left;
    q->left = traverse->left;
    switch (direction) {
        case 'l':
            parent->left = traverse->right;
            break;
        case 'r':
            parent->right = traverse->right;
            break;
        default:
            root = traverse->right;
            break;
    }
}
delete traverse;
```

37

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Example



38

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Record

```
// tree.cpp
void Tree::remove(char *remove_name) {
    Phone_node *traverse, *parent;
    traverse = root;
    bool found = false;
    char direction = 'k';
    while (traverse && !found) {
        int comparison = strcmp(remove_name, traverse->name);
        if (comparison < 0) {
            parent = traverse;
            direction = 'l';
            traverse = traverse->left;
        }
        else if (comparison > 0) {
            parent = traverse;
            direction = 'r';
            traverse = traverse->right;
        }
        else // found record to remove
            found = true;
    }

    if (found){
        ???
    }
    else
        cout << "Could not find"
              << " record to remove.\n";
}
```

39

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Record

```
// tree.cpp
void Tree::remove(char *remove_name) {
    Phone_node *traverse, *parent;
    traverse = root;
    bool found = false;
    char direction = 'k';
    while (traverse && !found) {
        int comparison = strcmp(remove_name, traverse->name);
        if (comparison < 0) {
            parent = traverse;
            direction = 'l';
            traverse = traverse->left;
        }
        else if (comparison > 0) {
            parent = traverse;
            direction = 'r';
            traverse = traverse->right;
        }
        else // found record to remove
            found = true;
    }

    if (found){
        if (direction == 'l')
            remove(&parent->left);
        else if (direction == 'r')
            remove(&parent->right);
        else remove(&root);
    }
    else
        cout << "Could not find"
              << " record to remove.\n";
}
```

40

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Removing a Record

```
// tree.cpp
void Tree::remove(Phone_node **p) {
    Phone_node *r, *q; // used to find place for left subtree
    r = *p;
    if (r == NULL) // attempt to delete nonexistent node
        return;
    else if (r->right == NULL) {
        *p = r->left; // reattach left subtree
        delete r;
    }
    else if (r->left == NULL) {
        *p = r->right; // reattach right subtree
        delete r;
    }
    else { // neither subtree is empty
        for (q = r->right; q->left; q = q->left); // inorder successor
        q->left = r->left; // reattach left subtree
        *p = r->right; // reattach right subtree
        delete r;
    }
}
```

p → pointer that will
change
r → traverse


41

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Practice

- If every person has more than one phone number
 - Add a linked list head pointer to the phonenum field of each node.



42

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees