Data Structures

Trees


Tree Definition


- The tree is a finite set of nodes.
 - There is a special node called the root.
 - The remaining nodes make up n separate, disjoint sets.
 - Each set has a separate tree structure.
 - These sets are called subtrees.
- The nodes one level below each node are the child nodes of that node.
- The node located one level above a node on the way to the root is the parent node.

2


İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

rees





Definitions



Level: Root is assumed to be at level 1 and the level increases down the tree.

Example:

- b: 2
- h: 4

Depth: The depth of the tree is the maximum node level.

Depth of example tree: 4

5

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Why a Tree?

- The list structure is not suited to storing and accessing large amounts of data.
 - Especially if fast access is desired.
- Many operations can be realized with O(log n) complexity on the tree structure.
 - For now, it suffices for us to know that tree operations, on average, can be performed much faster than list operations.
- Due to this speedup, tree structures are used in databases and many areas where indexing is necessary.
- In this course, we will study in detail the binary search tree, which is the simplest tree structure.
- You will learn about different tree structures in Advanced Data Structures.


6

ÎTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

rees


Binary Tree

- Every node has at most two subtrees.
 - The degree of a node cannot be larger than 2.
- Subtrees are called left and right subtrees.




7

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012




```
Data Structure
struct node {
                                        number
  int number:
                                     left
                                              right
  node *left;
  node *right;
};
struct tree {
                                     root
  node *root;
};
                                             number
                                         left
                                                  right
    İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012
```



Tree Representation

- From this point forward, we will not show left and right pointers in the diagrams. These always exist at each node.
- A simpler diagram:



11

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Trees

Tree Traversal

- Traversing a binary tree by visiting all nodes can be done in three ways:
 - Preorder
 - Inorder
 - Postorder
- All three types of traversals are, by definition, recursive operations.

12


ÎTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Preorder

- Traversal order
 - First, node itself
 - Then, left subtree
 - Finally, right subtree
- This operation repeats for each node.

Example:

3 8 5 2 6



13

ÎTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012


Trees

Inorder

- Traversal order
 - First, left subtree
 - · Then, node itself
 - Finally, right subtree
- This operation repeats for each node.

Example:

8 3 2 5 6



14


İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Postorder

- Traversal order
 - · First, left subtree
 - Then, right subtree
 - Finally, node itself
- This operation repeats for each node.

Example:

8 2 6 5 3



15

İTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

Tree

Coding the Traversal Methods

- All three traversal methods can easily be programmed recursively.
- Let us assume that the previously defined structure called "directory" has been created.
- Let us write the traversal functions that will work on this structure and print the data in the nodes to the screen.

16

ÎTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012

```
Preorder Function

void Preorder(node *nptr) {
   if (nptr) {
      cout << nptr->number << endl;
      Preorder(nptr->left);
      Preorder(nptr->right);
   }
}
```

```
Inorder Function

void Inorder(node *nptr) {
   if (nptr) {
      Inorder(nptr->left);
      cout << nptr->number << endl;
      Inorder(nptr->right);
   }
}
```

```
Postorder Function

void Postorder(node *nptr) {
  if (nptr) {
    Postorder(nptr->left);
    Postorder(nptr->right);
    cout << nptr->number << endl;
  }
}
```

```
Iterative Inorder Function
void Inorder(node *root) {
  node *current;
  char flag = 1;
  stack s;
  s.create();
  current = root;
  while (flag) {
    while (current != NULL) {
                                     if (!s.isempty()) {
       s.push(current);
                                          current = s.pop();
                                          cout << current->number
       current = current->left;
                                             << end1;
    }
                                          current = current->right;
                                      }
                                      else
                                          flag = 0;
    ÎTÜ, BLG 221E Data Structures, G. Eryiğit, S. Kabadayı © 2012
```

