

Text Generation & Question Answering

2110594: Natural Language Processing (NLP)


Peerapon Vateekul & Ekapol Chuangsuwanich
Department of Computer Engineering,
Faculty of Engineering, Chulalongkorn University

Credit: Can Udomcharoenchaikit & Nattachai Tretasayuth


+ Outline

2

Text Generation & Attention Mechanism



Question Answering and Deep Learning







Text Generation & Attention Mechanism

Different types of RNN architectures


many-to-many




many-to-one



one-to-many



many-to-many
(encoder-decoder)





Many-to-many

- You have seen and implemented this type of RNN architecture in your homework already.
- E.g. Tokenization, POS tagging
- Sequence Input, Sequence Output



5

Syntax: Part of Speech

Words

Morphology


Characters





Many-to-one


- You probably just implemented this type of RNN for your take-home exam.
- E.g. Sentiment Analysis, Text classification
- Sequence input





One-to-many


- Sequence output
- E.g. Music Generation, Image caption generation
- Music **generation**
 - Input: Initial seed
 - Output: Sequence of music notes
- Image caption **generation**
 - Input: Image features extracted by CNN
 - Output: Sequence of text





Many-to-many (encoder-decoder)

- Sequence Input, Sequence output
- These two sequences can be of different length
- E.g. **Machine Translation**
 - Input: English Sentence
 - Output: Thai Sentence
- Machine Translation is also a **text generation task**



+ Text generation model (training)

Training


Inference

9

■ One-to-Many RNN (autoregressive)

- The only real input is $x^{<1>}$
- $a^{<0>}$ is the initial hidden state.
- \hat{y} is the predicted output.
- y is an actual output.
- During **the training phase**, instead of using the predicted output to feed into the next time-step, we use the actual output.

$$a^{<t>} = W a^{<t-1>} + W x^{<t>} + b$$






Text generation model (inference)

10

Training

Inference


- To generate a novel sequence, the inference model (testing phase) randomly samples an output from a softmax distribution.





In class demo: Text generation

Simple demo: Generating a piece of text using RNN; **Random Date Generation** “2018-03-19”




Attention Mechanism (Many-to-Many)

Attention is commonly used in sequence-to-sequence model, it allows the decoder part of the network to focus/**attend** on a different part of the encoder's outputs for every step of the decoder's own outputs.

Why attention?

This is what we want you to think about: How can information travel from one end to another in neural networks?




Machine Translation Problem: English to Thai

+ Attention Mechanism (cont.)

Why attention?

“You can’t cram the meaning of a whole sentence into a single vector!” - Raymond Mooney (2014)



Reference: <http://yoavartzi.com/sp14/slides/mooney.sp14.pdf>

Machine Translation Problem: English to Thai




Attention Mechanism (cont.)

Why attention?

Main idea: We can use **multiple vectors** based on the length of the sentence instead of **one**.

Attention mechanism = Instead of encoding all the information into a fixed-length vector, the decoder gets to decide parts of the input source to pay attention.




Machine Translation Problem: English to Thai



Graphical Example: English-to-Thai machine translation

- This is a rough estimate of what might occur for English-to-Thai translation


	My	name	is	Sam	<u>encoder</u>
ฉัน					
ชื่อ					
แซ่ม					
<u>decoder</u>					



Machine Translation Problem: English to Thai



Graphical Example: English-to-French machine translation



Reference: Bahdanau, Dzmitry, Kyunghyun Cho, and Yoshua Bengio. "Neural machine translation by jointly learning to align and translate." ICLR(2015).



Attention Mechanism: Recap Basic Idea



- **Encode** each word in the sequence into a vector
- When **DECODING**, perform a linear combination of these encoded vectors from the encoding step with their corresponding “attention weights”.
 - (scalar 1)(encoded vector1) + (scalar 2)(encoded vector 2) + (scalar 3)(encoded vector 3)

$$\mathbf{c}_i = \sum_j a_{ij} \mathbf{h}_j$$

- A vector formed by this linear combination is called “**context vector**”
- Use context vectors as inputs for the decoding step





Figure 1: The graphical illustration of the proposed model trying to generate the t -th target word y_t given a source sentence (x_1, x_2, \dots, x_T) .

source = encoder

target word = decoder




RNN and attention mechanism




Attention Mechanism (1): C_i

We want to calculate a context vector \mathbf{c} based on hidden states $\mathbf{s}_0 \dots \mathbf{s}_{m-1}$ that can be used with the current state \mathbf{h}_j for prediction. The context vector \mathbf{c}_i at position “i” is calculated as an average of the previous states weighted with the attention scores \mathbf{a}_i .

i = decoder index
 j = encoder index



Attention Mechanism (2): f_{att}




The attention function $f_{att}(s_{i-1}, h_j)$ calculates an unnormalized alignment score between the current hidden state s_{i-1} and the previous hidden state h_j .


There are many variants of the attention function f_{att} .

i = decoder index
 j = encoder index

Attention Calculation Example (1): Attention Scores



Attention Calculation Example (2): Context Vector





$$a_{ij} = \text{softmax}(f_{att}(\mathbf{s}_{i-1}, \mathbf{h}_j))$$

Type of Attention mechanisms

	My	name	is	Sam	24
ฉัน					
ชื่อ					
อายุ					
decoder					
					encoder

(Remember that there are many variants of attention function f_{attn})

Additive attention: The original attention mechanism (Bahdanau et al., 2015) uses a one-hidden layer feed-forward network to calculate the attention alignment:

$$f_{attn}(\mathbf{s}_{i-1}, \mathbf{h}_j) = \tanh(\mathbf{W}_a[\mathbf{s}_{i-1}; \mathbf{h}_j])$$

Multiplicative attention: Multiplicative attention (Luong et al., 2015) simplifies the attention operation by calculating the following function:

$$f_{attn}(\mathbf{s}_{i-1}, \mathbf{h}_j) = \mathbf{s}_{i-1}^\top \mathbf{W}_a \mathbf{h}_j$$

Self-attention: Without any additional information, however, we can still extract relevant aspects from the sentence by allowing it to attend to itself using self-attention (Lin et al., 2017)

$$\mathbf{a} = \text{softmax}(\mathbf{w}_{s_2} \tanh(\mathbf{W}_{s_1} \mathbf{H}^T))$$

Key-value attention: key-value attention (Daniluk et al., 2017) is a recent attention variant that separates form from function by keeping separate vectors for the attention calculation.



$$a_{ij} = \text{softmax}(f_{att}(\mathbf{s}_{i-1}, \mathbf{h}_j))$$

Additive Attention

	My	name	is	Sam	encoder
\mathbf{s}_1					
\mathbf{s}_2					
\mathbf{s}_3					
decoder					

25

- The original attention mechanism (Bahdanau et al., 2015) uses a **one-hidden layer feed-forward network** to calculate the attention alignment:

$$f_{attn}(\mathbf{s}_{i-1}, \mathbf{h}_j) = \tanh(\mathbf{W}_a [\mathbf{s}_{i-1}; \mathbf{h}_j])$$

concatenation

One-hidden layer
(Dense)

- Where \mathbf{W}_a are learned attention parameters. Analogously, we can also use matrices \mathbf{W}_1 and \mathbf{W}_2 to learn separate transformations for \mathbf{s}_{i-1} and \mathbf{h}_j respectively, which are then summed (hence the name **additive**):

$$f_{attn}(\mathbf{s}_{i-1}, \mathbf{h}_j) = \tanh(\mathbf{W}_1 \mathbf{s}_{i-1} + \mathbf{W}_2 \mathbf{h}_j)$$

Reference: <http://ruder.io/deep-learning-nlp-best-practices/index.html#attention>

+

$$a_{ij} = \text{softmax}(f_{att}(\mathbf{s}_{i-1}, \mathbf{h}_j))$$

Multiplicative Attention

	My	name	is	Sam	encoder
ฉัน					
ก็					
บอก					
decoder					

26

- Multiplicative attention (Luong et al., 2015) [16] **simplifies** the attention operation by calculating the following function:

$$f_{attn}(\mathbf{s}_{i-1}, \mathbf{h}_j) = \mathbf{s}_{i-1}^\top \mathbf{W}_a \mathbf{h}_j$$

- **Faster**, more efficient than additive attention **BUT additive attention performs better** for larger dimensions
- One way to mitigate this is to scale f_{attn} by

$$\frac{1}{\sqrt{d_s}}$$

d_s = #dimensions of hidden states in LSTM
(context vector; latent factors)

+

$$a_{ij} = \text{softmax}(f_{\text{att}}(\mathbf{s}_{i-1}, \mathbf{h}_j))$$

Self Attention (1)

- Without any additional information, we can still extract relevant aspects from the sentence by allowing it to attend to itself using self-attention (Lin et al., 2017)




$$H = (\mathbf{h}_1, \mathbf{h}_2, \dots, \mathbf{h}_n)$$

Fully connected layer

$$\mathbf{a} = \text{softmax}(\mathbf{w}_{s_2} \underbrace{\tanh(\mathbf{W}_{s_1} \mathbf{H}^T)}_{\text{One-hidden layer (Dense)}})$$

One-hidden layer
(Dense)

- \mathbf{w}_{s_1} is a weight matrix, \mathbf{w}_{s_2} is a vector of parameters. Note that these parameters are tuned by the neural networks.
- The objective is to improve a quality of embedding vector by adding context information.





Self-attention (2)

- if I can give this restaurant **a 0** I will be just ask our waitress leave because someone with a reservation be wait for our table my father and father-in-law be still finish up their coffee and we have not yet finish our dessert I have never be so humiliated do not go to this restaurant their food **be mediocre at best** if you want excellent Italian in a small intimate restaurant go to dish on the South Side I will not be go back
- **this place suck the food be gross and taste like grease** I will never go here again ever sure the entrance look cool and the waiter can be very nice but the food simply be gross taste like cheap 99cent food do not go here the food shot out of me quick then it go in
- **everything be pre cook and dry its crazy most** Filipino people be used to very cheap ingredient and they do not know quality the food **be disgusting** I have eat at least 20 different Filipino family home this not **even mediocre**
- **seriously f *** this place disgust food and shitty service** ambience be great if you like dine in a hot cellar engulf in stagnate air truly it be over rate over price and they just under deliver forget try order a drink here it will take forever get and when it finally do arrive you will be ready pass out from heat exhaustion and lack of oxygen how be that a head change you do not even have pay for it I will not disgust you with the detailed review of everything I have try here but make it simple it all suck and after you get the bill you will be walk out with a sore ass save your money and spare your self **the disappointment**
- **i be so angry about my horrible experience** at Medusa today my previous visit be amaze 5/5 however my go to out of town and I land an appointment with Stephanie I go in with a picture of roughly what I want and come out look absolutely nothing like it my hair be **a horrible ashy** blonde not anywhere close to the platinum blonde I request she will not do any of the pop of colour I want and even after specifically tell her I do not like blunt cut my hair have lot of straight edge she do not listen to a single thing I want and when I tell her I be unhappy with the colour she basically tell me I be wrong and I have do it this way no no I do not if I can go from Little Mermaid red to golden blonde in 1 sitting that leave my hair fine I shall be able go from golden blonde to a shade of platinum blonde in 1 sitting thanks for ruin my New Year's with 1 **the bad hair job** I have ever have

(a) 1 star reviews

- **I really enjoy** Ashley and Ami salon she do a great job be friendly and professional I usually get my hair do when I go to MI because of the quality of the highlight and the price the price be **very affordable the highlight fantastic** thank Ashley i highly recommend you and ill be back
- **love this place it really be my favorite restaurant** in Charlotte they use charcoal for their grill and you can taste it steak with chimichurri be always perfect Fried yucca cilantro rice pork sandwich and **the good tres lech** I have had.The desert be **all incredible if** you do not like it you be a mutant if you will like diabeetus try the Inca Cola
- this place be **so much fun** I have never go at night because it seem a little too busy for my taste but that just prove how great this restaurant be they have amazing food and the staff definitely remember us every time we be in town I love when a waitress or waiter come over and ask if you want the cab or the Pinot even when there be a rush and the staff be run around like crazy whenever I grab someone they instantly smile acknowledge us the food be also killer I love when everyone know the special and can tell you they have try them all and what they pair well with this be a first last stop whenever we be in Charlotte and I highly recommend them
- **great food and good service** what else can you ask for everything that I have ever try here have be great
- first off I hardly remember waiter name because its rare you have an unforgettable experience the day I go I be celebrate my birthday and let me say I leave feel extra special our waiter be the best ever Carlos and the staff as well I be with a party of 4 and we order the potato salad shrimp cocktail lobster amongst other thing and boy be the food great the lobster be **the good lobster** I have ever eat if you eat a dessert I will recommend the cheese cake that be also the good I have ever have it be expensive but **so worth every penny** I will definitely be back there go again for the second time in a week and it be **even good** this place **be amazing**

(b) 5 star reviews


Figure 2: Heatmap of Yelp reviews with the two extreme score.

+


$$a_{ij} = \text{softmax}(f_{\text{att}}(\mathbf{s}_{i-1}, \mathbf{h}_j))$$

Key-value attention (1)

$$\mathbf{c}_i = \sum_j a_{ij} \mathbf{h}_j$$



(a) Neural language model with attention.




(b) Key-value separation.

Value=encoded vector
Key=used for attention score calculation

Reference: Daniluk, M., Rockt, T., Welbl, J., & Riedel, S. (2017). Frustratingly Short Attention Spans in Neural Language Modeling. In ICLR 2017.

Key-value attention (2)





Demo: Neural Machine Translation with attention (Additive Attention)

- Translate: one date format to another

- 27 January 2018 2018-01-27

- 27 JAN 2018 2018-01-27



Question Answering and Deep Learning

Introduction

Traditional QA


Memory Network

End-to-End Memory Network

Key-Valued Memory Network




Introduction





What's Question Answering (QA)?

- QA is a field that combines (1) Information Retrieval, (2) Information Extraction and (3) Natural Language Processing.
 - *We will focus on the NLP part*
- Most notable QA software is **IBM's Watson**
- Nowadays, QA also play a significant role in **Personal Assistant** (Siri, Cortana, etc.)



[Figure by Sandy Jakobs (left), IBM (right)]


+ Type Of QA

- By application **domains**
 - Restricted Domain
 - Open Domain
- By **source of data**
 - Structured data (Knowledge-based) - e.g. Freebase, Google Knowledge Graph
 - Unstructured data (Document)- Web, Wiki
- By **answer**
 - Factoid (single word - when, what, where)
 - non-Factoid (e.g., list, how, why)
- The **forms** of answer
 - Extracted text
 - Generated answer



Process Of QA


- Question Processing
 - What **type** of question?
 - Question **preprocessing**
- Document Processing
 - Rank candidate **document**
 - Rank candidate **paragraph**
- **Answer Processing**
 - **Extract** candidate answer from paragraph
 - **Construct** an answer



[Figure from “The Question Answering Systems: A Survey”]



Example of QA system



Types of QA systems

Structured Knowledge Base

Google

the hobbit book
 the hobbit book online
 the hobbit book summary
 the hobbit book review

Ad related to the hobbit book

Buy The Hobbit (The Book) - By J.R.R. Tolkien.
[www.bookdepository.co.uk/JRR-Tolkien](#)
 ★★★★★ 203 reviews for bookdepository.co.uk
 Up to 50% Discount. Free Worldwide Delivery. Order Now!

The Hobbit - Wikipedia, the free encyclopedia
[en.wikipedia.org/wiki/The_Hobbit](#)
 This article is about the **novel**. For the 2012 film, see **The Hobbit: An Unexpected Journey**. For other uses, see **Hobbit** (disambiguation) or **There and Back Again ... The Hobbit** (film series). • The Lord of the Rings • The Hobbit (1977 film) • Adaptations

11 PA	818	Z 102 LKs	S2D PCh	DA: 100	488,915,871 LKs	2,810,043 PCh	English
-------	-----	-----------	---------	---------	-----------------	---------------	---------

Five things changed/expanded from the book for 'The Hobbit' films ...
[www.cnn.com/2012/12/14/hobbit-book-movie/index.html...](#)
 17 Dec 2012 – When people complain about the nearly three-hour length of the first installment of **'The Hobbit'** film frenzy because the source book is a short ...

20 PA	1	5 LKs	0 PCh	DA: 100	84,181,432 LKs	548,520 PCh	English
-------	---	-------	-------	---------	----------------	-------------	---------

Images for the hobbit book Report Images

The Hobbit or There and Back Again J.R.R. Tolkien
[www.amazon.com › Books › Teen & Young Literature >](#)
 I purchased the Kindle edition of **The Hobbit** and

The Hobbit

The Hobbit, or There and Back Again, better known by its abbreviated title **The Hobbit**, is a fantasy novel and children's book by English author J. R. R. Tolkien. *Villains*

Published: September 21, 1937
Author: J. R. R. Tolkien
Original language: English
Preceded by: The Children of Húrin
Followed by: The Lord of the Rings
Characters: Bilbo Baggins, Gandalf, Smaug, Gollum, Thorin Oakenshield, Sauron, Elrond, Thranduil, Beorn, Balin


This is all linked to Google SERPs

People also search for

Diagram illustrating the relationships between various concepts related to The Hobbit:

- Companion** (red box) connects to **Mirror Shivers (Planet)** (blue box), **Calendar Event Range** (blue box), **Extraterrestrial location** (orange box), **Type to phenomenon feature** (orange box), **Coordinate (Extraterrestrial location)** (blue box), **Assumed descent** (blue box), **Coordinate system** (blue box), **Major axis** (blue box), **Minor axis** (blue box), and **Uncertainty Mass** (blue box).
- Mirror Shivers (Planet)** connects to **Calendar Event Range**.
- Calendar Event Range** connects to **Extraterrestrial location**.
- Extraterrestrial location** connects to **Type to phenomenon feature**.
- Type to phenomenon feature** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Coordinate system**.
- Coordinate system** connects to **Major axis** and **Minor axis**.
- Major axis** and **Minor axis** connect to **Uncertainty Mass**.
- Uncertainty Mass** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range** (green box).
- Assumed range** connects to **Prime revision feature** (green box).
- Prime revision feature** connects to **Metallurgical source** (green box).
- Metallurgical source** connects to **Phenomenological coordinate system** (red box).
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.
- Metallurgical source** connects to **Phenomenological coordinate system**.
- Phenomenological coordinate system** connects to **Coordinate system**.
- Coordinate system** connects to **Coordinate (Extraterrestrial location)**.
- Coordinate (Extraterrestrial location)** connects to **Assumed descent**.
- Assumed descent** connects to **Assumed range**.
- Assumed range** connects to **Prime revision feature**.
- Prime revision feature** connects to **Metallurgical source**.

Unstructured Knowledge Base



WIKIPEDIA

The Free Encyclopedia

Main Page

Talk

Main page

Contents

Featured content

Current events

Random article

Donate to Wikipedia

Wikipedia store

Interaction

Help

About Wikipedia

Community portal

Recent changes

Contact page

Tools

What links here

Related changes

Upload file

Special pages

Permanent link

Page information

Wikidata item

Print/export

Create a book

Download as PDF

Printable version


In other projects

Welcome to Wikipedia,

the free encyclopedia that anyone can edit.

5,592,410 articles in English

From today's featured article



Resident Evil: Apocalypse

is a 2004 science fiction action horror film filmed in Toronto, Canada, directed by Alexander Wilt and written by Paul W. S. Anderson. It is the second installment in the *Resident Evil* film series, which is based on the video game series of the same name. Milla Jovovich (*pictured*) reprises her role as Alice, and is joined by Sienna Guillory as Jill Valentine and Oded Fehr as Carlos Oliveira. *Resident Evil: Apocalypse* is set directly after the events of the first film, where Alice escaped from an underground facility overrun by *zombies*. She now bands together with other survivors to escape the zombie outbreak which has spread to the fictional Raccoon City. The film borrows elements from several games in the *Resident Evil* series, including the characters Valentine and Oliveira and the villain *Nemesis*. While it received mostly negative reviews from critics for its plot, the film was praised for its action sequences. Of the six films in the series, it has the lowest approval rating on *Rotten Tomatoes*. Earning \$129 million worldwide on a \$45 million budget, it surpassed the box office gross of the original film. ([Full article...](#))

Recently featured:

Elcor, Minnesota

Freedom Planet

Hurricane Marie (2014)

Archive

•

By email


•

More featured articles

Did you know...


... that London's **Bull and Mouth Inn** (*sign pictured*) was originally known as the Boulogne Mound, in reference to the town and harbor of Boulogne which was besieged by Henry VIII in the 1540s?

... that in 1998, **Dottie Lamm**, former First Lady of Colorado, ran for a US Senate seat against the same man who had defeated her husband in the



Bull and Mouth Inn

■ Open Question Answering Over Curated and Extracted Knowledge Bases (A.Fader SIGKDD 2014)



Example of Traditional Methods (cont.)

- Open Question Answering Over Curated and Extracted Knowledge Bases (A.Fader SIGKDD 2014)
 - 1) Paraphrase operator
 - are responsible for **rewording the input question** into the domain of a parsing operator
 - **Source template (open domain) → Target template (predefined format)**

<u>Source Template</u>	<u>Target Template</u>
How does _ affect your body?	What body system does _ affect?
What is the latin name for _?	What is _'s scientific name?
Why do we use _?	What did _ replace?
What to use instead of _?	What is a substitute for _?
Was _ ever married?	Who has _ been married to?

Table 3: Example paraphrase operators that extracted from a corpus of unlabeled questions.



Example of Traditional Methods (cont.)

- Open Question Answering Over Curated and Extracted Knowledge Bases (A.Fader SIGKDD 2014)
 - 2) Parsing operator
 - responsible for interfacing between natural language questions and the KB **query language**
 - **Target template (predefined format) → Query**

Question Pattern	Query Pattern	Example Question	Example Query
Who/What $RV_{rel} NP_{arg}$	(?x, rel, arg)	Who invented papyrus?	(?x, invented, papyrus)
Who/What Aux $NP_{arg} RV_{rel}$	(arg, rel, ?x)	What did Newton discover?	(Newton, discover, ?x)
Where/When Aux $NP_{arg} RV_{rel}$	(arg, rel in, ?x)	Where was Edison born?	(Edison, born in, ?x)
Where/When is NP_{arg}	(arg, is in, ?x)	Where is Detroit?	(Detroit, is in, ?x)
Who/What is NP_{arg}	(arg, is-a, ?x)	What is potassium?	(potassium, is-a, ?x)
What/Which $NP_{rel2} Aux NP_{arg} RV_{rel1}$	(arg, rel1 rel2, ?x)	What sport does Sosa play?	(Sosa, play sport, ?x)
What/Which NP_{rel} is NP_{arg}	(arg, rel, ?x)	What ethnicity is Dracula?	(Dracula, ethnicity, ?x)
What/Who is NP_{arg} 's NP_{rel}	(arg, rel, ?x)	What is Russia's capital?	(Russia, capital, ?x)
What/Which $NP_{type} Aux NP_{arg} RV_{rel}$	(?x, is-a, type) (arg, rel, ?x)	What fish do sharks eat?	(?x, is-a, fish) (sharks, eat, ?x)
What/Which $NP_{type} RV_{rel} NP_{arg}$	(?x, is-a, type) (?x, rel, arg)	What states make oil?	(?x, is-a, states) (?x, make, oil)

Example of Traditional Methods (cont.)


- Open Question Answering Over Curated and Extracted Knowledge Bases (A.Fader SIGKDD 2014)
 - 3) Query-rewrite operators
 - responsible for **interfacing** between the **vocabulary** used in the input question and the internal vocabulary **used by the KBs**
 - **Source Query** → **Target Query** (only vocab in knowledge base)

<u>Source Query</u>	<u>Target Query</u>
(?x, children, ?y)	(?y, was born to, ?x)
(?x, birthdate, ?y)	(?x, date of birth, ?y)
(?x, is headquartered in, ?y)	(?x, is based in, ?y)
(?x, invented, ?y)	(?y, was invented by, ?x)
(?x, is the language of, ?y)	(?y, languages spoken, ?x)

Table 4: Example query-rewrite operators mined from the knowledge bases described in Section 4.1.

Example of Traditional Methods (cont.)

- Open Question Answering Over Curated and Extracted Knowledge Bases (A.Fader SIGKDD 2014)
 - 4) Execution operator
 - responsible for **fetching and combining evidence** from the Knowledge based, given a query






Limitation

- Require a lot of time and linguistic knowledge to create a template
- Require many templates for each question type (manual process)
- Can only answer simple factoid question



Memory Network



Deep Learning and QA: Memory Network

■ Memory Network [Jason Weston, et'al, 2015]


- Deep Learning with a memory component.
- Incorporates **reasoning** over **memory**
- Why memory network and QA?
 - **LONG-term memory** is required to read a story to answer questions about it
 - Long-term = HDD (database)
 - Short-term = RAM (question, chat)

Long-Term Memories h_i	Shaolin Soccer directed_by Stephen Chow Shaolin Soccer written_by Stephen Chow Shaolin Soccer starred_actors Stephen Chow Shaolin Soccer release_year 2001 Shaolin Soccer has_genre comedy Shaolin Soccer has_tags martial arts, kung fu soccer, stephen chow Kung Fu Hustle directed_by Stephen Chow Kung Fu Hustle written_by Stephen Chow Kung Fu Hustle starred_actors Stephen Chow Kung Fu Hustle has_genre comedy action Kung Fu Hustle has_imdb_votes famous Kung Fu Hustle has_tags comedy, action, martial arts, kung fu, china, soccer, hong kong, stephen chow The God of Cookery directed_by Stephen Chow The God of Cookery written_by Stephen Chow The God of Cookery starred_actors Stephen Chow The God of Cookery has_tags hong kong Stephen Chow From Beijing with Love directed_by Stephen Chow From Beijing with Love written_by Stephen Chow From Beijing with Love starred_actors Stephen Chow , Anita Yuen ... <and more> ...
Short-Term Memories c_1^q	1) I'm looking a fun comedy to watch tonight, any ideas?
Input c_2^q	2) Have you seen Shaolin Soccer ? That was zany and great.. really funny but in a whacky way.
	3) Yes! Shaolin Soccer and Kung Fu Hustle are so good I really need to find some more Stephen Chow films I feel like there is more awesomeness out there that I haven't discovered yet ...
Output y	4) God of Cookery is pretty great, one of his mid 90's hong kong martial art comedies.



Example: Memory Network?


- Factoid QA with Two Supporting Facts (“where is actor + object”)






Example: Memory Network? (cont.)

- Factoid QA with Two Supporting Facts (“where is actor+object”)



+ What is Memory Network?

- MemNNs have **four component** networks (which may or may not have shared parameters):
 - I: (input feature map)** convert incoming data to the internal feature representation.
 - bag of words, RNN style reading at word or character level, etc.
 - G: (generalization) update** memories given new input.
 -
 - O: produce new output** (in feature representation space) given the memories.
 - multi-class classifier or uses an RNN to output sentences
 - R: (response)** convert output O into a response seen by the outside world.
 - For example, factoid (softmax), text generation



+ Memory Network: Core Inference

- The core of inference lies in the **O** and **R** modules.

- In case that we only have one supporting sentence, the model can find it by using input x

$$o_1 = O_1(x, \mathbf{m}) = \arg \max_{i=1, \dots, N} s_O(x, \mathbf{m}_i)$$


- If we have **2 supporting sentences**, we can use input x and the first supporting sentence to find the second supporting sentence

$$o_2 = O_2(x, \mathbf{m}) = \arg \max_{i=1, \dots, N} s_O([x, \mathbf{m}_{o_1}], \mathbf{m}_i)$$

- In general we can make any N inference step using x and all previous supporting sentences
- After that we can produce, the response (r) by selecting the single word answer with input and all supporting sentences

$$r = \operatorname{argmax}_{w \in W} s_R([x, \mathbf{m}_{o_1}, \mathbf{m}_{o_2}], w)$$

Memory Networks (MemNN)



Memory Network: Train and Loss


- Scoring function s is just a Matrix multiplication operation

- Where x =inputs, y =target

$$s(x, y) = \Phi_x(x)^\top U^\top U \Phi_y(y).$$

- Training

- **Max margin ranking loss** and stochastic gradient descent



$$\sum_{\bar{f} \neq \mathbf{m}_{o_1}} \max(0, \gamma - s_O(x, \mathbf{m}_{o_1}) + s_O(x, \bar{f})) + \quad (6)$$

$$\sum_{\bar{f}' \neq \mathbf{m}_{o_2}} \max(0, \gamma - s_O([x, \mathbf{m}_{o_1}], \mathbf{m}_{o_2}) + s_O([x, \mathbf{m}_{o_1}], \bar{f}')) + \quad (7)$$

$$\sum_{\bar{r} \neq r} \max(0, \gamma - s_R([x, \mathbf{m}_{o_1}, \mathbf{m}_{o_2}], r) + s_R([x, \mathbf{m}_{o_1}, \mathbf{m}_{o_2}], \bar{r})) \quad (8)$$

where \bar{f} , \bar{f}' and \bar{r} are all other choices than the correct labels, and γ is the margin. At every step of SGD we sample \bar{f} , \bar{f}' , \bar{r} rather than compute the whole sum for each training example, following e.g., Weston et al. (2011).



End-To-End Memory Network: Overview (1)

- Limitation of Memory Networks
 - Use **hard attention**
 - **Requires explicit supervision** of attention during training (must identify **all facts** for each questions)
 - Only feasible for simple tasks
- End-to-end (MemN2N) model (Sukhbaatar '15):
 - Reads from memory with **soft attention (weight)**
 - End-to-end training with backpropagation
 - Only need supervision on **the final output**

End-To-End Memory Network

Attention during **three memory hops**

■ Example of model mechanism

Story (1: 1 supporting fact)	Support	Hop 1	Hop 2	Hop 3
Daniel went to the bathroom.		0.00	0.00	0.03
Mary travelled to the hallway.		0.00	0.00	0.00
John went to the bedroom.		0.37	0.02	0.00
John travelled to the bathroom.	yes	0.60	0.98	0.96
Mary went to the office.		0.01	0.00	0.00
Where is John? Answer: bathroom Prediction: bathroom				


Story (16: basic induction)	Support	Hop 1	Hop 2	Hop 3
Brian is a frog.	yes	0.00	0.98	0.00
Lily is gray.		0.07	0.00	0.00
Brian is yellow.	yes	0.07	0.00	1.00
Julius is green.		0.06	0.00	0.00
Greg is a frog.	yes	0.76	0.02	0.00
What color is Greg? Answer: yellow Prediction: yellow				

Story (2: 2 supporting facts)	Support	Hop 1	Hop 2	Hop 3
John dropped the milk.		0.06	0.00	0.00
John took the milk there.	yes	0.88	1.00	0.00
Sandra went back to the bathroom.		0.00	0.00	0.00
John moved to the hallway.	yes	0.00	0.00	1.00
Mary went back to the bedroom.		0.00	0.00	0.00
Where is the milk? Answer: hallway Prediction: hallway				


Story (18: size reasoning)	Support	Hop 1	Hop 2	Hop 3
The suitcase is bigger than the chest.	yes	0.00	0.88	0.00
The box is bigger than the chocolate.		0.04	0.05	0.10
The chest is bigger than the chocolate.	yes	0.17	0.07	0.90
The chest fits inside the container.		0.00	0.00	0.00
The chest fits inside the box.		0.00	0.00	0.00
Does the suitcase fit in the chocolate? Answer: no Prediction: no				

End-To-End Memory Network: Overview (2); 2 hops


Story (16: basic induction)	Support	Hop 1	Hop 2	Hop 3
Brian is a frog.	yes	0.00	0.98	0.00
Lily is gray.		0.07	0.00	0.00
Brian is yellow.	yes	0.07	0.00	1.00
Julius is green.		0.06	0.00	0.00
Greg is a frog.	yes	0.76	0.02	0.00
What color is Greg? Answer: yellow Prediction: yellow				



End-To-End Memory Network: Memory Module




+ End-To-End Memory Network: Example



+ End-To-End Memory Network

Multiple Hops Reasoning




+ End-To-End Memory Network

Multiple Hops Reasoning

- There are two ways to do the multiple hops reasoning
- 1) Adjacent
 - The query representation (u) is updated every hop
 - $u_{k+1} = u_k + o_k$
 - Input embedding of the new layer is output embedding of the previous layer
 - $A_{k+1} = C_k$
- 2) Layer-wise (RNN-like)
 - The query representation (u) is updated every hop with H linear mapping
 - $u_{k+1} = H u_k + o_k$
 - Every embedding matrix is the same
 - $A_1 = A_2 = \dots = A_k$
 - $C_1 = C_2 = \dots = C_k$

+ End-To-End Memory Network

Memory Vector





End-To-End Memory Network

Memory Vector

- Word Embedding
 - Embed every word in a sentence
- Positional Encoding (PE)
 - Position is modeled by a multiplicative term on each word vector with weights depending on the position in the sentence.
- Sentence Embedding
 - Summation of all embedded words in the sentence
- Temporal Encoding (TE)
 - Encoded timestamp (or index) of the sentence in the story

+ End-To-End Memory Network

Positional Encoding

61

■ Positional Encoding (PE)

- Position is modeled by a multiplicative term on each word vector with weights depending on the position in the sentence

$S =$

J

I ate $fried$ $rice$

I

$f(j,d) = (1 - j/J) - (d/D)(1 - 2j/J)$

$PE(I) =$

1	0.13	○	0.70	0.09
2	0.04	○	0.65	0.03
...	...	○
...	...	○
D-1	0.91	○	0.30	0.27
D	0.82	○	0.25	0.20

$=$

○ is element-wise multiplication

+ End-To-End Memory Network

Sentence Embedding

62

- Sentence Embedding
 - Summation of all embedded words in the sentence

$$S = \begin{array}{c|c|c|c} \mathbf{I} & \mathbf{ate} & \mathbf{fried} & \mathbf{rice} \\ \hline 0.09 & 0.14 & 0.00 & 0.01 \\ 0.03 & 0.01 & 0.01 & 0.00 \\ \dots & \dots & \dots & \dots \\ \dots & \dots & \dots & \dots \\ 0.27 & 0.05 & 0.21 & 0.03 \\ 0.20 & 0.02 & 0.16 & 0.31 \end{array} = \begin{array}{c} 0.24 \\ 0.05 \\ \dots \\ \dots \\ 0.56 \\ 0.69 \end{array}$$

\sum

+ End-To-End Memory Network

Temporal Encoding (TE)

63

- Temporal Encoding (TE)
 - Encoded timestamp (or index) of the sentence in the story

The diagram illustrates the Temporal Encoding (TE) process. It shows a vector for 'Sentence' and a vector for 'T(index)' being added together to produce a result vector. The 'Sentence' vector has values [0.24, 0.05, ..., ..., 0.56, 0.69]. The 'T(index)' vector has values [0.01, 0.42, ..., ..., 0.03, -0.11]. The resulting vector has values [0.25, 0.47, ..., ..., 0.59, 0.58].

Sentence	T(index)	Result
0.24	0.01	0.25
0.05	0.42	0.47
...
...
0.56	0.03	0.59
0.69	-0.11	0.58



End-To-End Memory Network

Attention during three memory hops

■ Example of model mechanism

Story (1: 1 supporting fact)	Support	Hop 1	Hop 2	Hop 3
Daniel went to the bathroom.		0.00	0.00	0.03
Mary travelled to the hallway.		0.00	0.00	0.00
John went to the bedroom.		0.37	0.02	0.00
John travelled to the bathroom.	yes	0.60	0.98	0.96
Mary went to the office.		0.01	0.00	0.00
Where is John? Answer: bathroom Prediction: bathroom				

Story (16: basic induction)	Support	Hop 1	Hop 2	Hop 3
Brian is a frog.	yes	0.00	0.98	0.00
Lily is gray.		0.07	0.00	0.00
Brian is yellow.	yes	0.07	0.00	1.00
Julius is green.		0.06	0.00	0.00
Greg is a frog.	yes	0.76	0.02	0.00
What color is Greg? Answer: yellow Prediction: yellow				

Story (2: 2 supporting facts)	Support	Hop 1	Hop 2	Hop 3
John dropped the milk.		0.06	0.00	0.00
John took the milk there.	yes	0.88	1.00	0.00
Sandra went back to the bathroom.		0.00	0.00	0.00
John moved to the hallway.	yes	0.00	0.00	1.00
Mary went back to the bedroom.		0.00	0.00	0.00
Where is the milk? Answer: hallway Prediction: hallway				

Story (18: size reasoning)	Support	Hop 1	Hop 2	Hop 3
The suitcase is bigger than the chest.	yes	0.00	0.88	0.00
The box is bigger than the chocolate.		0.04	0.05	0.10
The chest is bigger than the chocolate.	yes	0.17	0.07	0.90
The chest fits inside the container.		0.00	0.00	0.00
The chest fits inside the box.		0.00	0.00	0.00
Does the suitcase fit in the chocolate? Answer: no Prediction: no				

+ Memory Network Briefing

- Memory Network [Jason Weston, et'al, 2015]
 - Machine learning with a memory component.
 - The model is trained to learn how to operate effectively with the memory component.
 - Multiple inference steps
 - Need strong supervision (Limitation)
- End-To-End Memory Network [Sainbayar Sukhbaatar, et' al, 2015]
 - Use attention to let model learn to select relevant memory
 - Weight tying let model remember previous step decision

+ Demo: QA (AllenNLP)

<https://demo.allennlp.org/reading-comprehension>

