




ARRAYS

JavaScript Fundamentals






Introduction

Arrays

- What are arrays?
- Creating arrays
- Accessing arrays
- Array methods



QA Creating arrays

- Arrays hold a set of related data, e.g. students in a class
 - The default approach is accessed by a numeric index

a is created with
no data
c is a 3 element
array of string

```
let a = Array();  
let b = Array(10);  
let c = Array("Tom", "Dick", "Harry");  
let d = [1,2,3];
```

b is a 10 element array
of undefined
d is shorthand for
an array

QA Creating arrays

- Arrays in JavaScript have some idiosyncrasies
 - They can be resized at any time
 - They index at 0
 - **So `Array(3)` would have elements with indexes 0, 1 and 2**
 - They can be *sparingly* filled
 - **Unassigned parts of an array are `undefined`**
 - They can be created in short hand using just square brackets

QA Accessing arrays

- Arrays are accessed with a square bracket notation

Access an array
via its index

```
let classRoom = new Array(5);  
classRoom[0] = "Dave";  
classRoom[4] = "Laurence";
```

← Elements 1 through 3
are not yet set

- Arrays have a length property that is useful in loops

```
for (let i = 0; i < classRoom.length; i++) {  
    console.log(classRoom[i]);  
}
```

← i has 1 added to it on
each iteration of the loop

QA Array object methods

- Array objects have methods
- **reverse()**
- **join([separator])**
 - Joins all the elements of the array into one string, using the supplied separator or a comma
- **sort([sort function])**
 - Sorts the array using string comparisons by default
 - Optional sort function compares two values and returns sort order

```
let fruit = ['Apples', 'Pears', 'Bananas', 'Oranges'];  
let fruitString = fruit.join("---");  
  
// Apples---Pears---Bananas---Oranges  
console.log(fruitString);
```

QA Pop and push array methods

- The **push()** method
 - Adds a new element to the end of the array
 - Array's length property is increased by one
 - This method returns the new length of the array

```
let fruit = ['Apples', 'Pears', 'Bananas', 'Oranges'];  
console.log(fruit.push('Lemons')); //5  
  
// ['Apples', 'Pears', 'Bananas', 'Oranges', 'Lemons']  
console.log(fruit);
```

QA Pop and push array methods

- The **pop()** method
 - Removes the last element from the end of the array
 - The array's length property is decreased by one
 - This method returns the array element that was removed

```
let fruit = ['Apples', 'Pears', 'Bananas', 'Oranges'];  
console.log(fruit.pop()); //Oranges  
  
//['Apples', 'Pears', 'Bananas']  
console.log(fruit);
```


QA Shift and unshift array methods

- The **unshift()** method
 - Adds a new element to the beginning of the array
 - Array's length property is increased by one
 - This method returns the new length of the array

```
let fruit = ['Apples', 'Pears', 'Bananas', 'Oranges'];  
console.log(fruit.unshift('Kiwis')); //5  
  
//['Kiwis','Apples', 'Pears', 'Bananas', 'Oranges']  
console.log(fruit);
```

QA Shift and unshift array methods

- The **shift()** method
 - removes the first element from the beginning of the array
 - Array's length property is decreased by one
 - This method returns the array element that was removed

```
let fruit = ['Apples', 'Pears', 'Bananas', 'Oranges'];  
console.log(fruit.shift()); //Apples  
  
//['Pears', 'Bananas', 'Oranges']  
console.log(fruit);
```

QA New Methods in ES2015

- **Array.from()** creates a real Array out of array-like objects

```
let formElements = document.querySelectorAll('input, select, textarea');  
formElements = Array.from(formElements);  
formElements.push(anotherElement); //works fine!
```

- **Array.prototype.find()** returns the first element for which the callback returns true
 - A callback is a function passed to another function – the one shown below is an anonymous function:

```
[`Chris`,`Bruford`,22].find(function(n) { return n === `Bruford`}); // Bruford
```

- This is an instance where an arrow function could be used to clean the code:

```
[`Chris`,`Bruford`,22].find( n => n === `Bruford`); // Bruford
```

QA New Methods in ES2015

- Similarly **findIndex()** returns the index of the first matching element

```
[`Chris`,`Bruford`,22].findIndex( n => n === `Bruford`}); // 1
```

- **fill()** overrides the specified elements

```
[`Chris`,`Bruford`,22,true].fill(null); // [null,null,null,null]  
[`Chris`,`Bruford`,22,true].fill(null,1,2); // [`Chris`,null,null,true]
```

QA New Methods in ES2015

- `.entries()`, `.keys()` & `.values()` each return a sequence of values via an iterator:

```
let arrayEntries = [`Chris`, `Bruford`, 22, true].entries();
console.log(arrayEntries.next().value);      // [0, `Chris`]
console.log(arrayEntries.next().value);      // [1, `Bruford`]
console.log(arrayEntries.next().value);      // [2, 22]
```

```
let arrayKeys = [`Chris`, `Bruford`, 22, true].keys();
console.log(arrayKeys.next().value);          // 0
console.log(arrayKeys.next().value);          // 1
console.log(arrayKeys.next().value);          // 2
```

```
let arrayValues = [`Chris`, `Bruford`, 22, true].values();
console.log(arrayValues.next().value);        // `Chris`
console.log(arrayValues.next().value);        // `Bruford`
console.log(arrayValues.next().value);        // 22
```

QA for...of loop

- The for-of loop is used for iterating over **iterable** objects (more on that later!)
- For an array it means we can loop through the array, returning each element in turn

```
//will print 1 then 2 then 3
let myArray = [1,2,3,4];
for (el of myArray) {
    if (el === 3) break;
    console.log(el);
}
```

- We could also loop through any of the iterables returned by the methods **.entries()**, **.values()** and **.keys()**

forEach loop

```
let text = "";
const fruits = ["apple", "orange", "cherry"];
fruits.forEach(myFunction);
```

```
function myFunction(item, index) {
    text += index + ": " + item + "<br>";
}
```



QuickLab 5 - Arrays

Creating and Managing arrays