

# Problem Set 6

Ekkapot Charoenwanit  
Efficient Algorithms

## Problem 6.1. Fibonacci numbers

1) The pseudocode given in Algorithm 1 implements a function computing the Fibonacci numbers in a top-down manner with the help of memoization.

---

**Algorithm 1** computes the Fibonacci numbers with memoization.

---

```
1: procedure FIB( $n, F[1..n]$ )
2:   if  $n \leq 1$  then
3:     return  $n$ 
4:   else
5:     if  $F[n] > 0$  then
6:       return  $F[n]$ 
7:      $F[n] = \text{FIB}(n-1, F) + \text{FIB}(n-2, F)$ 
8:     return  $F[n]$ 
```

---

What is the recursion depth and what is the space complexity of  $\text{FIB}(n)$ ?

2) Optimize the bottom-up implementation given in Algorithm 2 such that it uses  $\Theta(1)$  space.

---

**Algorithm 2** computes the Fibonacci numbers bottom-up.

---

```
1: procedure FIB( $n$ )
2:    $F = \text{NEW TABLE}[0..n]$ 
3:    $F[0] = 0$ 
4:    $F[1] = 1$ 
5:   for  $i = 2 \rightarrow n$  do
6:      $F[i] = F[i-1] + F[i-2]$ 
7:   return  $F[n]$ 
```

---

## Problem 6.2. Matrix Chain Multiplication

1) Find an optimal parenthesization for the chain product of 5 matrices with dimensions  $6 \times 7$ ,  $7 \times 8$ ,  $8 \times 3$ ,  $3 \times 10$  and  $10 \times 6$  in a bottom-up approach.

2) Show that the number of ways of parenthesization  $C(n)$  is  $\Omega(2^n)$ , where  $n$  is the matrix chain length. You may use induction to show that  $C(n) \geq c \cdot 2^n$  for some  $c \in \mathbb{R}^+$  and  $n_0 \in \mathbb{Z}^+$  for all  $n \geq n_0$ .

3) Calculate the exact number of distinct subproblems for a matrix chain of length  $n$ .

4) Does the maximum matrix chain problem also exhibit optimal substructure? If it is the case, prove your claim using a cut-and-paste argument.

**Problem 6.3. Longest Common Subsequence**

- 1) Give a memoized version of LCS-LENGTH that runs in  $\mathcal{O}(mn)$  time.
- 2) What is the maximum recursion depth of LCS?