

# **The *changes*-package**

Manual change markup — version 0.6.0

Ekkart Kleinod  
ekleinod@edgesoft.de

January 9, 2012



## Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
<b>2</b>	<b>Using the <i>changes</i>-package</b>	<b>3</b>
<b>3</b>	<b>Limitations and possible enhancements</b>	<b>5</b>
<b>4</b>	<b>User interface of the <i>changes</i>-package</b>	<b>6</b>
4.1	Package Options	6
4.1.1	draft	6
4.1.2	final	7
4.1.3	markup	7
4.1.4	addedmarkup, deletedmarkup	7
4.1.5	authormarkup	8
4.1.6	authormarkupposition	9
4.1.7	authormarkuptext	9
4.1.8	ulem	9
4.1.9	xcolor	10
4.2	Change management	10
4.2.1	\added	10
4.2.2	\deleted	10
4.2.3	\replaced	11
4.2.4	\listofchanges	11
4.3	Author management	11
4.3.1	\definechangesauthor	11
4.4	Adaptation of the output	12
4.4.1	\setaddedmarkup	12
4.4.2	\setdeletedmarkup	12
4.4.3	\setauthormarkup	12
4.4.4	\setauthormarkupposition	13
4.4.5	\setauthormarkuptext	13
4.4.6	\setremarkmarkup	14
4.4.7	\setlocextension	14
4.5	Other new commands	14
4.5.1	\textsubscript	14
4.6	Used packages	15
<b>5</b>	<b>Authors</b>	<b>15</b>
<b>6</b>	<b>Versions</b>	<b>15</b>
<b>7</b>	<b>Distribution, Copyright, License</b>	<b>17</b>

<b>8</b>	<b>The documented sourcecode</b>	<b>18</b>
8.1	Package information and options	18
8.1.1	Package options	19
8.1.2	Command options	23
8.1.3	Option processing	23
8.2	Packages	23
8.3	Language dependent texts	24
8.4	File extension	25
8.5	Authors	25
8.5.1	Author management	25
8.5.2	Author markup	27
8.6	Change management commands	28
8.6.1	Text markup definition	28
8.6.2	Change management command definition	29
8.7	List of changes	31

## 1 Introduction

This package provides means for manual change markup.

Any comments, thoughts or improvements are welcome. The package is maintained at *sourceforge*, please see

<http://changes.sourceforge.net/>

for source code access, bug and feature tracker, forum etc. If you want to contact me directly, please send an email to [ekleinod@edgesoft.de](mailto:ekleinod@edgesoft.de) . Please start your email subject with [changes].

README: The changes-package allows the user to manually markup changes of text, such as additions, deletions, or replacements. Changed text is shown in a different color; deleted text is striked out. The package allows free definition of additional authors and their associated color. It also allows you to change the markup of changes, authors, or annotations.

## 2 Using the *changes*-package

In this section a typical use case of the *changes*-package is described. You can find the detailed description of the package options and new commands in [section 4](#).

We start with the text you want to change. You want to markup the changes for each author individually. Such a change markup is well-known in WYSIWYG text processors such as *LibreOffice*, *OpenOffice*, or *Word*.

The *changes*-package was developed in order to support such change markup. The package provides commands for defining authors, and for marking text as added, deleted, or replaced. In order to use the package, you have to follow these steps:

1. use *changes*-package
2. define authors
3. markup text changes
4. typeset the document with  $\text{\LaTeX}$
5. output list of changes
6. remove markup

### use *changes*-package

In order to activate change management, use the *changes*-package as follows:

```
\usepackage{changes}
```

resp.

```
\usepackage[<options>]{changes}
```

You can use the options for defining the layout of the change markup. You can change the layout after using the *changes*-package as well.

For detailed information please refer to [section 4.1](#) and [section 4.4](#).

### **define authors**

The *changes*-package provides a default anonymous author. If you want to track your changes per author, you have to define the needed authors as follows:

```
\definechangesauthor[<options>]{id}
```

Every author is uniquely identified through its his or her id. You can give every author an optional name and/or color.

For detailed information please refer to [section 4.3](#).

### **markup text changes**

Now everything is set to markup the changed text. Please use the following commands according to your change:

for newly added text:

```
\added[<id>][<remark>]{text}
```

for deleted text:

```
\deleted[<id>][<remark>]{text}
```

for replaced text:

```
\replaced[<id>][<remark>]{text}
```

Stating the author's id and/or a remark is optional.

For detailed information please refer to [section 4.2](#).

### **typeset the document with L<sup>A</sup>T<sub>E</sub>X**

After marking your changes in the text you are able to display them in the generated document by processing it as usual with L<sup>A</sup>T<sub>E</sub>X. By processing your document the changed text is layouted as you stated by the corresponding options and/or special commands.

### **output list of changes**

You can print a list of changes using:

```
\listofchanges
```

The list is meant to be the analogon to the list of tables, or the list of figures. It provides a quick overview of the number and kind of changes of every author.

By running  $\TeX$  the data of the list is written into an auxiliary file. This data is used in the next  $\TeX$  run for typesetting the list of changes. Therefore, two  $\TeX$  runs are needed after every change in order to typeset an up-to-date list of changes.

### **remove markup**

Often you want to remove the change markup after acknowledging or rejecting the changes. You can suppress the output of changes with:

```
\usepackage[final]{changes}
```

In order to remove the markup from the  $\TeX$  source code you can use a script from Silvano Chiaradonna. You find the script in the directory:

```
<texpath>/scripts/changes/
```

The script removes all markups. It is not possible to select the markup to remove.

## **3 Limitations and possible enhancements**

The *changes*-package was carefully programmed and tested. Yet there exists the possibility of errors in the package, problems in the usage, or missing functions you would like to have. In that case, please go to

<http://changes.sourceforge.net/>

There you can report errors, ask for help in the forum, or give advice to other users. You can view the source code, and change it according to your needs. I will try to include your changes in the maintained package. If you are a registered *sourceforge* user you can be a co-author of the *changes*-package.

You can write me an email too, please send it to [ekleinod@edgesoft.de](mailto:ekleinod@edgesoft.de). In that case, please start your email subject with [changes].

Change markup of texts works well, it is possible to markup whole paragraphs. You cannot markup more than one paragraph at a time. You cannot markup figures or tables as well.

There is a problem of typesetting footnotes in special environments, such as tables or tabblings. Since footnotes are the default markup of remarks, this would be a problem. You can solve this problem by defining another annotation of remarks.

There are several possibilities of enhancing the *changes*-package. I will describe but a few here, I will not implement them due to time and/or skill lacks. You can have a look at the more complete list of enhancements on the *sourceforge* page.

- selecting of acknowledged and rejected texts; deletion of the corresponding markup
- markup of more than one paragraph
- markup of figures and tables
- automatic markup based on diff information (with regard to the limitations, such as markup of paragraphs, figures etc.)
- translation of language dependent texts and the user documentation in other languages

## 4 User interface of the *changes*-package

This section describes the user interface of the *changes*-package, i.e. all options and commands of the package. Every option resp. new command is described. If you want to see the options and commands in action, please refer to the examples in

`<texpath>/doc/latex/changes/examples/`

The example files are named with the used option resp. command.

A preliminary remark regarding typesetting of replaced text: replaced text is always typeset as follows: `<new text><old text>`. Thus, there is no possibility to influence the output of replaced text directly, but via changing the output of added resp. deleted text.

### 4.1 Package Options

#### 4.1.1 draft

The `draft`-option enables markup of changes. The list of changes is available via `\listofchanges`. This option is the default option, if no other option is selected.

The *changes* package reuses the declaration of `draft` in `\documentclass`. The local declaration of `final` overrules the declaration of `draft` in `\documentclass`.

`\usepackage[draft]{changes} \equiv \usepackage{changes}`



### 4.1.2 final

The `final`-option disables markup of changes, only the correct text will be shown. The list of changes is disabled, too.

The `changes` package reuses the declaration of `final` in `\documentclass`. The local declaration of `draft` overrules the declaration of `final` in `\documentclass`.

```
\usepackage[final]{changes}
```

### 4.1.3 markup

The `markup` option chooses a predefined visual markup of changed text. The default markup is chosen if no explicit markup is given. The markup chosen with `markup` can be overwritten with the more special markup options `addedmarkup` and/or `deletedmarkup`.

The following values are allowed:

**default** colored markup of added text, striked out for deleted text (default markup)

**underlined** underlined for added text, striked out for deleted text

**bfit** bold added text, italic deleted text

**nocolor** no colored markup, underlined for added text, striked out for deleted text

*Call*

```
\usepackage[markup=markup]{changes}
```

*Examples*

```
\usepackage[markup=default]{changes} ≅ \usepackage{changes}
```

```
\usepackage[markup=underlined]{changes}
```

```
\usepackage[markup=bfit]{changes}
```

```
\usepackage[markup=nocolor]{changes}
```

### 4.1.4 addedmarkup, deletedmarkup

The `addedmarkup` option chooses a predefined visual markup of added text. The `deletedmarkup` option chooses a predefined visual markup of deleted text respectively. The default markup is chosen if no explicit markup is given. The options `addedmarkup` and `deletedmarkup` overwrite the markup chosen with `markup`.

The following values are allowed:

**none** no markup – example (default markup for added text)

**uline** underlined text – example

**uuline** double underlined text – example  
**uwave** wavy underlined text – example  
**dashuline** dashed underlined text – example  
**dotuline** dotted underlined text – example  
**sout** striked out text – ~~example~~ (default markup for deleted text)  
**xout** crossed out text – ~~example~~  
**bf** bold text – **example**  
**it** italic text – *example*  
**sl** slanted text – *example*  
**em** emphasized text – *example*

*Call*

```
\usepackage[addedmarkup=markup]{changes}
```

*Examples*

```
\usepackage[addedmarkup=none]{changes} ≅ \usepackage{changes}  
\usepackage[addedmarkup=uuline]{changes}
```

*Call*

```
\usepackage[deletedmarkup=markup]{changes}
```

*Examples*

```
\usepackage[deletedmarkup=sout]{changes} ≅ \usepackage{changes}  
\usepackage[deletedmarkup=xout]{changes}  
\usepackage[deletedmarkup=uwave]{changes}
```

#### 4.1.5 authormarkup

The `authormarkup` option chooses a predefined visual markup of the author's identification. The default markup is chosen if no explicit markup is given.

The following values are allowed:

**superscript** superscripted text –  $\text{text}^{\text{author}}$  (default markup)  
**subscript** subscripted text –  $\text{text}_{\text{author}}$   
**brackets** text in brackets –  $\text{text}(\text{author})$   
**footnote** text in footnote –  $\text{text}^1$

*Call*

```
\usepackage[authormarkup=markup]{changes}
```

*Examples*

```
\usepackage[authormarkup=superscript]{changes} ≅ \usepackage{changes}  
\usepackage[authormarkup=subscript]{changes}  
\usepackage[authormarkup=brackets]{changes}  
\usepackage[authormarkup=footnote]{changes}
```

---

<sup>1</sup>author

#### 4.1.6 authormarkupposition

The `authormarkupposition` option chooses the position of the author's identification. The default value is chosen if no explicit markup is given.

The following values are allowed:

**right** right of the text –  $\text{text}^{\text{example}}$  (default value)

**left** left of the text –  $^{\text{example}}\text{text}$

*Call*

```
\usepackage[authormarkupposition=<markup>]{changes}
```

*Examples*

```
\usepackage[authormarkupposition=right]{changes} \cong \usepackage{changes}
```

```
\usepackage[authormarkupposition=left]{changes}
```

#### 4.1.7 authormarkuptext

The `authormarkuptext` option chooses the text that is used for the author's identification. The default value is chosen if no explicit markup is given.

The following values are allowed:

**id** author's id –  $\text{text}^{\text{id}}$  (default value)

**name** author's name –  $\text{text}^{\text{authorname}}$

*Call*

```
\usepackage[authormarkuptext=<markup>]{changes}
```

*Examples*

```
\usepackage[authormarkuptext=id]{changes} \cong \usepackage{changes}
```

```
\usepackage[authormarkuptext=name]{changes}
```

#### 4.1.8 ulem

All options for the *ulem* package can be specified as parameters of the `ulem`-option. Two or more options have to be embraced in curly brackets.

*Call*

```
\usepackage[ulem=<options>]{changes}
```

*Examples*

```
\usepackage[ulem=normalem]{changes}
```

```
\usepackage[ulem={normalem,normalfb}]{changes}
```

### 4.1.9 xcolor

All options for the *xcolor* package can be specified as parameters of the `xcolor`-option. Two or more option have to be embraced in curly brackets.

*Call*

```
\usepackage[xcolor=<options>]{changes}
```

*Examples*

```
\usepackage[xcolor=dvipdf]{changes}
```

```
\usepackage[xcolor={dvipdf,gray}]{changes}
```

## 4.2 Change management

### 4.2.1 \added

`\added`

The command `\added` marks new text. The new text is the mandatory argument for the command, thus it is written in curly braces. There are two optional arguments: `author-id` and `remark`. The `author-id` has to be defined using `\definechangesauthor`. Use an empty author for an anonymous remark.

*Call*

```
\added[<author's id>][<remark>]{<new text>}
```

*Examples*

This is `\added[EK]{new}` text.

This is `newEK` text.

This is `\added[EK][has to be in it]{new}` text.

This is `newEK(has to be in it)` text.

This is `\added[][anonymous]{new}` text.

This is `new(anonymous)` text.

### 4.2.2 \deleted

`\deleted`

The command `\deleted` marks deleted text. For arguments see `\added`.

*Call*

```
\deleted[<author's id>][<remark>]{<deleted text>}
```

*Examples*

This is `\deleted[][obsolete]{bad}` text.

This is `bad(obsolete)` text.

### 4.2.3 `\replaced`

`\replaced`

The command `\replaced` marks replaced text. Mandatory arguments are the new text and the old text. For optional arguments see `\added`.

*Call*

```
\replaced[author's id][remark]{new text}{old text}
```

*Examples*

This is `\replaced[EK]{nice}{bad}` text.

This is nicebad<sup>EK</sup> text.

### 4.2.4 `\listofchanges`

`\listofchanges`

The command `\listofchanges` outputs a list of changes. The first  $\TeX$ -run creates an auxiliary file, the second run uses the data of this file. Therefore you need two  $\TeX$ -runs for an up-to-date list of changes.

*Call*

```
\listofchanges
```

## 4.3 Author management

### 4.3.1 `\definechangesauthor`

`\definechangesauthor`

The command `\definechangesauthor` defines a new author for changes. You have to define a unique author's id, special characters or spaces are not allowed within the author's id. You may define a corresponding color and the author's name. If you do not define a color, black is used. The author's name is used in the list of changes and in the markup, if you set the corresponding option.

*Call*

```
\definechangesauthor[name={author's name}, color={color}]{author's id}
```

*Examples*

```
\definechangesauthor{EK}
```

```
\definechangesauthor[color=orange]{EK}
```

```
\definechangesauthor[name={Ekkart Kleinod}]{EK}
```

```
\definechangesauthor[name={Ekkart Kleinod}, color=orange]{EK}
```

## 4.4 Adaptation of the output

### 4.4.1 `\setaddedmarkup`

`\setaddedmarkup`

The command `\setaddedmarkup` defines the layout of added text. The default markup is colored text, or the markup set with the option `markup resp. addedmarkup`.

Values for definition: any  $\TeX$ -commands, added text can be used with "#1".

*Call*

```
\setaddedmarkup{<definition>}
```

*Examples*

```
\setaddedmarkup{\emph{#1}}
\setaddedmarkup{+++ : #1}
```

### 4.4.2 `\setdeletedmarkup`

`\setdeletedmarkup`

The command `\setdeletedmarkup` defines the layout of deleted text. The default markup is striked-out, or the markup set with the option `markup resp. deletedmarkup`.

Values for definition: any  $\TeX$ -commands, deleted text can be used with "#1".

*Call*

```
\setdeletedmarkup{<definition>}
```

*Examples*

```
\setdeletedmarkup{\emph{#1}}
\setdeletedmarkup{-- : #1}
```

### 4.4.3 `\setauthormarkup`

`\setauthormarkup`

The command `\setauthormarkup` defines the layout of the author's markup in the text. The default markup is a superscripted author's text.

Values for definition: any  $\TeX$ -commands, author's text can be used with "#1".

*Call*

```
\setauthormarkup{<definition>}
```

*Examples*

```
\setauthormarkup{(#1)}
```

```
\setauthormarkup{(#1)~---~}
```

```
\setauthormarkup{\marginpar{#1}}
```

**4.4.4 \setauthormarkupposition**

\setauthormarkupposition

The command `\setauthormarkupposition` defines the position of the author's markup relative to the changed text. The default position is right of the changed text.

Possible values: *left* == left of the changes; all other values: right

*Call*

```
\setauthormarkupposition{<position>}
```

*Examples*

```
\setauthormarkupposition{left}
```

**4.4.5 \setauthormarkuptext**

\setauthormarkuptext

The command `\setauthormarkuptext` defines the text for the author's markup. The default markup is the author's id.

Possible values: *name* == author's name; all other values: author's id

*Call*

```
\setauthormarkuptext{<text>}
```

*Examples*

```
\setauthormarkuptext{name}
```

#### 4.4.6 `\setremarkmarkup`

`\setremarkmarkup`

The command `\setremarkmarkup` defines the layout of remarks in the text. The default markup typesets the remark in a footnote.

Values for definition: any  $\TeX$ -commands, author's id can be used with "#1", the remark can be shown using "#2". Using the author's id you can use the author's color with `Changes@Color#1`.

*Call*

```
\setremarkmarkup{<definition>}
```

*Examples*

```
\setremarkmarkup{#2 -- #1}
```

```
\setremarkmarkup{\footnote{#1:\textcolor{Changes@Color#1}{#2}}}
```

#### 4.4.7 `\setlocextension`

`\setlocextension`

The command `\setlocextension` sets the extension of the auxiliary file for the list of changes (loc-file<sup>2</sup>). The default extension is "loc". In the example stated below, the loc-file for "foo.tex" would be named "foo.changes" instead of the default name "foo.loc".

*Call*

```
\setlocextension{<extension>}
```

*Examples*

```
\setlocextension{changes}
```

### 4.5 Other new commands

#### 4.5.1 `\textsubscript`

`\textsubscript`

$\TeX$  provides the command `\textsuperscript`, but not its counterpart `\textsubscript`. If the command is not defined yet, it will be provided by the *changes*-package. If the command is defined yet, it will not be changed.

---

<sup>2</sup> "loc" stands for "list of changes".



*Call*

`\textsubscript{<text>}`

*Examples*

This is a `\textsubscript{subscript}` text.

This is a <sub>subscript</sub> text.

## 4.6 Used packages

The *changes*-package uses already existing packages for its functions. You will find detailed description of the packages in their distributions.

The following packages are required always and have to be installed for the *changes*-package:

**xifthen** provides an enhanced `\if`-command as well as a while-loop

**xkeyval** provides options with key-value-pairs

The following packages are required sometimes and have to be installed if used by the corresponding option:

**pdfcolmk** loaded if colored text is used for markup (default markup); solves the problem of colored text and page breaks (with pdf<sub>l</sub>atex)

**ulem** loaded if text has to be striked or exed out (default markup)

**xcolor** loaded if colored text is used for markup (default markup)

## 5 Authors

Several authors contributed to the *changes*. The authors are (in alphabetical order):

- Chiaradonna, Silvano
- Giovannini, Daniele
- Kleinod, Ekkart
- Wölfel, Philipp
- Wolter, Steve

## 6 Versions

### Version 0.6.0

Date: 2011/0?/??

- Italian translations of captions by Daniele Giovannini

- redefined user interface for setting options and definitions of markup and authors
- restructuring and code improvement
- improved documentation including typical use case
- example files for all options and commands
- remarks are by default not colored anymore

#### **Version 0.5.4**

Date: 2011/04/25

- extraction of user documentation in separate file
- default language changed to English
- new script for removal of *changes* commands by Silvano Chiaradonna

#### **Version 0.5.3**

Date: 2010/11/22

- document options of `\documentclass` are used too (suggestion and code of Steve Wolter)

#### **Version 0.5.2**

Date: 2007/10/10

- package options for *ulem* and *xcolor* are passed to the packages

#### **Version 0.5.1**

Date: 2007/08/27

- deleted text is striked out again using package *ulem*, greying didn't work

#### **Version 0.5**

Date: 2007/08/26

- no usage of package *arrayjob* anymore, thus no errors using package *array*
- switch to UTF-8-encoding
- no usage of package *soul* anymore, thus no errors using UTF-8-encoding
- markup for deleted text changed to gray background, because there's no possibility to conveniently strikeout UTF-8-text
- new optional argument for author's name
- colored list of changes
- changed loc file format
- improved English documentation

## Version 0.4

Date: 2007/01/24

- included *pdfcolmk* to solve problem with colored text and page breaks
- extended `\setremarkmarkup` with author's id for using color in remarks
- remarks are by default colored now
- first version uploaded to CTAN

## Version 0.3

Date: 2007/01/22

- English user-documentation
- replaced command `\changed` with `\replaced`
- improved final-option: no additional space

## Version 0.2

Date: 2007/01/17

- defined loc-names when missing *babel*-package
- new commands `\setauthormarkup`, `\setlocextension`, `\setremarkmarkup`
- generated examples
- inserted LPPL

## Bugfixes

- fixed wrong *ifthen* package placement
- fixed error in loc, always showing “added”
- fixed authormarkup (`\if-condition` not bugfree)

## Version 0.1

Date: 2007/01/16

- initial version
- commands `\added`, `\deleted`, and `\changed`

# 7 Distribution, Copyright, License

Copyright 2007-2012 Ekkart Kleinod ([ekleinod@edgesoft.de](mailto:ekleinod@edgesoft.de))

This work may be distributed and/or modified under the conditions of the  $\text{\LaTeX}$  Project Public License, either version 1.3 of this license or any later version. The latest version of this license is in <http://www.latex-project.org/lppl.txt> and version 1.3 or later is part of all distributions of  $\text{\LaTeX}$  version 2005/12/01 or later.

This work has the LPPL maintenance status “maintained”. The current maintainer of this work is Ekkart Kleinod.

This work consists of the files

```
source/latex/changes/changes.drv
source/latex/changes/changes.dtx
source/latex/changes/changes.ins
source/latex/changes/examples.dtx
source/latex/changes/README
source/latex/changes/userdoc/*.tex
scripts/changes/delcmdchanges.bash
```

and the derived files

```
doc/latex/changes/changes.english.full.pdf
doc/latex/changes/changes.english.short.pdf
doc/latex/changes/changes.ngerman.full.pdf
doc/latex/changes/changes.ngerman.short.pdf
doc/latex/changes/examples/changes.example.*.tex
doc/latex/changes/examples/changes.example.*.pdf
tex/latex/changes/changes.sty
```

## 8 The documented sourcecode

The sourcecode is documented in English only. This is intended, please do not provide translations for the text below, just corrections or improvements.

```
1 ⟨*changes⟩
```

### 8.1 Package information and options

Set needed  $\TeX$ -format to  $\TeX_{2\epsilon}$ , provide name, date, version. Type some information to the console.

```
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{changes}
4 [2011/10/19 v0.6.0 changes-Paket]
5 \typeout{*** changes-Paket 2011/10/19 v0.6.0 ***}
```

Package *xkeyval* provides options with key-value-pairs.

```
6 \RequirePackage{xkeyval}
```

Package *xifthen* provides improved if as well as a while-loop.

```
7 \RequirePackage{xifthen}
```

### 8.1.1 Package options

Option *draft*, *default* is true.

```
8 \newboolean{Changes@optiondraft}
9 \setboolean{Changes@optiondraft}{true}
10 \DeclareOptionX{draft}{
11 \setboolean{Changes@optiondraft}{true}
12 \typeout{changes-option '\CurrentOption'}
13 }
```

Option *final*, sets *draft* to false.

```
14 \DeclareOptionX{final}{
15 \setboolean{Changes@optiondraft}{false}
16 \typeout{changes-option '\CurrentOption'}
17 }
```

Declare storage for markup options, they are set by the markup option but can be changed with the more special options, therefore they have to be declared at this place.

```
18 \newcommand{\Changes@optionaddedmarkup}{none}
19 \newcommand{\Changes@optiondeletedmarkup}{sout}
```

Option *markup*, sets markup options accordingly.

```
20 \newcommand{\Changes@optionmarkup}{default}
21 \DeclareOptionX{markup}{
22 \ifthenelse{\equal{\@empty}{#1}}{
23 {}
24 {
25 \ifthenelse{
26 \equal{#1}{default}\or
27 \equal{#1}{underlined}\or
28 \equal{#1}{bfit}\or
29 \equal{#1}{nocolor}
30 }
31 {\renewcommand{\Changes@optionmarkup}{#1}}
32 {\PackageWarning{changes}{markup '#1' unknown, using '\Changes@optionmarkup'}}
33 }
```

```
34 \ifthenelse{\equal{\Changes@optionmarkup}{default}}
35 {
36 \renewcommand{\Changes@optionaddedmarkup}{none}
37 \renewcommand{\Changes@optiondeletedmarkup}{sout}
38 }
39 {}
40 \ifthenelse{\equal{\Changes@optionmarkup}{underlined}}
41 {
42 \renewcommand{\Changes@optionaddedmarkup}{uline}
43 \renewcommand{\Changes@optiondeletedmarkup}{sout}
44 }
45 {}
46 \ifthenelse{\equal{\Changes@optionmarkup}{bfit}}
47 {
48 \renewcommand{\Changes@optionaddedmarkup}{bf}
49 \renewcommand{\Changes@optiondeletedmarkup}{it}
50 }
51 {}
52 \ifthenelse{\equal{\Changes@optionmarkup}{nocolor}}
53 {
54 \renewcommand{\Changes@optionaddedmarkup}{uline}
55 \renewcommand{\Changes@optiondeletedmarkup}{sout}
56 }
57 {}
58 \typeout{changes-option 'markup=\Changes@optionmarkup'}
59 }
```

Option addedmarkup, stored or set to default value “none”.

```
60 \DeclareOptionX{addedmarkup}{
61 \ifthenelse{\equal{\@empty}{#1}}
62 {}
63 {
64 \ifthenelse{
65 \equal{#1}{none}\or
66 \equal{#1}{uline}\or
67 \equal{#1}{uuline}\or
68 \equal{#1}{uwave}\or
69 \equal{#1}{dashuline}\or
70 \equal{#1}{dotuline}\or
71 \equal{#1}{sout}\or
72 \equal{#1}{xout}\or
73 \equal{#1}{bf}\or
74 \equal{#1}{it}\or
75 \equal{#1}{sl}\or
76 \equal{#1}{em}
77 }
78 {\renewcommand{\Changes@optionaddedmarkup}{#1}}
79 {\PackageWarning{changes}{addedmarkup '#1' unknown, using '\Changes@optionaddedmarkup'}}
80 }
```

```
81 \typeout{changes-option 'addedmarkup=\Changes@optionaddedmarkup'}
82 }
```

Option `deletedmarkup`, stored or set to default value “`striked`”.

```
83 \DeclareOptionX{deletedmarkup}{
84 \ifthenelse{\equal{\@empty}{#1}}
85 {}
86 {
87 \ifthenelse{
88 \equal{#1}{none}\or
89 \equal{#1}{uline}\or
90 \equal{#1}{uuline}\or
91 \equal{#1}{uwave}\or
92 \equal{#1}{dashuline}\or
93 \equal{#1}{dotuline}\or
94 \equal{#1}{sout}\or
95 \equal{#1}{xout}\or
96 \equal{#1}{bf}\or
97 \equal{#1}{it}\or
98 \equal{#1}{sl}\or
99 \equal{#1}{em}
100 }
101 {\renewcommand{\Changes@optiondeletedmarkup}{#1}}
102 {\PackageWarning{changes}{deletedmarkup '#1' unknown, using '\Changes@optiondeletedmarkup'}}
103 }
104 \typeout{changes-option 'deletedmarkup=\Changes@optiondeletedmarkup'}
105 }
```

Declare storage for `authormarkup` option and store option value or set to default value “`superscript`”.

```
106 \newcommand{\Changes@optionauthormarkup}{superscript}
107 \DeclareOptionX{authormarkup}{
108 \ifthenelse{\equal{\@empty}{#1}}
109 {}
110 {
111 \ifthenelse{
112 \equal{#1}{superscript}\or
113 \equal{#1}{subscript}\or
114 \equal{#1}{brackets}\or
115 \equal{#1}{footnote}
116 }
117 {\renewcommand{\Changes@optionauthormarkup}{#1}}
118 {\PackageWarning{changes}{authormarkup '#1' unknown, using '\Changes@optionauthormarkup'}}
119 }
120 \typeout{changes-option 'authormarkup=\Changes@optionauthormarkup'}
121 }
```

Declare storage for `authormarkupposition` option and store option value or set to default value “right”.

```
122 \newcommand{\Changes@optionauthormarkupposition}{right}
123 \DeclareOptionX{authormarkupposition}{
124 \ifthenelse{\equal{\@empty}{#1}}
125 {}
126 {
127 \ifthenelse{
128 \equal{#1}{right}\or
129 \equal{#1}{left}
130 }
131 {\renewcommand{\Changes@optionauthormarkupposition}{#1}}
132 {\PackageWarning{changes}{authormarkupposition '#1' unknown, using '\Changes@optionauthorma
133 }
134 \typeout{changes-option 'authormarkupposition=\Changes@optionauthormarkupposition'}
135 }
```

Declare storage for `authormarkuptext` option and store option value or set to default value “id”.

```
136 \newcommand{\Changes@optionauthormarkuptext}{id}
137 \DeclareOptionX{authormarkuptext}{
138 \ifthenelse{\equal{\@empty}{#1}}
139 {}
140 {
141 \ifthenelse{
142 \equal{#1}{id}\or
143 \equal{#1}{name}
144 }
145 {\renewcommand{\Changes@optionauthormarkuptext}{#1}}
146 {\PackageWarning{changes}{authormarkuptext '#1' unknown, using '\Changes@optionauthormarkup
147 }
148 \typeout{changes-option 'authormarkuptext=\Changes@optionauthormarkuptext'}
149 }
```

Options for package `ulem` are directly passed to the package.

```
150 \DeclareOptionX{ulem}{
151 \typeout{ulem-option '#1', passed to package ulem}
152 \PassOptionsToPackage{#1}{ulem}
153 }
```

Options for package `xcolor` are directly passed to the package.

```
154 \DeclareOptionX{xcolor}{
155 \typeout{xcolor-option '#1', passed to package xcolor}
156 \PassOptionsToPackage{#1}{xcolor}
157 }
```



Unknown options generate a package warning.

```
158 \DeclareOptionX*{
159 \PackageWarning{changes}{Unknown option '\CurrentOption'}
160 }
```

### 8.1.2 Command options

All options for commands (e.g. `\definechangesauthor`) have to be declared before option processing.

Declare available options of the command, define value storage.

```
161 \DeclareOptionX<Changes@definechangesauthor>{name}{\def\Changes@definechangesauthor@name{#1}}
162 \DeclareOptionX<Changes@definechangesauthor>{color}{\def\Changes@definechangesauthor@color{#1}}
```

Set the default values of the options.

```
163 \presetkeys{Changes@definechangesauthor}{
164 name=\@empty,
165 color=black
166 }{}
```

### 8.1.3 Option processing

Process the options.

```
167 \ProcessOptionsX*\relax
```

## 8.2 Packages

Package *xcolor* provides colored text. Package *pdfcolmk* solves the problem of colored text and page breaks (has to be loaded after *xcolor*).

```
168 \newboolean{Changes@colored}
169 \setboolean{Changes@colored}{true}
170 \ifthenelse{\equal{\Changes@optionmarkup}{nocolor}}{
171 {\setboolean{Changes@colored}{false}}
172 }{
173 \ifthenelse{\boolean{Changes@colored}}{
174 {
175 \RequirePackage{xcolor}
176 \RequirePackage{pdfcolmk}
177 }
178 }
```

Package `ulem` provides commands for striking out text.

```
179 \ifthenelse{
180 \equal{\Changes@optionaddedmarkup}{uline}\or
181 \equal{\Changes@optionaddedmarkup}{uuline}\or
182 \equal{\Changes@optionaddedmarkup}{uwave}\or
183 \equal{\Changes@optionaddedmarkup}{dashuline}\or
184 \equal{\Changes@optionaddedmarkup}{dotuline}\or
185 \equal{\Changes@optionaddedmarkup}{sout}\or
186 \equal{\Changes@optionaddedmarkup}{xout}\or
187 \equal{\Changes@optiondeletedmarkup}{uline}\or
188 \equal{\Changes@optiondeletedmarkup}{uuline}\or
189 \equal{\Changes@optiondeletedmarkup}{uwave}\or
190 \equal{\Changes@optiondeletedmarkup}{dashuline}\or
191 \equal{\Changes@optiondeletedmarkup}{dotuline}\or
192 \equal{\Changes@optiondeletedmarkup}{sout}\or
193 \equal{\Changes@optiondeletedmarkup}{xout}
194 }
195 {\RequirePackage[normalem,normalbf]{ulem}}
196 {}}
```

### 8.3 Language dependent texts

Declaration of language dependent names and identifiers. The check for `\addto` is a check for the `babel` package. If the `babel` package is not loaded, the default language is English, in order to use another language, the user has to redefine the variables.

```
197 \ifthenelse{\isundefined{\addto}}
198 {
199 \def\listchangesname{Changes}
200 \def\changesaddname{Added}
201 \def\changesdeletename{Deleted}
202 \def\changesreplacename{Replaced}
203 \def\changesauthorname{Author}
204 \def\changesanonymousname{anonymous}
205 \def\changesnoloc{List of changes is available after the next \LaTeX\ run.}
206 }{
207 \addto\captionsngerman{\def\listchangesname{"Anderungen}}
208 \addto\captionsngerman{\def\changesaddname{Eingef\ "ugt}}
209 \addto\captionsngerman{\def\changesdeletename{Gel\ "oscht}}
210 \addto\captionsngerman{\def\changesreplacename{Ersetzt}}
211 \addto\captionsngerman{\def\changesauthorname{Autor}}
212 \addto\captionsngerman{\def\changesanonymousname{Anonym}}
213 \addto\captionsngerman{\def\changesnoloc{"Anderungsliste nach dem n\ "achsten \LaTeX-Lauf v
214
215 \addto\captionsgerman{\def\listchangesname{"Anderungen}}
216 \addto\captionsgerman{\def\changesaddname{Eingef\ "ugt}}}
```

---

```

217 \addto\captionsgerman{\def\changesdeletename{Gel\ "oscht}}
218 \addto\captionsgerman{\def\changesreplacename{Ersetzt}}
219 \addto\captionsgerman{\def\changesauthorname{Autor}}
220 \addto\captionsgerman{\def\changesanonymousname{Anonym}}
221 \addto\captionsgerman{\def\changesnoloc{"Anderungsliste nach dem n\ "achsten \LaTeX-Lauf verf
222
223 \addto\captionsenglish{\def\listchangesname{Changes}}
224 \addto\captionsenglish{\def\changesaddname{Added}}
225 \addto\captionsenglish{\def\changesdeletename{Deleted}}
226 \addto\captionsenglish{\def\changesreplacename{Replaced}}
227 \addto\captionsenglish{\def\changesauthorname{Author}}
228 \addto\captionsenglish{\def\changesanonymousname{anonymous}}
229 \addto\captionsenglish{\def\changesnoloc{List of changes is available after the next \LaTeX\ r
230
231 \addto\captionssitalian{\def\listchangesname{Modifiche}}
232 \addto\captionssitalian{\def\changesaddname{Aggiunte}}
233 \addto\captionssitalian{\def\changesdeletename{Cancellazioni}}
234 \addto\captionssitalian{\def\changesreplacename{Sostituzioni}}
235 \addto\captionssitalian{\def\changesauthorname{Autore}}
236 \addto\captionssitalian{\def\changesanonymousname{anonimo}}
237 \addto\captionssitalian{\def\changesnoloc{La lista delle modifiche sar\ 'a disponibile alla pro
238 }

```

## 8.4 File extension

`Changes@extension` Store file extension in variable, set default to loc.

```
239 \newcommand{\Changes@extension}{loc}
```

`\setlocextension` Set a new file extension. Argument: new extension.

```

240 \newcommand{\setlocextension}[1]{
241 \renewcommand{\Changes@extension}{#1}
242 }

```

## 8.5 Authors

### 8.5.1 Author management

Author counter.

```

243 \newcounter{Changes@AuthorCount}
244 \setcounter{Changes@AuthorCount}{0}
245 \newcounter{Changes@iAuthor}

```

`definechangesauthor` Define a new author. Mandatory argument: author's id. Optional arguments (key-value): author's name (default: empty) and author's color (default: black).

Store id, name and color using named variables. Define counter and color per author.

```
246 \newcommand*\definechangesauthor[2][]{%
```

Call *setkeys* in order to evaluate the key-value-options and fill the value storage.

```
247 \setkeys{Changes@definechangesauthor}{#1}
```

Increment author counter, later needed for *while* loop of authors.

```
248 \stepcounter{Changes@AuthorCount}
```

Store the id in a name with the given counter/index. All other storage refers to the id.

```
249 \@namedef{Changes@AuthorID\theChanges@AuthorCount}{#2}
```

Store the author's definition in according variables/colors, create change counters.

```
250 \expandafter
251 \let\csname Changes@AuthorName#2\endcsname=\Changes@definechangesauthor@name
252 \newcounter{Changes@AddCount#2}
253 \newcounter{Changes@DeleteCount#2}
254 \newcounter{Changes@ReplaceCount#2}
255 \ifthenelse{\boolean{Changes@colored}}{
256 {
257 \expandafter
258 \let\csname Changes@AuthorColor#2\endcsname=\Changes@definechangesauthor@color
259 \colorlet{Changes@Color#2}{\@nameuse{Changes@AuthorColor#2}}
260 }
261 {}
262 }
```

Define default-author (anonymous) with empty id and blue color.

```
263 \definechangesauthor[color=blue]{\@empty}
```

## 8.5.2 Author markup

`\changes@Markup@Author` Store markup for authors.

```
264 \newcommand{\Changes@Markup@Author}[1]{%
265 \ifthenelse{\equal{\Changes@optionauthormarkup}{superscript}}{\textsuperscript{#1}}{%
266 \ifthenelse{\equal{\Changes@optionauthormarkup}{subscript}}{\textsubscript{#1}}{%
267 \ifthenelse{\equal{\Changes@optionauthormarkup}{brackets}}{(#1)}{%
268 \ifthenelse{\equal{\Changes@optionauthormarkup}{footnote}}{\footnote{#1}}{%
269 }
```

`\setauthormarkup` Set markup for authors.

```
270 \newcommand{\setauthormarkup}[1]{
271 \renewcommand{\Changes@Markup@Author}[1]{#1}
272 }
```

`\textsubscript` Define the command `\textsubscript` in case the author markup subscript is used and the command `\textsubscript` is not defined yet. `\textsubscript` is the antagonist of `\textsuperscript` which is predefined in  $\text{\LaTeX}$ . The code is taken from  $\text{\LaTeX}$ -FAQ 8.5.17.

```
273 \ifthenelse{\isundefined{\textsubscript}}
274 {
275 \DeclareRobustCommand*\textsubscript[1]{\@textsubscript{\selectfont#1}}
276 \newcommand{\@textsubscript}[1]{\math@ensuremath_{\mbox{\fontsize\sf@size\z@#1}}}}
277 }
```

`\setauthormarkupposition` Set position for author markup text.

```
278 \newcommand{\setauthormarkupposition}[1]{
279 \renewcommand{\Changes@optionauthormarkupposition}{#1}
280 }
```

`\setauthormarkuptext` Set author markup text to be displayed.

```
281 \newcommand{\setauthormarkuptext}[1]{
282 \renewcommand{\Changes@optionauthormarkuptext}{#1}
283 }
```

`\Changes@Remark` Markup of remarks. Default: in a footnote.

```
284 \newcommand{\Changes@Remark}[2]{%
285 \footnote{%
286 \ifthenelse{\not\equal{#1}{@empty}}{%
287 {#1: }%
288 }
```

```
289 #2%
290 }%
291 }
```

`\setremarkmarkup` Redefining the remark markup. Mandatory argument: markup definition.

```
292 \newcommand{\setremarkmarkup}[1]{%
293 \renewcommand{\Changes@Remark}[2]{#1}%
294 }
```

## 8.6 Change management commands

### 8.6.1 Text markup definition

Replaced text is always typeset as follows: `<added text><deleted text>`. Therefore no extra command for markup of replaced text is given.

`\Changes@Markup@Added` Store markup for added text.

```
295 \newcommand{\Changes@Markup@Added}[1]{%
296 \ifthenelse{\equal{\Changes@optionaddedmarkup}{none}}{#1}{}%
297 \ifthenelse{\equal{\Changes@optionaddedmarkup}{uline}}{\uline{#1}}{}%
298 \ifthenelse{\equal{\Changes@optionaddedmarkup}{uuline}}{\uuline{#1}}{}%
299 \ifthenelse{\equal{\Changes@optionaddedmarkup}{uwave}}{\uwave{#1}}{}%
300 \ifthenelse{\equal{\Changes@optionaddedmarkup}{dashuline}}{\dashuline{#1}}{}%
301 \ifthenelse{\equal{\Changes@optionaddedmarkup}{dotuline}}{\dotuline{#1}}{}%
302 \ifthenelse{\equal{\Changes@optionaddedmarkup}{sout}}{\sout{#1}}{}%
303 \ifthenelse{\equal{\Changes@optionaddedmarkup}{xout}}{\xout{#1}}{}%
304 \ifthenelse{\equal{\Changes@optionaddedmarkup}{bf}}{\textbf{#1}}{}%
305 \ifthenelse{\equal{\Changes@optionaddedmarkup}{it}}{\textit{#1}}{}%
306 \ifthenelse{\equal{\Changes@optionaddedmarkup}{sl}}{\textsl{#1}}{}%
307 \ifthenelse{\equal{\Changes@optionaddedmarkup}{em}}{\emph{#1}}{}%
308 }
```

`\setaddedmarkup` Set markup for added text.

```
309 \newcommand{\setaddedmarkup}[1]{
310 \renewcommand{\Changes@Markup@Added}[1]{#1}
311 }
```

`\Changes@Markup@Deleted` Store markup for deleted text.

```
312 \newcommand{\Changes@Markup@Deleted}[1]{%
313 \ifthenelse{\equal{\Changes@optiondeletedmarkup}{none}}{#1}{}%
314 \ifthenelse{\equal{\Changes@optiondeletedmarkup}{uline}}{\uline{#1}}{}%
315 \ifthenelse{\equal{\Changes@optiondeletedmarkup}{uuline}}{\uuline{#1}}{}%
```

```

316 \ifthenelse{\equal{\Changes@optiondeletedmarkup}{uwave}}{\uwave{#1}}{}%
317 \ifthenelse{\equal{\Changes@optiondeletedmarkup}{dashuline}}{\dashuline{#1}}{}%
318 \ifthenelse{\equal{\Changes@optiondeletedmarkup}{dotuline}}{\dotuline{#1}}{}%
319 \ifthenelse{\equal{\Changes@optiondeletedmarkup}{sout}}{\sout{#1}}{}%
320 \ifthenelse{\equal{\Changes@optiondeletedmarkup}{xout}}{\xout{#1}}{}%
321 \ifthenelse{\equal{\Changes@optiondeletedmarkup}{bf}}{\textbf{#1}}{}%
322 \ifthenelse{\equal{\Changes@optiondeletedmarkup}{it}}{\textit{#1}}{}%
323 \ifthenelse{\equal{\Changes@optiondeletedmarkup}{sl}}{\textsl{#1}}{}%
324 \ifthenelse{\equal{\Changes@optiondeletedmarkup}{em}}{\emph{#1}}{}%
325 }

```

`\setdeletedmarkup` Set markup for deleted text.

```

326 \newcommand{\setdeletedmarkup}[1]{
327 \renewcommand{\Changes@Markup@Deleted}[1]{#1}
328 }

```

## 8.6.2 Change management command definition

`\Changes@output` Output command for the changed text. This command has the following arguments:

1. changed text (including markup)
2. unchanged text
3. author's id
4. remark

```

329 \newcommand{\Changes@output}[4]{%

```

Output changed text if option draft is set, otherwise output unchanged text.

```

330 \ifthenelse{\boolean{Changes@optiondraft}}{%
331 {%

```

Save author text for output.

```

332 \ifthenelse{\equal{\Changes@optionauthormarkuptext}{id}}{%
333 {\@namedef{Changes@AuthorText}{#3}}%
334 }%
335 \ifthenelse{\equal{\Changes@optionauthormarkuptext}{name}}{%
336 {\@namedef{Changes@AuthorText}{\@nameuse{Changes@AuthorName#3}}}%
337 }%
338 {%

```

Change color, if colored text is used.

```

339 \ifthenelse{\boolean{Changes@colored}}{%
340 {\color{Changes@Color#3}}%
341 }%

```

Output author text if author's id is given and text should appear left of changes.

```
342 \ifthenelse{\equal{\Changes@optionauthormarkupposition}{left} \and \not\equal{#3}{\@empty}}
343 {\Changes@Markup@Author{\@nameuse{Changes@AuthorText}}}%
344 {}%
```

Output changed text.

```
345 {#1}%
```

Output author text if author's id is given and text should appear right of changes.

```
346 \ifthenelse{\equal{\Changes@optionauthormarkupposition}{right} \and \not\equal{#3}{\@empty}}
347 {\Changes@Markup@Author{\@nameuse{Changes@AuthorText}}}%
348 {}%
```

Output remark if a remark is given.

```
349 \ifthenelse{\not\equal{#4}{\@empty}}%
350 {\Changes@Remark{#3}{#4}}%
351 {}%
352 }%
353 }%
```

Output unchanged text (option final was set).

```
354 {#2}%
355 }
```

`\Changes@temp` Temporary variable for exchange of optional parameters between interlocked commands.

```
356 \newcommand{\Changes@temp}{\@empty}
```

`\added` The command formats text as new text. Defining a command with two optional parameters is rather complicated.

Mandatory argument: added text. Optional arguments: author's id, remark

```
357 \newcommand{\added}[1][\@empty]{%
358 \renewcommand{\Changes@temp}{#1}%
359 \Changes@added%
360 }
361 \newcommand{\Changes@added}[2][\@empty]{%
362 \Changes@output
363 {\Changes@Markup@Added{#2}}
364 {#2}
365 {\Changes@temp}
366 {#1}%
367 \stepcounter{Changes@AddCount}\Changes@temp}%
368 }
```



`\deleted` The command formats text as deleted text.

The definition of the empty text for unchanged text is taken from a tip from `de.comp.text.tex`. It solves the problem of additional space caused by an empty command.

Mandatory argument: deleted text. Optional arguments: author's id, remark

```
369 \newcommand{\deleted}[1][\@empty]{%
370 \renewcommand{\Changes@temp}{#1}%
371 \Changes@deleted%
372 }
373 \newcommand{\Changes@deleted}[2][\@empty]{%
374 \Changes@output
375 {\Changes@Markup@Deleted{#2}}
376 {\@bsphack \expandafter \@esphack}
377 {\Changes@temp}
378 {#1}%
379 \stepcounter{Changes@DeleteCount\Changes@temp}%
380 }
```

`\replaced` The command formats text as replaced text.

Mandatory arguments: new text and old text. Optional arguments: author's id, remark

```
381 \newcommand{\replaced}[1][\@empty]{%
382 \renewcommand{\Changes@temp}{#1}%
383 \Changes@replaced%
384 }
385 \newcommand{\Changes@replaced}[3][\@empty]{%
386 \Changes@output
387 {\Changes@Markup@Added{#2}}{\Changes@Markup@Deleted{#3}}
388 {#2}
389 {\Changes@temp}
390 {#1}%
391 \stepcounter{Changes@ReplaceCount\Changes@temp}%
392 }
```

## 8.7 List of changes

`\changes@chopline` Auxiliary command for reading the content of the loc-files. The content is read line by line. One line is parsed with this macro, the order of entries is: id, color, name, added, deleted, replaced. The contents have to be separated by a semicolon.

```
393 \def\changes@chopline#1;#2;#3;#4;#5;#6 \{\
394 \def\Changes@InID{#1}
395 \def\Changes@InColor{#2}
```

```
396 \def\Changes@InName{#3}
397 \def\Changes@InAdded{#4}
398 \def\Changes@InDeleted{#5}
399 \def\Changes@InReplaced{#6}
400 }
```

`\listofchanges` This command outputs the list of changes, separated by authors. The values are read from the loc-file, if it exists. If no loc-file exists, an according message is generated.

```
401 \newcommand{\listofchanges}{%
402 \ifthenelse{\boolean{Changes@optiondraft}}{
403 {
404 \section*{\listchangesname}
405 \IfFileExists{\jobname.\Changes@extension}
406 {
407 \newboolean{Changes@MoreLines}
408 \setboolean{Changes@MoreLines}{true}
409 \newread\Changes@InFile
410 \openin\Changes@InFile = \jobname.\Changes@extension
411 \whiledo{\boolean{Changes@MoreLines}}{
412 \read\Changes@InFile to \Changes@Line
413 \ifeof\Changes@InFile
414 \setboolean{Changes@MoreLines}{false}
415 \else
416 \expandafter\changes@chopline\Changes@Line\
417 \begin{tabbing}
418 mm\=mmmmmm\=kill
419 {
420 \ifthenelse{\boolean{Changes@colored}}{
421 {\color{\Changes@InColor}}
422 }{
423 \ifthenelse{\equal{\Changes@InID}{\@empty}}{
424 {\changesauthorname: \changesanonymousname}
425 {
426 \changesauthorname: \Changes@InID
427 \ifthenelse{\equal{\Changes@InName}{\@empty}}{
428 {}{
429 {(\Changes@InName)}
430 }
431 }\\
432 \>\changesaddname: \>\Changes@InAdded\\
433 \>\changesdeletename: \>\Changes@InDeleted\\
434 \>\changesreplacename: \>\Changes@InReplaced\\
435 \end{tabbing}
436 \fi
437 }
438 \closein\Changes@InFile
439 }{
```

```
440 \emph{\changesnoloc}
441 \PackageWarning{changes}{LaTeX rerun needed for list of changes}
442 }
443 {}
444 }
```

At the end of the document: write the list of changes in the loc-file, therefore open file, write values, close file. Changes are written as  $\LaTeX$ -formatted text, so they can simply be read via `\input`.

The order of entries is: id, color, name, added, deleted, replaced. The contents have to be separated by a semicolon.

```
445 \AtEndDocument{
446 \newwrite\Changes@OutFile
447 \immediate\openout\Changes@OutFile = \jobname.\Changes@extension
448 \setcounter{Changes@iAuthor}{0}
449 \whiledo{\value{Changes@iAuthor} < \value{Changes@AuthorCount}}{
450 \stepcounter{Changes@iAuthor}
451 \def\Changes@ID{\@nameuse{Changes@AuthorID}\theChanges@iAuthor}}
452 \immediate\write\Changes@OutFile{\Changes@ID;%
453 \@nameuse{Changes@AuthorColor}\Changes@ID};%
454 \@nameuse{Changes@AuthorName}\Changes@ID};%
455 \the\value{Changes@AddCount}\Changes@ID};%
456 \the\value{Changes@DeleteCount}\Changes@ID};%
457 \the\value{Changes@ReplaceCount}\Changes@ID}}
458 }
459 \closeout\Changes@OutFile
460 }

461 </changes>
```