

BUILD LOG 1/6 - PANEL CUTTING

17 rows x 20 gores + 2 extra panel N - 25 mm allowance - solid=cut dotted=sew - ROW HEIGHT across the 60 in bolt, GORE WIDTH along the 12 ft table

Item	Spec / reference	Done by	Date	Checked
Panel P x20	1206/774 x 1318 mm			
Panel O x20	1609/1190 x 1323 mm			
Panel N x22	1984/1595 x 1332 mm			
Panel M x20	2310/1971 x 1342 mm			
Panel L x20	2569/2299 x 1356 mm			
Panel K x20	2737/2561 x 1368 mm			
Panel J x20	2809/2732 x 1372 mm			
Panel i x20	2793/2808 x 1370 mm			
Panel H x20	2701/2795 x 1364 mm			
Panel G x20	2541/2705 x 1358 mm			
Panel F x20	2324/2548 x 1349 mm			
Panel E x20	2059/2333 x 1340 mm			
Panel D x20	1771/2069 x 1331 mm			
Panel C x20	1480/1782 x 1328 mm			
Panel B x20	1191/1491 x 1328 mm			
Panel A x20	905/1202 x 1327 mm			
Panel NOMEX x20	619/916 x 1327 mm - BLACK NOMEX			
Scale verified	calibration lines measured, both axes, every sheet			

BUILD LOG 2/6 - MOUTH APPLIQUE

black crescent 5.09 x 1.19 m - row C gores 20/1/2 - applied flat before gore assembly

Item	Spec / reference	Done by	Date	Checked
Piece gore 20	exact crescent + right seam extension			
Piece gore 1	exact crescent + both extensions			
Piece gore 2	exact crescent + left seam extension			
Zigzag applique	3-step zigzag, hot-cut edges only			
Extensions kept free	caught later in fells 20/1 & 1/2			
Alignment check	continuous crescent across seams			

BUILD LOG 3/6 - EYE PODS + FEED HOLES

pods gores 18-20 / 2-4, rows F-J - footprint 7.96 x 6.81 m, perimeter 23.18 m, lens 115 %

Item	Spec / reference	Done by	Date	Checked
Feed holes LEFT	gores 20/2: panel H +450 mm■/ gores 19/3: panel H +910 mm■/ gores 18/4: panel i +850 mm			
Feed holes RIGHT	mirror of left (gores 2/3/4)			
Hole finish	O450 hot-cut in the ENVELOPE, hem over Class 3 1/2 in tape, double-fold to O500			
Rim tape L+R	Class 3 1/2 in tape, twin-stitch, caught into the gore load tapes			
Lens fitted L+R	15 % ease distributed at 8 marks			
Load test	25 kg at 4 points, no failures			

BUILD LOG 4/6 - ANTENNAE

3.75 m total - row N gores 18 & 4 - 35 deg outboard lean - base reinforced by a SECOND PANEL N, not a patch

Item	Spec / reference	Done by	Date	Checked
Doublers x2	extra panel N on the inside face, gores 18 & 4, caught into all four seams			
Feed holes	O575 cut / O625 finished, BOTH plies, hem over Class 3 1/2 in tape, bar-tacked x4			
Cones x2	2.25 m, O875 to O312 taper			
Balls x2	O1.5 m, 16 gores, red #e9132f			
Equator zips	350 mm, black			
Mounting	ellipse marked mid-row N, long axis OUTBOARD; lean 35 deg			
Base ring x2	3.08 m of tape in the oblique base turn - NOT 2.8 m			
Inflation check	self-supporting when pressurized			

BUILD LOG 5/6 - TURNING VENTS

overlap (MOUSE) type - seams 15/16 & 16/17 - rows i-J - vent-marked panels; units 5542/5601 mm wide

Item	Spec / reference	Done by	Date	Checked
Inner J units x2	scaled vent-marked panel J; apex-up triangle			
Inner i units x2	scaled vent-marked panel i; vee-down triangle + R70 port			
Lip overlap	70 mm, J OUTSIDE i, double-fold over tape			
Sew lines	triangles twin-stitched, apexes bar-tacked			
Vent lines	through R70 ports to Y-pulley / Z-guide loops			
Function test	open/self-seal on the ground			

BUILD LOG 6/6 - PARACHUTE / SCOOP / FINAL

chute on the O5,000 mm hole - overlap 360 mm - rigging per spec summary

Item	Spec / reference	Done by	Date	Checked
Parachute gores x20 + centre	master pattern; TOP OPENING REFERENCE LINE aligned			
Confluence lines x20	3,600 mm			
Centering lines x20	start 3,639 mm; trim toward 3,598 mm on first inflation			
Crown line / red line	31.0 m / 34.0 m (+3 m each for knots & handling)			
Crown overstraps	shortened 1/2 ring opening + 50 mm			
Scoop	sized to burner frame; hung 100 mm below mouth; 600 mm leads			
Flying wires	per frame table on the scoop/rigging sheet			
Final inspection	seams, vents, pods, chute seating, paperwork			