Giga-Embeddings: Mixture-of-Experts Encoders for High-Throughput Text Embeddings

Anonymous Authors[1]

Abstract

We introduce Giga-Embeddings, a family of text embedding models designed to combine strong retrieval quality with efficient serving. Its largest member is a sparse 10B-parameter Mixture-of-Experts encoder that preserves substantial model capacity while activating only a fraction of it for each token. Across English, Russian, multilingual, and code MTEB benchmarks, the MoE model achieves the strongest aggregate performance within the family on all four evaluated suites. At an input length of 1024 tokens under our benchmark environment, its throughput is 25% higher than that of the dense 3B model and 1.56–2.65× that of the evaluated external systems. The family further includes a dense 3B model and a distilled 480M model, extending this quality–efficiency trade-off to tighter compute and memory budgets.

1. Introduction

Text embeddings support semantic search, retrieval-augmented generation, clustering, classification, and semantic textual similarity. MTEB (Muennighoff et al., 2023) and its multilingual expansion MMTEB (Enevoldsen et al., 2025) provide broad evaluation suites for these use cases. Recent embedding systems adapt decoder-only language models into bidirectional encoders and train them with large-scale contrastive objectives (BehnamGhader et al., 2024; Wang et al., 2024; Lee et al., 2025a; Kolodin et al., 2025). Although scaling the backbone generally improves representation quality, billion-parameter encoders are costly to store and serve.

Knowledge distillation offers one route to smaller encoders. For embedding models, supervision can be transferred by matching embeddings or by matching the teacher's relative similarity scores over candidate sets (Reimers & Gurevych, 2020; Xu et al., 2023; Zhao et al., 2026). The latter is attractive when the teacher and student have different hidden dimensions or architectures. It is also architecture-agnostic: a dense or sparse Mixture-of-Experts (MoE) teacher can supervise the same listwise objective through its final similarity scores.

We present two complementary approaches to efficient text embeddings: sparse activation for high-capacity models and similarity-distribution distillation for compact encoders. The 10B MoE model activates approximately 1.8B parameters per token and achieves the highest measured throughput among the compared systems. The distilled 480M model provides a compact alternative while remaining within 2.41–6.92 points of the dense 3B model across the four evaluation suites. Our contributions are:

1. Giga-Embeddings-10B-A1.8B, a sparse encoder that achieves the best aggregate scores in the model family, leads the external Russian comparison, and delivers the highest measured throughput at all three sequence lengths;

2. a dimension-agnostic similarity-distribution distillation method that produces a 480M encoder scoring 70.96 on Russian MTEB, matching the 70.95 score of FRIDA while using 42% fewer parameters (480M vs. 823M).

2. Related Work

General-purpose text embeddings. Sentence-BERT (Reimers & Gurevych, 2019) and SimCSE (Gao et al., 2021) established efficient bi-encoder and contrastive recipes. E5 (Wang et al., 2022), GTE (Li et al., 2023), BGE (Xiao et al., 2023), and Nomic Embed (Nussbaum et al., 2024) scaled data and negative mining. Instruction-conditioned systems such as INSTRUCTOR (Su et al., 2023), E5-Mistral (Wang et al., 2024), GritLM (Muennighoff et al., 2025), and NV-Embed (Lee et al., 2025a) adapt large language models to heterogeneous embedding tasks. Recent multilingual LLM-based embedders include Qwen3-Embedding (Zhang et al., 2025), which uses the

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the International Conference on Machine Learning (ICML). Do not distribute.

Table 1. Stage-specific training settings. Each fine-tuning and multitask sample contains one positive and seven negatives, giving 8,192 candidate texts per global batch.

Setting	Pretrain	Finetune	Multitask
Global batch size	16,384	1,024	1,024
Candidates/sample	in-batch	1 pos. + 7 neg.	1 pos. + 7 neg.
In-batch negatives	yes	no	no

same backbone family as our dense encoders, and Gemini Embedding (Lee et al., 2025b).

Embedding distillation. Classical knowledge distillation matches softened output distributions (Hinton et al., 2015), and compact encoders have long been obtained by direct compression of BERT-style models (Sun et al., 2019; Sanh et al., 2019; Jiao et al., 2020; Sun et al., 2020). In dense retrieval, cross-architecture and listwise similarity distillation are well established: Margin-MSE transfers cross-encoder margins to bi-encoders (Hofstätter et al., 2020), RocketQAv2 applies dynamic listwise distillation between retriever and re-ranker (Ren et al., 2021), and Gecko distills knowledge from large language models into a compact embedder (Lee et al., 2024). For sentence embeddings, Reimers & Gurevych (2020) transfer representations from a monolingual teacher to a multilingual student, while DistillCSE (Xu et al., 2023) studies contrastive self-distillation and teacher-logit variance. GUIDE (Trinh et al., 2025) combines guided initialization with representation transfer. Recent contrastive-plus-distillation recipes for compact embedders include KaLM-Embedding-V2 (Zhao et al., 2026), which weights contrastive loss against a KL divergence between teacher and student similarity distributions, and jina-embeddings-v5-text (Akram et al., 2026), which combines distillation with task-targeted contrastive training. Our method similarly combines contrastive learning with KL divergence between teacher and student similarity distributions.

Sparse teachers and dense students. MoE models increase total capacity while activating a subset of experts per token (Shazeer et al., 2017; Fedus et al., 2022; Jiang et al., 2024). Sparse-to-dense transfer has been studied for generative models; for example, Xue et al. (2022) compare several ways of gathering expert weights before distillation, and Fedus et al. (2022) describe sparse-to-dense distillation with partial retention of the sparse quality gain. Because final-output distillation operates on similarity scores, it can transfer knowledge from an MoE teacher to a dense student without matching internal routing decisions or expert states.

3. Model and Training Recipe

3.1. Encoder adaptation

Following the earlier Giga-Embeddings recipe (Kolodin et al., 2025), the model family adapts decoder-only language models for embedding generation. The causal attention mask is replaced by a fully visible bidirectional mask, as in LLM2Vec (BehnamGhader et al., 2024), so that each token can use both left and right context. We use mean pooling to aggregate token states into a fixed-dimensional vector and normalize the resulting vector before cosine-similarity scoring. The instruction templates follow the earlier Giga-Embeddings recipe (Kolodin et al., 2025) and distinguish asymmetric retrieval inputs from symmetric semantic-similarity inputs. We will release the complete instruction set with the model checkpoints.

The 480M, 3B, and 10B-A1.8B encoders produce embeddings with dimensions 1024, 2048, and 1536, respectively. The 480M and 3B models are dense bidirectional Qwen3 encoders (Zhang et al., 2025), while the largest model is a bidirectional DeepSeekMoE-style encoder (Dai et al., 2024) with 10B total parameters, 64 routed experts, one shared expert, and top-4 routing. Its release designation, A1.8B, denotes approximately 1.8B active parameters per token. We use "480M", "3B", and "10B-A1.8B" as short model-family names.

3.2. Three-stage contrastive training

As in the first Giga-Embeddings release (Kolodin et al., 2025), training has three stages: broad contrastive pretraining, retrieval fine-tuning with hard negatives, and multitask fine-tuning for retrieval, classification, clustering, and semantic similarity. The training mixture combines open-source datasets used in the earlier Giga-Embeddings recipe (Kolodin et al., 2025) with non-public datasets that cannot be disclosed under their contractual terms. Across all stages, the learning rate starts at 3×10^{-5} and follows a cosine decay schedule with a 1% warmup fraction and a minimum learning rate of 10^{-7}. We use weight decay of 0.01, Adam coefficients $\beta_1 = 0.9$ and $\beta_2 = 0.999$, and an InfoNCE temperature of 0.02. Fine-tuning runs for one epoch and multitask training for three epochs. The stage-specific settings are summarized in Table 1.




Figure 1. Three-stage embedding training pipeline. All models undergo contrastive pre-training, retrieval fine-tuning, and multitask fine-tuning. Similarity-distribution distillation is applied only to the 480M student during the fine-tuning and multitask stages.

Pre-training uses in-batch InfoNCE, includes query–query and document–document contrastive terms, and masks detected false negatives. Fine-tuning and multitask training disable in-batch negatives and use the explicit eight-candidate groups described in Table 1. For a batch of B queries, let $\mathcal{C}_i$ be the fixed candidate set for query q_i, let $p(i)$ index its positive candidate, and let s_{ij} be the student cosine similarity. We use batch-mean InfoNCE (van den Oord et al., 2018):

$$\mathcal{L}_{\text{NCE}} = -\frac{1}{B}\sum_{i=1}^{B}\log\frac{\exp(s_{i,p(i)}/\tau)}{\sum_{j\in\mathcal{C}_i}\exp(s_{ij}/\tau)}. \tag{1}$$

Hard negatives for retrieval fine-tuning are mined from a predefined retrieval-rank range.

3.3. Similarity-distribution distillation

We apply similarity-distribution distillation exclusively to the 480M model during retrieval fine-tuning and multitask fine-tuning. Its pre-training stage uses only the contrastive objective, and the 3B and 10B-A1.8B models are trained without distillation. For both distilled stages, $\lambda = 0.3$, $\tau_{\text{KD}} = 0.05$, and the contrastive temperature is 0.02. Because the objective aligns distributions over query–candidate similarity scores rather than embedding coordinates, the teacher and student may use different embedding dimensions. By contrast, direct MSE or cosine-similarity alignment between teacher and student embedding vectors requires equal dimensions or an additional learned projection. Let t_{ij} be the teacher cosine similarity for the same support $\mathcal{C}_i$. Teacher and student distributions are

$$P_T(j \mid q_i) = \frac{\exp(t_{ij}/\tau_{\text{KD}})}{\sum_{k\in\mathcal{C}_i}\exp(t_{ik}/\tau_{\text{KD}})}, \tag{2}$$

$$P_S(j \mid q_i) = \frac{\exp(s_{ij}/\tau_{\text{KD}})}{\sum_{k\in\mathcal{C}_i}\exp(s_{ik}/\tau_{\text{KD}})}. \tag{3}$$

The distillation term is a batch mean over identical supports:

$$\mathcal{L}_{\text{KD}} = \frac{1}{B}\sum_{i=1}^{B} D_{\text{KL}}(P_T(\cdot \mid q_i)\,\|\,P_S(\cdot \mid q_i))\,. \tag{4}$$

The combined objective is

$$\mathcal{L} = \lambda\mathcal{L}_{\text{KD}} + (1-\lambda)\mathcal{L}_{\text{NCE}}. \tag{5}$$

The KL term transfers the teacher's relative similarity structure over each candidate set, while InfoNCE preserves direct contrastive supervision. Because the loss depends only on final similarity scores, it does not require access to the teacher's internal architecture or routing decisions.

Table 2. Model architectures. "Active" denotes parameters used per token.

Type	Total	Active	Dim.
Dense	480M	480M	1024
Dense	3B	3B	2048
MoE, top-4	10B	∼1.8B	1536

Table 3. Task-macro MTEB scores (%) over 41 English, 23 Russian, 131 multilingual, and 12 code tasks. Bold marks the best result within the model family.

Scale	Dim.	English	Russian	Multilingual	Code
480M	1024	69.52	70.96	56.97	72.87
3B	2048	71.93	74.56	63.89	76.93
10B-A1.8B	1536	**72.23**	**74.98**	**65.64**	**78.41**

Table 4. Token throughput (thousands of tokens per second) with vLLM at fixed input lengths. Relative throughput is measured at 1024 tokens and normalized to our 10B-A1.8B-0826 model.

Model (vLLM)	512 tokens	1024 tokens	2048 tokens	Relative
Qwen3 Embedding 4B	70.1k	73.2k	71.2k	0.64×
F2LLM-v2-8B	43.2k	43.4k	42.6k	0.38×
Nemotron 8B	42.6k	43.2k	41.7k	0.38×
Ours: 3B-0826	87.9k	91.5k	90.4k	0.80×
Ours: 10B-A1.8B-0826	**112.6k**	**114.5k**	**102.3k**	**1.00×**

4. Evaluation

4.1. Evaluation protocol

We evaluate each benchmark using the tasks, subsets, and evaluation splits defined by MTEB. Scores are first aggregated within each task and then averaged uniformly across tasks to obtain the suite-level result. This prevents tasks with more languages, subsets, or splits from receiving additional weight. We additionally evaluate the 3B model on a Chinese-language MTEB suite comprising 31 tasks, obtaining a score of 59.87. Because corresponding results are unavailable for the 480M and 10B-A1.8B models, we report this score separately rather than include it in the main comparison. The Russian suite follows ruMTEB (Snegirev et al., 2025), while the multilingual suite follows MMTEB (Enevoldsen et al., 2025). We use the same aggregation procedure for all models.

Assuming fp16 weights, the 480M, 3B, and 10B-A1.8B models require approximately 0.96, 6, and 20 GB of weight storage, respectively. The distilled model therefore uses about 4.8% as much weight storage as the MoE model. These theoretical estimates exclude activations and other runtime state.

4.2. Aggregate results

Table 3 presents task-macro scores for all three models. The 480M distilled model reaches 69.52 on English, 70.96 on Russian, 56.97 on Multilingual, and 72.87 on Code. Relative to the 3B model, its gaps are 2.41, 3.60, 6.92, and 4.06 points, respectively, with the largest compression gap on the multilingual suite.

The 10B-A1.8B model achieves the highest score within the family on every benchmark. The improvement over 3B is modest on English (+0.30) and Russian (+0.42), and larger on Multilingual (+1.75) and Code (+1.48). Because each model is evaluated once, the sub-one-point differences on English and Russian should be interpreted cautiously. Moreover, this comparison does not define a scaling law: the models differ in architecture, training recipe, active parameter count, and embedding dimension.

A matched 480M model trained without teacher supervision is not yet available. The reported scores therefore establish the quality of the distilled model but do not quantify the improvement attributable to distillation.

4.3. Inference throughput

The MoE serving configuration has the highest measured throughput at every evaluated length. Relative to the dense Giga-Embeddings 3B model, its throughput is 1.28×, 1.25×, and 1.13× as high at 512, 1024, and 2048 tokens, respectively. All models in Table 4 use vLLM; the measurements remain specific to the benchmark environment and do not isolate the contribution of sparse activation. We do not measure throughput for the 480M model, so its efficiency comparison is limited to theoretical weight storage.

4.4. External baseline comparison

Tables 5 and 6 compare Giga-Embeddings with public results from the MTEB Leaderboard. Differences in prompts and evaluation settings make these contextual rather than controlled same-run comparisons. Giga-Embeddings-instruct-10B-A1.8B-0826 leads the Russian column, while Qwen3-Embedding-8B leads English and Multilingual and F2LLM-v2-14B leads Code.

Table 5. Comparison with compact models on MTEB benchmark suites (%). Public baselines use official MTEB Leaderboard `meanTask` values retrieved on 2026-08-08; our result is from Table 3. Bold marks the best score in each column, and a dash denotes an unavailable score.

Model	Params	Dim.	Russian	English	Multilingual	Code
sergeyzh/BERTA	128M	768	69.39	—	—	—
google/embeddinggemma-300m	308M	768	65.19	69.67	61.15	68.76
codefuse-ai/F2LLM-v2-0.6B	596M	1024	65.97	69.97	62.74	**77.41**
Qwen/Qwen3-Embedding-0.6B	596M	1024	64.29	**70.47**	**64.34**	75.42
ai-forever/FRIDA	823M	1536	70.95	—	—	—
Ours: 480M-0826	480M	1024	**70.96**	69.52	56.97	72.87

Table 6. Comparison with larger models on MTEB benchmark suites (%). Public baselines use official MTEB Leaderboard `meanTask` values retrieved on 2026-08-08; our results are from Table 3. Bold marks the best score in each column.

Model	Params	Dim.	Russian	English	Multilingual	Code
codefuse-ai/F2LLM-v2-1.7B	1.72B	2048	68.52	71.63	65.21	78.76
codefuse-ai/F2LLM-v2-4B	4.02B	2560	69.46	72.41	67.06	80.15
Qwen/Qwen3-Embedding-4B	4.02B	2560	70.13	74.61	69.45	80.07
Qwen/Qwen3-Embedding-8B	7.57B	4096	71.42	**75.23**	**70.58**	80.69
codefuse-ai/F2LLM-v2-8B	7.57B	4096	70.57	72.86	68.09	80.16
codefuse-ai/F2LLM-v2-14B	13.99B	5120	70.90	73.08	68.74	**80.75**
Ours: 3B-0826	3B	2048	74.56	71.93	63.89	76.93
Ours: 10B-A1.8B-0826	10B	1536	**74.98**	72.23	65.64	78.41

5. Conclusion

Giga-Embeddings-10B-A1.8B combines 10B parameters of resident MoE capacity with approximately 1.8B active parameters per token. It achieves the best aggregate scores in the Giga-Embeddings family and the highest throughput among the five evaluated serving configurations. The distilled 480M model remains within 2.41–6.92 points of the 3B model across English, Russian, Multilingual, and Code, while requiring only 4.8% as much theoretical fp16 weight storage as the MoE model. Quality gains from 3B to 10B-A1.8B are small on English and Russian but more visible on Multilingual and Code. A matched no-distillation ablation and broader measurements of latency, memory, and energy are left for future work.

References

Akram, M. K., Sturua, S., Havriushenko, N., Herreros, Q., Günther, M., Werk, M., and Xiao, H. jina-embeddings-v5-text: Task-targeted embedding distillation. *arXiv preprint arXiv:2602.15547*, 2026.

BehnamGhader, P., Adlakha, V., Mosbach, M., Bahdanau, D., Chapados, N., and Reddy, S. LLM2Vec: Large language models are secretly powerful text encoders. In *Proceedings of the First Conference on Language Modeling (COLM)*, 2024.

Dai, D., Deng, C., Zhao, C., Xu, R. X., Gao, H., Chen, D., Li, J., Zeng, W., Yu, X., Wu, Y., et al. DeepSeekMoE: Towards ultimate expert specialization in mixture-of-experts language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 1280–1297, 2024.

Enevoldsen, K., Chung, I., Kerboua, I., Kardos, M., Mathur, A., Stap, D., Gala, J., Siblini, W., Krzemiński, D., Winata, G. I., et al. MMTEB: Massive multilingual text embedding benchmark. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2025. URL https://arxiv.org/abs/2502.13595.

Fedus, W., Zoph, B., and Shazeer, N. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23(120):1–39, 2022.

Gao, T., Yao, X., and Chen, D. SimCSE: Simple contrastive learning of sentence embeddings. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 6894–6910, 2021.

Hinton, G., Vinyals, O., and Dean, J. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Hofstätter, S., Althammer, S., Schröder, M., Sertkan, M., and Hanbury, A. Improving efficient neural ranking models with cross-architecture knowledge distillation. *arXiv preprint arXiv:2010.02666*, 2020.

Jiang, A. Q., Sablayrolles, A., Roux, A., Mensch, A., Savary, B., Bamford, C., Chaplot, D. S., de las Casas,

D., Hanna, E. B., Bressand, F., Lengyel, G., Bour, G., Lample, G., Lavaud, L. R., Saulnier, L., Lachaux, M.-A., Stock, P., Subramanian, S., Yang, S., Antoniak, S., Scao, T. L., Gervet, T., Lavril, T., Wang, T., Lacroix, T., and Sayed, W. E. Mixtral of experts. *arXiv preprint arXiv:2401.04088*, 2024.

Jiao, X., Yin, Y., Shang, L., Jiang, X., Chen, X., Li, L., Wang, F., and Liu, Q. TinyBERT: Distilling BERT for natural language understanding. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 4163–4174, 2020.

Kolodin, E., Khomich, D., Savushkin, N., Ianina, A., and Minkin, F. GigaEmbeddings: Efficient Russian language embedding model. In *Proceedings of the 10th Workshop on Slavic Natural Language Processing (SlavicNLP 2025)*, pp. 17–24, 2025.

Lee, C., Roy, R., Xu, M., Raiman, J., Shoeybi, M., Catanzaro, B., and Ping, W. NV-Embed: Improved techniques for training LLMs as generalist embedding models. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2025a.

Lee, J., Dai, Z., Ren, X., Chen, B., Cer, D., Cole, J. R., Hui, K., Boratko, M., Kapadia, R., Ding, W., et al. Gecko: Versatile text embeddings distilled from large language models. *arXiv preprint arXiv:2403.20327*, 2024.

Lee, J., Chen, F., Dua, S., Cer, D., Shanbhogue, M., Naim, I., Ábrego, G. H., Li, Z., Chen, K., Vera, H. S., et al. Gemini embedding: Generalizable embeddings from Gemini. *arXiv preprint arXiv:2503.07891*, 2025b.

Li, Z., Zhang, X., Zhang, Y., Long, D., Xie, P., and Zhang, M. Towards general text embeddings with multi-stage contrastive learning. *arXiv preprint arXiv:2308.03281*, 2023.

Muennighoff, N., Tazi, N., Magne, L., and Reimers, N. MTEB: Massive text embedding benchmark. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics (EACL)*, pp. 2014–2037, 2023.

Muennighoff, N., Su, H., Wang, L., Yang, N., Wei, F., Yu, T., Singh, A., and Kiela, D. Generative representational instruction tuning. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2025.

Nussbaum, Z., Morris, J. X., Duderstadt, B., and Mulyar, A. Nomic embed: Training a reproducible long context text embedder. *arXiv preprint arXiv:2402.01613*, 2024.

Reimers, N. and Gurevych, I. Sentence-BERT: Sentence embeddings using siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 3982–3992, 2019.

Reimers, N. and Gurevych, I. Making monolingual sentence embeddings multilingual using knowledge distillation. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 4512–4525, 2020. doi: 10.18653/v1/2020.emnlp-main.365.

Ren, R., Qu, Y., Liu, J., Zhao, W. X., She, Q., Wu, H., Wang, H., and Wen, J.-R. RocketQAv2: A joint training method for dense passage retrieval and passage re-ranking. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 2825–2835, 2021.

Sanh, V., Debut, L., Chaumond, J., and Wolf, T. DistilBERT, a distilled version of BERT: Smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*, 2019.

Shazeer, N., Mirhoseini, A., Maziarz, K., Davis, A., Le, Q. V., Hinton, G. E., and Dean, J. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2017.

Snegirev, A., Tikhonova, M., Maksimova, A., Fenogenova, A., and Abramov, A. The Russian-focused embedders' exploration: ruMTEB benchmark and Russian embedding model design. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 236–254, 2025. doi: 10.18653/v1/2025.naacl-long.12.

Su, H., Shi, W., Kasai, J., Wang, Y., Hu, Y., Ostendorf, M., tau Yih, W., Smith, N. A., Zettlemoyer, L., and Yu, T. One embedder, any task: Instruction-finetuned text embeddings. In *Findings of the Association for Computational Linguistics: ACL 2023*, pp. 1102–1121, 2023.

Sun, S., Cheng, Y., Gan, Z., and Liu, J. Patient knowledge distillation for BERT model compression. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 4323–4332, 2019.

Sun, Z., Yu, H., Song, X., Liu, R., Yang, Y., and Zhou, D. MobileBERT: a compact task-agnostic BERT for resource-limited devices. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 2158–2170, 2020.

Trinh, K., Menghani, G., and Vee, E. GUIDE: Guided initialization and distillation of embeddings. *arXiv preprint arXiv:2510.06502*, 2025.

van den Oord, A., Li, Y., and Vinyals, O. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Wang, L., Yang, N., Huang, X., Jiao, B., Yang, L., Jiang, D., Majumder, R., and Wei, F. Text embeddings by weakly-supervised contrastive pre-training. *arXiv preprint arXiv:2212.03533*, 2022.

Wang, L., Yang, N., Huang, X., Yang, L., Majumder, R., and Wei, F. Improving text embeddings with large language models. *arXiv preprint arXiv:2401.00368*, 2024.

Xiao, S., Liu, Z., Zhang, P., Muennighoff, N., Lian, D., and Nie, J.-Y. C-Pack: Packed resources for general Chinese embeddings. *arXiv preprint arXiv:2309.07597*, 2023.

Xu, J., Shao, W., Chen, L., and Liu, L. DistillCSE: Distilled contrastive learning for sentence embeddings. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 8153–8165, 2023. doi: 10.18653/v1/2023.findings-emnlp.547.

Xue, F., He, X., Ren, X., Lou, Y., and You, Y. One student knows all experts know: From sparse to dense. *arXiv preprint arXiv:2201.10890*, 2022.

Zhang, Y., Li, M., Long, D., Zhang, X., Lin, H., Yang, B., Xie, P., Yang, A., Liu, D., Lin, J., et al. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*, 2025.

Zhao, X., Hu, X., Shan, Z., Huang, S., Zhou, Y., Zhang, X., Sun, Z., Liu, Z., Li, D., Wei, X., Pan, Y., Xiang, Y., Zhang, M., Wang, H., Yu, J., Hu, B., and Zhang, M. KaLM-Embedding-V2: Superior training techniques and data inspire a versatile embedding model. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2026.