TLS 1.3 Status

Eric Rescorla

Mozilla

ekr@rtfm.com

Overview of Changes Since IETF 92 (Major)

- Integrate DH-based handshake (per WG discussion in Dallas)
- Add initial cut at 0-RTT support
- HKDF-based key derivation (per WG discussion in Dallas)
- Moved ClientKeyShare into an extension
- Added support for PSK
- Removed resumption and merged ticket support with PSK

Overview of Changes Since IETF 92 (Minor)

- Prohibit RC4 negotiation
- Froze record-layer header
- Context field for signatures
- Replaced explicit IV with sequence number + mask

Open Issues Preview

- Indicating known configurations
- 0-RTT w/ PSK
- Interaction of 0-RTT and authentication
- 0-RTT rejection handling
- PSK resumption restrictions
- Traffic key generation


DH-Based Handshake (Review)

- Server has a semi-static DH key (just like 1-RTT)
- Probably really has long-term signing key
 - Used to sign the semi-static key
 - Agreement at previous IETFs to use online-only signing
- Common key exchange computations between all modes

Key Computation Inputs

Key Exchange	Static Secret (SS)	Ephemeral Secret (ES)
(EC)DHE	Client ephemeral	Client ephemeral
(full handshake)	w/ server ephemeral	w/ server ephemeral
(EC)DHE	Client ephemeral	Client ephemeral
(w/ known_configuration) w/ Known Key	w/ server ephemeral
PSK	Pre-Shared Key	Pre-shared key
PSK + (EC)DHE	Pre-Shared Key	Client ephemeral

Key Computations



Two New Mechanisms

- Server configurations and known configuration
 - Server publishes a configuration to the client in handshake n
 - Client reuses that configuration in handshake n+1
- Early data indication
 - Client indicates that he wants to do 0-RTT (client auth, data, both)
 - Server accepts or rejects

Example: Initial Handshake

```
ClientHello
  + ClientKeyShare
                                                 ServerHello
                                             ServerKeyShare*
                                       {EncryptedExtensions}
                                      {ServerConfiguration*} <- SEE HERE
                                              {Certificate*}
                                       {CertificateRequest*}
                                        {CertificateVerify*}
                                                  {Finished}
{Certificate*}
{CertificateVerify*}
{Finished}
[Application Data]
                                          [Application Data]
```

Known Configuration

```
struct {
    opaque configuration_id<1..2^16-1>;
    uint32 expiration_date;
    NamedGroup group;
    opaque server_key<1..2^16-1>;
    Boolean early_data_allowed;
} ServerConfiguration;
```

• The client's reuse of the configuration implicitly resurrects the previous state (See open issues)

Example: 0-RTT Handshake (w/o new configuration)

```
ClientHello
  + ClientKeyShare
  + KnownConfiguration
  + EarlyDataIndication
(Certificate*)
(CertificateVerify*)
(Application Data)
                                                 ServerHello
                                        + KnownConfiguration
                                       + EarlyDataIndication
                                              ServerKeyShare
                                                  {Finished}
{Finished}
[Application Data]
                          <--->
                                          [Application Data]
```

Early Data Indication

What do failed 0-RTT handshakes look like?

- Server doesn't respond with an EarlyDataIndication
 - System falls back to 1-RTT
 - All of the early data is just ignored
- This is kind of clunky
 - Early handshake messages have a different content type
 - What about encrypted content types
- Analysis needed that ignoring early data is OK
 - ... currently underway

Managing semi-static keys (I)

- Need two keys
 - Ephemeral (for PFS)
 - Semi-static (cached server 1-RTT, 0-RTT)
- Various options for making these work together
 - Always use a single semi-static key suboptimal performance
 - Have the server supply a separate key odd when you refresh keys

Managing semi-static keys (II)

- Current draft state
 - First handshake looks like draft-06
 - * Can supply a ServerConfiguration
 - Subsequent handshakes can reuse ServerConfiguration
 - * But need to sign if they want to provide one
- More modes than we would really like (but best perf profile)

Example: 0-RTT Handshake w/ new configuration

```
ClientHello
  + ClientKeyShare
  + KnownConfiguration
  + EarlyDataIndication
(Certificate*)
(CertificateVerify*)
(Application Data)
                                                 ServerHello
                                        + KnownConfiguration
                                       + EarlyDataIndication
                                              ServerKeyShare
                                      {ServerConfiguration*} <- SEE HERE
                                              {Certificate*} <- SEE HERE
                                        {CertificateVerify*} <- SEE HERE
                                                  {Finished}
{Finished}
[Application Data]
                          <---->
                                          [Application Data]
```

Pre-Shared Keys

- TLS 1.2 had PSK
 - But we kind of broke it
- draft-07 brings it back
 - But I did get rid of identity hint...

Example: Pure PSK Handshake

• Can also do this with DHE-PSK

18

PreSharedKey Extension

```
opaque psk_identity<0..2^16-1>;
struct {
  select (Role) {
   case client:
     psk_identity identities<0..2^16-1>;
    case server:
     psk_identity identity;
} PreSharedKeyExtension;
```

PSK For Resumption

- Resumption and PSK are very similar
 - Let's make them identical
- Basic idea
 - Server gives client a PSK label
 - PSK is derived from initial handshake (resumption master secret)

Example: Establishing a PSK for resumption

```
ClientHello
  + ClientKeyShare
                                                   ServerHello
                                               ServerKeyShare
                                        {EncryptedExtensions}
                                        {ServerConfiguration*}
                                                {Certificate*}
                                        {CertificateRequest*}
                                         {CertificateVerify*}
                                                    {Finished}
{Certificate*}
{CertificateVerify*}
{Finished}
                                           [NewSessionTicket] <- SEE HER</pre>
                                           [Application Data]
[Application Data]
```

ClientKeyShare Extension

- This used to be a separate message
 - That just made life complicated
- It's now an extension
- Nothing else has changed

Indicating Known Configurations

- Current design has client just indicate configuration ID
 - This means that the server needs to memorize each crypto configuration (ugh)
- Proposed redesign
 - Client indicates configuration ID and cryptographic configuration
 - * Cipher suites and cryptographic extensions
 - * MUST replicate the server's selection from a previous handshake
 - Server verifies client's ClientHello
 - * Checks that configuration ID is valid
 - * Verifies that client's parameters are what it would negotiate

Strawman

Analysis

- Pros
 - Server doesn't need to keep per-connection state
 - Neatly solves PSK (and any other key negotiation mechanism)
 - Explicit state is explicit
- Cons
 - Server has to compare client's offer
 - Very modest wire bloat
- Note: we could have the server not echo the parameters in ServerHello
 - But I'd rather keep things consistent

0-RTT Rejection Handling (I)

- Currently it's all or nothing
 - Server can't accept 0-RTT client auth but not 0-RTT data
 - maybe it should be able to express its preferences in ServerConfiguration
- This seems easiest
- Proposed resolution: Server gets to indicate what it wants in ServerConfiguration

0-RTT Rejection Handling (II)

- How do you distinguish client's early data (which you want to discard) from the client's second flight (which you want to process)
- Current algorithm uses content type
 - Early handshake data has early_handshake
 - Early data has application_data type
 - The next thing you want to process has handshake type
 - Just skip to the next handshake message
- This isn't maximally elegant
 - And will fail with encrypted content types (there you need trial decryption)
 - Other ideas welcome

0-RTT Rejection Handling (III)

- What is included in handshake hash?
 - Handshake hash generally includes plaintext
 - but in rejection cases, you probably don't have decryption cases
- Present draft just ignores this data with rejection
- Alternative: include *ciphertext*
- Proposal: keep with current version pending analysis

0-RTT and **Authentication**

- There isn't any per-connection data from the server to sign
 - Client provides all the freshness*
- What context does the client have to sign?
 - It should include server identity

configuration = ServerConfiguration || Certificate

^{*}Insert caveats about issues with 0-RTT anti-replay

PSK Resumption Restrictions?

- Resumption required that you use the same ciphers
 - But if you make resumption PSK then you could in principle negotiate a new cipher
- Should we require servers to pick the same symmetric cipher?
- This would be somewhat easier if we had a la carte negotiation

AEAD IV

- TLS 1.2 (well, GCM) uses a partially explicit IV
 - This chews up bandwidth
- Consensus to remove explicit IV
 - And reuse sequence number
 - Brian Smith raised concerns about every connection using the same nonce sequence

draft-07 design for AEAD IV

- $iv_length = max(8, N_MAX)$
- ullet Generate per-session mask of length iv_length
- ullet Left-pad RSN with 0s to iv_length
- XOR RSN with mask to produce per-record nonce

Traffic Key Generation

- Presently we generate a key_block
- ... and then slice and dice
- Generating independent keys with a context input would be more HSM-friendly
- Expected context
 - Key length
 - Usage
 - Algorithm (ugh)
- Should we do this?

This slide intentionally left blank