

Datagram Transport Layer Security (DTLS) Extension to Establish Keys for Secure Real-time Transport Protocol (SRTP) (Phew!)

Eric Rescorla
David McGrew

Overview

- SDP signals “I’m willing to do DTLS” (and here’s my fingerprint)
- Do DTLS key exchange in media channel
 - Allows reuse of existing DTLS authentication/key establishment mechanisms
 - Use extensions to negotiate SRTP protection profiles
- Use DTLS master secret to generate SRTP traffic keys

TLS Handshake Extension


```
uint8 SRTPProtectionProfile[2];
```

```
struct {  
    SRTPProtectionProfiles SRTPProtectionProfiles;  
    uint8 srtp_mki<255>;  
} UseSRTPData;
```

```
SRTPProtectionProfile SRTPProtectionProfiles<216-1>;
```

```
SRTPProtectionProfile SRTP_AES128_CM_SHA1_80 = {0x00, 0x01};  
SRTPProtectionProfile SRTP_AES128_CM_SHA1_32 = {0x00, 0x02};  
SRTPProtectionProfile SRTP_AES256_CM_SHA1_80 = {0x00, 0x03};  
SRTPProtectionProfile SRTP_AES256_CM_SHA1_32 = {0x00, 0x04};  
SRTPProtectionProfile SRTP_NULL_SHA1_80      = {0x00, 0x05};  
SRTPProtectionProfile SRTP_NULL_SHA1_32      = {0x00, 0x06};
```

Message Flow



Transporting DTLS Handshake Traffic

- Current draft:
 - Carried over same channel as media
 - Directly over UDP
 - Demuxable from RTP/STUN by first byte (S 3.6.2)
 - One DTLS connection per media stream
- Other alternatives
 - In RTCP channel
 - Header extension (a la ZRTP)

Requirements Evaluation

R1: Forking and retargeting MUST work with all end-points being SRTP.	Yes
R2: Forking and retargeting MUST allow establishing SRTP or RTP with a mixture of SRTP- and RTP-capable targets.	Yes
R3: With forking, only the entity to which the call is finally established, MUST get hold of the media encryption keys.	Yes (separate key exchange to each peer)
R5: A solution SHOULD avoid clipping media before SDP answer without additional signalling.	Yes
R6: A solution MUST provide protection against passive attacks.	Yes (including malicious proxies)
R7: A solution MUST be able to support Perfect Forward Secrecy.	Yes (DHE modes)
R8: A solution MUST support algorithm negotiation without incurring per-algorithm computational expense.	Yes (cipher suites negotiated first)
R9: A solution MUST support multiple cipher suites without additional computational expense	Yes
R10: Endpoint identification when forking. The Offerer must be able to associate answer with the appropriate flow endpoint. In case of forking one might not want to perform a DH with every party but instead to associate the SDP response with the right end point. This is a performance related requirement.	Yes (but latency tradeoff)
R11: A solution MUST NOT require 3rd-party certs. If two parties share an auth infrastructure they should be able to use it.	Yes (fingerprints but 3rd-party certs are usable)

Current status

- Bunch of drafts
 - draft-mcgrew-tls-srtp-00, draft-fischl-sipping-media-dtls-00, draft-fischl-mmusic-sdp-dtls-00
 - Looking for feedback
- Prototype implementations in OpenSSL and EyeBeam (thanks Derek MacDonald, Dragos Liciu, Jason Fischl, Nagendra Modadugu)

Open issue: transporting key management messages

- An issue for any media-plane key management protocol
- RTCP channel
 - Natural fit for RTP style
 - But deployment of RTCP is spotty
- RTP header extension
 - No dependency on RTCP
 - Not what header extension intended for
- Carried directly over UDP—demuxed like STUN
 - Keeps key management out of media packets
 - Not as good fit to the RTP style