



TECHNICAL MEMORANDUM

DATE: June 27, 2025

TO: Lauren Broudy and Karl Lisle | City of Portland

FROM: Garth Appanaitis and Kevin Chewuk | DKS Associates

SUBJECT: Performing Arts Center
Summary – Transportation Study Findings

This memorandum marks the conclusion of our initial study of the three potential performing arts scenarios, including the renovation of the Keller site, the construction of a new PSU site, and combined uses at both locations.

In summary, this study did not identify any fatal flaws for either site but did identify various opportunities and challenges with potential considerations for future site refinement to enable site function.

SUMMARY OF FINDINGS

1. Both the renovation of the Keller site and the construction of a new PSU site share two common benefits:
 - a. the traffic activity generally occurs outside of key congestion periods; and
 - b. the central location within the region means that patron travel will be spread more evenly among regional travel routes.

Key Takeaway—This decreases the opportunity for significant negative traffic impacts (such as congestion, bottlenecks, closures, etc.).

2. We collected information to help us learn how a new performing arts center might affect traffic. This includes how many cars are already on nearby roads, how many more car trips the center would cause, what time those trips would happen, and which roads people would use.

Key Takeaway— This new data can be used to support detailed traffic analysis for either site.

3. The Keller site is already in operation and is not expected to add more traffic to the system. However, the PSU site would bring new trip activity, either by replacing the Keller site or adding to it. Portland City Code 17.88.050 requires traffic studies for development that exceeds 100 vehicle trips during an hour in the peak direction. This threshold would be triggered if a new

performing arts center is built at PSU – through the details of the traffic study and requirements may depend on whether the Keller site stays open or if the PSU site takes its place.

Key takeaway—Additional coordination with PBOT and ODOT staff would be needed to determine the specific requirements of a traffic study that may be needed for the PSU site to address the requirements of Portland City Code 17.88.050.

4. A review of traffic volumes on SW 3rd Avenue indicates that the street could be a candidate for a lane reduction to improve pedestrian circulation and safety adjacent to the Keller site.

Key takeaway—Reducing traffic to one lane on this portion of SW 3rd Avenue could be a candidate for a pilot project with PBOT.

5. As the PSU site plan and design develops, the key traffic element to address will likely be reducing the potential for vehicle queuing on the SW 4th Avenue off ramp.

Key takeaway—Focusing on reducing the potential of vehicle queuing on the SW 4th Avenue off-ramp through the positioning of the site entry, maintaining traffic flow at site entry, and alerting patrons of other parking opportunities, for example, will be critical to reduce negative traffic impacts on this site.

RECOMMENDED NEXT STEPS

1. Lane Reduction Pilot Project at Existing Keller Site—Coordinate with PBOT staff to implement a pilot project that temporarily reduces the number of lanes on SW 3rd Avenue to one travel lane (and additional loading zone) between SW Clay Street and SW Market Street. The duration and implementation of this pilot should be determined by traffic engineers at PBOT.
2. Incorporate Traffic Impact Reduction Treatments at PSU Site as Project Design Advances—As site design advances, consider incorporating treatments that would reduce the potential for vehicle queuing on the SW 4th Avenue off-ramp. Additional coordination with PBOT and ODOT staff would be needed to determine the specific requirements of a traffic study that may be needed for the PSU site to address the requirements of Portland City Code 17.88.050.

Thank you for this opportunity to advance the understanding of the potential transportation impacts and needs for a Performing Arts Center.



TECHNICAL MEMORANDUM

DATE: June 27, 2025

TO: Lauren Broudy and Karl Lisle | City of Portland

FROM: Garth Appanaitis and Kevin Chewuk | DKS Associates

SUBJECT: Performing Arts Center
Transportation Study

This document summarizes a high-level transportation study that was conducted to identify key issues and needs for further review and evaluation of three potential Performing Arts Center scenarios in downtown Portland. This high-level analysis is based on readily available data to better understand the transportation system and its current conditions, opportunities, and constraints for the three scenarios.

This analysis is not intended to represent a full transportation study for specific uses at any location, and each potential scenario will require more study if it is recommended for further consideration by stakeholders. **This study did not identify any fatal flaws for either site but did identify various opportunities and challenges with potential considerations for future site refinement to enable site function.** The information summarized in this document may be leveraged to support the future additional transportation study related to site development.

The following sections summarize the key analysis findings. Additional technical data is included in the appendix.

GENERAL INFORMATION

- **Scope of Study:** Three potential scenarios were considered:
 - Scenario 1: Renovate the existing Keller Auditorium
 - Scenario 2: Construct a new venue at Portland State University (PSU)
 - Scenario 3: Renovate the existing Keller Auditorium (Scenario 1) + Construct a new venue at PSU (Scenario 2)
- **Data Collected:** Data was collected to inform and better understand the impacts and needs of a venue, regardless of specific location. This data is applicable for each scenario, with more information provided in the appendix.
 - Patron trip generation – Patrons were surveyed upon arriving at a Keller event to determine the type of travel mode and size of their group. This information is important

to estimate the amount of vehicular traffic that could be added to the transportation system for a new venue. The survey of approximately 320 patrons indicated that there is approximately one vehicle added to the system for every 2.6 patrons. This and the related survey data are needed to estimate the trip generation for the site since national data from other sources is limited.

- Patron trip distribution – Sales zip codes for an event (SIX - The Musical) were used to estimate where patrons were traveling from. This information is important to understand the potential impact and added traffic on regional roads. This was a non-member event and member event distribution may vary. The information for Six indicated:
 - 22 percent of patrons travel to/from the north of downtown Portland (e.g., N/NE Portland, Vancouver)
 - 36 percent to/from the south of downtown Portland (e.g., SW Portland, Tigard, Lake Oswego)
 - 21 percent to/from the east of downtown Portland (e.g., E/SE Portland, Happy Valley)
 - 21 percent to/from the west of downtown Portland (e.g., NW Portland, Beaverton, Hillsboro)
- Parking Arrival and Duration data – A mix of parking summary and raw data was obtained for several private and public garages in the area. Function of the ticketing systems limits some of the data that is available. However, based on a review of the 200 Market event parking data, it appears that approximately 20 percent of parking patrons arrive over an hour before the show time, while the remaining 80 percent arrive within the hour of the show. This data is important to understand the portion of event traffic that is added to the roadway system before a show.
- Traffic volumes – Traffic volume data was collected along streets in the vicinity of the Keller Auditorium and proposed PSU venues to better understand current travel patterns. The data included turn movement volumes at intersections and average daily traffic volumes along street segments.
- **General Use Opportunities:** The following benefits are applicable to both locations studied:
 - Location – Being centrally located within the region in downtown Portland allows traffic to arrive and disperse from a variety of directions and facilities.
 - Use Type – The typical programming for events and facility use (e.g., weekday evenings) is not during peak traffic system congestion periods.
- **Future Needs:** This high-level transportation study identifies key issues and needs for further review and evaluation.
 - This is not a full traffic study for any potential scenario. Each potential scenario will require more study if it is recommended for further consideration by stakeholders.

SCENARIO 1: RENOVATE THE EXISTING KELLER AUDITORIUM

- The existing Keller Auditorium remains in its current location, bounded by SW 3rd Avenue, SW Market Street, SW 2nd Avenue, and SW Clay Street.
 - The venue is renovated, although the capacity remains at 3,000 seats.

CURRENT CONDITIONS

- The existing trips are already served by the transportation system, and no changes are expected in that estimated demand.
 - During a sold-out event, the current venue generates an estimated:
 - 923 pre-event peak and 981 post-event peak motor vehicle trips
 - 144 pre-event peak and 153 post-event peak transit, walking, or biking trips
- The transportation system generally functions adequately with the current arrival and departure patterns for patrons¹.
- Existing vehicular parking is abundant in the area, with over 3,000 spaces located within a one-block walk and an additional 2,000 spaces within five blocks.

KEY ISSUES

- Peak event flows for patrons creates congestion along frontages adjacent to the venue entrances along SW 3rd Avenue and SW Clay Street.
- Pedestrians walking from nearby parking garages are frequently using crosswalks on SW Market Street and SW Clay Street at SW 3rd Avenue, and conflicting with vehicular traffic along these streets. With adjacent parking garages located kitty-corner from the Keller venue, pedestrians typically cross two legs of the intersection to arrive at the front door.

POTENTIAL OPPORTUNITIES

- Changing the configuration of SW 3rd Avenue between SW Clay Street and SW Market Street could be considered to accommodate peak event pedestrian flows.
 - SW 3rd Avenue currently has two travel lanes and a lane for loading along both the east and west block faces. Potential alternative configurations for SW 3rd Avenue along this segment include:
 - Option 1: Close SW 3rd Avenue to vehicular traffic permanently
 - Option 2: Close SW 3rd Avenue to vehicular traffic only during events
 - Option 3: Narrow SW 3rd Avenue to one travel lane, but always keep one-lane open for vehicular traffic
 - This block of SW 3rd Avenue is the last block before the street ends at SW Market Street

OVERALL FINDINGS

- Option 3 (narrow to one travel lane) is recommended for further consideration. It is expected to have a minimal impact on the surrounding transportation system throughout a typical day, and current arrival and departure patterns for patrons during events.

¹ Field observations were conducted on Friday, May 2nd, 2025 while events were occurring at both the Keller Auditorium and Arlene Schnitzer Concert Hall. SIX - The Musical was occurring at Keller Auditorium, and had an attendance of 2,817, which was 94 percent of capacity. The Trisha Paytas Tour was occurring at the Arlene Schnitzer Concert Hall, and it was also heavily sold at near capacity.

- Vehicles will continue to have access along this segment of SW 3rd Avenue between SW Clay Street and SW Market Street at all times.
- Some added congestion may occur as vehicles maneuver between the travel lane and loading lane and temporarily block the movement of vehicles with a single lane configuration.
- A single travel lane would restrict left turn movements onto SW Market Street as a single lane movement. The traffic count showed approximately 100 vehicles during the PM peak hour, and a single lane should be able to provide adequate capacity for this turn. The intersection is controlled by a traffic signal with a simple two-phase control (SW Market Street has green or SW 3rd Avenue has green). This control allows for efficient movement of traffic. Intersections with a single left turn lane often have turn movements much higher than 100 vehicles per hour. In this case, there are no conflicting pedestrian movements, and a single lane should be able to provide adequate capacity for the left turn onto Market Street. If congestion and vehicles queued on SW Market Street limit vehicles turning from SW 3rd Avenue, this phenomenon may occur regardless of SW 3rd Avenue having one or two lanes.
- A configuration to pilot test a single lane closure of SW 3rd Avenue could be coordinated with PBOT.
- Option 1 has the most impact on the surrounding transportation system, although it will only be slightly more impactful than Option 2.
 - Vehicles will not have access along this segment of SW 3rd Avenue between SW Clay Street and SW Market Street during events for both Options, and throughout the remainder of the day for Option 1.
 - Vehicles would have to reroute to adjacent travel routes to reach SW Market Street, such as via SW 5th Avenue or SW 1st Avenue. Although the traffic count data along these routes suggests that this shift would have a minor impact on operations.
 - Both Options 1 and 2 would require patron drop-off during events to occur elsewhere with the closure of SW 3rd Avenue during events. This could potentially occur along the frontage of SW Clay Street where some of the existing on-street parking could be redesignated to serve as a loading zone.

SCENARIO 2: CONSTRUCT A NEW VENUE AT PSU

- Construct a new Performing Arts Center along SW Lincoln Street just east of SW 4th Avenue.
 - Two venues are proposed with a total capacity of 4,200 seats:
 - 3,000 seat performing arts center facility
 - 1,200 seat event venue

CURRENT CONDITIONS

- Since the use does not currently exist, these venues would add additional traffic
 - During sold-out events, the proposed venues are expected to generate an estimated:
 - 1,474 pre-event peak and 1,566 post-event peak motor vehicle trips
 - 202 pre-event peak and 214 post-event peak transit, walking, or biking trips
- Existing traffic volume data at the SW 4th Avenue/SW Lincoln Street intersection during the anticipated pre-event peak hour (i.e., 6:30-7:30 p.m.) indicated that utilization is minimal.

- This included 348 vehicles on the northbound I-405 exit ramp and SW 4th Avenue approach, of which 51 turned right from the I-405 exit ramp to SW Lincoln Street where the proposed venue will add more trips traveling to the new proposed on-site parking garage
- Existing observations indicate that the SW 4th Avenue/SW Lincoln Street intersection operates well, with minimal delay observed for vehicles during the anticipated pre-event peak hour.
- Existing vehicular parking is available in the area with over 3,000 spaces within a five-block walk.
- A MAX station is located adjacent to the site, as well as two pedestrian paths located along the alignment of SW 2nd Avenue and SW 3rd Avenue.

KEY ISSUES

- Vehicular access will be constrained from SW Lincoln Street to a proposed on-site parking garage with 740 spaces.
 - MAX platform and tracks on SW Lincoln Street to north
 - No site access to the east (existing development) or west / south (I-405 exit ramp)
- Potential for increased vehicular congestion and queuing at the SW Lincoln Street/SW 4th Avenue intersection and I-405 exit ramp during the peak event arrival and departure periods. Traffic spilling back onto I-405 from the SW 4th Avenue off ramp is likely the most critical traffic issue to be addressed and will require additional study and coordination with ODOT.
 - Trip distribution data shows that approximately 36% of trips would travel from the south, of which a majority will likely use the I-405 exit ramp (i.e., assumed as 75%) which would potentially add 374 trips to the I-405 ramp during the pre-arrival peak hour. Additional traffic analysis would be required to determine the potential impacts to the ramp and potential for vehicle queues to reach I-405 mainline.
 - The remainder of these trips from the south (i.e., 25% or 125 pre-arrival peak hour trips) would likely use SW Naito Parkway or S Harbor Drive to reach the proposed PSU venues and nearby parking.
- There is potential for conflicts between pedestrians and vehicular traffic at the pedestrian crossing on SW Lincoln Street adjacent to the Lincoln Street/SW 3rd Avenue MAX stop.

POTENTIAL OPPORTUNITIES

- Various opportunities could be considered to improve vehicle flow to the site and manage the potential for traffic queues on the I-405 off-ramp.
 - SW Lincoln Street Site Access
 - Locate the site access as far as possible to the east along the site frontage to maximize queue storage potential
 - Add an eastbound right turn lane to enter the site and avoid blocking through traffic on SW Lincoln Street
 - Provide an additional curb loading lane on SW Lincoln Street for drop off

- Consider alternative signal timing and/or turn restrictions at the intersection, including the potential restriction of westbound left turn movements during and before events
- Maximize vehicle queue storage and maintain circulation on site to reduce opportunity for vehicles entering the site to spill back to SW Lincoln Street
- Consider treatments to manage the conflicts between pedestrians crossing SW Lincoln Street and vehicles entering the site
- SW 4th Avenue at Lincoln Street
 - Consider opportunities to modify the intersection to improve flow for the right turn from SW 4th Avenue to SW Lincoln Street. Currently vehicles cannot turn on red.
 - Signing and wayfinding to direct some from SW 4th Avenue to park elsewhere and continue straight on SW 4th Avenue rather than turning at SW Lincoln Street. This may include dynamic parking signs that indicate where additional parking supplies exists.

OVERALL FINDINGS

- Since the use does not currently exist, these venues would add additional traffic. However, traffic would be arriving from multiple directions and locations and could likely be managed.
- The SW 4th Avenue off-ramp from I-405 will require additional study and coordination with ODOT to address concerns about potential vehicle queue spillback onto the I-405 mainline.
- Opportunities to manage the potential for vehicle queues on the I-405 ramp were identified and could be considered through the site refinement process. The feasibility and effectiveness of each option will likely depend on other site conditions and constraints.

FINDINGS AND NEXT STEPS

In summary, this study did not identify any fatal flaws for either site but did identify various opportunities and challenges with potential considerations for future site refinement to enable site function. Based on the transportation study, the following summarizes the overall findings and potential next steps.

SUMMARY OF FINDINGS

1. Both the renovation of the Keller site and the construction of a new PSU site share two common benefits:
 - a. the traffic activity generally occurs outside of key congestion periods; and
 - b. the central location within the region means that patron travel will be spread more evenly among regional travel routes.

Key Takeaway—This decreases the opportunity for significant negative traffic impacts (such as congestion, bottlenecks, closures, etc.).

2. We collected information to help us learn how a new performing arts center might affect traffic. This includes how many cars are already on nearby roads, how many more car trips the center would cause, what time those trips would happen, and which roads people would use.

Key Takeaway— This new data can be used to support detailed traffic analysis for either site.

3. The Keller site is already in operation and is not expected to add more traffic to the system. However, the PSU site would bring new trip activity, either by replacing the Keller site or adding to it. Portland City Code 17.88.050 requires traffic studies for development that exceeds 100 vehicle trips during an hour in the peak direction. This threshold would be triggered if a new performing arts center is built at PSU – through the details of the traffic study and requirements may depend on whether the Keller site stays open or if the PSU site takes its place.

Key takeaway—Additional coordination with PBOT and ODOT staff would be needed to determine the specific requirements of a traffic study that may be needed for the PSU site to address the requirements of Portland City Code 17.88.050.

4. A review of traffic volumes on SW 3rd Avenue indicates that the street could be a candidate for a lane reduction to improve pedestrian circulation and safety adjacent to the Keller site.

Key takeaway—Reducing traffic to one lane on this portion of SW 3rd Avenue could be a candidate for a pilot project with PBOT.

5. As the PSU site plan and design develops, the key traffic element to address will likely be reducing the potential for vehicle queuing on the SW 4th Avenue off ramp.

Key takeaway—Focusing on reducing the potential of vehicle queuing on the SW 4th Avenue off-ramp through the positioning of the site entry, maintaining traffic flow at site entry, and alerting patrons of other parking opportunities, for example, will be critical to reduce negative traffic impacts on this site.

RECOMMENDED NEXT STEPS

1. Lane Reduction Pilot Project at Existing Keller Site—Coordinate with PBOT staff to implement a pilot project that temporarily reduces the number of lanes on SW 3rd Avenue to one travel lane (and additional loading zone) between SW Clay Street and SW Market Street. The duration and implementation of this pilot should be determined by traffic engineers at PBOT.
2. Incorporate Traffic Impact Reduction Treatments at PSU Site as Project Design Advances—As site design advances, consider incorporating treatments that would reduce the potential for vehicle queuing on the SW 4th Avenue off-ramp. Additional coordination with PBOT and ODOT staff would be needed to determine the specific requirements of a traffic study that may be needed for the PSU site to address the requirements of Portland City Code 17.88.050.

TECHNICAL APPENDIX

The following sections include additional technical material and detail.

POTENTIAL PERFORMING ARTS CENTER SCENARIOS

High-level transportation opportunities and constraints were evaluated for the following three performing arts center scenarios:

1. Renovate the existing Keller Auditorium
 - Assumes similar venue capacity (3,000 seats), event flows and arrival/departure patterns for patrons as the existing facility
2. Build a new Performing Arts Facility along SW Lincoln Street, just east of SW 4th Avenue
 - New Performing Arts Center along SW Lincoln Street
 - Two venues proposed:
 - 3,000 seat performing arts center facility
 - 1,200 seat event venue
 - New parking garage with 740 parking spaces
3. Renovate the existing Keller Auditorium and Build a new Performing Arts Facility at Portland State University
 - Includes the assumptions listed under Scenarios 1 and 2

EXISTING SITE OBSERVATIONS

Field observations were conducted on Friday, May 2nd, 2025 while events were occurring at both the Keller Auditorium and Arlene Schnitzer Concert Hall. Both events were sold to near capacity², and these observed conditions were assumed to closely represent those that may occur during Scenario 3, when events may occur at both a renovated existing Keller Auditorium and the new Performing Arts Facility at Portland State University. Observations were made during the pre-event arrival period between 5:00 p.m. and 7:30 p.m., with doors opening at 6:30 p.m. and the showtime at 7:30 p.m.

² SIX - The Musical was occurring at Keller Auditorium, and had an attendance of 2,817, which was 94 percent of capacity. The Trisha Paytas Tour was occurring at the Arlene Schnitzer Concert Hall, and it was also heavily sold at near capacity.

Key observations from these events are summarized below:

- Some patrons arrived early for food service at Keller Auditorium between 5:00-6:00 p.m., and then most patrons arrived just before showtime between 6:30-7:30 p.m.
- Pedestrian queueing occurred at the SW 3rd Avenue and SW Clay Street entrances.
- Pedestrians walking from nearby parking garages are frequently using crosswalks on SW Market Street and SW Clay Street at SW 3rd Avenue, and conflicting with vehicular traffic along these streets. With adjacent parking garages located kitty-corner from the Keller venue, pedestrians typically cross two legs of the intersection to arrive at the front door.
- Vehicular queueing was observed at nearby parking garage entrances, particularly along SW 3rd Avenue extending from the entry to the Auditorium Garage through the SW Columbia Street and SW Jefferson Street intersections. This was most noteworthy during the pre-event peak hour between 6:30-7:30 p.m.
- Some vehicular queueing was observed along SW Clay Street at the SW 1st Avenue intersection around 7:00 p.m., and it was noted that there was minimal traffic on the SW 1st Avenue approaches during this time.
- Minimal vehicular queueing was observed along SW Market Street during the observation period.

TRIP DISTRIBUTION

The regional origin/destination of trips for patrons of SIX - The Musical at Keller Auditorium was also obtained. This data for nearly 1,800 account holders was based on home area codes and revealed that about:

- 22 percent of patrons travel to/from the north of downtown Portland (e.g., N/NE Portland, Vancouver)
- 36 percent to/from the south of downtown Portland (e.g., SW Portland, Tigard, Lake Oswego)
- 21 percent to/from the east of downtown Portland (e.g., E/SE Portland, Happy Valley)
- 21 percent to/from the west of downtown Portland (e.g., NW Portland, Beaverton, Hillsboro).

PARKING

Available data from nearby parking garages was also reviewed to estimate arrival times for patrons³. This data is limited in scope but provides a representative view of the number of patrons who may arrive at the nearby parking garages and immediately head to the show and those who may arrive a little earlier and patron nearby businesses before heading to the show. Based on an

³ Parking data from 200 Market Garage, Auditorium Garage, Crown Plaza Garage and Fifth Avenue Building was provided, although time stamped entry data was only available for the 200 Market Garage.

analysis of vehicles entering the garage within four hours of showtime⁴, 80 percent of patrons are estimated to arrive during the pre-event peak hour before showtime, with the remaining 20 percent of patrons estimated to arrive two to three hours before showtime.

TRIP ESTIMATES

The estimated trips generated by the proposed venue will be based on programming information provided by the venue operators. The following assumptions are proposed to be used to generate vehicle trips from the existing and proposed venues.

EVENT CHARACTERISTICS

The existing Keller Auditorium and the proposed PSU Performing Arts Center Facility will have a maximum attendance capacity of approximately 3,000 people, while the proposed PSU Event venue will have a maximum attendance capacity of approximately 1,200 people (see Table 1).

Events are primarily anticipated to occur during the weekday and weekend evening hours. Typically, the doors for events will open at 6:30 p.m. and the show will start at approximately 7:30 p.m. and conclude at approximately 10:00 p.m.

TABLE 1: EVENT CHARACTERISTICS OF PERFORMING ARTS CENTER FACILITIES

VENUE		ATTENDANCE (MAXIMUM)
KELLER AUDITORIUM		3,000
PROPOSED PSU PERFORMING ARTS CENTER FACILITY		3,000
PROPOSED PSU EVENT VENUE		1,200
TYPICAL SHOW SCHEDULE		
6:30 P.M.	Doors open to the venue	
7:30 P.M.	Show begins	
10:00 P.M.	Show ends	

TOTAL TRIPS GENERATED BY SOLD-OUT EVENTS

⁴ It was assumed that vehicles entering garages earlier in the day were likely not related to shows occurring in the evening, so only entry data within four hour of the showtime were considered.

The total estimated trips generated by the venues during sold-out events occurring simultaneously at the three venues (i.e., 7,200 total attendees) are shown in Table 2. As shown, the venues are expected to generate 5,760 pre-event peak trips and 6,120 post-event peak trips.

Pre-event peak hour attendee arrivals are estimated at 80 percent of total attendee arrivals (i.e., 5,760 attendees for a sold-out event), while post-event peak hour attendee departures are estimated at 85 percent of total attendee departures (i.e., 6,120 attendees for a sold-out event)⁵.

TABLE 2: PEAK HOUR PERSON TRIPS FOR SOLD-OUT EVENTS

VENUE	PRE-EVENT PEAK HOUR (6:30-7:30 P.M.)			POST-EVENT PEAK HOUR (10 P.M. -11 P.M.)		
	IN	OUT	TOTAL	IN	OUT	TOTAL
KELLER AUDITORIUM	2,400	0	2,400	0	2,550	2,550
PROPOSED PSU PERFORMING ARTS CENTER	2,400	0	2,400	0	2,550	2,550
PROPOSED PSU EVENT VENUE	960	0	960	0	1,020	1,020
TOTAL	5,760	0	5,760	0	6,120	6,120

Source: Attendee arrival and departure information based on sold-out events, with 80 percent of total attendee arrivals during the pre-event peak hour and 85 percent departing during the post-event peak hour.

Mode Choice of Trips

A door survey was completed at Keller Auditorium during the pre-event arrival period (i.e., 5:00 to 7:30 p.m.) that interviewed 320 groups totaling 787 patrons. This represented nearly 30 percent of the patrons for the show, with the results summarized in Table 3. The surveyed patrons arrived mostly via private vehicle (i.e., 88 percent or 692 people) or drop-off vehicle trips (i.e., 6 percent or 45 people), with the remaining 6 percent using transit (4 percent), walking (2 percent) or biking (less than 1 percent).

⁵ Arrival patterns are estimated based on parking information provided by the parking garage operators. Departure patterns are estimated

TABLE 3: PRE EVENT TRIPS BY MODE FOR EVENT AT KELLER AUDITORIUM

TRAVELER TYPE	PRE-EVENT ARRIVAL PERIOD (5:00-7:30 P.M.)	
	TOTAL PEOPLE	MODE SHARE
TOTAL ATTENDEE TRIPS *	787	100%
TRANSIT TRIPS	31	4%
WALKING TRIPS	16	2%
BIKING TRIPS	3	0%
PRIVATE VEHICLE TRIPS	692	88%
DROP OFF VEHICLE TRIPS	45	6%

Notes: * Estimates based on door survey of patrons at Keller Auditorium during the pre-event arrival period for SIX - The Musical between 5:00 p.m. and 7:30 p.m. on Friday, May 2nd, 2025.

As shown in Table 4, the venues are estimated to generate 2,872 pre-event peak and 3,051 post-event peak trips, including 346 pre-event peak and 367 post-event peak transit, walking, or biking trips, and 2,526 pre-event peak and 2,684 post-event peak motor vehicle trips. Of these trips, 202 pre-event peak and 214 post-event peak transit, walking, or biking trips, and 1,474 pre-event peak and 1,566 post-event peak motor vehicle trips would be traveling to/from the proposed PSU venues, with the remaining trips (i.e., 144 pre-event peak and 153 post-event peak transit, walking, or biking trips, and 1,053 pre-event peak and 1,118 post-event peak motor vehicle trips) traveling to/from the Keller Auditorium as they do today for sold-out events.

TABLE 4: PEAK HOUR TRIPS BY MODE FOR SOLD-OUT EVENTS

TRAVELER TYPE	PRE-EVENT PEAK HOUR (6:30-7:30 P.M.)			POST-EVENT PEAK HOUR (10 P.M. -11 P.M.)		
	IN	OUT	TOTAL	IN	OUT	TOTAL
KELLER AUDITORIUM ATTENDEE TRIPS **	1,133	63	1,197	67	1,204	1,271
TRANSIT TRIPS (4 PERCENT)	96	0	96	0	102	102
WALKING TRIPS (1.5 PERCENT)	36	0	36	0	38	38
BIKING TRIPS (0.5 PERCENT)	12	0	12	0	13	13
PRIVATE VEHICLE TRIPS (88 PERCENT) *	926	0	926	0	984	984
DROP OFF VEHICLE TRIPS (6 PERCENT) *	63	63	126	67	67	134
PROPOSED PSU PERFORMING ARTS CENTER ATTENDEE TRIPS **	1,133	63	1,197	67	1,204	1,271
TRANSIT TRIPS (4 PERCENT)	96	0	96	0	102	102
WALKING TRIPS (1.5 PERCENT)	36	0	36	0	38	38
BIKING TRIPS (0.5 PERCENT)	12	0	12	0	13	13
PRIVATE VEHICLE TRIPS (88 PERCENT) *	926	0	926	0	984	984
DROP OFF VEHICLE TRIPS (6 PERCENT) *	63	63	126	67	67	134
PROPOSED PSU EVENT VENUE ATTENDEE TRIPS **	453	25	479	27	482	509
TRANSIT TRIPS (4 PERCENT)	38	0	38	0	41	41
WALKING TRIPS (1.5 PERCENT)	14	0	14	0	15	15
BIKING TRIPS (0.5 PERCENT)	5	0	5	0	5	5
PRIVATE VEHICLE TRIPS (88 PERCENT) *	371	0	371	0	394	394
DROP OFF VEHICLE TRIPS (6 PERCENT) *	25	25	51	27	27	54
TOTOAL ATTENDEE TRIPS **	2,720	152	2,872	161	2,890	3,051
TRANSIT TRIPS (4 PERCENT)	230	0	230	0	245	245
WALKING TRIPS (1.5 PERCENT)	86	0	86	0	92	92
BIKING TRIPS (0.5 PERCENT)	29	0	29	0	31	31
PRIVATE VEHICLE TRIPS (88 PERCENT) *	2,223	0	2,223	0	2,362	2,362
DROP OFF VEHICLE TRIPS (6 PERCENT) *	152	152	303	161	161	322

Notes: * Average vehicle occupancy was estimated at 2.28 persons per vehicle for attendees based on a survey of attendees at Keller Auditorium.

** Estimates derived from sold out events occurring simultaneously at all three venues.

EXISTING TRAFFIC VOLUMES

Traffic volume data was collected along streets in the vicinity of the Keller Auditorium and proposed PSU venues to better understand current travel patterns. The data included turn movement volumes at intersections and average daily traffic volumes along street segments. A summary of the data from a few key locations is provided below:

SW 3rd Avenue between SW Clay Street and SW Market Street

- Segment adjacent to Keller Auditorium
- Average daily traffic volume: 2,537
- AM Peak hour volume: 53
- PM Peak hour volume: 100

SW Clay Street between SW 3rd Avenue and SW 2nd Avenue

- Segment adjacent to Keller Auditorium
- Average daily traffic volume: 6,686
- AM Peak hour volume: 140
- PM Peak hour volume: 146

SW Market Street between SW 4th Avenue and SW 3rd Avenue

- Segment approaching Keller Auditorium
- Average daily traffic volume: 6,464
- AM Peak hour volume: 166
- PM Peak hour volume: 186

SW 4th Avenue/ SW Lincoln Street

- Intersection adjacent to proposed PSU venues
- Data collected from 6:00-8:00 p.m. to coincide with the pre-arrival period for evening events
- Existing traffic volume data at the SW 4th Avenue/SW Lincoln Street intersection during the anticipated pre-event peak hour (i.e., 6:30-7:30 p.m.) indicated that utilization is minimal.
- 348 vehicles on the northbound I-405 exit ramp and SW 4th Avenue approach, of which 51 turned right from the I-405 exit ramp to SW Lincoln Street where the proposed venue will add more trips traveling to the new proposed on-site parking garage
- 71 vehicles on the eastbound SW Lincoln Street approach
- 83 vehicles on the westbound SW Lincoln Street approach

