Source: https://developers.hubtel.com/docs/business/api_documentation/payment_apis/direct_debit_money

Direct Debit Money

Last updated September 18th, 2026

Overview

The **Hubtel Sales API** allows you to sell goods and services online, in-store and on mobile. With a single integration, you can:

1. Accept mobile money payments on your application, sell services in-store, online and on mobile as well as process all your sales on your Hubtel account.
2. Send money to your customers.

This API can be used to provide a range of services including: processing e-commerce payments, mobile banking, bulk payments and more. You can also accept payments for goods and services into your account.

The following provides an overview of the **Direct Debit API** endpoints for interacting programmatically within your application.

Available Channels

The following are the available channels through which a merchant can **directly debit** money from a Mobile Money wallet into their Hubtel Merchant Account.

Mobile Money Provider	Channel Name
MTN Ghana	**mtn-gh-direct-debit**
Telecel Ghana	**vodafone-gh-direct-debit**

Getting Started

Business IP Whitelisting

You must share your public IP address with your Retail System Engineer for whitelisting.

Note

All API Endpoints are live and only requests from whitelisted IP(s) can reach these endpoints shared in this reference.

Requests from IP addresses that have not been whitelisted will return a **403 Forbidden** error response or a **timeout**.

We permit a maximum of 4 IP addresses per service.

Understanding the Service Flow

The Hubtel Direct Debit API service consist of **two (2) main** flows which are used together to setup a direct debit on a mobile wallet. The **last one (1)** is used to check transaction status of a debit transaction. These are:

- Direct Debit Preapproval Process: This process allows you to gain customer authorization by the customer's involvement through either USSD prompt authorization or an OTP code. This is a one-time process for a mobile wallet per a Merchant account. Preapproval has 3 sub-processes.
- Direct Debit Charge API: This allows you to directly debit a mobile wallet without any OTP or Mobile Money PIN. This is only successful when preapproval process is completed by customer for your Hubtel merchant account.
- Transaction Status Check API: REST API to check for the status of any debit transaction initiated after five (5) or more minutes of the debit transaction's completion. It is mandatory to implement the Transaction Status Check API only for transactions that you do not receive a callback from Hubtel.

The table below describes the steps involved in using the Direct Debit API:

Step	Description
1	Client App makes a Preapproval request to Hubtel.
2	Hubtel performs authentication on the request and sends a response to Client App accordingly.
3	Once preapproval process is successful, Client App makes a Direct Debit Charge request to Hubtel.
4	A final callback is sent to Client App via the callbackUrl provided in the request. (See sample callback here)
5	In instances where a merchant does not receive the final status of the transaction **after five (5) minutes** from Hubtel, it is **mandatory** to perform a status check using the Status Check API to determine the final status of the transaction. (Refer here)

API Reference

Direct Debit Preapproval Process allows you to gain customer authorization by the customer's involvement through an OTP code and a PIN confirmation. The preapproval process has **three sub-processes** which ensure completion of a preapproval.

Note

The preapproval process must be completed once for every mobile wallet you want to directly debit.

Initiate Process

To initiate a Direct Debit transaction, send an HTTP **POST** request to the below URL with the required parameters. It is also **mandatory** to pass your **Collection Account Number** for Direct Debit requests in the endpoint. Find your **Collection Account Number** here.

API Endpoint	https://preapproval.hubtel.com/api/v2/merchant/{Collection_Account_Number}/preapproval/initiate
Request Type	**POST**
Content Type	**JSON**

REQUEST PARAMETERS

Parameter	Type	Requirement	Description
clientReferenceId	String	Mandatory	The reference provided by the API user and must be **unique for every transaction** and preferably be **alphanumeric** characters. Maximum length is **36 characters**.
CustomerMsisdn	String	Mandatory	The customer's mobile money number. This should be in the international format without plus(+). **E.g.: "233249111411"**
channel	String	Mandatory	The mobile money channel provider. Available channels are: **mtn-gh-direct-debit**, **vodafone-gh-direct-debit**
callbackUrl	String	Mandatory	The URL expected to receive callback on the final status of a payment from Hubtel.

Note

Kindly note that a **clientReference** must never be duplicated for any transaction.

SAMPLE REQUEST

HTTP

```
POST /api/v2/merchant/11684/preapproval/initiate HTTP/1.1
Host: preapproval.hubtel.com
Accept: application/json
Content-Type: application/json
Authorization: Basic endjeOBiZHhza250fT3==
Cache-Control: no-cache
{
    "clientReferenceId": "3jL2KlUy3vt21debitC",
    "customerMsisdn": "233200000000",
    "channel": "vodafone-gh-direct-debit",
    "callbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede"
}
```

cURL

```
curl --location 'https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/initiat
e' \
--header 'Content-Type: application/json' \
--header 'Authorization: Basic endjeOBiZHhza250fT3==' \
--data '{
  "clientReferenceId": "3jL2KlUy3vt21debitC",
  "customerMsisdn": "233200000000",
  "channel": "vodafone-gh-direct-debit",
  "callbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede"
}'
```

PHP

```
<?php

$curl = curl_init();

curl_setopt_array($curl, array(
  CURLOPT_URL => 'https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/initia
te',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_ENCODING => '',
  CURLOPT_MAXREDIRS => 10,
  CURLOPT_TIMEOUT => 0,
  CURLOPT_FOLLOWLOCATION => true,
  CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
  CURLOPT_CUSTOMREQUEST => 'POST',
  CURLOPT_POSTFIELDS =>'{
  "clientReferenceId": "3jL2KlUy3vt21debitC",
  "customerMsisdn": "233200000000",
```

```
  "channel": "vodafone-gh-direct-debit",
  "callbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede"
}',
  CURLOPT_HTTPHEADER => array(
    'Content-Type: application/json',
    'Authorization: Basic endjeOBiZHhza250fT3=='
  ),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
```

Python

```
import requests
import json

url = "https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/initiate"

payload = json.dumps({
  "clientReferenceId": "3jL2KlUy3vt21debitC",
  "customerMsisdn": "233200000000",
  "channel": "vodafone-gh-direct-debit",
  "callbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede"
})
headers = {
  'Content-Type': 'application/json',
  'Authorization': 'Basic endjeOBiZHhza250fT3=='
}

response = requests.request("POST", url, headers=headers, data=payload)

print(response.text)
```

JavaScript - Fetch

```
const myHeaders = new Headers();
myHeaders.append("Content-Type", "application/json");
myHeaders.append("Authorization", "Basic endjeOBiZHhza250fT3==");

const raw = JSON.stringify({
  "clientReferenceId": "3jL2KlUy3vt21debitC",
  "customerMsisdn": "233200000000",
  "channel": "vodafone-gh-direct-debit",
  "callbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede"
});

const requestOptions = {
  method: "POST",
  headers: myHeaders,
  body: raw,
  redirect: "follow"
};

fetch("https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/initiate", reques
tOptions)
```

```
  .then((response) => response.text())
  .then((result) => console.log(result))
  .catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
message	String	The description of response received from the Direct Debit API that is related to the ResponseCode.
responseCode	String	The unique response code on the status of the transaction.
data	Object	An object containing the required data response from the API.
hubtelPreApprovalId	String	The verification preapproval ID which is received in the initiate process response.
clientReferenceId	String	The reference provided by the API user and must be **unique** and **preferably** be **alphanumeric** characters. Maximum length is **36 characters**.
verificationType	String	The verification type; can be **USSD** or **OTP**.
otpPrefix	String	First part of **OTP** sent to customer; **null** when verificationType is **USSD**.
preapprovalStatus	String	Status of the preapproval eg: **APPROVED**, **REJECTED**, **PENDING** (will eventually have final status).

SAMPLE INITIATE PROCESS RESPONSE (USSD)

200 OK


```
{
    "message": "Request received! Pending preapproval",
    "responseCode": "2000",
    "data": {
        "hubtelPreApprovalId": "5f20092321d54eefb974dbfea6de5c34",
        "clientReferenceId": "3jL2KlUy3vt21debitC",
        "verificationType": "USSD",
        "otpPrefix": null,
        "preapprovalStatus": "PENDING"
    }
}
```

SAMPLE INITIATE PROCESS RESPONSE (OTP)

200 OK


```
{
    "message": "Request received! Pending preapproval",
    "responseCode": "2000",
    "data": {
        "hubtelPreApprovalId": "5f20092321d54eefb974dbfea6de5c34",
        "clientReferenceId": "3jL2KlUy3vt21debitC",
        "verificationType": "OTP",
        "otpPrefix": "HNRM",
        "preapprovalStatus": "PENDING"
    }
}
```


Verify Process

The next process is to verify or authorize a preapproval request after initiate process request is made. This comes in two forms **USSD** or **OTP** which is **not selectable**.

USSD

This verificationType is for a number which is new. For verifying Preapproval, the number receives a **USSD prompt** which the number must approve to confirm authorization. ***OTP verification is to be skipped***.

Note

For MTN numbers, all pending requests are accessible in the preapprovals list on ***170#**. Your customers can use this feature in case they do not get a prompt after a preapproval request. Steps;

1. Dial ***170#**
2. Navigate to **6. My Wallet**
3. Choose **3. My Approvals**
4. Select **2. PreApprovals**
5. Approve

OTP

This verificationType is for a number which has **already been preapproved** by another Merchant. In this case, the number gets an OTP with a 4-digit code you'll need in verifying the customer.

To verify an **OTP**, send an HTTP **POST** request to the below URL with the required parameters:

API Endpoint	https://preapproval.hubtel.com/api/v2/merchant/{Collection_Account_Number}/preapproval/verifyotp
Request Type	**POST**
Content Type	**JSON**

REQUEST PARAMETERS

Parameter	Type	Requirement	Description
customerMsisdn	String	Mandatory	The customer's mobile money number. This should be in the international format without plus(+). **E.g.: "233249111411"**
hubtelPreApprovalId	String	Mandatory	The verification preapproval ID which is received in the initiate process response.
clientReferenceId	String	Mandatory	The reference provided by the API user and must be **unique for every transaction** and preferably be **alphanumeric** characters. Maximum length is **36 characters**.
otpCode	String	Mandatory	The OTP code used for verification. It consists of the four letter otpPrefix received in the initiate process response and the four digit OTP code sent to the customer. **Eg:"RTYE-9231"**.

SAMPLE VERIFY OTP REQUEST

HTTP

```
POST /api/v2/merchant/11684/preapproval/verifyotp HTTP/1.1
Host: preapproval.hubtel.com
Accept: application/json
Content-Type: application/json
Authorization: Basic endjeOBiZHhza250fT3==
Cache-Control: no-cache

{
  "customerMsisdn": "233200000000",
```

```
  "hubtelPreApprovalId": "5f20092321d54eefb974dbfea6de5c34",
  "clientReferenceId": "3jL2KlUy3vt21debitC",
  "otpCode": "HNRM-8852"
}
```

cURL

```
curl --location 'https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/verifyotp' \
--header 'Content-Type: application/json' \
--header 'Authorization: Basic endjeOBiZHhza250fT3==' \
--data '{
    "customerMsisdn": "233200000000",
    "hubtelPreApprovalId": "5f20092321d54eefb974dbfea6de5c34",
    "clientReferenceId": "3jL2KlUy3vt21debitC",
    "otpCode": "HNRM-8852"
}'
```

PHP

```
<?php

$curl = curl_init();

curl_setopt_array($curl, array(
  CURLOPT_URL => 'https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/verifyotp',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_ENCODING => '',
  CURLOPT_MAXREDIRS => 10,
  CURLOPT_TIMEOUT => 0,
  CURLOPT_FOLLOWLOCATION => true,
  CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
  CURLOPT_CUSTOMREQUEST => 'POST',
  CURLOPT_POSTFIELDS =>'{
    "customerMsisdn": "233200000000",
    "hubtelPreApprovalId": "5f20092321d54eefb974dbfea6de5c34",
    "clientReferenceId": "3jL2KlUy3vt21debitC",
    "otpCode": "HNRM-8852"
}',
  CURLOPT_HTTPHEADER => array(
    'Content-Type: application/json',
    'Authorization: Basic endjeOBiZHhza250fT3=='
  ),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
```

Python

```
import requests
import json

url = "https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/verifyotp"
```

```python
payload = json.dumps({
  "customerMsisdn": "233200000000",
  "hubtelPreApprovalId": "5f20092321d54eefb974dbfea6de5c34",
  "clientReferenceId": "3jL2KlUy3vt21debitC",
  "otpCode": "HNRM-8852"
})
headers = {
  'Content-Type': 'application/json',
  'Authorization': 'Basic endjeOBiZHhza250fT3=='
}

response = requests.request("POST", url, headers=headers, data=payload)

print(response.text)
```

JavaScript - Fetch

```javascript
const myHeaders = new Headers();
myHeaders.append("Content-Type", "application/json");
myHeaders.append("Authorization", "Basic endjeOBiZHhza250fT3==");

const raw = JSON.stringify({
  "customerMsisdn": "233200000000",
  "hubtelPreApprovalId": "5f20092321d54eefb974dbfea6de5c34",
  "clientReferenceId": "3jL2KlUy3vt21debitC",
  "otpCode": "HNRM-8852"
});

const requestOptions = {
  method: "POST",
  headers: myHeaders,
  body: raw,
  redirect: "follow"
};

fetch("https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/verifyotp", reque
stOptions)
  .then((response) => response.text())
  .then((result) => console.log(result))
  .catch((error) => console.error(error));
```

SAMPLE VERIFY OTP RESPONSE

200 OK

```
  {
    "message": "OTP Verified! Pending preapproval",
    "responseCode": "2000",
    "data": {
      "hubtelPreApprovalId": "5f20092321d54eefb974dbfea6de5c34",
      "preapprovalStatus": "PENDING"
    }
  }
```

Preapproval Callback

Since the Preapproval Process has an **asynchronous flow** on all networks, Hubtel mandatory sends callback payload to the callbackURL specified in the Initiate Process for their final status. Hence the callback URL you specified in the Initiate Process request should be implemented to listen for HTTP **POST** payload from Hubtel.

SAMPLE CALLBACK (Approved)

JSON


```json
{
  "CustomerMsisdn": "233200000000",
  "VerificationType": "USSD",
  "PreapprovalStatus": "APPROVED",
  "HubtelPreapprovalId": "5f20092321d54eefb974dbfea6de5c34",
  "ClientReferenceId": "3jL2KlUy3vt21debitC",
  "CreatedAt": "2022-11-14T21:08:16.7533466Z"
}
```


SAMPLE CALLBACK (Failed)

JSON


```json
{
  "CustomerMsisdn": "233200000000",
  "VerificationType": "OTP",
  "PreapprovalStatus": "FAILED",
  "HubtelPreapprovalId": "5f20092321d54eefb974dbfea6de5c34",
  "ClientReferenceId": "3jL2KlUy3vt21debitC",
  "CreatedAt": "2022-11-14T21:08:16.7533466Z"
}
```


Preapproval Status Check

In rare instances where callback was not received due to timeout or for double confirmation, the Preapproval Status Check can be called. To check a preapproval status, send an HTTP **GET** request to the below URL with the required parameters in the endpoint. Find your **Collection Account Number** here.

API Endpoint	https://preapproval.hubtel.com/api/v2/merchant/{Collection_Account_Number}/preapproval/{clientReferenceId}/status

Request Type	**GET**
Content Type	**JSON**

SAMPLE PREAPPROVAL STATUS CHECK REQUEST

HTTP

```
GET /api/v2/merchant/11684/preapproval/3jL2KlUy3vt21debitC/status HTTP/1.1
Host: preapproval.hubtel.com
Accept: application/json
Content-Type: application/json
Authorization: Basic endjeOBiZHhza250fT3=
Cache-Control: no-cache
```

cURL

```
curl --location 'https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/3jL2KlU
y3vt21debitC/status' \
--header 'Authorization: Basic endjeOBiZHhza250fT3=='
```

PHP

```
<?php

$curl = curl_init();

curl_setopt_array($curl, array(
  CURLOPT_URL => 'https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/3jL2Kl
Uy3vt21debitC/status',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_ENCODING => '',
  CURLOPT_MAXREDIRS => 10,
  CURLOPT_TIMEOUT => 0,
  CURLOPT_FOLLOWLOCATION => true,
  CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
  CURLOPT_CUSTOMREQUEST => 'GET',
  CURLOPT_HTTPHEADER => array(
    'Authorization: Basic endjeOBiZHhza250fT3=='
  ),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
```

Python

```
import requests
```

```
url = "https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/3jL2KlUy3vt21debitC/status"

payload = {}
headers = {
  'Authorization': 'Basic endjeOBiZHhza250fT3=='
}

response = requests.request("GET", url, headers=headers, data=payload)

print(response.text)
```

JavaScript - Fetch

```
const myHeaders = new Headers();
myHeaders.append("Authorization", "Basic endjeOBiZHhza250fT3==");

const requestOptions = {
  method: "GET",
  headers: myHeaders,
  redirect: "follow"
};

fetch("https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/3jL2KlUy3vt21debitC/status", requestOptions)
  .then((response) => response.text())
  .then((result) => console.log(result))
  .catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
message	String	The description of response received from the **Direct Debit API** that is related to the ResponseCode.
responseCode	String	The unique response code on the status of the transaction.
data	Object	An object containing the required data response from the **Preapproval Process**.
customerMsisdn	String	The customer's mobile money number. This should be in the international format without plus(+). **E.g.: "233249111411"**
verificationType	String	The channel used for preapproval/verification. **E.g.: USSD**, **OTP**.
preapprovalStatus	String	Status of the preapproval eg: **APPROVED**, **FAILED**, **EXPIRED**.
hubtelPreApprovalId	String	The verification preapproval ID which is received in the initiate process response.
clientReferenceId	String	The reference provided by the API user and must be **unique** and **preferably** be **alphanumeric** characters. Maximum length is **36 characters**.

Parameter	Type	Description
createdAt	String	Date and time preapproval was initiated.

SAMPLE PREAPPROVAL STATUS CHECK RESPONSE

200 OK


```
{
  "message": "Success",
  "code": "2000",
  "data": {
    "customerMsisdn": "233546335113",
    "verificationType": "USSD",
    "preapprovalStatus": "APPROVED",
    "hubtelPreapprovalId": "5f20092321d54eefb974dbfea6de5c34",
    "clientReferenceId": "3jL2KlUy3vt21debitC",
    "createdAt": "2023-08-11T18:18:55.6439374Z"
  }
}
```


Cancel Preapproval

In instances where the need arises to revoke a customer's authorization or preapproval, there is the option to call the Cancel Preapproval. To cancel preapproval, send an HTTP **GET** request to the below URL with the required parameters in the endpoint. Find your **Collection Account Number** here.

API Endpoint	https://preapproval.hubtel.com/api/v2/merchant/{Collection_Account_Number}/preapproval/{customerMsisdn}/cancel
Request Type	**GET**
Content Type	**JSON**

SAMPLE CANCEL PREAPPROVAL REQUEST

HTTP

```
GET /api/v2/merchant/11684/preapproval/233200000000/cancel HTTP/1.1
Host: preapproval.hubtel.com
Accept: application/json
Content-Type: application/json
```

```
Authorization: Basic endjeOBiZHhza250fT3==
Cache-Control: no-cache
```

cURL

```
curl --location 'https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/233200000000/cancel' \
--header 'Authorization: Basic endjeOBiZHhza250fT3=='
```

PHP

```
<?php

$curl = curl_init();

curl_setopt_array($curl, array(
  CURLOPT_URL => 'https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/233200000000/cancel',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_ENCODING => '',
  CURLOPT_MAXREDIRS => 10,
  CURLOPT_TIMEOUT => 0,
  CURLOPT_FOLLOWLOCATION => true,
  CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
  CURLOPT_CUSTOMREQUEST => 'GET',
  CURLOPT_HTTPHEADER => array(
    'Authorization: Basic endjeOBiZHhza250fT3=='
  ),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
```

Python

```
import requests

url = "https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/233200000000/cancel"

payload = {}
headers = {
  'Authorization': 'Basic endjeOBiZHhza250fT3=='
}

response = requests.request("GET", url, headers=headers, data=payload)

print(response.text)
```

JavaScript - Fetch

```
const myHeaders = new Headers();
myHeaders.append("Authorization", "Basic endjeOBiZHhza250fT3==");

const requestOptions = {
```

```
  method: "GET",
  headers: myHeaders,
  redirect: "follow"
};

fetch("https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/233200000000/cancel", requestOptions)
  .then((response) => response.text())
  .then((result) => console.log(result))
  .catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
message	String	The description of response received from the **Cancel Preapproval API** that is related to the response code.
responseCode	String	The unique response code on the status of the transaction.
data	Object	A Boolean value related to the response code from the **Preapproval Process**.

SAMPLE CANCEL PREAPPROVAL RESPONSE

200 OK

```
  {
    "message": "Successfully cancelled preapproval for customer 233548359582 and business gershon",
    "responseCode": "2000",
    "data": true
  }
```

Reactivate Preapproval

In instances where the need arises to activate preapproval after the customer cancels, the Reactivate Preapproval API can be called. To reactivate preapproval, send an HTTP **POST** request to the below URL with the required parameters. Find your **Collection Account Number** here.

API Endpoint	https://preapproval.hubtel.com/api/v2/merchant/{Collection_Account_Number}/preapproval/reactivate
Request Type	**POST**

Content Type	**JSON**

REQUEST PARAMETERS

Parameter	Type	Description
callbackUrl	String	The URL expected to receive callback payload of Preapproval Status.
customerMsisdn	String	The customer's mobile money number. This should be in the international format without plus(+). **E.g.: "233249111411"**

SAMPLE REACTIVATE PREAPPROVAL REQUEST

HTTP

```
POST /api/v2/merchant/11684/preapproval/reactivate HTTP/1.1
Host: preapproval.hubtel.com
Accept: application/json
Content-Type: application/json
Authorization: Basic endjeOBiZHhza250fT3=
Cache-Control: no-cache

{
  "callbackUrl": "https://webhook.site/b503d1af9-e726-f315254a6ede",
  "customerMsisdn": "233200000000",
}
```

cURL

```
curl --location 'https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/reactiv
ate' \
--header 'Content-Type: application/json' \
--header 'Authorization: Basic endjeOBiZHhza250fT3==' \
--data '{
    "callbackUrl": "https://webhook.site/b503d1af9-e726-f315254a6ede",
    "customerMsisdn": "233200000000"
}'
```

PHP

```
<?php

$curl = curl_init();

curl_setopt_array($curl, array(
  CURLOPT_URL => 'https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/reacti
vate',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_ENCODING => '',
```

```
  CURLOPT_MAXREDIRS => 10,
  CURLOPT_TIMEOUT => 0,
  CURLOPT_FOLLOWLOCATION => true,
  CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
  CURLOPT_CUSTOMREQUEST => 'POST',
  CURLOPT_POSTFIELDS =>'{
    "callbackUrl": "https://webhook.site/b503d1af9-e726-f315254a6ede",
    "customerMsisdn": "233200000000"
}',
  CURLOPT_HTTPHEADER => array(
    'Content-Type: application/json',
    'Authorization: Basic endjeOBiZHhza250fT3=='
  ),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
```

Python

```
import requests
import json

url = "https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/reactivate"

payload = json.dumps({
  "callbackUrl": "https://webhook.site/b503d1af9-e726-f315254a6ede",
  "customerMsisdn": "233200000000"
})
headers = {
  'Content-Type': 'application/json',
  'Authorization': 'Basic endjeOBiZHhza250fT3=='
}

response = requests.request("POST", url, headers=headers, data=payload)

print(response.text)
```

JavaScript - Fetch

```
const myHeaders = new Headers();
myHeaders.append("Content-Type", "application/json");
myHeaders.append("Authorization", "Basic endjeOBiZHhza250fT3==");

const raw = JSON.stringify({
  "callbackUrl": "https://webhook.site/b503d1af9-e726-f315254a6ede",
  "customerMsisdn": "233200000000"
});

const requestOptions = {
  method: "POST",
  headers: myHeaders,
  body: raw,
  redirect: "follow"
};
```

```
fetch("https://preapproval.hubtel.com/api/v2/merchant/11684/preapproval/reactivate", requ
estOptions)
  .then((response) => response.text())
  .then((result) => console.log(result))
  .catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
message	String	The description of response received from the Direct Debit API that is related to the ResponseCode.
mesponseCode	String	The unique response code on the status of the transaction.
data	Object	An object containing the required data response from the API.
hubtelPreApprovalId	String	The verification preapproval ID which is received in the initiate process response.
clientReferenceId	String	The reference provided by the API user and must be **unique** and **preferably** be **alphanumeric** characters. Maximum length is **36 characters**.
verificationType	String	The verification type; can be **USSD** or **OTP**.
otpPrefix	String	First part of **OTP** sent to customer; **null** when verificationType is **USSD**.
preapprovalStatus	String	Status of the preapproval eg: **APPROVED**, **REJECTED**, **PENDING** (will eventually have final status).

SAMPLE REACTIVATE PREAPPROVAL RESPONSE

200 OK


```
{
    "message": "Request received! Pending preapproval",
    "responseCode": "2000",
    "data": {
        "hubtelPreApprovalId": "5f20092321d54eefb974dbfea6de5c34",
        "clientReferenceId": "3jL2KlUy3vt21debitC",
        "verificationType": "OTP",
        "otpPrefix": "GNCC",
        "preapprovalStatus": "PENDING"
    }
}
```

Direct Debit Charge

This allows you to directly debit a mobile wallet without any OTP or Mobile Money PIN. **This is only successful when the preapproval process is completed by the customer for your Hubtel merchant account**. Note that the flow for charging mobile subscribers differs across the various Telco networks.

To initiate a Debit Charge transaction, send an HTTP **POST** request to the below URL with the required parameters. It is also **mandatory** to pass your **Collection Account Number** for Direct Debit requests in the endpoint. Find your **Collection Account Number** here.

API Endpoint	https://rmp.hubtel.com/merchantaccount/merchants/{Collection_Account_Number}receive/mobilemoney
Request Type	POST
Content Type	JSON

REQUEST PARAMETERS

Parameter	Type	Requirement	Description
CustomerName	String	Optional	The name on the customer's mobile money wallet.
CustomerMsisdn	String	Mandatory	The customer's mobile money number. This should be in the international format. **E.g.: "233249111411"**
CustomerEmail	String	Optional	Email of customer.
Channel	String	Mandatory	The mobile money channel provider. Available channels are: **mtn-gh-direct-debit**, **vodafone-gh-direct-debit**.
Amount	Float	Mandatory	Amount of money to be debited during this transaction. **NB**: Only 2 decimal places is allowed **E.g.: 0.50**.
PrimaryCallbackURL	String	Mandatory	The URL expected to receive callback on the final status of a payment from Hubtel.
Description	String	Mandatory	A brief description of the transaction.
ClientReference	String	Mandatory	The reference provided by the API user and must be **unique for every transaction** and preferably be **alphanumeric** characters. Maximum length is **36 characters**.

Note

Kindly note that a **clientReference** must never be duplicated for any transaction.

SAMPLE DEBIT CHARGE REQUEST

HTTP

```
POST /merchantaccount/merchants/11684/receive/mobilemoney HTTP/1.1
Host: rmp.hubtel.com
Accept: application/json
Content-Type: application/json
Authorization: Basic endjeOBiZHhza250fT3==
Cache-Control: no-cache

{
    "CustomerName": "Joe Doe",
    "CustomerMsisdn": "233200000000",
    "CustomerEmail": "username@example.com",
    "Channel": "vodafone-gh-direct-debit",
    "Amount": 0.8,
    "PrimaryCallbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede",
    "Description": "Union Dues",
    "ClientReference": "3jL2KlUy3vt21"
}
```

cURL

```
curl --location 'https://rmp.hubtel.com/merchantaccount/merchants/11684/receive/mobilemon
ey' \
--header 'Content-Type: application/json' \
--header 'Authorization: Basic endjeOBiZHhza250fT3==' \
--data '{
    "CustomerName": "Joe Doe",
    "CustomerMsisdn": "233200000000",
    "CustomerEmail": "username@example.com",
    "Channel": "vodafone-gh-direct-debit",
    "Amount": 0.8,
    "PrimaryCallbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede",
    "Description": "Union Dues",
    "ClientReference": "3jL2KlUy3vt21"
}'
```

PHP

```
<?php

$curl = curl_init();

curl_setopt_array($curl, array(
  CURLOPT_URL => 'https://rmp.hubtel.com/merchantaccount/merchants/11684/receive/mobilemo
ney',
  CURLOPT_RETURNTRANSFER => true,
```

```
  CURLOPT_ENCODING => '',
  CURLOPT_MAXREDIRS => 10,
  CURLOPT_TIMEOUT => 0,
  CURLOPT_FOLLOWLOCATION => true,
  CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
  CURLOPT_CUSTOMREQUEST => 'POST',
  CURLOPT_POSTFIELDS =>'{
    "CustomerName": "Joe Doe",
    "CustomerMsisdn": "233200000000",
    "CustomerEmail": "username@example.com",
    "Channel": "vodafone-gh-direct-debit",
    "Amount": 0.8,
    "PrimaryCallbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede",
    "Description": "Union Dues",
    "ClientReference": "3jL2KlUy3vt21"
}',
  CURLOPT_HTTPHEADER => array(
    'Content-Type: application/json',
    'Authorization: Basic endjeOBiZHhza250fT3=='
  ),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
```

Python

```
import requests
import json

url = "https://rmp.hubtel.com/merchantaccount/merchants/11684/receive/mobilemoney"

payload = json.dumps({
  "CustomerName": "Joe Doe",
  "CustomerMsisdn": "233200000000",
  "CustomerEmail": "username@example.com",
  "Channel": "vodafone-gh-direct-debit",
  "Amount": 0.8,
  "PrimaryCallbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede",
  "Description": "Union Dues",
  "ClientReference": "3jL2KlUy3vt21"
})
headers = {
  'Content-Type': 'application/json',
  'Authorization': 'Basic endjeOBiZHhza250fT3=='
}

response = requests.request("POST", url, headers=headers, data=payload)

print(response.text)
```

JavaScript - Fetch

```
const myHeaders = new Headers();
myHeaders.append("Content-Type", "application/json");
myHeaders.append("Authorization", "Basic endjeOBiZHhza250fT3==");
```

```
const raw = JSON.stringify({
  "CustomerName": "Joe Doe",
  "CustomerMsisdn": "233200000000",
  "CustomerEmail": "username@example.com",
  "Channel": "vodafone-gh-direct-debit",
  "Amount": 0.8,
  "PrimaryCallbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede",
  "Description": "Union Dues",
  "ClientReference": "3jL2KlUy3vt21"
});

const requestOptions = {
  method: "POST",
  headers: myHeaders,
  body: raw,
  redirect: "follow"
};

fetch("https://rmp.hubtel.com/merchantaccount/merchants/11684/receive/mobilemoney", reque
stOptions)
  .then((response) => response.text())
  .then((result) => console.log(result))
  .catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
Message	String	The description of response received from the API that is related to the ResponseCode.
ResponseCode	String	The unique response code on the status of the transaction.
Data	Object	An object containing the required data response from the API.
TransactionId	String	The unique ID used to identify a Hubtel transaction (**from Hubtel**).
Description	String	The description initially provided by API user in the request payload.
ClientReference	String	The reference ID that is initially provided by the client/API user in the request payload (**from merchant**).
Amount	Float	The transaction amount.
Charges	Float	The charge/fee for the transaction.
AmountAfterCharges	Float	The transaction amount after charges/fees deduction.
AmountCharged	Float	The actual amount that is charged from the customer’s mobile money wallet.
DeliveryFee	Float	The delivery fee of the transaction is normally zero (0.0).

SAMPLE RESPONSE

200 OK


```
{
  "Message": "Transaction pending. Expect callback request for final state",
  "ResponseCode": "0001",
  "Data": {
    "TransactionId": "09f84e20a283942e807128e8c21d08d6",
    "Description": "Union Dues",
    "ClientReference": "3jL2KlUy3vt21",
    "Amount": 0.8,
    "Charges": 0.05,
    "AmountAfterCharges": 0.8,
    "AmountCharged": 0.85,
    "DeliveryFee": 0.0
  }
}
```


Direct Debit Charge Callback

The **Direct Debit Charge API** mandatorily sends a payload to callbackURL provided in each request. The callback payload determines **final status** of a pending transaction response i.e.; transaction with **0001** ResponseCode. The callback URL you specified in the Direct Debit request should be implemented to listen for an HTTP **POST** payload from Hubtel.

Debit Charge request has an **asynchronous flow** on all networks. This means that the final status of a transaction cannot be determined immediately after the request. It may take some time (usually less than 30 seconds). Hence, it is **paramount** and **required** to implement a HTTP callback on your server to be able to receive **final status** of each transaction.

Note

Businesses that want to add an extra layer of security to ensure callbacks reach their endpoint securely can whitelist Hubtel's callback IP address: **18.202.122.131**

SAMPLE CALLBACK (Successful)

JSON


```
{
    "ResponseCode": "0000",
    "Message": "success",
```

```
      "Data": {
          "Amount": 0.8,
          "Charges": 0.05,
          "AmountAfterCharges": 0.8,
          "Description": " The Vodafone Cash payment has been approved and processed succ
essfully",
          "ClientReference": "3jL2KlUy3vt21",
          "TransactionId": "09f84e20a283942e807128e8c21d08d6",
          "ExternalTransactionId": "2116938399",
          "AmountCharged": 0.85,
          "OrderId": "09f84e20a283942e807128e8c21d08d6",
          "PaymentDate": "2024-05-14T00:44:57.5142719Z"
      }
  }
```


SAMPLE CALLBACK (Failed)

JSON


```
  {
      "ResponseCode": "2001",
      "Message": "failed",
      "Data": {
          "Amount": 0.8,
          "Charges": 0.05,
          "AmountAfterCharges": 0.8,
          "Description": "FAILED",
          "ClientReference": "3jL2KlUy3vt21",
          "TransactionId": "09f84e20a283942e807128e8c21d08d6",
          "ExternalTransactionId": "2116938399",
          "AmountCharged": 0.85,
          "OrderId": "09f84e20a283942e807128e8c21d08d6",
          "PaymentDate": "2024-05-14T00:44:57.5142719Z"
      }
  }
```


Transaction Status Check

It is **mandatory** to implement the **Transaction Status Check API** as it allows merchants to check for the status of a transaction in rare instances where a merchant does not receive the final status of the transaction from Hubtel **after five (5) minutes**.

To check the status of a transaction, send an HTTP **GET** request to the below URL, with either one or more unique transaction identifiers as parameters.

It is also **mandatory** to parse your **Collection Account Number** for Status Check requests in the endpoint. Find your **Collection Account Number** here.

Note

Only requests from whitelisted IP(s) can reach the endpoint. Requests from IP addresses that have not been whitelisted will return a **403 Forbidden** error response or a **timeout**. Submit your public IP(s) to your Retail Systems Engineer to be whitelisted.

We permit a maximum of 4 IP addresses per service.

API Endpoint	https://api-txnstatus.hubtel.com/transactions/{Collection_Account_Number}/status
Request Type	**GET**
Content Type	**JSON**

REQUEST PARAMETERS

Parameter	Type	Requirement	Description
clientReference	String	Mandatory (preferred)	The client reference of the transaction specified in the request payload.
hubtelTransactionId	String	Optional	Transaction ID from Hubtel after successful payment.
networkTransactionId	String	Optional	The transaction reference from the mobile money provider.

Note

Although either one of the unique transaction identifiers above could be passed as parameters, **clientReference** is recommended to be used often.

SAMPLE REQUEST

HTTP

```
GET /transactions/11684/status?clientReference=3jL2KlUy3vt21 HTTP/1.1
Host: api-txnstatus.hubtel.com
Authorization: Basic QmdfaWghe22NU6bXVhaHdpYW8pfQ==
```

cURL

```
curl --location 'https://api-txnstatus.hubtel.com/transactions/11684/status?clientReference=3jL2KlUy3vt21' \
--header 'Authorization: Basic QmdfaWghe22NU6bXVhaHdpYW8pfQ=='
```

PHP

```php
<?php

$curl = curl_init();

curl_setopt_array($curl, array(
CURLOPT_URL => 'https://api-txnstatus.hubtel.com/transactions/11684/status?clientReference=3jL2KlUy3vt21',
CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => '',
CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 0,
CURLOPT_FOLLOWLOCATION => true,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => 'GET',
CURLOPT_HTTPHEADER => array(
    'Authorization: Basic QmdfaWghe22NU6bXVhaHdpYW8pfQ=='
),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
```

Python

```python
import requests

url = "https://api-txnstatus.hubtel.com/transactions/11684/status?clientReference=3jL2KlUy3vt21"

payload = {}
headers = {
    'Authorization': 'Basic QmdfaWghe22NU6bXVhaHdpYW8pfQ=='
}

response = requests.request("GET", url, headers=headers, data=payload)

print(response.text)
```

Javascipt - Fetch

```javascript
const myHeaders = new Headers();
myHeaders.append("Authorization", "Basic QmdfaWghe22NU6bXVhaHdpYW8pfQ==");

const requestOptions = {
method: "GET",
headers: myHeaders,
redirect: "follow"
};

fetch("https://api-txnstatus.hubtel.com/transactions/11684/status?clientReference=3jL2KlUy3vt21", requestOptions)
    .then((response) => response.text())
```

```
    .then((result) => console.log(result))
    .catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
message	String	The description of response received from the API that is related to the ResponseCode.
responseCode	String	The response code of the API after the request.
data	Object	An object containing the required data response from the API.
date	String	Date of the transaction.
status	String	Status of the transaction i.e.: **Paid**, **Unpaid** or **Refunded**.
transactionId	String	The unique ID used to identify a Hubtel transaction (**from Hubtel**).
externalTransactionId	String	The transaction reference from the mobile money provider (**from Telco**).
paymentMethod	String	The mode of payment.
clientReference	String	The reference ID that is initially provided by the client/API user in the request payload (**from merchant**).
currencycode	String	Currency of the transaction; could be **null**.
amount	Float	The transaction amount.
charges	Float	The charge/fee for the transaction.
amountAfterCharges	Float	The transaction amount after charges/fees deduction.
isFulfilled	Boolean	Whether service was fulfilled; could be **null**.

SAMPLE RESPONSE (Paid)

200 OK


```
{
  "message": "Successful",
  "responseCode": "0000",
  "data": {
      "date": "2024-04-25T21:45:48.4740964Z",
      "status": "Paid",
      "transactionId": "7fd01221faeb41469daec7b3561bddc5",
      "externalTransactionId": "0000006824852622",
```

```
      "paymentMethod": "mobilemoney",
      "clientReference": "3jL2KlUy3vt21",
      "currencyCode": null,
      "amount": 0.1,
      "charges": 0.02,
      "amountAfterCharges": 0.08,
      "isFulfilled": null
  }
}
```


SAMPLE RESPONSE (Unpaid)

200 OK


```
{
  "message": "Successful",
  "responseCode": "0000",
  "data": {
      "date": "2024-04-25T21:45:48.4740964Z",
      "status": "Unpaid",
      "transactionId": "7fd01221faeb41469daec7b3561bddc5",
      "externalTransactionId": "0000006824852622",
      "paymentMethod": "mobilemoney",
      "clientReference": "3jL2KlUy3vt21",
      "currencyCode": null,
      "amount": 0.1,
      "charges": 0.02,
      "amountAfterCharges": 0.08,
      "isFulfilled": null
  }
}
```


Response Codes

The Hubtel Sales API uses standard HTTP error reporting. Successful requests return HTTP status codes in the 2xx. Failed requests return status codes in 4xx and 5xx. Response codes are included in the JSON response body, which contain information about the response.

Response Code	Description	Required Action
0000	The transaction has been processed successfully.	None
0001	Request has been accepted. A callback will be sent on final state	None

Response Code	Description	Required Action
2000	success Request received! Pending preapproval OTP Verified! Pending preapproval success, Customer is already preapproved	None
2001	The MTN Mobile Money user has reached counter or balance limits, has insufficient funds or is missing permissions. The Vodafone Cash failed Dear Customer, you have insufficient funds. Avail. Balance:#### 5 successive invalid transfers will lock your account. Thank you. Transaction id is invalid	• Mobile network not able to parse your request • USSD session timeout • Having strange characters (&*!%@) in your description • Ensure that the number provided matches the channel
4000	Validation errors	Validation errors. Something is not quite right with this request. Please check again.
4070	We're unable to complete this payment at the moment. Please try again later. Fees not set for given conditions.	Ensure you are passing the required minimum amount or contact your Hubtel relationship manager to setup fees for your account if error persists.
4101	The business you're trying to pay isn't fully set up to receive payments at the moment. Please try again later Supplied API keys does not have "mobilemoney-receive-direct" in scopes. Client request keys do not match API keys on business	• Contact your Retail Systems Engineer to enable Receive Money Scopes • Ensure that you're providing the correct Basic Auth key for the Authorization header and ensure you’re passing your Collection Account Number in the endpoint.
4103	Permission denied. Sorry, your account is not allowed to transact on this channel	Contact your Retail Systems Engineer
4204	Preapproval request failed! Please try again.	Inspect your request and try again