Source: developers.hubtel.com/docs/business/api_documentation/payment_apis/direct_receive_money

Direct Receive Money

Last updated September 18th, 2026

Overview

The **Hubtel Sales API** allows you to sell goods and services online, instore and on mobile. With a single integration, you can:

1. Accept mobile money payments on your application, sell services in-store, online and on mobile as well as process all your sales on your Hubtel account.
2. Send money to your customers.

This API can be used to provide a range of services including processing e-commerce payments, mobile banking, bulk payments and more. You can also accept payments for goods and services into your account.

The following provides an overview of the **Receive Money API** endpoints for interacting programmatically within your application.

> **Note**
>
> Businesses are required to implement a security feature for this API in order to prevent individuals from receiving unsolicited prompts.
>
> This security feature may be:
>
> 1. Only registered users can make payments and before payment initiation, they cannot edit their numbers.
>   **OR**
> 2. Send OTP to unregistered users to confirm the numbers before proceeding to initiate payment.

AVAILABLE CHANNELS

The following are the available channels through which a merchant can **receive mobile money** into a Hubtel Merchant Account.

Mobile Money Provider	Channel Name
MTN Ghana	**mtn-gh**
Telecel Ghana	**vodafone-gh**
AirtelTigo Ghana	**tigo-gh**

Getting Started

BUSINESS IP WHITELISTING

You must share your public IP address with your Retail System Engineer for whitelisting.

> **Note**
>
> All API Endpoints are live and only requests from whitelisted IP(s) can reach these endpoints shared in this reference.
>
> Requests from IP addresses that have not been whitelisted will return a **403 Forbidden** error response or a **timeout**.
>
> We permit a maximum of 4 IP addresses per service.

UNDERSTANDING THE SERVICE FLOW

The **Hubtel Sales API** allows you to integrate multiple functionalities into your applications. This document focuses on:

- Direct Receive Money API: REST API to receive money directly into your Hubtel Merchant Account from a Mobile Money Wallet for all available networks.
- Transaction Status Check API: REST API to check for the status of any debit transaction initiated after five (5) or more minutes of the debit transaction's completion. It is mandatory to implement the Transaction Status Check API only for transactions that you do not receive a callback from Hubtel.

The entire process is asynchronous. The figure below demonstrates the service flow using these two endpoints:

[Service flow diagram not included in the saved page]

The table below describes the steps involved in Receiving Money using the API:

Step	Description
1	Client App makes a Receive Money request to Hubtel.
2	Hubtel performs authentication on the request and sends a response to Client App accordingly.
3	A final callback is sent to Client App via the PrimaryCallbackURL provided in the request. (See sample callback here)
4	In instances where a merchant does not receive the final status of the transaction **after five (5) minutes** from Hubtel, it is **mandatory** to perform a status check using the Status Check API to determine the final status of the transaction. (Refer here)

API Reference

Direct Receive Money allows you to accept direct mobile money payments into your Hubtel Merchant Account. Note that the flow for charging mobile subscribers differs across the various Telco networks.

To initiate a Receive Money transaction, send an HTTP **POST** request to the below URL with the required parameters. It is also **mandatory** to pass your **Collection Account Number** for Receive Money requests in the endpoint. Find your **Collection Account Number** here.

API Endpoint	https://rmp.hubtel.com/merchantaccount/merchants/{Collection_Account_Number}/receive/mobilemoney
Request Type	**POST**
Content Type	**JSON**

REQUEST PARAMETERS

Parameter	Type	Requirement	Description
CustomerName	String	Optional	The name on the customer's mobile money wallet.
CustomerMsisdn	String	Mandatory	The customer's mobile money number. This should be in the international format. **E.g.: "233249111411"**
CustomerEmail	String	Optional	Email of customer.
Channel	String	Mandatory	The mobile money channel provider. Available channels are: **mtn-gh**, **vodafone-gh**, **tigo-gh**.
Amount	Float	Mandatory	Amount of money to be debited during this transaction. **NB**: Only 2 decimal places is allowed **E.g.: 0.50**.
PrimaryCallbackURL	String	Mandatory	URL used to receive callback payload of Receive Money transactions from Hubtel.

Description	String	Mandatory	A brief description of the transaction.
ClientReference	String	Mandatory	The reference provided by the API user and must be **unique for every transaction** and preferably be **alphanumeric** characters. Maximum length is **36 characters**.

> **Note**
>
> Kindly note that a **clientReference** must never be duplicated for any transaction.

SAMPLE REQUEST

HTTP

```
POST /merchantaccount/merchants/11684/receive/mobilemoney HTTP/1.1
Host: rmp.hubtel.com
Accept: application/json
Content-Type: application/json
Authorization: Basic endjeOBiZHhza250fT3==
Cache-Control: no-cache

{
    "CustomerName": "Joe Doe",
    "CustomerMsisdn": "233200000000",
    "CustomerEmail": "username@example.com",
    "Channel": "vodafone-gh",
    "Amount": 0.8,
    "PrimaryCallbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede",
    "Description": "Union Dues",
    "ClientReference": "3jL2KlUy3vt21"
}
```

cURL

```
curl --location 'https://rmp.hubtel.com/merchantaccount/merchants/11684/receive/mobilemoney' \
--header 'Content-Type: application/json' \
--header 'Authorization: Basic endjeOBiZHhza250fT3==' \
--data '{
    "CustomerName": "Joe Doe",
    "CustomerMsisdn": "233200000000",
    "CustomerEmail": "username@example.com",
    "Channel": "vodafone-gh",
    "Amount": 0.8,
    "PrimaryCallbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede",
    "Description": "Union Dues",
    "ClientReference": "3jL2KlUy3vt21"
}'
```

PHP

```php
<?php

$curl = curl_init();

curl_setopt_array($curl, array(
  CURLOPT_URL => 'https://rmp.hubtel.com/merchantaccount/merchants/11684/receive/mobilemoney',
  CURLOPT_RETURNTRANSFER => true,
  CURLOPT_ENCODING => '',
  CURLOPT_MAXREDIRS => 10,
  CURLOPT_TIMEOUT => 0,
  CURLOPT_FOLLOWLOCATION => true,
  CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
  CURLOPT_CUSTOMREQUEST => 'POST',
  CURLOPT_POSTFIELDS =>'{
    "CustomerName": "Joe Doe",
    "CustomerMsisdn": "233200000000",
    "CustomerEmail": "username@example.com",
    "Channel": "vodafone-gh",
    "Amount": 0.8,
    "PrimaryCallbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede",
    "Description": "Union Dues",
    "ClientReference": "3jL2KlUy3vt21"
}',
  CURLOPT_HTTPHEADER => array(
    'Content-Type: application/json',
    'Authorization: Basic endjeOBiZHhza250fT3=='
  ),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
```

Python

```python
import requests
import json

url = "https://rmp.hubtel.com/merchantaccount/merchants/11684/receive/mobilemoney"

payload = json.dumps({
  "CustomerName": "Joe Doe",
  "CustomerMsisdn": "233200000000",
  "CustomerEmail": "username@example.com",
  "Channel": "vodafone-gh",
  "Amount": 0.8,
  "PrimaryCallbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede",
  "Description": "Union Dues",
  "ClientReference": "3jL2KlUy3vt21"
})
headers = {
  'Content-Type': 'application/json',
  'Authorization': 'Basic endjeOBiZHhza250fT3=='
}

response = requests.request("POST", url, headers=headers, data=payload)

print(response.text)
```

JavaScript - Fetch

```
const myHeaders = new Headers();
myHeaders.append("Content-Type", "application/json");
myHeaders.append("Authorization", "Basic endjeOBiZHhza250fT3==");

const raw = JSON.stringify({
  "CustomerName": "Joe Doe",
  "CustomerMsisdn": "233200000000",
  "CustomerEmail": "username@example.com",
  "Channel": "vodafone-gh",
  "Amount": 0.8,
  "PrimaryCallbackUrl": "https://webhook.site/b503d1a9-e726-f315254a6ede",
  "Description": "Union Dues",
  "ClientReference": "3jL2KlUy3vt21"
});

const requestOptions = {
  method: "POST",
  headers: myHeaders,
  body: raw,
  redirect: "follow"
};

fetch("https://rmp.hubtel.com/merchantaccount/merchants/11684/receive/mobilemoney", requestOptions)
  .then((response) => response.text())
  .then((result) => console.log(result))
  .catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
Message	String	The description of response received from the Receive Money API that is related to the ResponseCode.
ResponseCode	String	The unique response code on the status of the transaction.
Data	Object	An object containing the required data response from the API.
Amount	Float	The transaction amount.
Charges	Float	The charge/fee for the transaction.
AmountAfterCharges	Float	The transaction amount after charges/fees deduction.
AmountCharged	Float	The actual amount that is charged from the customer’s mobile money wallet.
Description	String	The description initially provided by API user in the request payload.
ClientReference	String	The reference ID that is initially provided by the client/API user in the request payload (**from merchant**).
TransactionId	String	The unique ID used to identify a Hubtel transaction (**from Hubtel**).
ExternalTransactionId	String	The transaction reference from the mobile money provider (**from Telco**).
OrderID	String	The unique ID used to identify a transaction order.
DeliveryFee	Float	The delivery fee of the transaction is normally zero (0.0).

SAMPLE RESPONSE

200 OK


```
{
  "Message": "Transaction pending. Expect callback request for final state",
  "ResponseCode": "0001",
  "Data": {
      "TransactionId": "09f84e20a283942e807128e8c21d08d6",
      "Description": "Union Dues",
      "ClientReference": "3jL2KlUy3vt21",
      "Amount": 0.8,
      "Charges": 0.05,
      "AmountAfterCharges": 0.8,
      "AmountCharged": 0.85,
      "DeliveryFee": 0.0
  }
}
```


Receive Money Callback

The **Hubtel Receive Money API** mandatorily sends a payload to the callbackURL provided in each request. The callback payload determines **final status** of a pending transaction response i.e.; transaction with **0001** ResponseCode. The callback URL you specified in the Receive Money request should be implemented to listen for an HTTP **POST** payload from Hubtel.

To process a **Receive Money** request, customer **approval** is required to transfer money from their mobile money account to your Hubtel Merchant Account. Consequently, the transaction flow is **asynchronous**. This means the **final status** of a transaction is not immediately available and may take up to 30 seconds to be confirmed. Therefore, it is **crucial** to implement an HTTP callback on your server to receive the **final transaction status**.

> **Note**
>
> Businesses that want to add an extra layer of security to ensure callbacks reach their endpoint securely can whitelist Hubtel's callback IP address: **18.202.122.131**

SAMPLE CALLBACK (SUCCESSFUL)

JSON


```
{
  "ResponseCode": "0000",
  "Message": "success",
  "Data": {
      "Amount": 0.8,
      "Charges": 0.05,
      "AmountAfterCharges": 0.8,
      "Description": " The Vodafone Cash payment has been approved and processed successfully",
      "ClientReference": "3jL2KlUy3vt21",
      "TransactionId": "09f84e20a283942e807128e8c21d08d6",
      "ExternalTransactionId": "2116938399",
      "AmountCharged": 0.85,
      "OrderId": "09f84e20a283942e807128e8c21d08d6",
      "PaymentDate": "2024-05-14T00:44:57.5142719Z"
  }
}
```


SAMPLE CALLBACK (FAILED)

JSON


```
{
  "ResponseCode": "2001",
  "Message": "failed",
  "Data": {
      "Amount": 0.8,
      "Charges": 0.05,
      "AmountAfterCharges": 0.8,
      "Description": "FAILED",
      "ClientReference": "3jL2KlUy3vt21",
      "TransactionId": "09f84e20a283942e807128e8c21d08d6",
      "ExternalTransactionId": "2116938399",
      "AmountCharged": 0.85,
      "OrderId": "09f84e20a283942e807128e8c21d08d6",
      "PaymentDate": "2024-05-14T00:44:57.5142719Z"
  }
}
```


Transaction Status Check

It is **mandatory** to implement the **Transaction Status Check API** as it allows merchants to check for the status of a transaction in rare instances where a merchant does not receive the final status of the transaction from Hubtel **after five (5) minutes**.

To check the status of a transaction, send an HTTP **GET** request to the below URL, with either one or more unique transaction identifiers as parameters.

It is also **mandatory** to parse your **Collection Account Number** for Status Check requests in the endpoint. Find your **Collection Account Number** here.

> **Note**
>
> Only requests from whitelisted IP(s) can reach the endpoint. Requests from IP addresses that have not been whitelisted will return a **403 Forbidden** error response or a **timeout**. Submit your public IP(s) to your Retail Systems Engineer to be whitelisted.

API Endpoint	https://api-txnstatus.hubtel.com/transactions/{Collection_Account_Number}/status
Request Type	**GET**
Content Type	**JSON**

REQUEST PARAMETERS

Parameter	Type	Requirement	Description
clientReference	String	Mandatory (preferred)	The client reference of the transaction specified in the request payload.
hubtelTransactionId	String	Optional	Transaction ID from Hubtel after successful payment.
networkTransactionId	String	Optional	The transaction reference from the mobile money provider.

> **Note**
>
> Although either one of the unique transaction identifiers above could be passed as parameters, **clientReference** is recommended to be used often.

SAMPLE REQUEST

HTTP

```
GET /transactions/11684/status?clientReference=3jL2KlUy3vt21 HTTP/1.1
Host: api-txnstatus.hubtel.com
Authorization: Basic QmdfaWghe22NU6bXVhaHdpYW8pfQ==
```

cURL

```
curl --location 'https://api-txnstatus.hubtel.com/transactions/11684/status?clientReference=3jL2KlUy3vt21' \
--header 'Authorization: Basic QmdfaWghe22NU6bXVhaHdpYW8pfQ=='
```

PHP

```
<?php

$curl = curl_init();

curl_setopt_array($curl, array(
CURLOPT_URL => 'https://api-txnstatus.hubtel.com/transactions/11684/status?clientReference=3jL2KlUy3vt21',
CURLOPT_RETURNTRANSFER => true,
CURLOPT_ENCODING => '',
CURLOPT_MAXREDIRS => 10,
CURLOPT_TIMEOUT => 0,
CURLOPT_FOLLOWLOCATION => true,
CURLOPT_HTTP_VERSION => CURL_HTTP_VERSION_1_1,
CURLOPT_CUSTOMREQUEST => 'GET',
CURLOPT_HTTPHEADER => array(
    'Authorization: Basic QmdfaWghe22NU6bXVhaHdpYW8pfQ=='
),
));

$response = curl_exec($curl);

curl_close($curl);
echo $response;
```

Python

```
import requests

url = "https://api-txnstatus.hubtel.com/transactions/11684/status?clientReference=3jL2KlUy3vt21"

payload = {}
headers = {
    'Authorization': 'Basic QmdfaWghe22NU6bXVhaHdpYW8pfQ=='
}

response = requests.request("GET", url, headers=headers, data=payload)

print(response.text)
```

Javascipt - Fetch

```
const myHeaders = new Headers();
myHeaders.append("Authorization", "Basic QmdfaWghe22NU6bXVhaHdpYW8pfQ==");

const requestOptions = {
method: "GET",
headers: myHeaders,
redirect: "follow"
};

fetch("https://api-txnstatus.hubtel.com/transactions/11684/status?clientReference=3jL2KlUy3vt21", requestOptions)
    .then((response) => response.text())
    .then((result) => console.log(result))
    .catch((error) => console.error(error));
```

RESPONSE PARAMETERS

Parameter	Type	Description
message	String	The description of response received from the API that is related to the ResponseCode.
responseCode	String	The response code of the API after the request.
data	Object	An object containing the required data response from the API.

date	String	Date of the transaction
status	String	Status of the transaction i.e.: **Paid**, **Unpaid** or **Refunded**.
transactionId	String	The unique ID used to identify a Hubtel transaction (**from Hubtel**).
externalTransactionId	String	The transaction reference from the mobile money provider (**from Telco**).
paymentMethod	String	The mode of payment.
clientReference	String	The reference ID that is initially provided by the client/API user in the request payload (**from merchant**).
currencycode	String	Currency of the transaction; could be **null**.
amount	Float	The transaction amount.
charges	Float	The charge/fee for the transaction.
amountAfterCharges	Float	The transaction amount after charges/fees deduction.
isFulfilled	Boolean	Whether service was fulfilled; could be **null**.

SAMPLE RESPONSE (PAID)

200 OK


```
{
  "message": "Successful",
  "responseCode": "0000",
  "data": {
      "date": "2024-04-25T21:45:48.4740964Z",
      "status": "Paid",
      "transactionId": "7fd01221faeb41469daec7b3561bddc5",
      "externalTransactionId": "0000006824852622",
      "paymentMethod": "mobilemoney",
      "clientReference": "3jL2KlUy3vt21",
      "currencyCode": null,
      "amount": 0.1,
      "charges": 0.02,
      "amountAfterCharges": 0.08,
      "isFulfilled": null
  }
}
```


SAMPLE RESPONSE (UNPAID)

200 OK


```
{
  "message": "Successful",
  "responseCode": "0000",
  "data": {
      "date": "2024-04-25T21:45:48.4740964Z",
      "status": "Unpaid",
      "transactionId": "7fd01221faeb41469daec7b3561bddc5",
      "externalTransactionId": "0000006824852622",
      "paymentMethod": "mobilemoney",
      "clientReference": "3jL2KlUy3vt21",
      "currencyCode": null,
      "amount": 0.1,
      "charges": 0.02,
      "amountAfterCharges": 0.08,
      "isFulfilled": null
  }
}
```


Response Codes

The Hubtel Sales API uses standard HTTP error reporting. Successful requests return HTTP status codes in the 2xx. Failed requests return status codes in 4xx and 5xx. Response codes are included in the JSON response body, which contain

information about the response.

Response Code	Description	Required Action
0000	The transaction has been processed successfully.	None
0001	Request has been accepted. A callback will be sent on final state	None
2001	The MTN Mobile Money user has reached counter or balance limits, has insufficient funds or is missing permissions. The Vodafone Cash failed You entered the wrong PIN. Please try again Dear Customer, you have insufficient funds. Avail. Balance:#### 5 successive invalid transfers will lock your account. Thank you. MTN Exception: Account Holder with FRI Not Found Transaction id is invalid	• Customer either entered no or invalid PIN • Mobile network not able to parse your request • USSD session timeout • Having strange characters (&*!%@) in your description • Ensure that the number provided matches the channel
4000	Validation errors	Validation errors. Something is not quite right with this request. Please check again.
4070	We're unable to complete this payment at the moment. Please try again later. Fees not set for given conditions.	Ensure you are passing the required minimum amount or contact your Hubtel relationship manager to setup fees for your account if error persists.
4101	The business you're trying to pay isn't fully set up to receive payments at the moment. Please try again later Supplied API keys does not have "mobilemoney-receive-direct" in scopes. Client request keys do not match API keys on business	• Contact your Retail Systems Engineer to enable Receive Money Scopes • Ensure that you're providing the correct Basic Auth key for the Authorization header and ensure you’re passing your Collection Account Number in the endpoint.
4103	Permission denied. Sorry, your account is not allowed to transact on this channel	Contact your Retail Systems Engineer