

COIN OR

Dimitris
Dimou
Alexandros
Zigouris

CLP for Linear
Programming

Installation
Overview
Usage
Executable

COIN OR Project (Computational Infrastructure for Operations Research)

Dimitris Dimou
Alexandros Zigouris

University of Patras

mijuomij@gmail.com

April 14, 2016

Overview

COIN OR

Dimitris
Dimou
Alexandros
Zigouris

CLP for Linear
Programming

Installation
Overview
Usage
Executable

1 CLP for Linear Programming

- Installation
- Overview
- Usage
- Executable

Installation

COIN-OR

Dimitris
Dimou
Alexandros
Zigouris

CLP for Linear
Programming

Installation
Overview
Usage
Executable

- 1 `svn co https://projects.coin-or.org/svn/Clp/stable/1.16 coin-Clp`
- 2 `cd coin-Clp`
- 3 `./configure -C`
- 4 `make`
- 5 `make test`
- 6 `make install`
- 7 `make doxydoc` (documentation)

Background

COIN OR

Dimitris
Dimou
Alexandros
Zigouris

CLP for Linear
Programming
Installation
Overview
Usage
Executable

Clp is written in C++ and is released as open source code under the Eclipse Public License (EPL). It is available from the COIN-OR initiative. The code is written primarily by John J. Forrest, now retired from IBM Research. The project is currently managed by John Forrest, Julian Hall, and the rest of the Clp team.

The latest stable version is 1.16.

Basic model classes

COIN OR

Dimitris
Dimou
Alexandros
Zigouris

CLP for Linear
Programming


Installation

Overview

Usage

Executable

The top three levels of the hierarchy are depicted in the figure below. The first two levels (i.e. ClpModel, ClpSimplex, ClpInterior) contain all the problem data which define a model (that is, a problem instance). The third level contains most of the algorithmic aspects of CLP.



Load model

COIN OR

Dimitris
Dimou
Alexandros
Zigouris

CLP for Linear
Programming

Installation
Overview
Usage
Executable

■ Load from matrix

```
void ClpModel::loadProblem (const ClpMatrixBase &matrix,  
                             const double *collb,  
                             const double *colub,  
                             const double *obj,  
                             const double *rowlb,  
                             const double *rowub,  
                             const double *rowObjective = NULL)
```

■ Load from MPS file

```
int ClpModel::readMps (const char *filename,  
                       bool keepNames = false,  
                       bool ignoreErrors = false)
```

■ Load from GMPL file

```
int ClpModel::readGMPL (const char *filename,  
                        const char *dataName,  
                        bool keepNames = false)
```

MPS format

COIN OR

Dimitris
Dimou
Alexandros
Zigouris

CLP for Linear
Programming

Installation

Overview

Usage

Executable

NAME		DOVETAIL			
ROWS					
N	obj				
L	c1				
L	c2				
L	c3				
L	c4				
COLUMNS					
MARK0000	'MARKER '		'INTORG '		
x1	obj	3	c1		1
x1	c2	3	c3		1
x2	obj	2	c1		1
x2	c2	1	c4		1
MARK0001	'MARKER '		'INTEND '		
RHS					
RHS	c1	9	c2		18
RHS	c3	7	c4		6
BOUNDS					
LO BND	x1	0			
LO BND	x2	0			
ENDATA					

COIN OR

Dimitris
Dimou
Alexandros
Zigouris

CLP for Linear
Programming

Installation
Overview

Usage
Executable

```
#include "ClpSimplex.hpp"

int main (int argc, const char *argv[])
{
    ClpSimplex model;
    int status;
    if (argc < 2)
        status=model.readMps("dovetail.mps");
    else
        status=model.readMps(argv[1]);
    if (!status) {
        model.primal();
    }
    return 0;
}
```


Solution inspection

COIN OR

Dimitris
Dimou
Alexandros
Zigouris

CLP for Linear
Programming

Installation
Overview

Usage
Executable

- `double * model.primalColumnSolution();`
- `double * model.primalRowSolution();`
- `bool model.isProvenOptimal();`
- `bool model.isProvenPrimalInfeasible();`
- `bool model.isProvenDualInfeasible();`
- `bool model.isIterationLimitReached();`

Other useful methods

COIN OR

Dimitris
Dimou
Alexandros
Zigouris

CLP for Linear
Programming
Installation
Overview
Usage
Executable

Set methods

- `model.setMaximumIterations(int value);`
- `model.setMaximumSeconds(double value);`
- `model.setDualBound(double value);`
- `model.setOptimizationDirection(double value);`

Get methods

- `model.numberRows();`
- `model.numberColumns();`
- `model.objectiveValue();`
- `model.objective();`

Pivot choices

COIN OR

Dimitris
Dimou
Alexandros
Zigouris

CLP for Linear
Programming

Installation
Overview

Usage
Executable

- ClpPrimalColumnPivot
 - ClpPrimalColumnSteepest
 - ClpPrimalColumnDantzig
- ClpDualRowSteepest
 - ClpDualRowSteepest
 - ClpDualRowDantzig

Quick start

COIN OR

Dimitris
Dimou
Alexandros
Zigouris

CLP for Linear
Programming

Installation
Overview
Usage
Executable

■ Commands

- `import (filename)`
- `primals`
- `duals`
- `max`
- `min`
- `maxlt (num)`
- `presolve (on/off)`
- `allslack`
- `solution (filename)`
- `quit`

■ Example :

`clp filename -maximize -dualsimplex -solution solfile`