

# An Introduction to the Operating Systems of the IoT

Elahe Jalalpoor and Parham Alvani

Amirkabir University of Technology

`elahejalalpoor@gmail.com`

`parham.alvani@gmail.com`

Jun 29, 2015




- ▶ Introduction
- ▶ IoT Requirements & Challenges
- ▶ IoT OS
- ▶ Existing OSs
- ▶ Protocol stack
- ▶ Test & Development Environments
- ▶ Conclusion

- ▶ Introduction
- ▶ IoT Requirements & Challenges
- ▶ IoT OS
- ▶ Existing OSs
- ▶ Protocol stack
- ▶ Test & Development Environments
- ▶ Conclusion

- ▶ Introduction
  - What is the IoT

## What is IoT...

The Internet of Things (IoT) is a scenario in which objects, animals or people are provided with unique identifiers and the ability to transfer data over a network without requiring human-to-human or human-to-computer interaction.




- ▶ Introduction
- ▶ IoT Requirements & Challenges
- ▶ IoT OS
- ▶ Existing OSs
- ▶ Protocol stack
- ▶ Test & Development Environments
- ▶ Conclusion

# IoT Requirements & Challenges

- ▶ IoT Requirements & Challenges
  - Effect of the requirements on OS

## IoT Requirements & Challenges

- ▶ Scalability
- ▶ Modularity
- ▶ Connectivity
- ▶ Reliability





- ▶ Can you build an IoT system with familiar Web technologies?

# Internet Usage and Protocols for the IoT

- ▶ Can you build an IoT system with familiar Web technologies?
- ▶ Yes you can, although the result would not be as **efficient** as with the **newer protocols**.

# Internet Usage and Protocols for the IoT

## Web Hundreds / thousands of bytes



- Inefficient content encoding
- Huge overhead, difficult parsing
- Requires full Internet devices

## Internet of Things Tens of bytes



- Efficient objects
- Efficient Web
- Optimized IP access

# Internet Usage and Protocols for the IoT

<i>Protocol</i>	<i>Transport</i>	<i>Messaging</i>	<i>2G,3G,4G (1000's)</i>	<i>LowPower and Lossy (1000's)</i>	<i>Compute Resources</i>	<i>Security</i>	<i>Success Stories</i>	<i>Arch</i>
<b>CoAP</b>	UDP	Rqst/Rspnse	Excellent	Excellent	10Ks/RAM Flash	Medium - Optional	Utility field area ntwns	Tree
<b>Continua HDP</b>	UDP	Pub/Subsrbr Rqst/Rspnse	Fair	Fair	10Ks/RAM Flash	None	Medical	Star
<b>DDS</b>	UDP	Pub/Subsrbr Rqst/Rspnse	Fair	Poor	100Ks/RAM Flash +++	High- Optional	Military	Bus
<b>DPWS</b>	TCP		Good	Fair	100Ks/RAM Flash ++	High- Optional	Web Servers	Client Server
<b>HTTP/ REST</b>	TCP	Rqst/Rspnse	Excellent	Fair	10Ks/RAM Flash	Low- Optional	Smart Energy Phase 2	Client Server
<b>MQTT</b>	TCP	Pub/Subsrbr Rqst/Rspnse	Excellent	Good	10Ks/RAM Flash	Medium - Optional	IoT Msging	Tree
<b>SNMP</b>	UDP	Rqst/Response	Excellent	Fair	10Ks/RAM Flash	High- Optional	Network Monitoring	Client- Server
<b>UPnP</b>		Pub/Subsrbr Rqst/Rspnse	Excellent	Good	10Ks/RAM Flash	None	Consumer	P2P Client Server
<b>XMPP</b>	TCP	Pub/Subsrbr Rqst/Rspnse	Excellent	Fair	10Ks/RAM Flash	High- Mandatory	Rmt Mgmt White Gds	Client Server
<b>ZeroMQ</b>	UDP	Pub/Subsrbr Rqst/Rspnse	Fair	Fair	10Ks/RAM Flash	High- Optional	CERN	P2P

- ▶ IoT device will require a modular operating system that separates the core kernel from middleware, protocols, and applications.

- ▶ Introduction
- ▶ IoT Requirements & Challenges
- ▶ IoT OS
- ▶ Existing OSs
- ▶ Protocol stack
- ▶ Test & Development Environments
- ▶ Conclusion

## ► IoT OS

- General OS vs IoT OS
- What are the main requirements in IoT OS
- What are the main components in IoT OS


- ▶ Introduction
- ▶ IoT Requirements & Challenges
- ▶ IoT OS
- ▶ Existing OSs
- ▶ Protocol stack
- ▶ Test & Development Environments
- ▶ Conclusion



- ▶ Existing OSs
  - OS Classification
  - Overview of Open Source OSs
  - Overview of Closed Source OSs
  - Why Not Linux?

# Overview of Open Source OSs

- ▶ FreeRTOS
- ▶ RIOT
- ▶ Contiki
- ▶ TinyOS
- ▶ Embedded Linux
- ▶ OpenWSN



- ▶ FreeRTOS is designed to be **small** and **simple**.
- ▶ The kernel itself consists of only three or four C files.
- ▶ It provides methods for multiple threads or tasks, mutexes, semaphores and software timers.
- ▶ Key features are **very small memory footprint**, **low overhead**, and **very fast execution**.



- ▶ RIOT is a **real-time multi-threading** operating system.
- ▶ RIOT is based on design objectives including:
  - Energy-Efficiency
  - Reliability
  - Real-Time Capabilities
  - Small Memory Footprint
  - Modularity
  - Uniform API Accessindependent of the underlying hardware  
(this API offers partial POSIX compliance)



- ▶ Contiki is an open source operating system for **networked**, **memory-constrained** systems
- ▶ Contiki provides three network mechanisms:
  - The uIP stack, which provides IPv4 networking,
  - The uIPv6 stack, which provides IPv6 networking,
  - The Rime stack, which is a set of custom lightweight networking protocols designed specifically for low-power wireless networks.




- ▶ TinyOS is a **component-based** operating system and platform targeting wireless sensor networks.
- ▶ TinyOS is an embedded operating system written in the **nesC programming language** as a set of cooperating tasks and processes.



# Embedded Linux

- ▶ Embedded Linux is created using OpenEmbedded, the build framework for embedded Linux.
- ▶ OpenEmbedded offers a best-in-class cross-compile environment.




- ▶ The goal of the OpenWSN project is to provide open-source implementations of a complete protocol stack based on Internet of Things standards, on a variety of software and hardware platforms.





# Comparison

OS	Min RAM	Min ROM	C Support	C++ Support
Contiki	$< 2kB$	$< 30kB$	Partial support	No support
Tiny OS	$< 1kB$	$< 4kB$	No support	No support
Linux	$\sim 1MB$	$\sim 1MB$	Full support	Full support
RIOT	$\sim 1.5kB$	$\sim 5kB$	Full support	Full support



# Comparison

OS	Multi-Threading	Modularity	Real-Time
Contiki	Partial support	Partial support	Partial support
Tiny OS	Partial support	No support	No support
Linux	Full support	Partial support	Partial support
RIOT	Full support	Full support	Full support




# Operating Systems Availability

OS	Wsn430 Node	M3 Node	A8 Node
Contiki	Full support	Full support	No support
Tiny OS	Full support	No support	No support
Linux	No support	No support	Full support
RIOT	Full support	Full support	No support



# Overview of Closed Source OSs

- ▶ ARM mbed
- ▶ Huawei LiteOS
- ▶ Google Brillo



- ▶ Automation of power management
- ▶ Software asset protection and secure firmware updates for device security & management
- ▶ Connectivity protocol stack support for Bluetooth low energy, Cellular, Ethernet, Wi-fi, Zigbee IP, Zigbee NAN, 6LoWPAN



- ▶ The company says that its LiteOS is the **lightest** software of its kind and can be used to power a range of smart devices



- ▶ Brillo is **derived** from Android but **polished** to just the lower levels.
- ▶ It supports Wi-Fi, Bluetooth Low Energy, and other Android things.



# Why Not Linux?

## Real-Time Linux

Controlling a laser with Linux is crazy, but everyone in this room is crazy in his own way. So if you want to use Linux to control an industrial welding laser, I have no problem with your using PREEMPT\_RT.

- Linus Torvalds





# Why Not Linux?

- ▶ Linux certainly is a robust, developer-friendly OS
- ▶ Linux has a disadvantage when compared to a real-time operating system:
  - Memory footprint
  - It simply will not run on 8 or 16-bit MCUs
- ▶ Linux will certainly have many uses in embedded devices, particularly ones that provide graphically rich user interfaces.
- ▶ There are thousands of applications for which Linux is ill suited.



# Multi-Tasking, Thread Model

- ▶ Most RTOS products on the market are thread model.
- ▶ **Tasks** are now called **threads**.
- ▶ All the **tasks** code and data occupy **the same address space**, along with that of the RTOS itself.



# Event-Driven, Non-Blocking I/O Model

- ▶ Networking Event-Driven
- ▶ Non-Blocking I/O



# Questions?