

Design of a Custom STM32 - SX1280 PCB for Drone Communication

Submitted By :
Elaine Anna Joseph
2023EEB1199

Submitted to:
Prof. Satyam Agarwal

Introduction:

Modern drone communication systems require compact, reliable, and efficient hardware platforms capable of supporting high-speed embedded processing and wireless RF communication. In drone applications, proper PCB design is essential for maintaining signal integrity, reducing noise, improving communication reliability, and ensuring stable operation of RF transceiver modules.

Objectives:

This project focuses on the design and development of a custom PCB integrating the STM32 microcontroller and SX1280 RF transceiver for drone communication applications. The work involved schematic design, component selection, PCB layout, power supply integration, signal routing, and RF hardware interfacing.

The PCB was designed to support wireless communication between drone transmitter and receiver systems while maintaining compact size and reliable electrical performance. Proper attention was given to SPI routing, grounding, decoupling, and RF layout considerations to achieve stable communication and efficient hardware operation.

System Overview

The developed hardware system consists of an STM32 microcontroller connected with the SX1280 RF transceiver through SPI communication. Additional supporting circuits such as voltage regulation, decoupling capacitors, reset circuitry, and communication connectors were integrated into the PCB.

The hardware platform was designed to support both transmitter and receiver side communication for drone applications.

Main hardware blocks include:

- STM32 Microcontroller
- SX1280 RF Transceiver
- Power Supply Section
- SPI Communication Interface
- UART Communication Interface

- GPIO Control Signals
- RF Communication Section

Study of Embedded Hardware Requirements

Before starting the PCB design, the hardware requirements for the communication system were studied. The design required:

- High-speed SPI communication between STM32 and SX1280
- Stable 3.3V power supply
- Low-noise RF operation
- Reliable UART communication
- Compact PCB structure
- Proper grounding and decoupling

Special attention was required because RF communication systems are sensitive to noise, unstable power supply, and improper PCB routing.

STM32 Hardware Integration

The STM32 microcontroller was selected as the main processing unit of the system due to its peripheral support, processing capability, and compatibility with embedded communication applications.

The following hardware peripherals were integrated:

- UART interface for CRSF communication
- SPI interface for SX1280 communication
- GPIO pins for control and interrupt handling
- Power supply connections
- Reset circuitry

Proper pin configuration and routing were performed to ensure stable operation of the microcontroller.

SX1280 RF Transceiver Integration

The SX1280 RF transceiver was integrated into the PCB for wireless communication in the 2.4 GHz ISM band.

The following connections were implemented between STM32 and SX1280:

- SCK
- MOSI
- MISO
- NSS
- BUSY

- RESET
- DIO1 interrupt line

The RF transceiver required careful layout planning because high-frequency communication circuits are highly sensitive to PCB noise and routing issues.

Proper placement of the RF module helped minimize communication instability and signal interference.

Power Supply Design

A stable power supply section was designed to provide regulated 3.3V power to both STM32 and SX1280.

The power supply section included:

- Voltage regulation circuitry
- Decoupling capacitors
- Noise filtering capacitors
- Power routing

Decoupling capacitors were placed close to IC power pins to reduce voltage fluctuations and suppress switching noise during operation.

Stable power delivery was important for preventing RF communication errors and microcontroller instability.

SPI and UART Hardware Routing

SPI communication lines between STM32 and SX1280 were routed carefully to maintain signal integrity.

The following considerations were taken during routing:

- Short SPI trace lengths
- Reduced signal crossing
- Proper grounding near communication traces
- Organized routing structure

UART communication lines were also routed for reliable high-speed serial communication.

Proper routing reduced timing issues and communication errors during hardware operation.

PCB Schematic Design

The schematic design was created using Altium Designer. The schematic included all required hardware components and electrical connections necessary for communication system operation.

Major sections of the schematic included:

- STM32 microcontroller connections
- SX1280 transceiver connections
- Power supply circuitry
- Communication interfaces
- Reset and control circuits

Component footprints were assigned based on package compatibility and PCB size requirements.

PCB Layout and Routing

After schematic completion, PCB layout design was carried out.

The layout process involved:

- Component placement
- Trace routing
- Ground plane creation
- Power routing
- Signal separation

Special attention was given to RF-related routing and grounding because improper layout can significantly affect wireless communication performance.

The PCB was designed to maintain compact size while ensuring reliable signal routing and electrical connectivity.

Conclusion

A custom PCB integrating the STM32 microcontroller and SX1280 RF transceiver was successfully designed for drone communication applications. The project involved schematic creation, component integration, PCB layout design, power supply implementation, and communication interface routing.

The developed hardware platform successfully supported embedded processing and wireless RF communication while maintaining compact size and stable operation. Proper attention to grounding, signal routing, and decoupling techniques improved communication reliability and hardware stability.

The project provided practical exposure to embedded hardware development, PCB design workflows, RF hardware integration, and debugging of real-world communication systems. Valuable understanding was gained in schematic design, signal integrity, power distribution, and RF layout considerations required for modern wireless embedded applications.