

Motion

Design guidelines · Parent Guidance · Updated October 5, 2026

The prototype animates with `motion` (Framer Motion, `motion/react`). Principle: **safe, unhurried** motion, never bouncy, and always respecting reduced-motion.

4.1 Tokens

Durations and curves live in `tokens.css`:

Band	Duration	CSS variable	Tailwind class	Use
Micro	0.15s	<code>--pg-dur-micro</code>	<code>duration-(--pg-dur-micro)</code>	Press, color change, sort menus
Fast	0.22s	<code>--pg-dur-fast</code>	<code>duration-(--pg-dur-fast)</code>	Hover, icons, pop-ups
Base	0.35s	<code>--pg-dur-base</code>	<code>duration-(--pg-dur-base)</code>	Accordions, menus, modals, view changes
Reveal	0.55s	<code>--pg-dur-reveal</code>	<code>duration-(--pg-dur-reveal)</code>	Content entrance on scroll

Curve	Value	Use
<code>ease-pg-out</code>	<code>[0.25, 0.46, 0.45, 0.94]</code>	Brand curve: entrances, reveals, pop-ups
<code>ease-pg-in-out</code>	<code>[0.65, 0, 0.35, 1]</code>	Open/close, accordions, tabs

In `motion` props, write the numbers (`transition={{ duration: 0.55, ease: [0.25, 0.46, 0.45, 0.94] }}`). Stagger between cards in a grid: **0.06s**, for the first 6 items only.

4.2 Patterns

Reveal on scroll

Used gently and **only once**:

```
<motion.div
  initial={{ opacity: 0, y: 16 }}
  whileInView={{ opacity: 1, y: 0 }}
  viewport={{ once: true, margin: "-60px" }}
  transition={{ duration: 0.55, ease: [0.25, 0.46, 0.45, 0.94] }}
/>
```

- Vertical offset of **16–24px**. Horizontal offsets (`x`) only in heroes and image + text rows, 32–48px at most, and a page that uses them gets `overflow-x-clip` so it doesn't create horizontal scroll on mobile.
- Always `once: true`: content doesn't hide again when scrolling up.
- Grids: `delay: index * 0.06`, for the first 6 items only.

Interaction feedback

Element	Animation
Buttons (<code><Button></code>)	<code>whileTap={{ scale: 0.97 }}</code> + color with <code>transition-colors</code> . Hover changes color only
Clickable cards	Hover: <code>card-hover</code> shadow and <code>y: -2</code> . No scaling
Featured images	Hover: 1.02 maximum scale (or no animation)
Social icons	Hover: <code>y: -2</code> , no scaling
Accordion / FAQ	<code>auto</code> height + opacity, 0.35s; the <code>+</code> icon rotates 45°
Pop-ups and modals	Backdrop fades; panel <code>opacity 0 → 1</code> , <code>scale 0.97 → 1</code> , <code>y: -6 → 0</code> , 0.22s
Confirmations ("✓ Question Submitted")	<code>opacity 0 → 1</code> , <code>scale 0.9 → 1</code> , 0.35s, <code>ease-pg-out</code>

What to avoid

- Bouncy `type: "spring"`.
- `whileHover` scaling above 1.02.
- `whileHover` color changes in `motion`: use Tailwind `hover:` classes.
- Infinite or decorative animations. The only exception is the "live" dot (soft pulse), and only while that state is active.
- Entrance animations on the **Get Help** page: crisis content is visible from the very first moment (`initial={false}`).
- Animating the hero or the first visible block in a way that makes the page look empty on load.

4.3 Scrolling

- Every navigation opens the new page at the top (`<ScrollRestoration />` in the root layout); back/forward restores the position.
- "Back to top" buttons and page changes use `scrollBehavior()` from `src/app/utils/motion.ts`: `"smooth"`, or `"auto"` when the user asks for reduced motion.

4.4 Reduced-motion contract (mandatory)

Implemented. The app is wrapped in `MotionConfig`:

```
// src/app/App.tsx
<MotionConfig reducedMotion="user">{/* ...app... */}</MotionConfig>
```

With `reducedMotion="user"`, `motion` turns off movement and scaling for anyone who has the system setting enabled, and keeps opacity changes. CSS transitions are turned off by the `@media (prefers-reduced-motion: reduce)` rule in `accessibility.css`.

Rule: **no content may stay hidden** (`opacity: 0`) if the animation doesn't run.