This is the folder structure we need to create on our cloud server:

```
# Flask app (backend)
/opt/gptsweetheart/

— app.py

- .env
 – venv/
                                  # Python virtual env
└ logs/
   └ gunicorn.log
/var/www/gptsweetheart/
                                 # Static site (frontend)
sign-up.html

─ login.html

— redirect.html
├ dashboard.html
                                  # css/js/images for frontend
— assets/
└ media/
                                  # generated images served at /media/*
```

For that we use the following bashes:

## #1 - Main Project folder

sudo mkdir -p /opt/gptsweetheart sudo chown \$USER:\$USER /opt/gptsweetheart

## #2 - Backend folders (with dummy files that we replace)

sudo mkdir -p /opt/gptsweetheart/logs sudo touch /opt/gptsweetheart/app.py /opt/gptsweetheart/.env /opt/gptsweetheart/logs/ gunicorn.log sudo chown -R \$USER:\$USER /opt/gptsweetheart

# #3 - Frontend folders (with dummy files that we replace)

## #4 - Create the .env file in the right folder

cd /opt/gptsweetheart && nano .env

#### #5 - Paste that with YOUR values and then safe and close with Control + O, Enter, Control + X

SUPABASE\_URL=https://your-supabase-project-url.supabase.co SUPABASE\_SERVICE\_ROLE\_KEY=your-supabase-service-role-key

STRIPE\_SECRET\_KEY=sk\_test\_your\_stripe\_secret\_key STRIPE\_PRICE\_ID\_PRO=price\_your\_stripe\_price\_id STRIPE\_WEBHOOK\_SECRET=whsec\_your\_stripe\_webhook\_secret

FRONTEND\_URL=https://gptsweetheart.com

## #6 Navigate to the right folder

cd /opt/gptsweetheart

## #7 Python + venv install

sudo apt-get update sudo apt-get install -y python3-venv python3-pip

## #8 Create venv + install deps

python3 -m venv venv source venv/bin/activate pip install --upgrade pip pip install flask flask-cors supabase python-dotenv stripe gunicorn

```
#9 install NGINX:
sudo apt update
sudo apt install nginx -y
#10 NGINX create server block:
sudo tee /etc/nginx/sites-available/gptsweetheart >/dev/null << 'EOF'
server {
  listen 80;
  listen [::]:80;
  server_name gptsweetheart.com www.gptsweetheart.com;
  root /var/www/gptsweetheart;
  index index.html;
  # Pretty URLs: serve file.html when /file is requested
  location / {
    try_files $uri $uri.html =404;
  # API -> Flask (gunicorn) on localhost:5002
  location /api/ {
     proxy_pass http://127.0.0.1:5002/;
    proxy_http_version 1.1;
    proxy_set_header Host $host;
    proxy_set_header X-Forwarded-For $remote_addr;
    proxy set header X-Forwarded-Proto $scheme;
    proxy_read_timeout 180s;
  }
  # (Optional) serve generated images later
  location /media/ {
    alias /var/www/gptsweetheart/media/;
    add_header Cache-Control "public, max-age=31536000, immutable";
  }
ÉOF
#11 Disable default site if present
sudo rm -f /etc/nginx/sites-enabled/default
#12 Enable new site
sudo In -sf /etc/nginx/sites-available/gptsweetheart /etc/nginx/sites-enabled/gptsweetheart
#13 Test & reload
```

sudo nginx -t

sudo systemctl reload nginx

**#14 Firewall adjustment** sudo ufw allow 'Nginx Full'

## #15 Install certbot (if not installed)

sudo apt-get update sudo apt-get install -y certbot python3-certbot-nginx

#### #16 # Issue certs

sudo certbot --nginx -d gptsweetheart.com -d www.gptsweetheart.com

## #17 Replace the dummy files

Replace the dummy files on the server with the real files (app.py and the html pages)

## #18 Create the systems unit

sudo tee /etc/systemd/system/gptsweetheart.service >/dev/null << 'EOF' [Unit]
Description=GPTSweetheart Flask (gunicorn)
After=network.target

[Service]

Type=simple

WorkingDirectory=/opt/gptsweetheart

Environment="PYTHONUNBUFFERED=1"

ExecStart=/opt/gptsweetheart/venv/bin/gunicorn -w 3 -b 127.0.0.1:5002 app:app --timeout 120

Restart=always

User=www-data

Group=www-data

[Install]
WantedBy=multi-user.target
EOF

#### #19 Permission and start

sudo chmod -R 750 /opt/gptsweetheart

# Start service sudo systemctl daemon-reload sudo systemctl enable --now gptsweetheart sudo systemctl status gptsweetheart --no-pager