

Jenkins Load Testing load_example configuration

[Back to Dashboard](#)[Status](#)[Changes](#)[Workspace](#)[Delete Project](#)**Configure**[Embeddable Build Status](#)[Set Next Build Number](#)[GitHub Hook Log](#)[Job Config History](#)**Build History** (trend) —

Project name

load_example

Description

[Escaped HTML] [Preview](#)☒ Discard Old Builds

Strategy

Log Rotation

Days to keep builds

if not empty, build records are only kept up to this number of days

Max # of builds to keep

15

if not empty, only up to this number of build records are kept

[Advanced...](#)☐ Block build if certain jobs are running

GitHub project

HipChat Notifications

Project Room

Start Notification ☐☒ This build is parameterized**String Parameter**

Name

DOMAIN

Default Value

https://www.example.com

Description

Set the base domain. Make sure to specify http or https.

[Save](#)[Apply](#)[Delete](#)**Boolean Parameter**

Name

USE_LOGIN

Default Value ☐

Description

You can check this box if you'd like to pass credentials for logging into the site before testing endpoints. We assume the that login is not desired. The username and password can be changed from the below.

[Escaped HTML] [Preview](#)[Delete](#)

String Parameter

Name

EXAMPLE_USERNAME



Default Value

siegeuser@example.com



Description

Only change if you are testing using a specific user.

[Escaped HTML] [Preview](#)

Delete

String Parameter

Name

PASSWORD



Default Value

Password1



Description

Only change if you are using a different user than the default.

[Escaped HTML] [Preview](#)

Delete

String Parameter

Name

URL_LIST



Default Value

/url/userHome.php?page=billing_info/example



Description

Add a list of endpoints separated by pipes. No space between the pipes and the endpoints.

[Escaped HTML] [Preview](#)

Delete

String Parameter

Name

ETC_HOSTS



Default Value

192.168.59.103 example.com admin.example



Description

You must change this IP in order for the tests to work. We have an invalid IP address to prevent an accidental DDOS of example.com.

[Escaped HTML] [Preview](#)

Delete

String Parameter

Name

CONCURRENT



Default Value ?

Description ?

[Escaped HTML] [Preview](#)

Delete

String Parameter ?

Name ?

Default Value ?

Description ?

[Escaped HTML] [Preview](#)

Delete

String Parameter ?

Name ?

Default Value ?

Description ?

[Escaped HTML] [Preview](#)

Delete

Choice Parameter ?

Name ?

Choices ?

Description ?

[Escaped HTML] [Preview](#)

Delete

String Parameter ?

Name ?

Default Value

Description

[Escaped HTML] [Preview](#)**Choice Parameter**

Name

Choices

us-west-2
eu-west-1
us-east-1
eu-central-1
ap-southeast-1
ap-southeast-2
ap-northeast-1
sa-east-1

Description

US West (N. California) : us-west-1
US West (Oregon) : us-west-2
EU (Ireland) : eu-west-1
EU (Frankfurt) : eu-central-1
Asia Pacific (Singapore) : ap-southeast-1
Asia Pacific (Sydney) : ap-southeast-2
Asia Pacific (Tokyo) : ap-northeast-1
South America (Sao Paulo) : sa-east-1[Escaped HTML] [Preview](#)☐ Permission to Copy Artifact**Delivery Pipeline configuration**

Stage Name

Task Name

Rebuild options:

☐ Rebuild Without Asking For Parameters☐ Throttle Concurrent Builds☐ Prepare an environment for the run☐ Disable Build (No new builds will be executed until the project is re-enabled.)☒ Execute concurrent builds if necessary☐ Restrict where this project can be run**Advanced Project Options****Source Code Management**☐ CVS☐ CVS Projectset☒ Git

Repositories

Repository URL

Credentials

- none -

Add

Advanced...

Add Repository

Delete Repository

Branches to build

Branch Specifier (blank for 'any')

*/master

Add Branch

Delete Branch

Repository browser

(Auto)

Additional Behaviours

Add

☐ None

☐ Subversion

Build Triggers

☐ Build after other projects are built

☐ Trigger builds remotely (e.g., from scripts)

☐ Build periodically

☒ Build when a change is pushed to GitHub

☐ GitHub Pull Request Builder

☐ Poll SCM

☐ [BuildResultTrigger] - Monitor build results of other jobs

Build Environment

☒ Delete workspace before build starts

Advanced...

☐ Abort the build if it's stuck

☐ Assign unique TCP ports to avoid collisions

☐ Color ANSI Console Output

☐ Copy files into the job's workspace before building

☐ Create Delivery Pipeline version

☐ Inject environment variables to the build process

☐ Inject passwords to the build as environment variables

☐ Restore OS X keychains after build process as defined in global configuration

☒ Send console log to Logstash

☐ Set jenkins user build variables

☐ Run an Android emulator during build

Build

Execute shell

Command

```
LOGIN_URL="/example/apps/login.php?username=${EXAMPLE_USERNAME}&password=${PASSWORD}"
echo ${LOGIN_URL}

source ~/.python/bin/activate
python ec2_loadtest.py "${DOMAIN}" "${USE_LOGIN}" "${LOGIN_URL}"
"$@"
```

See [the list of available environment variables](#)

Delete

Add build step

Post-build Actions

https://jenkins.intern.weebly.net/view/Load%20Testing/job/load_example/configure

5/6

Post build task

Tasks

Log text

Operation

-- AND --

Delete Log

Text

Add

Script

```
#Activate Python
source
~/.python/bin/activate

#Using the pip AWS
```

Run script only if all previous steps were successful ☐

Escalate script execution status to job status ☐

Add another task

Delete

Add post-build action