

Web Programming

JavaScript II

Prof. Josué Obregón

Department of Industrial Engineering- ITM
Seoul National University of Science and Technology



Objectives

- Identify and describe more complex JavaScript statements that are used for manipulating local storage and handling asynchronous server calls.
- Apply the acquired knowledge of JavaScript to construct dynamic web pages.

Agenda

- Create DOM elements
- Local Storage
- JSON
- AJAX

DOM element creation: createElement

```
const li = document.createElement('li');  
li.innerHTML = project;  
document.querySelector('#projects').append(li);
```

JS

- The createElement() method creates an element node.
- It creates the HTML element specified by *tagName*

Accessing local storage: `localStorage`

```
localStorage.getItem('counter');  
localStorage.setItem('counter',0);  
localStorage.removeItem('counter');  
localStorage.clear();
```

JS

- The `localStorage` object allows you to save key/value pairs in the browser.
- The `localStorage` object stores data with no expiration date
 - ▣ The data is not deleted when the browser is closed, and are available in future sessions
- The `sessionStorage` object stores data for only one session
 - ▣ The data is deleted when the browser is closed

JavaScript object syntax

```
let person = {  
    name: "Philip J. Fry",           // string  
    age: 23,                        // number  
    "weight": 172.5,                // number  
    friends: ["Farnsworth", "Hermes", "Zoidberg"], // array  
};  
  
person.age;  
person["weight"];  
person.friends[2];
```

JS

- in JavaScript, you can create a new object without creating a class
- can refer to the fields with `.fieldName` or `["fieldName"]` syntax

JavaScript Object Notation (JSON)

- JavaScript Object Notation (JSON): Data format that represents data as a set of JavaScript objects
 - natively supported by all modern browsers (and libraries to support it in old ones)
 - ~~• not yet as popular as XML, but steadily rising due to its simplicity and ease of use~~
 - JSON is a lightweight substitute for XML and it is more popular than XML because of JavaScript's dominance as the most widely used language of today.

Example of JSON


```
{  
  "origin": "New York",  
  "destination": "London",  
  "duration": 415  
}
```



```
{  
  "origin": {  
    "city": "New York",  
    "code": "JFK"  
  },  
  "destination": {  
    "city": "London",  
    "code": "LHR"  
  },  
  "duration": 415  
}
```

JSON format for exchange rate API


```
{  
  "rates": {  
    "EUR": 0.907,  
    "JPY": 109.716,  
    "GBP": 0.766,  
    "AUD": 1.479,  
  },  
  "base_code": { "USD"  
}
```



- **Synchronous:** user must wait while new pages load
 - ▣ The typical communication pattern used in web pages (click, wait, refresh)

Web applications and AJAX

- **web application:** a dynamic web site that mimics the feel of a desktop app
 - presents a continuous user experience rather than disjoint pages
 - examples: [Gmail](#), [Facebook](#), etc.
- **AJAX:** Asynchronous JavaScript and XML
 - not a programming language; a particular way of using JavaScript
 - downloads data from a server in the background
 - allows dynamically updating a page without making the user wait
 - avoids the "click-wait-refresh" pattern



- Asynchronous: user can keep interacting with page while data loads
 - ▣ communication pattern made possible by AJAX
 - ▣ we can ask additional requests to our own server or third-party servers

How AJAX Works

- [XMLHttpRequest](#) (callback-based)
 - XMLHttpRequest (XHR) objects are used to interact with servers. You can retrieve data from a URL without having to do a full-page refresh.
 - This enables a Web page to update just part of a page without disrupting what the user is doing.
- [Fetch API](#) (promise-based)
 - It provides a global `fetch()` method that provides an easy, logical way to fetch resources asynchronously across the network.
 - Unlike XMLHttpRequest that is a callback-based API, Fetch is promise-based and provides a better alternative

Web Programming

Some of the content of this slide are based or adapted from the chapter 8 slides of the book "[Web Programming Step by Step](#)" by Marty Stepp, Jessica Miller and Victoria Kirst.

Some of the contents of this slide are based or adapted from CS50web course. Attribution is given to the creators of this course. CS50web course is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International (CC BY-NC-SA 4.0) license.