SECURITY INCIDENT INVESTIGATION REPORT

INTERNAL — INVESTIGATION

Organisation	Report date	Classification
Northgate Retail Ltd	6.9.2026	Critical

Investigation team

Role	Name	Sections owned
Case Lead	Elay	1, 2, 4, 10
Identity & Access	Yossef	3, 5a
Data & Impact	Gavriel	5b, 7
Intel & Context	Elay	8, 9

1 · Executive Summary

Starting August 9, an outside party gained unauthorized access to our supplier web portal and pulled inventory data for all 38 branches. Over the following ten days, they moved deeper into our internal network using administrator-level access, reached the system that manages our payment registers, pushed changes to 34 individual registers, and gathered log files from those registers on an internal server. On August 19, they sent roughly 180 MB of data outside the company — the largest such transfer seen in three months — then deleted their access tools and erased over 2,500 files, likely to hide further evidence.

The incident is not fully contained. While the attacker removed some of their cleanup tools, automated data harvesting remained active after the initial deletion phase. The intrusion began with a successful login to the supplier portal from 77.124.66.19; the account used and the method that led to code execution on our internal application server have not been identified, and this entry path has not yet been remediated.

To fully contain the breach and protect operations, we urgently require executive authorization to isolate all affected payment registers, forensically image the staging server before any remediation, deploy EDR across the POS machines, enforce a reset of all administrative credentials, and start a specialized forensic audit of the collected log files to detect potential cardholder exposure.

2 · Incident Classification & Severity

Category: Data exfiltration **Severity:** Critical

Justification & Reasoning

- **Asset Criticality & Operational Scope:**
  - Compromised Critical Assets: The attacker executed code on SRV-VEND-APP, logged on to SRV-FILE-HQ as a.mizrahi with special privileges (4672), and accessed SRV-POSMGT — a highest-priority (Critical) asset — as r.stern. Additionally, we have high confidence the attacker took over the admin user a.mizrahi, which led to control of user r.stern.
  - Scope of Endpoints: The attacker deployed configuration modifications (`ngpos-cfg.exe`) and executed automated data collection across 34 out of 42 Point-of-Sale (POS) branch terminals. All affected POS terminals are designated as High-criticality assets lacking EDR agents.
- **Confirmed Impact:**
  - Verified Data Exfiltration: On August 19, 2026, between 02:55:01 and 04:10:01 UTC, the attacker exfiltrated 180.0 MiB of data from SRV-STAGE-01 to an external server (edge-sync-eu.net) across 6 HTTP POST requests, all allowed by the proxy.
  - Defense Evasion & Cleanup: The attacker deleted the scheduled task (`schtasks /delete`), erased 2,510 staged POS log files on SRV-STAGE-01, and took deliberate steps to cover their tracks.
  - Confirmed Business Impact: Notifications were received from the merchant acquiring bank regarding credit card fraud linked to transactions conducted at retail branches within the incident timeframe.
- **Potential Impact:**
  - Payment Card Data Exposure (PCI-DSS): The exfiltrated archive was built from POS log files (`*.log.1`). The type of data within the logs could not be verified due to missing information, but the log file types combined with the merchant bank's fraud alerts present a high risk of cardholder data compromise.
  - Active & Ongoing Exposure: The incident remains a live operational threat. Automated data collection continued for roughly 17 hours after the initial log deletion, with data capture truncating on August 20 mid-day while malicious activity was still active. Furthermore, the initial web application entry vector has not yet been remediated.

3 · Entities

Entity	Type	Role in the incident	Confidence
77.124.66.19	IP address	Logged in to the supplier portal and enumerated the inventory of all 38 branches through the supplier API	Confirmed
77.124.66.31	IP address	None	Ruled out
34 POS terminals: POS-B01-01 to POS-B38-01, excluding B04, B12, B27 and B35	POS	Ran `ngpos-cfg.exe` and sent `*.log.1` files to SRV-STAGE-01	Confirmed
WEB-SUPPLIER	Web server	Received the successful login and the API enumeration from 77.124.66.19. A web shell is inferred; the code execution itself was observed on SRV-VEND-APP	Confirmed
SRV-VEND-APP	Server	Ran attacker commands under IIS APPPOOL\supplier, hosted the scheduled task NGSupplierSync, and was the source of the a.mizrahi and r.stern logons	Confirmed
SRV-POSMGT	Server	Manages the POS terminals and hosts `pos-profile.dat`; accessed by r.stern from SRV-VEND-APP	Confirmed
SRV-STAGE-01	Server	Received and archived the files collected from the POS terminals; source of the exfiltration	Confirmed
SRV-FILE-HQ	Server	a.mizrahi enumerated 6 shared folders on this server (objective still unknown)	Confirmed
SRV-CARDPROC	Server	None	Ruled out
SRV-DC-01	Server	None	Ruled out
a.mizrahi	Admin user	The only admin account; the attacker used its privileges to carry out the attack	Confirmed
r.stern	Standard user	The main account used to access SRV-POSMGT and carry out most of the attack	Confirmed
e.katz	Standard user	None	Ruled out
y.oren	Standard user	None	Ruled out
IIS APPPOOL\supplier	Service identity	Ran the attacker's commands and scheduled task on SRV-VEND-APP	Confirmed
edge-sync-eu.net	External domain	Destination of the 6 POST requests (180 MiB)	Confirmed
NGSupplierSync	Scheduled task	Persistence on SRV-VEND-APP; created 08-10, deleted 08-19	Confirmed
ngpos-cfg.exe	Binary (POS management)	Applied `pos-profile.dat` on 34 POS terminals	Confirmed

Entity	Type	Role in the incident	Confidence
pos-profile.dat	Configuration file	Profile applied to the 34 terminals from \\SRV-POSMGT\cfg; content unknown	Confirmed
ngarch.exe	Binary (archiver)	Created the archive `ngsync-0819.dat` on SRV-STAGE-01	Confirmed
ngsync-0819.dat	Archive	D:\temp on SRV-STAGE-01; built from `*.log.1` files	Confirmed

4 · Timeline

All times are UTC. `winevent` is recorded in UTC+3; rows marked "converted from UTC+3" were adjusted.

Time (UTC)	Source	Host / Actor	What happened	Evidence ref
2026-08-09 07:12:00	weblog	WEB-SUPPLIER / 77.124.66.19	Successful POST to `/supplier/login`; the weblog has no user field, so the account cannot be identified.	Appendix B #1
2026-08-09 07:40:01 → 07:47:54	weblog	WEB-SUPPLIER / 77.124.66.19	44 requests to `/supplier/api/v2/inventory?branch=B<nn>` for branches B01–B38 at fixed 11-second intervals, all HTTP 200.	Appendix B #1
2026-08-10 23:04:01 (converted from UTC+3)	winevent 4688	SRV-VEND-APP / IIS APPPOOL\supplier	`w3wp.exe` spawned `cmd.exe` running whoami, ipconfig /all and net view.	Appendix B #2
2026-08-10 23:31:01 (converted from UTC+3)	winevent 4698	SRV-VEND-APP / IIS APPPOOL\supplier	Scheduled task NGSupplierSync created to run every 4 hours, with no program specified. Raw command: `schtasks /create /tn NGSupplierSync /sc hourly /mo 4`	Appendix B #2
2026-08-11 02:15:01 (converted from UTC+3)	winevent 4624 + 4672	SRV-FILE-HQ / a.mizrahi from SRV-VEND-APP	a.mizrahi logon (Type 3) to SRV-FILE-HQ from SRV-VEND-APP with special privileges (4672).	Appendix B #3
2026-08-12 22:00:00 → 08-15 22:46:12 (converted from UTC+3)	winevent 5140	SRV-FILE-HQ / a.mizrahi from SRV-VEND-APP	40 share-access events across 6 distinct shared folders; no file activity recorded.	Appendix B #12, #13
2026-08-15 21:46:59 (converted from UTC+3)	winevent 4624	SRV-POSMGT / r.stern from SRV-VEND-APP	r.stern logon (Type 3) to SRV-POSMGT from SRV-VEND-APP; all 188 earlier r.stern logons in 90 days came from WKS-PAY-02.	Appendix B #5
2026-08-16 01:19:59 → 01:29:20 (converted from UTC+3)	winevent 4688	34 × POS / r.stern	`ngpos-cfg.exe /apply /src \\SRV-POSMGT\cfg\pos-profile.dat` got executed on 34 POS machines at a fixed 17-second interval, consistent with a scripted rollout.	Appendix B #7
2026-08-16 03:00:00	fileaudit	SRV-STAGE-01 / r.stern	Collection begins on \\SRV-STAGE-01\temp.	Appendix B #8

Time (UTC)	Source	Host / Actor	What happened	Evidence ref
2026-08-16 → 2026-08-19, daily 03:00:00–22:34:19	fileaudit	SRV-STAGE-01 / r.stern from 34 × POS	r.stern wrote 2,850 distinct files (~430 MB) from 34 POS machines to SRV-STAGE-01 between 2026-08-16 and 2026-08-19, averaging ~84 files per machine.	Appendix B #8
2026-08-19 00:10:01 (converted from UTC+3)	winevent 4688	SRV-STAGE-01 / r.stern	Archive created from the 2,138 files (322.53 MiB) staged at that time. Raw command: `ngarch.exe -a -q -o D:\temp\ngsync-0819.dat \\SRV-STAGE-01\temp\*.log.1`	Appendix B #7, #6
2026-08-19 02:55:01 → 04:10:01	proxy	SRV-STAGE-01 / unknown	6 POSTs to edge-sync-eu.net, 180 MiB in total, 15 minutes apart, all allowed.	Appendix B #9
2026-08-19 04:30:00 (converted from UTC+3)	winevent 4698	SRV-VEND-APP / IIS APPPOOL\supplier	Scheduled task NGSupplierSync deleted (logged under EventCode 4698; the standard Windows ID for task deletion is 4699). Raw command: `schtasks /delete /tn NGSupplierSync /f`	Appendix B #2
2026-08-19 04:30:00 → 05:07:38	fileaudit	SRV-STAGE-01 / r.stern	2,510 files deleted in 37m 38s, while 22 new files were written in the same window.	Appendix B #10, #11
2026-08-19 22:34:19	fileaudit	SRV-STAGE-01 / r.stern	Last staged write; 340 files (53,820,040 bytes) from all 34 terminals were never deleted.	Appendix B #14

5 · Investigation — What We Checked

5a · Identity & Access

Question	Query / method	Result
Is e.katz's 1116 Event ID malicious?	`index=northgate sourcetype=winevent EventCode="1116"`	The alert fired because of a Windows Defender trigger; none were malicious.
How did the attacker get initial access?	`index=northgate sourcetype=winevent | where extracted_host="SRV-VEND-APP"`	3 logs containing the initial access and more.
What are all the actions done with the malicious files (ngpos-cfg.exe, ngarch.exe) by r.stern, with the time difference between logs?	`index=northgate sourcetype=winevent EventCode=4688 actor="r.stern" process="ngpos-cfg.exe" OR process="ngarch.exe" | streamstats window=1 current=f last(_time) as prev_time | eval delta_seconds = prev_time - _time | eval time_diff = tostring(abs(delta_seconds), "duration") | table _time, extracted_host, process, cmdline, time_diff | sort _time`	ngpos-cfg.exe ran on 34/42 POS terminals at fixed 17-second intervals, and 2 days 22 hours later ngarch.exe was used to archive the collected data.
What are all the scheduled task events (Event ID 4698)?	`index=northgate sourcetype=winevent EventCode=4698`	Only the 2 we already knew about: creation of the scheduled task, and its deletion after the POST requests through the proxy.
Did the attacker get access using Kerberoasting?	`index=northgate sourcetype=winevent EventCode=4769 OR EventCode=4768 earliest="08/01/2026:00:00:00" latest="08/20/2026:00:00:00" | streamstats window=1 current=f last(_time) as prev_time | eval delta_seconds = prev_time - _time | eval time_diff = tostring(abs(delta_seconds), "duration") | table _time, actor, EventCode, time_diff`	After checking all the logs we did not see any fixed intervals. a.mizrahi and r.stern were also checked separately. Nothing found; searched at different times as well.
How did the attacker know how many POS machines there are?	`index=northgate 77.124.66.19`	77.124.66.19 is known to be malicious, so we filtered on it and saw the reconnaissance on all the branches.
How many process creations	`index=northgate sourcetype=winevent EventCode=4688`	All r.stern processes; among them the

Question	Query / method	Result
did r.stern do?	`| where actor="r.stern"`	POS modifications and the data gathering.
Is y.oren a part of the attack?	`index=northgate actor="y.oren" action="create"`	He created files he is not supposed to, but further investigation showed they relate to his line of work.
How many POS machines are available in the logs?	`| inputlookup assets.csv`	38 branches with one primary terminal each (-01), plus 4 second terminals (-02) at B09, B18, B27 and B36 — a total of 42.
Has anyone else used the malicious exe files?	`index=northgate ngpos-cfg.exe AND index=northgate ngpos-cfg.exe r.stern`	Searching the whole log base for the exe returned 34 events; filtering by r.stern returned 34 again, meaning no one else used it.
Had a.mizrahi used any abnormal exe files?	`index=northgate sourcetype=winevent a.mizrahi EventCode=4688 | table _time, process`	Only legitimate processes such as Outlook, Word, Chrome and Excel.

5b · Data & Impact

Question	Query / method	Result
Which accounts move abnormal file volume?	`index=northgate sourcetype=fileaudit | stats count sum(bytes_out) by actor`	FINDING — r.stern: 5,457 events, 466,845,388 bytes, about 50× the ~110-event user baseline. Only svc_pricefeed is higher, and it is the sanctioned nightly price push.
Does any server show single-actor use?	`index=northgate sourcetype=fileaudit | stats count dc(actor) values(actor) by server`	FINDING — SRV-STAGE-01: 5,360 events, exactly one actor across 90 days. SRV-FILE-HQ, by contrast, is used by 30 accounts.
Was that server in use before the incident?	`index=northgate server=SRV-STAGE-01 latest="08/16/2026:00:00:00" | stats count`	NULL RESULT — zero events in the preceding 85 days. The first file activity on the host is the start of the harvest.
What was staged, how much, from where, and when?	`index=northgate server=SRV-STAGE-01 action=write | stats count sum(bytes_out) dc(src_host) min(_time) max(_time)`	FINDING — 2,850 files, 450,879,900 bytes (430.0 MiB), 34 terminals, 2026-08-16 03:00:00 → 2026-08-19 22:34:19.
Was the collection manual or automated?	`index=northgate server=SRV-STAGE-01 action=write | bin _time span=1d | stats count min(_time) max(_time) by _time`	FINDING — 713/712/713/712 files per day, start and end identical to the second daily (03:00:00 → 22:34:19), ~101-second cadence, two parallel write streams. Automated.

Question	Query / method	Result

Was evidence destroyed, and completely?	`index=northgate action=delete`
	`| stats count min(_time) max(_time)`
	`(write-minus-delete comparison`
	`by object_path)`
		PARTIAL — 2,510 files destroyed in 37m 38s on 19/08. 340 files (53,820,040 bytes) were never deleted, spanning all 34 terminals.

Did collection stop during the cleanup?	`index=northgate action=write`
	`earliest="08/19/2026:04:30:00"`
	`latest="08/19/2026:05:07:38"`
		NEGATIVE — no. 22 files were written during the deletion window; the two processes ran concurrently.

Did the activity stop at all?	`index=northgate action=write` `earliest="08/19/2026:05:07:39"`	NEGATIVE — no. 624 further files to 22:34:19. Data ends 20/08 11:56 with the operation still active.

What did the compromised account read?	`index=northgate actor=r.stern`
	`action=read`
	`| stats count sum(bytes_out) by`
	`server`
		NULL RESULT — zero reads on the staging server; all 5,360 events there are writes and deletes. The account's only reads are 80 Payments documents on \\SRV-FILE-HQ\Payments from its own workstation, spread across 90 days.

Did the source terminals have endpoint detection?	`index=northgate action=write`
	`| stats count by src_host`
	`| lookup assets.csv hostname as`
	`src_host`
	`OUTPUT has_edr criticality`
		NULL RESULT — none. All 34 are has_edr=no, criticality=high, segment pos-branch. No process telemetry exists from any branch terminal.

Were all POS terminals affected?	`| inputlookup assets.csv`
	`| search hostname=POS-*`
	`(compared against observed src_host)`
		PARTIAL — 34 of 42. Four were enumerated then skipped despite logging normally; four emit no events at all. 34 is a floor, not a total.

Was the cloud platform the exfiltration channel?	`index=northgate sourcetype=cloudaudit`
	`actor=r.stern | stats count by`
	`operation;`
	`operation=share_link_create`
	`| stats count by link_scope`
		NULL RESULT — no. 37 r.stern events spread evenly across 90 days with no clustering on 16–19/08. r.stern's 5 share links are internal, as are all 63 share links organisation-wide; zero external.

Were backups deleted, failed or tampered with?	`index=northgate sourcetype=backup`
	`| stats count by status`
	`(weekly archive size trend)`
		NULL RESULT — no. 103 of 103 jobs SUCCESS. The weekly card-processing archive ran all 13 weeks at 1,906–2,265 GB with no anomalous drop.

Is backup coverage adequate?	`index=northgate sourcetype=backup` `| stats count by target`	GAP — all 103 jobs target SRV-FILE-HQ alone. All three critical servers are unprotected, as are SRV-STAGE-01 and all 42 terminals.

Was the cardholder environment accessed?	`index=northgate sourcetype=winevent`
	`EventCode=5140`
	`object_name="*CARDPROC*"`
	`| stats count by actor src_host`
		NULL RESULT — no. All 74 connections to \\SRV-CARDPROC\Payments originate from four Payments workstations

Question	Query / method	Result
		operated by their assigned users. None from SRV-VEND-APP or SRV-STAGE-01.
Were the POS price files tampered with?	`index=northgate object_path="*\\prices\\*" | stats count by actor action`	NULL RESULT — no. All 27,360 events are svc_pricefeed writes, uniform at 40,000–46,300 bytes, continuing normally through 20/08.
Was anything taken from the file server?	`index=northgate sourcetype=fileaudit src_host=SRV-VEND-APP | stats count`	NULL RESULT — no. During the four-night share enumeration, r.stern has zero file events on SRV-FILE-HQ and a.mizrahi has four, from their own workstation.
Was m.saban, the registered owner of the staging server, involved?	`index=northgate actor=m.saban | stats count by server; winevent | stats count by src_host`	RULED OUT — all 126 file events are on \\SRV-FILE-HQ\IT from WKS-IT-09; zero events on the server they own. All 522 winevent events originate from that same workstation.
Did the staged data leave the network?	`index=northgate sourcetype=proxy src_host=SRV-STAGE-01 (cross-source, Intel & Context)`	FINDING — yes. Six POSTs to edge-sync-eu.net, 188,743,680 bytes (180.0 MiB), 19/08 02:55:01–04:10:01, all permitted. The only six proxy events that host generates in 90 days.
Was the account's earlier file activity malicious?	`index=northgate actor=r.stern server=SRV-FILE-HQ | stats count min(_time) max(_time) by action`	COULD NOT DETERMINE — 97 events on \\SRV-FILE-HQ\Payments from the account's own workstation, matching its department and function, at 08:00–16:00 local. Not separable from legitimate work.

5c · Intel & Context

Question	Query / method	Result
Who sends the most bytes out through the proxy?	`index="northgate" sourcetype="proxy" | table time, method, bytes_out, verdict, dest_host | sort -bytes_out`	SRV-STAGE-01 accounts for the six largest bytes-out requests in the proxy, all allowed.
Did SRV-STAGE-01 speak to the proxy at other times as well?	`index="northgate" sourcetype="proxy" src_host="SRV-STAGE-01" method!="POST"`	No logs found.
What other hosts talked with edge-sync-eu.net?	`index="northgate" sourcetype="proxy" dest_host="edge-sync-eu.net" | stats dc(src_host) values(src_host)`	Only SRV-STAGE-01 sends traffic to edge-sync-eu.net.
What are the distinct user agents in the proxy? Are there	`index=northgate sourcetype=proxy | stats count by user_agent`	There is no suspicious user agent.

Question	Query / method	Result

any suspicious ones?	`| eval is_suspicious=case(`
	`  isnull(user_agent) OR user_agent=""`
	`  OR user_agent="-",`
	`  "Suspicious: Missing User-Agent",`
	`  len(user_agent) < 10,`
	`  "Suspicious: Extremely short User-Agent",`
	`  match(user_agent, "(?i)(curl|wget|python|`
	`  powershell|cmd|nikto|sqlmap|nmap|`
	`  go-http-client|java)"),`
	`  "Suspicious: Automated/CLI tool",`
	`  true(), "Legitimate / Standard")`
	`| stats dc(user_agent) as`
	`  total_distinct_user_agents,`
	`  values(user_agent) as user_agent_list,`
	`  values(is_suspicious) as analysis_status`	

Are there hosts whose average daily bytes out during the last two weeks is at least double their average before that?	`index="northgate" sourcetype="proxy" earliest="05/23/2026:11:08:27" latest="08/06/2026:23:59:59"`
	`| bucket time span=1d`
	`| stats sum(bytes_out) as bytes_per_day`
	`  by src_host, time`
	`| stats avg(bytes_per_day) as`
	`  daily_avg_before_incident by src_host`
	`| join type=left src_host [`
	`  search index="northgate" sourcetype="proxy"`
	`  earliest="08/07/2026:00:00:00"`
	`  latest="08/20/2026:11:48:58"`
	`  | bucket time span=1d`
	`  | stats sum(bytes_out) as bytes_per_day`
	`  by src_host, time`
	`  | stats avg(bytes_per_day) as`
	`  daily_avg_in_incident by src_host]`
	`| where daily_avg_in_incident >=`
	`  (daily_avg_before_incident*2)`
		WKS-HQ-13, WKS-HQ-20 and WKS-IT-08 doubled their average daily outbound traffic during the incident window compared to their baseline. After further investigation, this anomaly is not a strong indicator of malicious activity.

What outbound proxy access was not approved, and for how many unique machines?	`index="northgate" sourcetype="proxy" verdict!="allowed"` `| stats dc(src_host), values(src_host)`	30 machines found, no anomaly found.

Question	Query / method	Result

What IP addresses make the most requests to WEB-SUPPLIER?	`index="northgate" sourcetype=weblog`
	`| stats count as total_requests,`
	`  sum(bytes_out) as total_bytes_sent,`
	`  dc(host) as unique_hosts_visited,`
	`  dc(uri_path) as unique_paths_requested`
	`  by src_ip`
	`| eval total_MB =`
	`  round(total_bytes_sent/1024/1024, 2)`
	`| table src_ip, total_requests, total_MB,`
	`  unique_hosts_visited,`
	`  unique_paths_requested`
	`| sort - total_requests`
		77.124.66.31 made 91 requests and 77.124.66.19 made 48 requests, while all the others made between 1 and 2 requests.

Which distinct paths did those suspicious addresses access on the company's public website?	`index=northgate sourcetype=weblog`
	`| where src_ip="77.124.66.31"`
	`  or src_ip="77.124.66.19"`
	`| stats count(uri_path) as total_count,`
	`  dc(uri_path) as unique_uri_count,`
	`  values(uri_path) as requested_paths,`
	`  sum(bytes_out) as total_bytes by src_ip`
	`| table src_ip, total_count,`
	`  unique_uri_count, requested_paths`
		77.124.66.19 enumerated /supplier/api/v2/inventory for all branches (possible IDOR; the account's authorisation scope was not verified).
		77.124.66.31 accessed 6 unique paths — no malicious activity was found.

6 · What Could Not Be Determined

Item	Reason	What this means for the reader
Obtaining a web shell on SRV-VEND-APP via the API enumeration	No data source	Cannot rely on: Assuming the API enumeration directly led to the web shell vulnerability on SRV-VEND-APP. Needed to close: Web application access logs, WAF telemetry, or code audit for SRV-VEND-APP.
Relationship between WEB-SUPPLIER and SRV-VEND-APP	No data source	Cannot rely on: Assuming requests received by WEB-SUPPLIER (dmz-supplier) were routed to SRV-VEND-APP (corp). The asset inventory has no role field, and no available source records traffic between the two. Needed to close: Firewall or network flow logs, or architecture documentation.
What was inside the POST requests sent to edge-sync-eu.net	No access	Cannot rely on: Confirming that the exfiltrated data matches the archived files staged in \\SRV-STAGE-01\temp. Needed to close: PCAP files, proxy payload inspection for outbound traffic to edge-sync-eu.net.
The identity behind the POST requests to edge-sync-eu.net	No data source	Cannot rely on: Attributing outbound C2 traffic to a specific user or service account, since proxy logs lack actor details. Needed to close: Endpoint EDR telemetry.
Initial credential theft method for r.stern and a.mizrahi	No access	Cannot rely on: Determining the exact technique (e.g., LSASS dumping, phishing) used to compromise these accounts. Needed to close: Memory forensic dumps from compromised hosts.
Actions performed by ngpos-cfg.exe on POS terminals and staging content sent to \\SRV-STAGE-01\temp	No data source	Cannot rely on: Knowing the exact nature of harvested data (whether credit card Track data, configs, or system logs). Needed to close: Deploying EDR on POS endpoints and performing forensic investigation on ngpos-cfg.exe and ngsync-0819.dat.
Exact execution details of scheduled task NGSupplierSync	No data source	Cannot rely on: Verifying the specific payload or commands executed by NGSupplierSync; the command has no /tr flag, which is the flag that specifies the program to run. Needed to close: Task Cache registry and process tree analysis — inspect HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks to extract the defined action/payload, and reconstruct the process tree by tracing parent-child relationships.
Confirmation of HTTP request receipt at edge-sync-eu.net	Outside our authority	Cannot rely on: Verifying whether the remote C2 server successfully received and stored the transferred data. Needed to close: Seizure/analysis of the external infrastructure by law enforcement, or external ISP logs.

Item	Reason	What this means for the reader
Full containment verification of attacker foothold in the internal network	Insufficient time	Cannot rely on: Assuming the adversary has been completely evicted or that no secondary backdoors remain. Needed to close: Forensic disk analysis of SRV-VEND-APP, reverse engineering of pos-profile.dat, and an enterprise-wide Active Directory compromise assessment.

7 · Impact Assessment

The incident affected the branch point-of-sale estate and resulted in confirmed data egress. The cardholder data environment itself was not reached. Whether payment card data was present in the material taken cannot be determined from the supplied logs, and that distinction governs everything below.

Scope

- **Hosts:**
  - 34 of Northgate's 42 branch POS terminals, all rated high criticality, none carrying endpoint detection.
  - SRV-STAGE-01 — the staging server used to aggregate and export the harvest.
  - SRV-VEND-APP and the critical-rated SRV-POSMGT — used as access points.
- **Accounts:**
  - a.mizrahi (IT-Infra administrator) and r.stern (Payments) — credentials used without authorisation. Both logged on from SRV-VEND-APP, and r.stern's account wrote the staged files from the 34 POS terminals.
  - IIS APPPOOL\supplier — the web application service identity, the attacker's foothold.
- **Data:**
  - 2,850 POS log files (`*.log.1`), 450,879,900 bytes (430.0 MiB), collected 2026-08-16 03:00:00 → 2026-08-19 22:34:19 UTC.

Confirmed Impact

- **Data left the estate:**
  - On 19 August between 02:55:01 and 04:10:01 UTC, 188,743,680 bytes (180.0 MiB) were transmitted from SRV-STAGE-01 to the external host edge-sync-eu.net across six HTTP POST requests. Every request was permitted by the proxy.
  - No POS terminal appears as a source in the proxy logs; the only observed egress path is SRV-STAGE-01.
- **Collection and destruction:**
  - The material was assembled over four days from 34 branch terminals. Twenty minutes after the final upload, the attacker deleted 2,510 of the staged files. 340 files, 53,820,040 bytes, survived.
- **What was demonstrably NOT affected:**
  - The cardholder data environment was never reached. All 74 connections to \\SRV-CARDPROC\Payments across 90 days originate from four Payments workstations operated by their assigned users. The share was never even enumerated, despite the attacker holding administrator credentials.
  - Nothing was taken from the corporate file server. Four nights of share enumeration produced zero file opens.
  - Backup integrity is sound. 103 of 103 jobs successful, no evidence of tampering.

Potential Impact

- **Presence of cardholder data — unresolved:**

  - The file naming (`ngpos-*.log.1`) and the source hosts suggest these are rotated POS application logs, which makes card data plausible. No source in the supplied set records file contents. The assessment rests on provenance, not observation.
  - The acquirer's report of fraud on cards used in Northgate branches matches this incident in timing and scope. The logs alone do not prove the connection.
- **Volume discrepancy:**
  - 180.0 MiB was transmitted against 430.0 MiB staged. An archiving operation on 19 August at 00:10:01 (2,138 files, 322.53 MiB) accounts for the gap at a 56% compression ratio, normal for text logs, but a transfer through an unlogged channel cannot be excluded.
- **Scope is a floor, not a total:**
  - Four terminals emit no telemetry whatsoever, so 34 affected terminals is the minimum, not the maximum.
  - SRV-CARDPROC has no file-level auditing. We observe connections to it but not what was opened inside legitimate sessions.

Business Impact

- **Card fraud and notification exposure:**
  - Fraudulent transactions have already been reported by the card processor against cards used in Northgate branches during the affected window. Should cardholder data be confirmed in the exfiltrated material, breach-notification duties and card-scheme consequences follow, a determination requiring evidence this dataset does not contain.
- **Loss of recovery capability (independent of the intrusion):**
  - All 103 backup jobs target SRV-FILE-HQ alone. All three critical servers — SRV-CARDPROC, SRV-DC-01 and SRV-POSMGT — have no recovery capability, nor does the branch estate.
  - Northgate cannot currently restore its card processing, domain, or point-of-sale management infrastructure from backup.

Current Exposure

- **The operation was still running when logging ended:**
  - No event in any of the seven sources shows the activity stopping. Collection continued for seventeen hours after the cleanup and was never interrupted by it. The final staged file was written at 2026-08-19 22:34:19; logging ends the following midday with the operation active.
- **Surviving evidence exists in one location only:**
  - 340 files spanning all 34 affected terminals remain on the live disk of SRV-STAGE-01, alongside the archive D:\temp\ngsync-0819.dat. That host is covered by no backup job — this material cannot be recovered once lost, and it is the sole remaining route to establishing whether cardholder data was in scope.
  - Forensic imaging of SRV-STAGE-01 must precede any remediation, rebuild or restart of that host.
- **Access cannot be confirmed closed:**
  - The attacker removed their persistence mechanism on 19 August. The intrusion began with a successful login to the supplier portal from 77.124.66.19, but the account used and the method that led to code execution on SRV-VEND-APP remain unidentified — no web server log exists for SRV-VEND-APP. This entry path has not been remediated, and we cannot state that access has been closed.

Assessment & Confidence Level

Confidence Level: High — for the confirmed impact. Egress volume, timing, destination and the surviving file count are each established by a single unambiguous log source and were independently re-derived.

Confidence Level: Medium — for the link between the exfiltrated material and the acquirer's fraud report. Timing and scope align closely, but the absence of content logging means the connection is inferential.

Confidence Level: Not assessable — for the presence of cardholder data in the exfiltrated files. This is not a matter of insufficient analysis but of absent telemetry, and it will remain unresolved until SRV-STAGE-01 is imaged.

8 · MITRE ATT&CK Mapping & Detection Gaps

Stage	Tactic	Technique	Detected ?	By what
POST /supplier/login	Initial Access (TA0001)	Valid Accounts (T1078) — suspected; the account was not identified	Yes	weblog
44 API requests enumerating /inventory	Reconnaissance (TA0043)	Active Scanning (T1595) — sequential branch IDs B01–B38	Yes	weblog
w3wp.exe spawns cmd.exe and runs whoami, ipconfig /all, net view	Execution (TA0002) Discovery (TA0007)	Command and Scripting Interpreter: Windows Command Shell (T1059.003) System Owner/User Discovery (T1033) System Network Configuration Discovery (T1016) Network Share Discovery (T1135)	Yes	winevent
Scheduled task creation	Persistence (TA0003) Privilege Escalation (TA0004)	Scheduled Task/Job: Scheduled Task (T1053.005)	Yes	winevent
Account takeover of a.mizrahi — admin credentials used from the compromised host	Privilege Escalation (TA0004), Lateral Movement (TA0008) or Credential Access (TA0006)	Valid Accounts: Domain Accounts (T1078.002) Use Alternate Authentication Material (T1550) OS Credential Dumping (T1003)	No	—
a.mizrahi logon Type 3 from the compromised asset (SRV-VEND-APP)	Lateral Movement (TA0008) Defense Evasion (TA0005)	Remote Services (T1021) Valid Accounts: Domain Accounts (T1078.002)	Yes	winevent
Automated network share enumeration (Event 5140)	Discovery (TA0007)	Network Share Discovery (T1135)	Yes	winevent
Account takeover of r.stern on SRV-VEND-APP	Privilege Escalation (TA0004), Lateral Movement (TA0008) or Credential Access (TA0006)	Valid Accounts: Domain Accounts (T1078.002) Use Alternate Authentication Material (T1550) OS Credential Dumping (T1003)	No	—
r.stern logon Type 3 from the compromised asset (SRV-VEND-APP)	Lateral Movement (TA0008)	Remote Services: SMB/Windows Admin Shares (T1021.002) Valid Accounts: Domain Accounts (T1078.002)	Yes	winevent

Stage	Tactic	Technique	Detected ?	By what
Automated POS profile deployment via ngpos-cfg.exe	Execution (TA0002)	Command and Scripting Interpreter (T1059) System Services: Service Execution (T1569.002) — possible; the remote launch method was not logged	Yes	winevent
Data collection on \\SRV-STAGE-01\temp (*.log.1)	Collection (TA0009)	Data Staged: Remote Data Staging (T1074.002)	Yes	fileaudit
Archive *.log.1 files into ngsync-0819.dat	Collection (TA0009) Defense Evasion (TA0005)	Archive Collected Data: Archive via Utility (T1560.001)	Yes	winevent
6 POSTs to edge-sync-eu.net	Exfiltration (TA0010) Command and Control (TA0011)	Exfiltration Over C2 Channel (T1041) Scheduled Transfer (T1029) Application Layer Protocol: Web Protocols (T1071.001)	Yes	proxy
Deletion of the scheduled task	Defense Evasion (TA0005)	Indicator Removal (T1070)	Yes	winevent
Deletion of 2,510 *.log.1 files on \\SRV-STAGE-01\temp	Defense Evasion (TA0005)	Indicator Removal: File Deletion (T1070.004)	Yes	fileaudit

9 · What This Resembles

The overall attack chain observed in this incident resembles the TTPs of financial cybercrime groups specializing in Point-of-Sale (POS) compromises and retail supply-chain intrusions, such as FIN6 and FIN7.

What Fits

- **Initial Access & Supply Chain Targeting:** The attacker came in through the supplier portal (POST /supplier/login), then ran commands through the IIS worker process on SRV-VEND-APP (`w3wp.exe` spawning `cmd.exe`), consistent with a web shell. This matches how groups like FIN6/FIN7 target third-party vendors or public web servers to get inside an enterprise network.
- **Automated Reconnaissance & Evasion:** The attacker used scripted, fixed-interval requests (every 11s for API branches, every 396s for SMB shares) to scan the network. This is a common tactic to map out internal assets while trying to stay under the radar of volume-based alerts.
- **POS Terminal Targeting & Software Deployment:** Using `ngpos-cfg.exe` to push `pos-profile.dat` across 34 terminals at exact 17-second intervals is a classic "Living-off-the-Land" technique. Attackers frequently abuse internal management tools to push malicious configurations or code to POS devices.
- **Staging, Masquerading, and Log Harvesting:** Gathering 2,138 `.log.1` files into a single `.dat` archive (`ngsync-0819.dat`) and sending them out via HTTP POSTs matches standard POS staging and exfiltration patterns.

What Does NOT Fit

- **No memory-scraping malware:** Traditional POS attacks rely on dedicated memory-scraping malware injected directly into POS processes. In this incident, the attacker modified system settings via `pos-profile.dat` using the native management binary (`ngpos-cfg.exe`).
- **Stealing logs instead of live memory dumps:** Rather than dumping process memory live to disk, the attacker collected application log files (`*.log.1`) from the POS terminals to SRV-STAGE-01. This suggests the configuration change may have caused the POS software to write payment card data into log files. File contents could not be verified (see Section 7).

Assessment & Confidence Level

Confidence Level: High — that this is a financially motivated campaign targeting payment card data on POS systems.

Basis: the full attack lifecycle (supply-chain web access, Living-off-the-Land execution, POS-focused targeting, automated staging, and cleanup of the scheduled task and staged files), together with the acquiring bank's report of card fraud on cards used at Northgate branches during the same period.

Whether card data was actually captured remains unverified (see Section 7).

10 · Recommendations

Immediate — within 24 hours

#	Recommendation	Ties to finding	Authority
1	Block IP/domain on proxy and perimeter firewall for edge-sync-eu.net.	6 HTTP POST requests exfiltrating 180 MB to edge-sync-eu.net.	Requires approval
2	Threat intelligence enrichment about edge-sync-eu.net.	C2 exfiltration via 6 HTTP POST requests.	Tier 1
3	Revoke credentials and force password reset for users a.mizrahi and r.stern. Terminate active SMB and network sessions.	Lateral movement from compromised assets.	Requires approval
4	Isolate SRV-VEND-APP and remove any persisting web shell files/processes spawning from w3wp.exe.	Web shell foothold on IIS server (w3wp.exe spawning cmd.exe).	Requires approval
5	Audit and revert any modified POS profile files (pos-profile.dat) across all 34 terminals.	Unauthorized POS profile deployment via ngpos-cfg.exe.	Management / Legal
6	Forensically image SRV-STAGE-01 (disk and memory) before any remediation, rebuild or restart of that host.	340 surviving files and ngsync-0819.dat exist only on this host, which no backup job covers.	Requires approval
7	Reset all administrative credentials (Domain-Admins), not only the two compromised accounts.	Admin account a.mizrahi used from a compromised host; credential theft method unknown.	Requires approval

Short term — within 30 days

#	Recommendation	Ties to finding	Authority
1	Escalate to Tier 2 to deploy new SIEM detection rules for Event ID 4698 (scheduled task creation) and Event ID 5140 (network share access).	Unmonitored creation of the NGSupplierSync scheduled task and share access across 6 shares.	Tier 1
2	Recommend implementing authentication logging and user ID mapping on /supplier/login.	Successful POST to /supplier/login lacked user field logging in web logs.	Tier 1
3	Recommend applying API rate-limiting and authorization checks on /supplier/api/v2/inventory.	Sequential enumeration of 38 branch codes (B01–B38) at fixed 11-second intervals.	Tier 1
4	Recommend restricting execution of administrative tools ngpos-cfg.exe and ngarch.exe via AppLocker/WDAC policy.	Abuse of ngpos-cfg.exe and ngarch.exe for profile updates and log archiving (322.5 MiB).	Tier 1
5	Deploy EDR on all 42 POS terminals.	All 34 affected terminals have no EDR and no process telemetry.	Requires approval

#	Recommendation	Ties to finding	Authority
6	Extend backup coverage to SRV-CARDPROC, SRV-DC-01, SRV-POSMGT, SRV-STAGE-01 and the POS estate.	All 103 backup jobs target SRV-FILE-HQ alone.	Management / Legal

Long term

#	Recommendation	Ties to finding	Authority
1	Review the POS application's logging configuration to confirm *.log.1 files cannot contain cardholder data, and redesign it if they can.	Archiving of 2,138 *.log.1 files from \\SRV-STAGE-01\temp.	Management / Legal
2	Restrict direct SMB/RPC traffic between SRV-VEND-APP, POS management servers and POS terminals by enforcing network micro-segmentation.	Direct lateral movement from SRV-VEND-APP to SRV-FILE-HQ and SRV-POSMGT.	Management / Legal
3	Implement MFA and source IP allow-listing for all external supplier access portals.	Initial access gained via external IP 77.124.66.19 accessing the supplier web portal.	Management / Legal

Appendix A · AI Verification Log

`ai-verification-log-project.xlsx`

Where AI helped, where it failed, and what we changed

Throughout the investigation, AI was particularly useful in calculating precise time intervals between sequential requests, which allowed us to identify automated patterns such as the fixed 11-second API enumeration and the 17-second configuration rollout across POS machines. Additionally, AI assisted us in crafting highly effective Splunk queries for analyzing file transfers sent from the POS terminals to SRV-STAGE-01 (as detailed in Appendix B #8), allowing us to rapidly quantify the staged log volume and daily write cadences. Beyond technical analysis, AI also helped design a clean, visually appealing slide presentation to effectively communicate our findings. Where AI fell short was in mishandling time zone translations and occasionally missing subtle correlation context between disparate log sources, which required us to manually validate all timestamps, correct query logic, and ground every conclusion directly in raw log evidence.

Appendix B · Queries Used

#	Section	Query

1	4	`index=northgate sourcetype=weblog src_ip="77.124.66.19"`
		`| table time, src_ip, uri_path, status, bytes_out, method, user_agent`
		`| sort time`

2	4	`index=northgate sourcetype=winevent`
		`| where extracted_host="SRV-VEND-APP"`
		`| table _time, extracted_host, EventCode, actor, src_host, logon_type,`
		`cmdline, target_account, object_name`
		`| sort _time`

3	4	`index=northgate sourcetype=winevent src_host="SRV-VEND-APP"`
		`extracted_host="SRV-FILE-HQ"`
		`| where EventCode=4672 or EventCode=4624`
		`| sort _time`

4	4	`index=northgate sourcetype=winevent EventCode=5140 src_host="SRV-VEND-APP"`
		`extracted_host="SRV-FILE-HQ" actor="a.mizrahi"`
		`| stats count min(_time) as min_time_epoch by object_name`
		`| sort min_time_epoch`
		`| streamstats current=f window=1 last(min_time_epoch) as prev_time_epoch`
		`| eval time_diff_sec = min_time_epoch - prev_time_epoch`
		`| eval time_diff = tostring(time_diff_sec, "duration")`
		`| eval min_time = strftime(min_time_epoch, "%Y-%m-%d %H:%M:%S")`
		`| table object_name count min_time time_diff`

5	4	`index=northgate sourcetype=winevent EventCode=4624 src_host="SRV-VEND-APP"`
		`extracted_host="SRV-POSMGT" actor="r.stern"`
		`| lookup assets hostname AS src_host OUTPUT owner AS current_src_owner`
		`| lookup assets owner AS actor OUTPUT hostname AS typical_user_hostname`
		`| eval is_expected_hostname = if(lower(typical_user_hostname) ==`
		`lower(src_host), "True", "False")`
		`| table _time, actor, typical_user_hostname, src_host, current_src_owner,`
		`is_expected_hostname, extracted_host`

6	4	`index=northgate sourcetype=fileaudit server="SRV-STAGE-01"`
		`object_path="*.log.1*" latest="08/19/2026:00:10:01"`
		`| stats dc(object_path) as object_path_count sum(bytes_out) as total_bytes_out`
		`| eval total_MB_transfered = round(total_bytes_out / 1024 / 1024, 2)`
		`| fields object_path_count, total_MB_transfered`

#	Section	Query

7	4	`index=northgate sourcetype=winevent EventCode=4688 actor="r.stern"`
		`(process="ngpos-cfg.exe" OR process="ngarch.exe")`
		`| sort _time`
		`| streamstats window=1 current=f last(_time) as prev_time`
		`| eval delta_seconds = _time - prev_time`
		`| eval time_diff = tostring(abs(delta_seconds), "duration")`
		`| eval _time=strftime(_time, "%Y-%m-%d %H:%M:%S")`
		`| table _time, extracted_host, process, cmdline, time_diff`

8	4	`index=northgate sourcetype=fileaudit actor="r.stern" src_host!="WKS-PAY-02" src_host!`
		`="SRV-STAGE-01"`
		`| rex field=object_path "(?<file_type>\.[^\\\\]+)$"`
		`| fillnull value="no_extension" file_type`
		`| stats dc(object_path) as distinct_files values(action) as actions`
		`values(file_type) as file_types sum(bytes_out) as bytes`
		`min(_time) as first_seen max(_time) as last_seen by src_host, server`
		`| eventstats sum(bytes) as total_bytes values(file_types) as all_file_types`
		`dc(src_host) as total_hosts`
		`| eval MB_per_host=round(bytes/1024/1024,2), total_MB=round(total_bytes/1024/1024,2)`
		`| eval only_log1=if(mvcount(all_file_types)=1 AND`
		`mvindex(all_file_types,0)=".log.1","yes","no")`
		`| sort first_seen`
		`| eval first_seen=strftime(first_seen,"%Y-%m-%d %H:%M:%S"),`
		`last_seen=strftime(last_seen,"%Y-%m-%d %H:%M:%S")`
		`| table src_host, server, distinct_files, actions, MB_per_host, first_seen,`
		`last_seen, total_hosts, total_MB, only_log1, all_file_types`

9	4	`index=northgate sourcetype=proxy src_host="SRV-STAGE-01"`
		`| eval MB_out = round(sum(bytes_out/1024/1024),2)`
		`| table time, method, MB_out, verdict, dest_host`
		`| eventstats sum(MB_out) as total_MB_out`
		`| sort time`

10	4	`index=northgate sourcetype=fileaudit src_host="SRV-STAGE-01"`
		`actor="r.stern" action="delete"`
		`| stats count as deleted_files, min(_time) as min_time, max(_time) as max_time`
		`| eval duration_sec = max_time - min_time`
		`| eval duration = tostring(duration_sec, "duration")`
		`| eval first_delete = strftime(min_time, "%Y-%m-%d %H:%M:%S"),`
		`last_delete = strftime(max_time, "%Y-%m-%d %H:%M:%S")`
		`| table deleted_files first_delete last_delete duration`

#	Section	Query
11	4	`index=northgate sourcetype=fileaudit actor="r.stern" earliest="08/19/2026:04:30:00" latest="08/19/2026:05:07:38" | where src_host!="WKS-PAY-02" and src_host!="SRV-STAGE-01" | stats count, dc(object_path) as distinct_object_path, values(action) as action, sum(bytes_out) as total_bytes, min(time) as min_time, max(time) as max_time by src_host, server | eventstats sum(count) as total_actions_all, sum(total_bytes) as total_bytes_all | eval MB_transferred = round(total_bytes / 1024 / 1024, 2) | eval total_MB_transferred_all = round(total_bytes_all / 1024 / 1024, 2) | sort min_time | where distinct_object_path=count | table src_host, server, count, distinct_object_path, action, MB_transferred, min_time, max_time, total_actions_all, total_MB_transferred_all`
12	4	`index=northgate sourcetype=winevent EventCode=5140 actor="a.mizrahi" src_host="SRV-VEND-APP" extracted_host="SRV-FILE-HQ" | eventstats count as total_count_share_folders | stats dc(object_name) as distinct_share_folders values(object_name) as values_share_folders min(_time) as first_seen max(_time) as last_seen | eval first_time_formatted=strftime(first_seen, "%Y-%m-%d %H:%M:%S") | eval last_time_formatted=strftime(last_seen, "%Y-%m-%d %H:%M:%S") | fields - first_seen, last_seen`
13	4	`index=northgate sourcetype=fileaudit src_host=SRV-VEND-APP | stats count`
14	4	`index=northgate sourcetype=fileaudit actor="r.stern" | where src_host!="WKS-PAY-02" and src_host!="SRV-STAGE-01" | stats min(_time) as min_time, max(_time) as max_time by src_host, server | sort limit=1 -max_time | eval min_time=strftime(min_time, "%Y-%m-%d %H:%M:%S") | eval max_time=strftime(max_time, "%Y-%m-%d %H:%M:%S")`

Appendix C · Evidence Excerpts

#1

time	src_ip	uri_path	status	bytes_out	method	user_agent
2026-08-09 07:12:00	77.124.66.19	/supplier/login	200	1450	POST	Mozilla/5.0 (Macintosh; Intel Mac OS X 14_5) Safari/17.5

#2

_time	extracted_host	EventCode	actor	src_host	logon_type	cmdline	target_account	object_name
2026-08-10 23:04:01.468	SRV-VEND-APP	4688	IIS APPPOOL\supplier			cmd.exe /c "whoami & ipconfig /all & net view" (spawned by w3wp.exe)		
2026-08-10 23:31:01.469	SRV-VEND-APP	4698	IIS APPPOOL\supplier			schtasks /create /tn NGSupplierSync /sc hourly /mo 4	NGSupplierSync	\NGSupplierSync
2026-08-19 04:30:00.469	SRV-VEND-APP	4698	IIS APPPOOL\supplier			schtasks /delete /tn NGSupplierSync /f	NGSupplierSync	\NGSupplierSync

#3

Time	Event
8/11/26 2:15:00.462 AM	2026-08-11 05:15:00,4624,SRV-FILE-HQ,a.mizrahi,3,SRV-VEND-APP,,,, host = DESKTOP-RR49OMB source = northgate_winevent.csv sourcetype = winevent
8/11/26 2:15:01.467 AM	2026-08-11 05:15:01,4672,SRV-FILE-HQ,a.mizrahi,3,SRV-VEND-APP,,,, host = DESKTOP-RR49OMB source = northgate_winevent.csv sourcetype = winevent

#4

object_name	count	min_time	time_diff
\\SRV-FILE-HQ\IT	8	2026-08-12 22:00:00	
\\SRV-FILE-HQ\Payments	8	2026-08-12 22:06:36	00:06:36.0000
\\SRV-FILE-HQ\Finance	7	2026-08-12 22:13:12	00:06:36.0000
\\SRV-FILE-HQ\Vendors	6	2026-08-12 22:19:48	00:06:36.0000
\\SRV-FILE-HQ\Branches	6	2026-08-12 22:26:24	00:06:36.0000
\\SRV-FILE-HQ\Logistics	5	2026-08-12 22:33:00	00:06:36.0000

#5

_time	actor	typical_user_hostname	src_host	current_src_owner	is_expected_hostname	extracted_host
2026-08-15 21:46:59.462	r.stern	SRV-POSMGT SRV-CARDPROC WKS-PAY-02	SRV-VEND-APP	a.mizrahi	False	SRV-POSMGT

#6

object_path_count	total_MB_transfered
1425	214.93

#7

_time	extracted_host	process	cmdline	time_diff
2026-08-16 01:19:59	POS-B01-01	ngpos-cfg.exe	ngpos-cfg.exe /apply /src \\SRV-POSMGT\cfg\pos-profile.dat	
2026-08-16 01:20:16	POS-B02-01	ngpos-cfg.exe	ngpos-cfg.exe /apply /src \\SRV-POSMGT\cfg\pos-profile.dat	00:00:17.0000
2026-08-16 01:20:33	POS-B03-01	ngpos-cfg.exe	ngpos-cfg.exe /apply /src \\SRV-POSMGT\cfg\pos-profile.dat	00:00:17.0000
2026-08-16 01:20:50	POS-B05-01	ngpos-cfg.exe	ngpos-cfg.exe /apply /src \\SRV-POSMGT\cfg\pos-profile.dat	00:00:17.0000
2026-08-16 01:21:07	POS-B06-01	ngpos-cfg.exe	ngpos-cfg.exe /apply /src \\SRV-POSMGT\cfg\pos-profile.dat	00:00:17.0000
2026-08-16 01:21:24	POS-B07-01	ngpos-cfg.exe	ngpos-cfg.exe /apply /src \\SRV-POSMGT\cfg\pos-profile.dat	00:00:17.0000
2026-08-16 01:21:41	POS-B08-01	ngpos-cfg.exe	ngpos-cfg.exe /apply /src \\SRV-POSMGT\cfg\pos-profile.dat	00:00:17.0000
2026-08-19 00:10:01	SRV-STAGE-01	ngarch.exe	ngarch.exe -a -q -o D:\temp\ngsync-0819.dat \\SRV-STAGE-01\temp*.log.1	2+22:40:41.0000

#8

src_host	server	count	distinct_object_path	action	MB_transferred	min_time	max_time	total_actions_all	total_MB_transferred_all
POS-B01-01	SRV-STAGE-01	84	84	write	12.68	2026-08-16 03:00:00	2026-08-19 22:15:50	2850	429.99
POS-B23-01	SRV-STAGE-01	84	84	write	12.67	2026-08-16 03:00:00	2026-08-19 21:52:19	2850	429.99
POS-B02-01	SRV-STAGE-01	84	84	write	12.68	2026-08-16 03:01:41	2026-08-19 22:17:31	2850	429.99
POS-B24-01	SRV-STAGE-01	84	84	write	12.66	2026-08-16 03:01:41	2026-08-19 21:54:00	2850	429.99
POS-B03-01	SRV-STAGE-01	84	84	write	12.69	2026-08-16 03:03:22	2026-08-19 22:19:12	2850	429.99

#9

time	method	MB_out	verdict	dest_host	total_MB_out
2026-08-19 02:55:01	POST	27.38	allowed	edge-sync-eu.net	180.00
2026-08-19 03:10:01	POST	28.43	allowed	edge-sync-eu.net	180.00
2026-08-19 03:25:01	POST	29.48	allowed	edge-sync-eu.net	180.00
2026-08-19 03:40:01	POST	30.52	allowed	edge-sync-eu.net	180.00
2026-08-19 03:55:01	POST	31.57	allowed	edge-sync-eu.net	180.00
2026-08-19 04:10:01	POST	32.62	allowed	edge-sync-eu.net	180.00

#10

deleted_files	first_delete	last_delete	duration
2510	2026-08-19 04:30:00	2026-08-19 05:07:38	00:37:38

#11

src_host	server	count	distinct_object_path	action	MB_transferred	min_time	max_time	total_actions_all	total_MB_transferred_all
POS-B15-01	SRV-STAGE-01	1	1	write	0.15	2026-08-19 04:30:43	2026-08-19 04:30:43	22	3.32
POS-B16-01	SRV-STAGE-01	1	1	write	0.15	2026-08-19 04:32:24	2026-08-19 04:32:24	22	3.32
POS-B17-01	SRV-STAGE-01	1	1	write	0.15	2026-08-19 04:34:05	2026-08-19 04:34:05	22	3.32
POS-B18-01	SRV-STAGE-01	1	1	write	0.15	2026-08-19 04:35:46	2026-08-19 04:35:46	22	3.32
POS-B19-01	SRV-STAGE-01	1	1	write	0.15	2026-08-19 04:37:26	2026-08-19 04:37:26	22	3.32
POS-B20-01	SRV-STAGE-01	1	1	write	0.15	2026-08-19 04:39:07	2026-08-19 04:39:07	22	3.32

#12

distinct_share_folders	values_share_folders	first_time_formatted	last_time_formatted
6	\\SRV-FILE-HQ\Branches \\SRV-FILE-HQ\Finance \\SRV-FILE-HQ\IT \\SRV-FILE-HQ\Logistics \\SRV-FILE-HQ\Payments \\SRV-FILE-HQ\Vendors	2026-08-12 22:00:00	2026-08-15 22:46:12

#13

count
0

#14

src_host	server	min_time	max_time
POS-B14-01	SRV-STAGE-01	2026-08-16 03:18:29	2026-08-19 22:34:19