Oscillogram No.: HPL3-77439 OCV = 244 V **ANALYSIS RESULTS TABLE** Schneider Blectric Date of Test: 10/5/2023 Time of Test: 9:57:30 AM Closing Angle 5 Deg. Closing time (V0)+ 229.4 µ Sec **AVAILABLE CIRCUIT CHARACTERISTICS:** Peak Current (lp) 11.34 k Amps Osc. No: 57423 Calibration Date: 10/20/2022 Time to Ip 3.859 m Sec OCV = 244 V Rms Sym Current = 25.5 kA 407.7 k Amp^2sec High Power Laboratory, HPL3 Facility Power Factor = 15% I Duration Cedar Rapids, Iowa, USA 6.854 m Sec Project No.: 6000001332 TestFlow No.: TESLA Test Device: Eaton BWH 25kA MAIN w/ Eaton 125 Performance Observations Sample No.: 4 Was the Breaker Tripped after the test? Yes 520.0 Volts Could the Breaker be Reset? Yes Did it have continuity in all poles? Yes 400.0 Volts Was the Enclosure Fuse Opened? No 300.0 200.0 Comment Section 100.0 Main & Branch BreakerTripped Voltage 0.0 GRID ON, NEW DOOR INVESTIGATION -100.0 Analysis results are based on this data -200.0 -300.0 12.0 kAmps 10.0 k 8.0 k -400.0 Volts 4.0 k 20 k -480.0 Volts 0.0 Amps 15.7 kAmps -20.00 ms -18.00 ms -16.00 ms -14.00 ms 14.0 kAmps Sweep#: 1 **TOTAL VIEW** 12.0 k 10.0 k -480.0 Volts 8.0 k 6.0 k Current -4.3 kAmp 080 h ms 000.0 ms 040.0 ms Sweep#: 1 040.0 ms 4.0 k INSTRUMENTATION DATA 2.0 k Data Recording System: HBM GEN3T C/N 063-163 PLOT FILE HPL3 CR_1_M Voltage "A":100X Scope Probe, C/N 131-554, 1% 0.0 Current "A":Rogowski CT Coil, C/N 045-444 -2.0 kAmps NOTE: Channel offset removed for analysis -4.3 kAmps but not for display OSC. NO.: HPL3-77439 -25.00 ms -20.00 ms -15.00 ms -10.00 ms Sweep#: 1