

CERTIFICATE OF CALIBRATION

Client: Aldi
Address: 17603
County:
Service Location:
Equipment ID:
Equipment Location: ddd
Equipment Type:
Testing Method:
Next Calibration Due: 03/30/2021

Test Results	
Calibration Date:	03/30/2021
Environment:	Acceptable
Temp/RH:	36/45
As Found:	FAIL
As Left:	FAIL

Indicating Element	Load Receiving Element	Capacity: 500 mg
Manufacturer:	Manufacturer: Ohaus	Resolution: 5
Model:	Model: Kit 40 Misc Ratio	Unit Of Measure: Kg
Serial:	Serial: 444	Tolerance: 33

LINEARITY/ACCURACY											
AS FOUND						AS FOUND					
Standard	Description	Tolerance-Range	As Found	Pass/Fail	Uncertainty	Standard	Description	Tolerance-Range	As Left	Pass/Fail	Uncertainty
10	test	0-0	0	Pass	0	10	test	0-0	0	Pass	0
20	test	0-0	0	Pass	0	20	test	0-0	0	Pass	0
30	test	0-0	0	Pass	0	30	test	0-0	0	Pass	0
40	test	0-0	0	Pass	0	40	test	0-0	0	Pass	0
40	test	0-0	0	Pass	0	40	test	0-0	0	Pass	0

REPEATABILITY			
No.	Standard	As Found	As Left
1	0	0	0
2	0	0	0
3	0	0	0
4	0	0	0
5	0	0	0
6	0	3	4
7	0	0	0
8	0	0	0
9	0	0	0
10	0	0	0

SHIFT/ECCENTRICITY									
<div><div><div>12</div><div><div>1</div><div>452</div><div>43</div></div></div><div><div>Standard:</div><table><tr><th>Position</th><th>As Found</th><th>As Left</th></tr><tr><td colspan="3"></td></tr></table></div></div>				Position	As Found	As Left			
Position	As Found	As Left							
Standard	Description	Certificate #	Cal Due						
1		TEST	01/01/0001						

Technician Printed Name

Technician Signature

Date

* All calibrations, when specified, are performed in accordance with current ISO/IEC 17025, and ANSI/NCSL Z540-1 Standards and Bitterman Scales, LLC Quality System.
 * Standards used are traceable to the International System of Units (SI) through the National Institute of Standards and Technology (NIST) or other National Metrology Institute (NMI).
 * Results obtained apply to the unit under test only and are reflective of conditions at the time of calibration.
 * Calibration results may drift from document values prior to calibration due date.
 * This certificate shall not be reproduced except in full, without written approval of Bitterman Scales, LLC.
 * Expanded uncertainties are calculated using methods described in the guide to the Expression of Uncertainty Measurement (GUM) using a coverage factor of k=2 indicating a 95% confidence level.
 * An "In Tolerance" (Pass) or "Out of Tolerance" (Fail) result indicates all measured values fall within or outside unmodified tolerance limits. The statements of compliance do not take the reported measurement uncertainty into account. This is a shared risk decision rule which the customer also has responsibility for determining acceptance of the results.

Calibrated By:

Approved By:

Form FORMCERT Rev. xx

SIR Licence #:

SIR Licence #: